



ONVIF™

Feature discovery specification

Version 17.01

January 2017



© 2017 by ONVIF, Inc. All rights reserved.

Recipients of this document may copy, distribute, publish, or display this document so long as this copyright notice, license and disclaimer are retained with all copies of the document. No license is granted to modify this document.

THIS DOCUMENT IS PROVIDED "AS IS," AND THE CORPORATION AND ITS MEMBERS AND THEIR AFFILIATES, MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THIS DOCUMENT ARE SUITABLE FOR ANY PURPOSE; OR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

IN NO EVENT WILL THE CORPORATION OR ITS MEMBERS OR THEIR AFFILIATES BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES, ARISING OUT OF OR RELATING TO ANY USE OR DISTRIBUTION OF THIS DOCUMENT, WHETHER OR NOT (1) THE CORPORATION, MEMBERS OR THEIR AFFILIATES HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, OR (2) SUCH DAMAGES WERE REASONABLY FORESEEABLE, AND ARISING OUT OF OR RELATING TO ANY USE OR DISTRIBUTION OF THIS DOCUMENT. THE FOREGOING DISCLAIMER AND LIMITATION ON LIABILITY DO NOT APPLY TO, INVALIDATE, OR LIMIT REPRESENTATIONS AND WARRANTIES MADE BY THE MEMBERS AND THEIR RESPECTIVE AFFILIATES TO THE CORPORATION AND OTHER MEMBERS IN CERTAIN WRITTEN POLICIES OF THE CORPORATION.

Revision History

Ver.	Date	Description
11.12	22 nd /Dec, 2011	First issue
12.06	22 nd /Jun, 2012	Update for a new version of the ONVIF Device Test Tool. No changes made for Feature Discovery.
12.12	20 th /Dec, 2012	Update for a new version of the ONVIF Device Test Tool. Recording Control Service, Recording Search Service, Replay Control Service, Receiver Service specific features were added.
13.06	Jun, 2013	Update for a new version of the ONVIF Device Test Tool. Access Control Service, Door Control Service specific features were added.
13.12	Dec, 2013	Advanced Security features were added. tns1:RecordingConfig/DeleteTrackData feature was added into 5.5.9 Recording Control Service support and 5.6.11 Recording Control Service support items.
14.06	Jun, 2014	'Metadata Recording support' item was removed. Recording Control features support (GetServices) was added in 5.5.9 Recording Control Service support Item, Table 24
14.12	Dec, 2014	IrCutoffConfiguration function support was added into 5.5.8 Imaging Service support Item and into 5.6.10 Imaging Service support Item. Scope was updated. Passphrase Management feature support was added into 5.5.16 Advanced Security Service Support Item, Table 41. Feature definition for Profile Q was added: 5.5.3 Monitoring Events support Item was added, 5.6.5 Monitoring Events support Item was added, 5.5.1 Device Management Service Capabilities and 5.6.1 Device Service Capabilities configuration functionality in Device Management Service items were updated.
15.06	Jun, 2015	CRLs Management, Certification path validation policies Management, TLS WWW client auth extended key usage extension, TLS client authentication features support was added into 5.5.17 Advanced Security Service support, Table 41. Credential Service features support was added into 5.5.18 Credential Service support and 5.6.19 Credential Service support. Access Rules Service features support was added into 5.5.19 Access Rules Service support and 5.6.20 Access Rules Service support. Schedule Service features support was added into 5.5.20 Schedule Service support and 5.6.21 Schedule Service support.
16.06	Jan 27, 2016	The item 8 has been added to the section 1.1. The section 5.5.5 Media2 Service – general has been added.
16.06	Mar 15, 2016	The tables 60 and 12 have been updated. The conditions in table #18 have been updated.
16.07	July 7, 2016	Changed version number, added Media2 Profile Configuration for PTZ Control



16.09	Sept, 2016	TLS1.0, TLS1.1, TLS1.2 features added into 5.5.1 and 5.6.1 items
16.10	Oct, 2016	Media2 Service features support item was added
17.01	Jan, 2017	Minor changes: typos were fixed in 5.5.4, 5.5.5, and 5.6.6 sections
17.01	Jan, 2017	TLS1.0, TLS1.1, TLS1.2 features removed from 5.5.1 and 5.6.1 items



Table of Contents

- 1 Introduction 7
 - 1.1 Scope 7
- 2 Normative references 14
- 3 Informative references 15
- 4 Terms and Definitions 16
 - 4.1 Definitions 16
 - 4.2 Abbreviations 16
- 5 Discovery procedure 17
 - 5.1 General policy 17
 - 5.2 Feature Support Criteria 17
 - 5.3 Discovery Types Support 18
 - 5.4 Capabilities 18
 - 5.5 Discovery Procedure (GetServices and GetServiceCapabilities) 20
 - 5.5.1 Device Management Service Capabilities 20
 - 5.5.2 I/O functionality in Device Management Service 23
 - 5.5.3 Monitoring Events support 25
 - 5.5.4 Media Service – general 27
 - 5.5.5 Media2 Service – general 33
 - 5.5.6 Event Service 35
 - 5.5.7 Device IO Service 37
 - 5.5.8 PTZ Service support 38
 - 5.5.9 Imaging Service support 41
 - 5.5.10 Video Analytics Service support 43
 - 5.5.11 Recording Control Service support 43
 - 5.5.12 Recording Search Service support 45
 - 5.5.13 Replay Service support 47
 - 5.5.14 Receiver Service support 48
 - 5.5.15 Door Control Service support 49
 - 5.5.16 Access Control Service support 53
 - 5.5.17 Advanced Security Service support 59
 - 5.5.18 Credential Service support 62
 - 5.5.19 Access Rules Service support 64



- 5.5.20 Schedule Service support.....65
- 5.6 Discovery Procedure (GetCapabilities).....67
 - 5.6.1 Device Service Capabilities configuration functionality in Device Management Service
67
 - 5.6.2 Security (HTTP digest authentication) support.....69
 - 5.6.3 NTP support.....70
 - 5.6.4 I/O functionality in Device Management Service.....70
 - 5.6.5 Monitoring Events support.....72
 - 5.6.6 Media Service – general.....74
 - 5.6.7 Event Service.....79
 - 5.6.8 Device IO Service79
 - 5.6.9 PTZ Service support81
 - 5.6.10 Imaging Service support.....84
 - 5.6.11 Video Analytics Service support85
 - 5.6.12 Recording Control Service support86
 - 5.6.13 Recording Search Service support87
 - 5.6.14 Replay Service support89
 - 5.6.15 Receiver Service support90
 - 5.6.16 Door Control Service support90
 - 5.6.17 Access Control Service support.....90
 - 5.6.18 Advanced Security Service support91
 - 5.6.19 Credential Service support91
 - 5.6.20 Access Rules Service support91
 - 5.6.21 Schedule Service support.....91
- 5.7 Devices scopes retrieval via GetDeviceScopes91
- 5.8 Devices information retrieval via GetDeviceInformation.....91
- Annex A93
 - A.1 Selection / Creation of Media Profile that contains PTZConfiguration93
 - A.2 Media2 Service - Media Profile Configuration for PTZ Control.....93
 - A.3 Get Complete Door Info List.....94
 - A.4 Get Complete Access Point Info List95
 - A.5 Get Complete Area Info List95



1 Introduction

ONVIF Test Specification ([ONVIF Test]) defines/describes test cases need to verify according to [ONVIF Network Interface Specs], [ONVIF Conformance] in conjunction with a certain Profile Specification requirements. However, requirement on which test cases need to be executed and passed is out of the scope of [ONVIF Test]. Such requirements have to be described in a separate document.

This document focuses on detailing out feature discovery procedure for ONVIF Device Test Tool (hereafter, it is referred to as ONVIF Client) to identify which functionality is supported / not supported by DUT. Based on these results of the feature discovery, which test cases shall be executed and passed will be determined for the purpose of claiming conformance to Profile specification. Some feature detection will be based on capability query, and some other feature detection will be based on error code response retrieval toward a specific request.

1.1 Scope

The scope of this document is to define feature discovery procedure of the functionality listed below.

1. Security
 - a. WS-UsernameToken
 - b. HTTP digest authentication
2. Discovery
 - a. Bye Message support
 - b. Types
 - i. dn:NetworkVideoTransmitter
 - ii. tds:Device
3. Device Service
 - a. Capabilities
 - i. GetCapabilities
 - ii. GetServices
 - b. Network
 - i. Zero Configuration
 - ii. NTP support
 - iii. IPv6
 - iv. DHCPv6
 - v. Dynamic DNS
 - vi. IP Filter
 - c. System

- i. System logging
 - ii. Http System Logging
 - iii. Http Firmware Upgrade
 - iv. Http Support Information
 - v. Http System Backup
 - d. Security
 - i. Maximum Users
 - ii. Default Access Policy
 - iii. Remote User Handling
 - iv. Maximum Username Length
 - v. Maximum Password Length
 - e. I/O functionality
 - i. Relay Outputs
 - 1. Bistable
 - a. Open
 - b. Closed
 - 2. Monostable
 - a. Open
 - b. Closed
- 4. Monitoring Events
 - a. Monitoring/ProcessorUsage
 - b. Monitoring/OperatingTime/LastReset
 - c. Monitoring/OperatingTime/LastReboot
 - d. Monitoring/OperatingTime/LastClockSynchronization
 - e. Monitoring/Backup/Last
 - f. Monitoring/Mechanical/FanFailed
 - g. Monitoring/Mechanical/PowerSupplyFailed
 - h. Monitoring/Mechanical/StorageFailed
 - i. Monitoring/EnvironmentalConditions/CriticalTemperature
- 5. Device scopes retrieval via GetDeviceScopes
- 6. Event Service

- a. Persistent notification storage support
 - b. WS Basic Notification
 - c. GetServiceCapabilities
 - i. MaxPullPoints capability
7. Media Service – general
- a. Video encoding support
 - i. JPEG
 - ii. H.264
 - iii. MPEG4
 - b. Audio encoding support
 - i. G.711
 - ii. G.726
 - iii. AAC
 - c. Audio outputs support
 - i. G.711
 - ii. G.726
 - iii. AAC
 - d. Real-time streaming
 - i. RTP/UDP
 - ii. RTP/RTSP/HTTP
 - iii. RTP/RTSP/TCP
 - iv. RTP-Multicast/UDP
 - e. GetSnapshotUri support
8. Media2 Service – general
- a. Video encoding support
 - i. H.265
 - ii. H.264
 - b. Audio encoding support
 - i. G.711
 - ii. AAC
9. PTZ Service support

- a. Absolut Move
 - i. Pan/Tilt Movement
 - ii. Zoom Movement
 - b. Relative Move
 - i. Pan/Tilt Movement
 - ii. Zoom Movement
 - c. Continuous Move
 - i. Pan/Tilt Movement
 - ii. Zoom Movement
 - d. Preset
 - e. Home Position
 - i. Configurable
 - ii. Fixed
 - f. Auxiliary operations
 - g. Speed
 - i. Speed for Pan/Tilt
 - ii. Speed for Zoom
10. Device IO Service support – general
- a. Relay outputs support
 - b. Digital inputs support
11. Imaging Service support
- a. IrCutfilterConfiguration
12. Video Analytics Service support
13. Recording Control Service support
- a. Dynamic Recordings support
 - b. Dynamic Tracks support
 - c. Audio Recording support
 - d. Recording Options
 - e. tns1:RecordingConfig/DeleteTrackData
 - f. Metadata Recording support
14. Recording Search Service support

- a. Metadata Search support
- b. PTZ Position Search support
- 15. Replay Service
 - a. Reverse Replay
 - b. RTP/RTSP/TCP
- 16. Receiver Service
- 17. Door Control Service support
 - a. Door Entity support
 - i. Access Door
 - ii. Lock Door
 - iii. Unlock Door
 - iv. Double Lock Door
 - v. Block Door
 - vi. Lock Down Door
 - vii. Lock Open Door
 - viii. Door Monitor
 - ix. Lock Monitor
 - x. Double Lock Monitor
 - xi. Alarm
 - xii. Tamper
 - xiii. Fault
 - b. Door Events support
 - i. Door/State/DoorMode
 - ii. Door/State/DoorPhysicalState
 - iii. Door/State/LockPhysicalState
 - iv. Door/State/DoubleLockPhysicalState
 - v. Door/State/DoorAlarm
 - vi. Door/State/DoorTamper
 - vii. Door/State/DoorFault
 - viii. Configuration/Door/Changed
 - ix. Configuration/Door/Removed

18. Access Control Service support

- a. Area Entity support
- b. Access Point Entity support
 - i. Enable/Disable Access Point feature
 - ii. Duress feature
 - iii. Access Taken feature
 - iv. External Authorization feature
 - v. Anonymous Access feature
- c. Access Point Events support
 - i. AccessControl/AccessGranted/Anonymous
 - ii. AccessControl/AccessGranted/Credential
 - iii. AccessControl/AccessTaken/Anonymous
 - iv. AccessControl/AccessTaken/Credential
 - v. AccessControl/AccessNotTaken/Anonymous
 - vi. AccessControl/AccessNotTaken/Credential
 - vii. AccessControl/Denied/Anonymous
 - viii. AccessControl/Denied/Credential
 - ix. AccessControl/Denied/CredentialNotFound/Card
 - x. AccessControl/Duress
 - xi. AccessControl/Request/Anonymous
 - xii. AccessControl/Request/Credential
 - xiii. AccessControl/Request/Timeout
 - xiv. AccessPoint/State/Enabled
 - xv. Configuration/AccessPoint/Changed
 - xvi. Configuration/AccessPoint/Removed
 - xvii. Configuration/Area/Changed
 - xviii. Configuration/Area/Removed

19. Advanced Security Service support

- a. Keystore features support
 - i. RSA Key Pair Generation
 - ii. PKCS10 External Certification with RSA

- iii. Self-Signed Certificate Creation with RSA
 - iv. Passphrase Management
 - v. PKCS8 Container Upload
 - vi. PKCS12 Container Upload
 - vii. CRLs
 - viii. Certification path validation policies
 - ix. TLS WWW client auth extended key usage extension
- b. TLS features support
 - i. TLS Server
 - ii. TLS client authentication
20. Credential Service support
- a. Supported Identifier Types
 - i. pt:Card
 - ii. pt:PIN
 - iii. pt:Fingerprint
 - iv. pt:Face
 - v. pt:Iris
 - vi. pt:Vein
 - b. Credential Validity
 - c. Credential Access Profile Validity
 - d. Validity Supports Time Value
 - e. Reset Antipassback Violation
21. Access Rules Service support
- a. Multiple Schedules per Access Point
22. Schedule Service support
- a. Extended Recurrence
 - b. Special Days
 - c. State Reporting

The coverage of the discovery procedure will be evolving in accordance with [ONVIF Test] version evolution and addition of Profile Specification.




2 Normative references

[ONVIF Network Interface Specs]	ONVIF Network Interface Specification documents http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Conformance]	ONVIF Conformance Process Specification http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Test]	ONVIF Test Specification version 16.06, Jun 2015 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Base Test]	ONVIF Base Test Specification version 16.06, Jun 2015 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Media Test]	ONVIF Media Test Specification version version 16.06, Jun 2015 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF PTZ Test]	ONVIF PTZ Test Specification version 14.06, Jun 2014 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Imaging Test]	ONVIF Imaging Test Specification version 14.12, Dec 2014 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Recording Control Test]	ONVIF Recording Control Test Specification version 14.12, Dec 2014 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Receiver Test]	ONVIF Receiver Test Specification version 13.06, Jun 2013 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Replay Control Test]	ONVIF Replay Control Test Specification version 14.06, Jun 2014 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Recording Search Test]	ONVIF Recording Search Test Specification version 14.12, Dec 2014 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Access Test]	ONVIF Access Control Test Specification version 13.06, Jun 2013 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Door Test]	ONVIF Door Control Test Specification version 14.06, Jun 2014 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Advanced Security Test]	ONVIF Advanced Security Test Specification version 16.06, Jun 2015 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Credential Test]	ONVIF Credential Test Specification version 16.06, Jun 2015 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Access Rules Test]	ONVIF Access Rules Test Specification version 16.06, Jun 2015 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Schedule Test]	ONVIF Schedule Test Specification version 16.06, Jun 2015 http://www.onvif.org/Documents/Specifications.aspx



3 Informative references

[ONVIF Test Case Summary for Profile S]	ONVIF Test Case Summary for Profile S Conformance version 14.12, Dec 2014 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Profile S]	ONVIF Profile S Specification http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Test Case Summary for Profile G]	ONVIF Test Case Summary for Profile G Conformance version 14.12, Dec 2014 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Profile G]	ONVIF Profile G Specification http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Test Case Summary for Profile C]	ONVIF Test Case Summary for Profile C Conformance version 14.12, Dec 2014 http://www.onvif.org/Documents/Specifications.aspx
[ONVIF Profile C]	ONVIF Profile C Specification http://www.onvif.org/Documents/Specifications.aspx



4 Terms and Definitions

4.1 Definitions

This section defines terms that are specific to the ONVIF Feature Discovery.

Capability	The capability commands allow a client to ask for the services provided by an ONVIF device.
Network	A network is an interconnected group of devices communicating using the Internet protocol.
ONVIF Client	ONVIF Device Test Tool in the context of this document
Key	A key is an input to a cryptographic algorithm. Sufficient randomness of the key is usually a necessary condition for the security of the algorithm. This specification supports RSA key pairs as keys.
Key Pair	A key that consists of a public key and (optionally) a private key.
RSA key pair	A key pair that is accepted as input by the RSA algorithm.
Certificate	A certificate as used in this specification binds a public key to a subject entity. The certificate is digitally signed by the certificate issuer (the certification authority) to allow for verifying its authenticity

4.2 Abbreviations

This section describes abbreviations used in this document.

DUT	Device Under Test
DNS	Domain Name System
DHCP	Dynamic Host Configuration Protocol
IP	Internet Protocol
IPv4	Internet Protocol version 4
IPv6	Internet Protocol version 6
NTP	Network Time Protocol
RTCP	RTP Control Protocol
RTSP	Real Time Streaming Protocol
RTP	Real-time Transport Protocol
URI	Uniform Resource Identifier
TLS	Transport Layer Security



5 Discovery procedure

This section describes policy on how ONVIF Client assumes that a certain feature is supported or not, followed by respective feature discovery procedures.

5.1 General policy

ONVIF Client will issue capability query command (GetCapabilities or GetServices/GetServiceCapabilities depending on DUT possibilities) to get to know whether a certain feature is supported by DUT. If the DUT returns correct response, ONVIF Client determines whether a feature in question is supported or not, based on the content of the response. If the DUT returns unexpected response or it does not return any response, ONVIF Client assumes that the capability query command which is being used is not supported by DUT.

There are a number of functions which are defined as conditionally required. And there are some of functions which are not present in any capability response fields. As for these commands, ONVIF Client will issue the very function command to determine whether the function is supported or not. In the case that the DUT returns a correct response to indicate no function support such as SOAP fault env:Receiver/ter:ActionNotSupported/ter:NoSuchService, ONVIF Client assumes that the function is not supported by DUT. In case the DUT returns an unexpected response or it does not return any response, ONVIF Client will mark the function support in question as undefined.

After going through all the feature discovery steps based on the above general policy, what are marked as supported and undefined will be processed as supported features during conformance testing.

5.2 Feature Support Criteria

Feature support criteria in the specification are defined using the following table format outlined in Table 1.

Table 1 Feature support criteria description outline used in this specification

Criterion Item	Criteria_item_description	
Feature	Supported	Not Supported
Feature_name1	Supported_criteria_feature1	NotSupported_criteria_feature 1
Feature_name2	Supported_criteria_feature2	NotSupported_criteria_feature 2
...
Feature_nameN	Supported_criteria_featureN	NotSupported_criteria_feature N

The **Feature** column includes a list of features that is defined in current table.



The **Criterion item** field contains item description which value will be used as criteria to check feature support.

The **Supported** column includes conditions when feature in the same row will be assumed as supported depending on criteria item value.

The **Not Supported** column includes conditions when feature in the same row will be assumed as not supported depending on criteria item value.

5.3 Discovery Types Support

From the first version of ONVIF Core Specification document, Device Type that is required for Discovery functionality was “dn:NetworkVideoTransmitter”. Device Type was modified in the later version of [ONVIF Network Interface Specs] to “tds:Device”. Which Device Type shall be used by DUT is defined in the scope of [ONVIF Profile S], [ONVIF Profile G] and [ONVIF Profile C]. The following procedure discovers which Types are supported by DUT.

Discovery Procedure:

1. ONVIF Client invokes Unicast Probe request (empty Types, empty Scopes) to get ProbeMatches response.
2. ONVIF Client receives ProbeMatch and checks features support as defined in Table 2.

Note: If DUT does not return ProbeMatch or ProbeMatch <d:Types> does not contain neither “dn:NetworkVideoTransmitter” nor “tds:Device”, the following features will be marked as undefined:

- WS-Discovery\Types\tds:Device
- WS-Discovery\Types\dn:NetworkVideoTransmitter

Table 2 Discovery Types

Criterion Item	<d:Types> in ProbeMatch response	
Feature	Supported	Not Supported
tds:Device	Contains “tds:Device”	Does not contain “tds:Device”
dn:NetworkVideoTransmitter	Contains “dn:NetworkVideoTransmitter”	Does not contain “dn:NetworkVideoTransmitter”

5.4 Capabilities

From the first version of ONVIF Core Specification document, GetCapabilities command defined in Device Management Service was the only command to get to know the various feature capabilities by DUT. This capability query scheme was modified in the later version of [ONVIF Network Interface Specs] in order to enhance its scalability. In the case when only GetCapabilities command is



supported by DUT, the following procedure focuses on GetCapabilities commands as supported capability query method by DUT. In the case when GetServices/GetServiceCapabilities commands are supported by DUT the following procedure focuses on GetServices commands as supported capability query method, which provides more possibilities for feature discovery.

Discovery Procedure:

1. ONVIF Client invokes GetCapabilitiesRequest message without any authentication to retrieve the capabilities and check GetCapabilities command support by DUT.
2. If DUT returns correct GetCapabilitiesResponse message. Go to step 4
3. If DUT returns fault message (any SOAP fault except Sender/NotAuthorized) or it does not return any response. Go to step 4.
4. If DUT returns fault message (SOAP fault Sender/NotAuthorized), go to step 2.
5. If DUT returns HTTP 401 Unauthorized error, go to step 3.
6. ONVIF Client invokes GetCapabilitiesRequest message with WS-UsernameToken authentication to retrieve the capabilities and check GetCapabilities command support of DUT.
7. If DUT returns correct GetCapabilitiesResponse message. Go to step 4.
8. If DUT does not return correct GetCapabilitiesResponse message. Go to step 4.
9. ONVIF Client invokes GetCapabilitiesRequest message with HTTP Digest authentication to retrieve the capabilities and check GetCapabilities command support of DUT.
10. If DUT returns correct GetCapabilitiesResponse message. Go to step 4.
11. If DUT does not return correct GetCapabilitiesResponse message. Go to step 4.
12. ONVIF Client invokes GetServicesRequest message without any authentication to retrieve the capabilities and check GetServices command support by DUT.
13. If DUT returns GetServicesResponse message. Go to step 7.
14. If DUT returns fault message (any SOAP fault except Sender/NotAuthorized) or it does not return any response. Go to step 7.
15. If DUT returns fault message (Sender/NotAuthorized), go to step 5.
16. If DUT returns HTTP 401 Unauthorized error, go to step 6.
17. ONVIF Client invokes GetServicesRequest message with WS-UsernameToken authentication to retrieve the capabilities and check GetServices command support of DUT.
18. If DUT returns GetServicesResponse message. Go to step 7.
19. If DUT does not return GetServicesResponse message. Go to step 7.
20. ONVIF Client invokes GetServicesRequest message with HTTP Digest authentication to retrieve the capabilities and check GetServices command support by DUT.
21. If DUT returns GetServicesResponse message.
22. If DUT does not return GetServicesResponse message.



23. ONVIF Client checks features support as defined in Table 3.

Note: If both GetCapabilities and GetServices functions are defined as unsupported, other features will be marked as undefined.

Note: Next steps will depend on GetServices support. If GetServices is supported by DUT, then 5.5 Discovery Procedure (GetServices and GetServiceCapabilities) will be used. If only GetCapabilities is supported by DUT then 5.6 Discovery Procedure (GetCapabilities) will be used.

Table 3 Capabilities

Criterion Item	GetServicesResponse message and GetCapabilitiesResponse message	
Feature	Supported	Not Supported
GetCapabilities	GetCapabilitiesResponse was received	No GetCapabilitiesResponse was received (fault was received or DUT does not return any response)
GetServices	GetServicesResponse was received	No GetServicesResponse was received (fault was received or DUT does not return any response)

5.5 Discovery Procedure (GetServices and GetServiceCapabilities)

If GetServices is supported by the DUT, then GetServices and GetServiceCapabilities commands will be used for feature discovery procedure. The following provides with the functionality discovery procedure for this case.

5.5.1 Device Management Service Capabilities

There are various device management functions defined in [ONVIF Core] as a part of ONVIF Device Management Service.

In the first version of [ONVIF Core], WS-UsernameToken support was the only method defined as a mandatory feature for user authentication. This has been changed in the later version of [ONVIF Core] where it also defines the HTTP digest authentication support as a mandatory feature.

The following discovery procedure will be performed for ONVIF Client to determine which user authentication function will be used in conformance testing. Also network configuration, security support, WS-Discovery features, and system logging will be done during this discovery procedure.

Discovery Procedure:

1. ONVIF Client invokes GetServiceCapabilitiesRequest message for Device Management without any authentication to retrieve the Device Management Service capabilities of the DUT.
2. If the DUT returns correct GetServiceCapabilitiesResponse message, go to step 4.



3. If the DUT returns fault message (SOAP fault Sender/NotAuthorized), go to step 2.
4. If the DUT returns HTTP 401 Unauthorized error, go to step 3.
5. ONVIF Client invokes `GetServiceCapabilitiesRequest` message with WS-UsernameToken authentication to retrieve the Device Management Service capabilities of the DUT. Go to the step 4.
6. ONVIF Client invokes `GetServiceCapabilitiesRequest` message with HTTP Digest authentication to retrieve the Device Management Service capabilities of the DUT. Go to the step 4.
7. ONVIF Client checks features support as defined in Table 4.

Note: If the DUT returns no response for step 1 or response differs from the provided in a, b, and c items at step 1, then all Device Management features will be marked as undefined.

Note: If the DUT does not return `GetServiceCapabilitiesResponse` message for steps 2 or 3, then all Device Management features will be marked as undefined.

Note: If both of WS-UsernameToken and Digest are defined as unsupported, WS-UsernameToken will be used for test performance and discovering of following features.

Note: If HTTP digest authentication is assumed as supported, the HTTP digest authentication scheme will be used in the following feature discovery procedure whenever necessary as well as in conformance testing.

Table 4 Device Capabilities configuration functionality in Device Management Service (GetServices)

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
NTP	Capabilities.Network.NTP > 0	Skipped Capabilities.Network.NTP or Capabilities.Network.NTP = 0
IPv6	Capabilities.Network.IPVersion6 = true	Skipped Capabilities.Network.IPVersion6 or Capabilities.Network.IPVersion6 = false
Zero Configuration	Capabilities.Network.ZeroConfiguration = true	Skipped Capabilities.Network.ZeroConfiguration or Capabilities.Network.ZeroConfiguration = false
Dynamic DNS	Capabilities.Network.DynDNS = true	Skipped Capabilities.Network.DynDNS or Capabilities.Network.DynDNS = false

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
IP Filter	Capabilities.Network.IPFilte r = true	Skipped Capabilities.Network. IPFilter or Capabilities.Network. IPFilter = false
Stateful IPv6 DHCP	Capabilities.Network.DHCPv 6 = true	Skipped Capabilities.Network. DHCPv6 or Capabilities.Network. DHCPv6 = false
WS-UsernameToken	Capabilities.Security. UsernameToken = true	Skipped Capabilities.Security. UsernameToken or Capabilities. Security.UsernameToken = false
HTTP Digest	Capabilities.Security. HttpDigest = true	Skipped Capabilities.Security. HttpDigest or Capabilities. Security.HttpDigest = false
Maximum Users	Capabilities.Security. MaxUsers element is present	Capabilities.Security. MaxUsers element is not present
Default Access Policy	Capabilities.Security. DefaultAccessPolicy = true	Skipped Capabilities.Security. HttpDigest or Capabilities. Security. DefaultAccessPolicy = false
Remote User Handling	Capabilities.Security. RemoteUserHandling = true	Skipped Capabilities. Security. RemoteUserHandling or Capabilities.Security. RemoteUserHandling = false
Maximum Username Length	Capabilities.Security. MaxUsernameLength element is present	Capabilities.Security. MaxUsernameLength element is not present
Maximum Password Length	Capabilities.Security. MaxPasswordLength element is present	Capabilities.Security. MaxPasswordLength element is not present
Bye Message	Capabilities.System. DiscoveryBye = true	Skipped Capabilities.System. DiscoveryBye or Capabilities. System.DiscoveryBye = false
System logging	Capabilities.System. SystemLogging = true	Skipped Capabilities.System. SystemLogging or

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
		Capabilities. System.SystemLogging = false
Http Firmware Upgrade	Capabilities.System. HttpFirmwareUpgrade = true	Skipped Capabilities.System. HttpFirmwareUpgrade or Capabilities. System. HttpFirmwareUpgrade = false
Http System Backup	Capabilities.System. HttpSystemBackup = true	Skipped Capabilities.System. HttpSystemBackup or Capabilities. System. HttpSystemBackup = false
Http System Logging	Capabilities.System. HttpSystemLogging = true	Skipped Capabilities.System. HttpSystemLogging or Capabilities. System. HttpSystemLogging = false
Http Support Information	Capabilities.System. HttpSupportInformation = true	Skipped Capabilities.System. HttpSupportInformation or Capabilities. System. HttpSupportInformation = false

5.5.2 I/O functionality in Device Management Service

I/O related functionality support can be retrieved by checking correspondent element of GetCapabilitiesResponse. The following is the procedure to determine the function support.

Discovery Procedure:

1. ONVIF Client invokes GetCapabilitiesRequest to check I/O functionality support.
2. ONVIF Client receives GetCapabilitiesResponse and checks features support as defined in Table 5.
3. ONVIF Client invokes GetRelayOutputsRequest message to retrieve a relay output list.
4. The DUT returns GetRelayOutputsResponse with a list of relay outputs.
5. ONVIF Client invokes SetRelayOutputSettingsRequest message (RelayOutputToken = “[first token from GetRelayOutputsResponse]”, Properties.Mode = “Bistable”, Properties.DelayTime = “PT30S”, Properties.IdleState = “open”).
6. ONVIF Client receives SetRelayOutputSettingsResponse.



7. ONVIF Client invokes SetRelayOutputSettingsRequest message (RelayOutputToken = “[first token from GetRelayOutputsResponse]”, Properties.Mode = “Bistable”, Properties.DelayTime = “PT30S”, Properties.IdleState = “closed”).
8. ONVIF Client receives SetRelayOutputSettingsResponse.
9. ONVIF Client invokes SetRelayOutputSettingsRequest message (RelayOutputToken = “[first token from GetRelayOutputsResponse]”, Properties.Mode = “Monostable”, Properties.DelayTime = “PT30S”, Properties.IdleState = “open”).
10. ONVIF Client receives SetRelayOutputSettingsResponse.
11. ONVIF Client invokes SetRelayOutputSettingsRequest message (RelayOutputToken = “[first token from GetRelayOutputsResponse]”, Properties.Mode = “Monostable”, Properties.DelayTime = “PT30S”, Properties.IdleState = “closed”).
12. ONVIF Client receives SetRelayOutputSettingsResponse.
13. ONVIF Client checks features support as defined in Table 6.

Note: Absence of Capabilities.Device.IO element in the GetCapabilitiesResponse will be defined as absence of Capabilities.Device.IO.RelayOutputs.

Note: If Capabilities.Device element is not included in the GetCapabilitiesResponse, Relay Outputs feature will be marked as unsupported.

Note: If the DUT does not return GetRelayOutputsResponse or list of relay outputs in the GetRelayOutputsResponse is empty, Relay Outputs features will be marked as undefined.

Note: If GetCapabilities command is not supported by the DUT I/O feature for Device Management Service will be defined as unsupported.

Table 5 Relay Outputs in Device Management Service (GetServices)

Criterion Item	GetCapabilitiesResponse message	
Feature	Supported	Not Supported
RelayOutputs	Capabilities.Device.IO.RelayOutputs > 0	Skipped Capabilities.Device.IO.RelayOutputs or Capabilities.Device.IO.RelayOutputs = 0

Table 6 Relay Outputs Mode and Idle State in Device Management Service (GetServices)

Criterion Item	SetRelayOutputSettingsResponse	
Feature	Supported	Not Supported
Bistable Mode/Open Idle State	DUT returns SetRelayOutputSettings Response for step 6	DUT returns any SOAP fault for step 6

Criterion Item	SetRelayOutputSettingsResponse	
Feature	Supported	Not Supported
Bistable Mode/Closed Idle State	DUT returns SetRelayOutputSettings Response for step 8	DUT returns any SOAP fault for step 8
Bistable Mode	DUT returns SetRelayOutputSettings Response for step 6 or 8	DUT returns any SOAP fault for step 6 and 8
Monostable Mode/Open Idle State	DUT returns SetRelayOutputSettings Response for step 9	DUT returns any SOAP fault for step 9
Monostable Mode/Closed Idle State	DUT returns SetRelayOutputSettings Response for step 11	DUT returns any SOAP fault for step 11
Monostable Mode	DUT returns SetRelayOutputSettings Response for step 9 or 11	DUT returns any SOAP fault for step 9 and 11

5.5.3 Monitoring Events support

Monitoring Events support under Device Control Service is determined according to the following procedure.

Pre-requisite

- This procedure assumes that GetEventPropertiesResponse has already been retrieved via preceding procedure described in Section 5.5.6.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 7.

Note: If the DUT does not return Event Service or GetEventPropertiesResponse message, then the following features will be marked as undefined:

- Monitoring/ProcessorUsage
- Monitoring/OperatingTime/LastReset
- Monitoring/OperatingTime/LastReboot
- Monitoring/OperatingTime/LastClockSynchronization
- Monitoring/Backup/Last



- Device/HardwareFailure/TemperatureCritical
- Device/HardwareFailure/FanFailure
- Device/HardwareFailure/PowerSupplyFailure
- Device/HardwareFailure/StorageFailure

Table 7 Monitoring Events support (GetServices)

Criterion Item	GetEventPropertiesResponse	
Feature	Supported	Not Supported
Monitoring/ProcessorUsage	Contains tns1:Monitoring/ProcessorUsage Event topic	Does not contain tns1:Monitoring/ProcessorUsage Event topic
Monitoring/OperatingTime/LastReset	Contains tns1:Monitoring/OperatingTime/LastReset Event topic	Does not contain tns1:Monitoring/OperatingTime/LastReset Event topic
Monitoring/OperatingTime/LastReboot	Contains tns1:Monitoring/OperatingTime/LastReboot Event topic	Does not contain tns1:Monitoring/OperatingTime/LastReboot Event topic
Monitoring/OperatingTime/LastClockSynchronization	Contains tns1:Monitoring/OperatingTime/LastClockSynchronization Event topic	Does not contain tns1:Monitoring/OperatingTime/LastClockSynchronization Event topic
Monitoring/Backup/Last	Contains tns1:Monitoring/Backup/Last Event topic	Does not contain tns1:Monitoring/Backup/Last Event topic
Device/HardwareFailure/TemperatureCritical	Contains tns1:Device/HardwareFailure/TemperatureCritical Event topic	Does not contain tns1:Device/HardwareFailure/TemperatureCritical Event topic
Device/HardwareFailure/FanFailure	Contains tns1:Device/HardwareFailure/FanFailure Event topic	Does not contain tns1:Device/HardwareFailure/FanFailure Event topic
Device/HardwareFailure/PowerSupplyFailure	Contains tns1:Device/HardwareFailure/PowerSupplyFailure Event topic	Does not contain tns1:Device/HardwareFailure/PowerSupplyFailure Event topic



Criterion Item	GetEventPropertiesResponse	
Feature	Supported	Not Supported
Device/HardwareFailure/StorageFailure	Contains tns1:Device/HardwareFailure/StorageFailure Event topic	Does not contain tns1:Device/HardwareFailure/StorageFailure Event topic

5.5.4 Media Service – general

Media Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 8.

Note: If GetServicesResponse contains several services with “http://www.onvif.org/ver10/media/wsdl” namespace ONVIF Client will use service with the latest version.

Note: If Media service is not supported, the following feature discovery (Media Service features support) will be skipped.

Table 8 Media Service – general (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
Media Service	Includes service with “http://www.onvif.org/ver10/media/wsdl” namespace	Does not include service with “http://www.onvif.org/ver10/media/wsdl” namespace

Media Service – Video encoding support

Video encoding function support in Media Service is determined according to the following procedure.

Discovery Procedure:

1. ONVIF Client invokes GetVideoEncoderConfigurationOptionsRequest (no ConfigurationToken, no ProfileToken) message to retrieve all supported codecs.



- The DUT returns `GetVideoEncoderConfigurationOptionsResponse` with a list of supported codecs. ONVIF Client checks features support as defined in Table 9.

Note: If the DUT does not return `GetVideoEncoderConfigurationOptionsResponse`, MPEG4 and H.264 feature will be marked as undefined.

Table 9 Media Service – Video encoding support (GetServices)

Criterion Item	GetVideoEncoderConfigurationOptionsResponse	
Feature	Supported	Not Supported
JPEG	Mandatory functionality	-
MPEG-4	Includes Options.MPEG4	Does not include Options.MPEG4
H.264	Includes Options.H264	Does not include Options.H264

Media Service – Audio encoding support

Audio encoding function support in Media Service is determined according to the following procedure.

Discovery Procedure:

- ONVIF Client invokes `GetAudioEncoderConfigurationOptionsRequest` (no `ConfigurationToken`, no `ProfileToken`) message to retrieve all supported audio codecs.
- The DUT returns `GetAudioEncoderConfigurationOptionsResponse` with a list of supported codecs or SOAP fault. ONVIF Client checks features support as defined in Table 10.

Note: If the DUT returns no response for `GetAudioEncoderConfigurationOptionsRequest`, Audio encoding feature will be marked as undefined.

Table 10 Media Service – Audio encoding support (GetServices)

Criterion Item	GetAudioEncoderConfigurationOptionsResponse	
Feature	Supported	Not Supported
Audio encoding	DUT returns GetAudioEncoderConfigurationOptionsResponse	DUT returns any SOAP fault
G.711	DUT returns GetAudioEncoderConfigurationOptionsResponse	DUT returns any SOAP fault
G.726	Includes Options.Options.Encoding = "G726"	Does not include Options.Options.Encoding = "G726"
AAC	Includes Options.Options.Encoding = "AAC"	Does not include Options.Options.Encoding = "AAC"

Media Service – Real-time streaming

Real-time streaming support in Media Service is determined according to the following procedure.

Discovery Procedure:

1. ONVIF Client invokes GetServiceCapabilitiesRequest message to check Multicast streaming capability support by the DUT.
2. The DUT returns GetServiceCapabilitiesResponse. ONVIF Client checks features support as defined in Table 11.

Note: If the DUT does not return GetServiceCapabilitiesResponse, then Real-time streaming feature and features from Media Service – Supported Real-time streaming Setup will be marked as undefined. Procedure described in Media Service – Supported Real-time streaming Setup will be skipped.

Note: If the DUT does not support Real-time streaming feature, all features from Media Service – Supported Real-time streaming Setup will be marked as unsupported. Procedure described in Media Service – Supported Real-time streaming Setup will be skipped.

Table 11 Media Service – Supported Real-time streaming Setup (GetServices)

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
Real-time streaming	Skipped Capabilities. StreamingCapabilities. NoRTSPStreaming or Capabilities. StreamingCapabilities. NoRTSPStreaming = false	Capabilities. StreamingCapabilities. NoRTSPStreaming = true

Media Service – Supported Real-time streaming Setup

Which Real-time streaming Setup features is supported under Real-time Streaming is determined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServiceCapabilitiesResponse has already been retrieved via preceding procedure described in Media Service – Real-time streaming.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 12.

Table 12 Media Service – Supported Real-time streaming Setup (GetServices)

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
RTP/UDP	Mandatory functionality, if Real-time Streaming supported	-
RTP/RTSP/HTTP	Mandatory functionality, if Real-time Streaming supported	-
RTP/RTSP/TCP	Capabilities. StreamingCapabilities. RTP_RTSP_TCP = true	Skipped Capabilities. StreamingCapabilities. RTP_RTSP_TCP or Capabilities. StreamingCapabilities. RTP_RTSP_TCP = false



Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
RTP-Multicast/UDP	Capabilities. StreamingCapabilities. RTPMulticast = true	Skipped Capabilities. StreamingCapabilities. RTPMulticast or Capabilities. StreamingCapabilities. RTPMulticast = false

Media Service - GetSnapshotUri

GetSnapshotUri function support is determined according to the following procedure.

Discovery Procedure:

1. ONVIF Client invokes GetProfilesRequest message to retrieve existing Media Profiles list.
2. The DUT returns GetProfilesResponse with the list of existing Media Profiles.
3. ONVIF Client looks for ready-to-use profile (a profile with VideoSourceConfiguration and VideoEncoderConfiguration in the GetProfilesResponse. If there are no ready-to-use profiles found in the GetProfilesResponse, ONVIF Client marks GetSnapshotUri support by DUT as undefined.
4. ONVIF Client invokes GetSnapshotUriRequest (ProfileToken = found ready-to-use profile token) message to get Snapshot URI.
5. The DUT returns GetSnapshotUriResponse or SOAP fault. ONVIF Client checks features support as defined in Table 13.

Note: If no GetProfilesResponse is returned by the DUT, GetSnapshotUri function support by the DUT is marked as undefined.

Note: If no GetSnapshotUriResponse is returned by the DUT, GetSnapshotUri function support by the DUT is marked as undefined.

Table 13 Media Service – GetSnapshotUri (GetServices)

Criterion Item	GetSnapshotUriResponse	
Feature	Supported	Not Supported
GetSnapshotUri	DUT returns GetSnapshotUriResponse	DUT returns any SOAP fault

Media Service – Audio outputs support

Audio outputs support in conjunction with its Audio decoding function is determined according to the following procedure.



Discovery Procedure:

1. ONVIF Client invokes GetAudioOutputsRequest message to retrieve Audio outputs list.
2. The DUT returns GetAudioOutputsResponse or SOAP fault. ONVIF Client checks features support as defined in Table 14. Go to the next feature definition.
3. ONVIF Client invokes GetAudioDecoderConfigurationOptionsRequest (no ConfigurationToken, no ProfileToken) message to retrieve all supported Audio codec's for decoding by DUT.
4. The DUT returns GetAudioDecoderConfigurationOptionsResponse. ONVIF Client checks features support as defined in Table 15.


Note: If the DUT does not return GetAudioDecoderConfigurationOptionsResponse, ONVIF Client assumes that G.711, G.726 and AAC Audio decoding function support is marked as undefined.

Table 14 Media Service – Audio outputs support (GetServices)

Criterion Item	GetAudioOutputsResponse	
Feature	Supported	Not Supported
Audio output	DUT returns GetAudioOutputsResponse and there are at least one AudioOutput on the list	DUT returns any SOAP fault or GetAudioOutputsResponse and there are no AudioOutput on the list

Table 15 Media Service – Audio outputs decoding support (GetServices)

Criterion Item	GetAudioDecoderConfigurationOptionsResponse	
Feature	Supported	Not Supported
G.711	Includes Options.G711DecOptions	Does not include Options.G711DecOptions
G.726	Includes Options.G726DecOptions	Does not include Options.G726DecOptions
AAC	Includes Options.AACDecOptions	Does not include Options.AACDecOptions



5.5.5 Media2 Service – general

The methods for Media2 Service are defined in ONVIF Media2 Service WSDL file. The following “Discovery Procedure” determines if DUT supports Media2 Service.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 16.

Note: If GetServicesResponse contains several services with “http://www.onvif.org/ver20/media/wsd!” namespace ONVIF Client will use service with the latest version.

Note: If Media2 service is not supported, the following feature discovery (“Media2 Service – Video encoding support” and “Media2 Service – Audio encoding support”) will be skipped.

Table 16 Media2 Service – general (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
Media2 Service	Includes service with “http://www.onvif.org/ver20/media/wsd!” namespace	Does not include service with “http://www.onvif.org/ver20/media/wsd!” namespace

Media2 Service – Video encoding support

Video encoding function support in Media2 Service is determined according to the following discovery procedure.

Discovery Procedure:

1. ONVIF Client invokes GetVideoEncoderConfigurationOptionsRequest (no ConfigurationToken, no ProfileToken) message to retrieve all supported codecs.
2. The DUT returns GetVideoEncoderConfigurationOptionsResponse with a list of supported codecs. ONVIF Client checks features support as defined in Table 17.

Note: If the DUT does not return GetVideoEncoderConfigurationOptionsResponse, MEDIA2_H.264 and MEDIA2_H.265 feature will be marked as undefined.

Table 17 Media2 Service – Video encoding support (GetServices)

Criterion Item	GetVideoEncoderConfigurationOptionsResponse	
Feature	Supported	Not Supported
MEDIA2_H.265	Includes Options encoding="H265"	Does not include Options encoding="H265"
MEDIA2_H.264	Options encoding="H264"	Does not include Options encoding="H264"

Media2 Service – Audio encoding support

Audio encoding function support in Media2 Service is determined according to the following discovery procedure.

Discovery Procedure:

1. ONVIF Client invokes GetAudioEncoderConfigurationOptionsRequest (no ConfigurationToken, no ProfileToken) message to retrieve all supported audio codecs.
2. The DUT returns GetAudioEncoderConfigurationOptionsResponse with a list of supported codecs or SOAP fault. ONVIF Client checks features support as defined in Table 18.

Note: If the DUT returns no response for GetAudioEncoderConfigurationOptionsRequest, Media2 Audio encoding features (Media2_G.711 and Media2_AAC) will be marked as undefined.

Table 18 Media2 Service – Audio encoding support (GetServices)

Criterion Item	GetAudioEncoderConfigurationOptionsResponse	
Feature	Supported	Not Supported
Media2_G.711	Includes Options encoding = “PCMU”	Does not include Options encoding = “PCMU”
Media2_AAC	Includes Options encoding = “MP4A-LATM”	Does not include Options encoding = “MP4A-LATM”

Media2 Service features support

Snapshot Uri support under Media2 Service is determined according to the following procedure.

Discovery Procedure:

1. ONVIF Client invokes GetServiceCapabilitiesRequest message to retrieve Media2 Service capabilities.
2. The DUT returns GetServiceCapabilitiesResponse with Media2 Service capabilities. ONVIF Client checks features support as defined in Table 19.

Note: If the DUT returns no response for GetServiceCapabilitiesRequest, Media2 Snapshot Uri feature will be marked as undefined.

Table 19 Media2 Service features support (GetServices)

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
Media2 Snapshot Uri	Capabilities.SnapshotUri = true	Skipped Capabilities.SnapshotUri or Capabilities.SnapshotUri = false

5.5.6 Event Service

Event Service shall be defined as supported as it is a mandatory feature to be supported by the DUT. The following procedure will be used as pre-requisite for other features support check.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.



Discovery Procedure:

1. ONVIF Client invokes GetEventProperties message to retrieve all supported events.

Event service features

Persistent Notification Storage and WS Basic Notification support under Event Service is determined according to the following procedure in conjunction with the above procedure.

Discovery Procedure:

1. ONVIF Client invokes GetServiceCapabilitiesRequest message to check Persistent Notification Storage capability support by DUT.

The DUT returns GetServiceCapabilitiesResponse. ONVIF Client checks features support as defined in

2. Table 20.

Note: If the DUT does not return Event Service or GetServiceCapabilitiesResponse, then Persistent Notification Storage feature and WS Basic Notification feature will be marked as undefined.

Note: Value of Capabilities.MaxPullPoints shall be saved to be used during Profiles support check.

Table 20 Event service features (GetServices)

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
Persistent Notification Storage	Capabilities. PersistentNotificationStorage = true	Skipped Capabilities. PersistentNotificationStorage or Capabilities. PersistentNotificationStorage = false
WS Basic Notification	Capabilities. MaxNotificationProducers > 0 or skipped Capabilities. MaxNotificationProducers	Capabilities. MaxNotificationProducers = 0
GetServiceCapabilities\MaxPullPoints capability	Includes Capabilities.MaxPullPoints	Does not include Capabilities.MaxPullPoints



5.5.7 Device IO Service

Device IO Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 21.

Note: If GetServicesResponse contains several services with “http://www.onvif.org/ver10/deviceIO/wsdI” namespace ONVIF Client will use service with the latest version.

Note: If Device IO service is not supported, the following feature discovery (Relay Outputs and Digital Inputs features support) will be skipped.

Table 21 Device IO Service (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
Device IO Service	Includes service with “http://www.onvif.org/ver10/deviceIO/wsdI” namespace	Does not include service with “http://www.onvif.org/ver10/deviceIO/wsdI” namespace

Relay outputs and digital inputs support

Relay Outputs and Digital Inputs support under Device IO Service is determined according to the following procedure in conjunction with the above procedure.

Discovery Procedure:

1. ONVIF Client invokes GetServiceCapabilitiesRequest message to check Relay Output capability support by DUT.
2. The DUT returns GetServiceCapabilitiesResponse. ONVIF Client checks features support as defined in Table 22.

Note: If the DUT does not return GetServiceCapabilitiesResponse then Relay Outputs and Digital Inputs feature will be marked as undefined.

Table 22 Relay outputs and digital inputs support (GetServices)

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
Relay Outputs	Capabilities.RelayOutputs > 0	Skipped Capabilities.RelayOutputs or Capabilities.RelayOutputs = 0
Digital Inputs	Capabilities.DigitalInputs > 0	Skipped Capabilities.DigitalInputs or Capabilities.DigitalInputs = 0

5.5.8 PTZ Service support

PTZ Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

- ONVIF Client checks features support as defined in Table 52.

Note: If GetServicesResponse contains several services with “http://www.onvif.org/ver20/ptz/wsd1” namespace, ONVIF Client will use service with the latest version.

Note: If PTZ service is not supported, the following feature discovery (Various functions support and Fixed / Configurable Home Position support) will be skipped.

Table 23 PTZ Service (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
PTZ Service	Includes service with “http://www.onvif.org/ver20/ ptz/wsd1” namespace	Does not include service with “http://www.onvif.org/ver20/pt z/wsd1” namespace

Various functions support in PTZ Service

The number of function support in PTZ Service is determined according to the following procedure.



Pre-requisite

- A PTZNode which is used in the function discovery procedure should be provided prior to the execution of the procedure. Otherwise, ONVIF Client will invoke GetNodesRequest message to get the PTZNodes that can be used for the procedure and the first PTZNode present in GetNodesResponse will be used in the procedure. In case PTZNode token is provided, ONVIF Client will use the provided PTZNode token to derive PTZNode via GetNodeRequest.
- Continuous move function is considered as supported if DUT supports PTZ Service feature.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 52.

Note: If neither GetPTZNodesResponse nor GetPTZNodeResponse is returned correctly by the DUT, all functions support under PTZ Service is marked as undefined.

Table 24 Various functions support in PTZ Service (GetServices)

Criterion Item	First PTZNode from GetNodesResponse or PTZNode from GetNodeResponse	
Feature	Supported	Not Supported
Continuous Pan/Tilt movement	SupportedPTZSpaces. ContinuousPanTiltVelocitySpace element is present	SupportedPTZSpaces. ContinuousPanTiltVelocitySpace element is not present
Continuous Zoom movement	SupportedPTZSpaces. ContinuousZoomVelocitySpace element is present	SupportedPTZSpaces. ContinuousZoomVelocitySpace element is not present
Continuous movement	Mandatory	-
Absolute Pan/Tilt movement	SupportedPTZSpaces. AbsolutePanTiltPositionSpace element is present	SupportedPTZSpaces. AbsolutePanTiltPositionSpace element is not present
Absolute Zoom movement	SupportedPTZSpaces. AbsoluteZoomPositionSpace element is present	SupportedPTZSpaces. AbsoluteZoomPositionSpace element is not present
Absolute movement	Absolute Pan/Tilt movement or Absolute Zoom movement is supported	Absolute Pan/Tilt movement and Absolute Zoom movement is not supported
Relative Pan/Tilt movement	SupportedPTZSpaces. RelativePanTiltTranslationSpace element is present	SupportedPTZSpaces. RelativePanTiltTranslationSpace element is not present

Criterion Item	First PTZNode from GetNodesResponse or PTZNode from GetNodeResponse	
Feature	Supported	Not Supported
Relative Zoom movement	SupportedPTZSpaces. RelativeZoomTranlationSpace element is present	SupportedPTZSpaces. RelativeZoomTranlationSpace element is not present
Relative movement	Relative Pan/Tilt movement or Relative Zoom movement is supported	Relative Pan/Tilt movement and Relative Zoom movement is not supported
Speed configuration function for Pan/Tilt movement	SupportedPTZSpaces. PanTiltSpeedSpace element is present	SupportedPTZSpaces. PanTiltSpeedSpace element is not present
Speed configuration function for Zoom movement	SupportedPTZSpaces. ZoomSpeedSpace element is present	SupportedPTZSpaces. ZoomSpeedSpace element is not present
Preset position	MaximumNumberOfPresets > 0	MaximumNumberOfPresets = 0
Auxiliary operation	AuxiliaryCommands element is present	AuxiliaryCommands element is not present
Home Position	HomeSupported = true	HomeSupported = false

Fixed / Configurable Home Position support


In case Home Position function is supported by the DUT, either Fixed or Configurable Home Position shall be supported by the DUT. The following defines the discovery procedure to determine which Home Position function is supported by DUT.

Pre-requisite

- This procedure assumes that Media Service has already been retrieved via preceding procedure described in Section 5.2.
- A PTZNode which is used in the function discovery procedure should be provided prior to the execution of the procedure. Otherwise, ONVIF Client will invoke GetNodesRequest message to get the PTZNodes that can be used for the procedure and the first PTZNode present in GetNodesResponse will be used in the procedure. In case PTZNode token is provided, ONVIF Client will use the provided PTZNode token to derive PTZNode via GetNodeRequest.

Discovery Procedure:

1. ONVIF Client invokes GetConfigurationsRequest message to retrieve a PTZNodes list.



2. The DUT returns GetConfigurationsResponse with the list of PTZConfiguration that contains PTZNode. ONVIF Client identifies first PTZConfiguration which has the corresponding PTZNode with the provided PTZNode.
3. ONVIF Client either selects or creates Media Profile anew along with the identified PTZConfiguration. Refer to Annex A.1 for the details.
4. ONVIF Client invokes SetHomePositionRequest (ProfileToken = selected or newly created profile token) message to check Configurable Home Position is supported by DUT.
5. ONVIF Client checks features support as defined in Table 25.
6. ONVIF Client restores Media Profiles setting in case it changes some of the Media Profiles configuration.

Note: If Media Service is not supported by the DUT, Fixed and Configurable Home Position features will be marked as undefined.

Table 25 Fixed / Configurable Home Position support (GetServices)

Criterion Item	SetHomePositionResponse	
Feature	Supported	Not Supported
Configurable Home Position	DUT returns SetHomePositionResponse	DUT returns SOAP fault
Fixed Home Position	DUT returns SOAP fault	DUT returns SetHomePositionResponse

5.5.9 Imaging Service support

Imaging Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 26.

Note: If GetServicesResponse contains several services with “http://www.onvif.org/ver20/imaging/wsd1” namespace ONVIF Client will use service with the latest version.

Table 26 Imaging Service (GetServices)

Criterion Item	GetServicesResponse	
	Supported	Not Supported
Imaging Service	Includes service with “http://www.onvif.org/ver20/imaging/wsd1” namespace	Does not include service with “http://www.onvif.org/ver20/imaging/wsd1” namespace

IrCutfilterConfiguration function support in Imaging Service

IrCutfilterConfiguration function support in Imaging Service is determined according to the following procedure.

Pre-requisite

- This procedure assumes that Media Service address or DeviceIO Service address were received from the DUT

Discovery Procedure:

1. ONVIF Client invokes GetVideoSourcesRequest message to retrieve all video sources from the DUT.
2. The DUT returns GetVideoSourcesResponse message with a list of existing Video Sources.
3. ONVIF Client invokes GetOptionsRequest message (VideoSourceToken = VideoSourceToken1, where VideoSourceToken1 is the first token of the Video Source in GetVideoSourcesResponse) to retrieve all supported parameters from the DUT.
4. The DUT returns GetOptionsResponse message.
5. ONVIF Client checks IrCutfilterConfiguration feature support as defined in Table 27.
6. If IrCutfilterConfiguration is supported by the VideoSourceToken1, ONVIF Client skips other steps and assumes that IrCutfilterConfiguration feature is supported by the DUT.
7. If IrCutfilterConfiguration is not supported by the VideoSourceToken1, then ONVIF Client repeats steps 3-7 for the next not tested VideoSourceToken. If there is not untested VideoSourceToken, then ONVIF Client assumes that IrCutfilterConfiguration feature is not supported by the DUT.

Note: If neither Media service, nor DeviceIO service are supported, the following feature discovery (IrCutfilter Configuration) will be skipped and assumed as not supported.

Table 27 IrCutfilter Configuration function support in Imaging Service (GetServices)

Criterion Item	At least one VideoSourceToken from GetVideoSources	
Feature	Supported	Not Supported
IrCutfilter Configuration	At least two IrCutFilterModes elements are present in GetOptionsResponse.Imagi	GetOptionsResponse. ImagingOptions does not contain at least two IrCutFilterModes elements or GetOptionsResponse.



Criterion Item	At least one VideoSourceToken from GetVideoSources	
Feature	Supported	Not Supported
	ngOptions and one of them equal to OFF	ImagingOptions does not contain IrCutFilterModes equal to OFF

5.5.10 Video Analytics Service support

Video Analytics Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 28.

Note: If GetServicesResponse contains several services with “http://www.onvif.org/ver10/analyticsdevice/wsd1” namespace ONVIF Client will use service with the latest version.

Table 28 Video Analytics Service (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
Video Analytics Service	Includes service with “http://www.onvif.org/ver10/analyticsdevice/wsd1” namespace	Does not include service with “http://www.onvif.org/ver10/analyticsdevice/wsd1” namespace

5.5.11 Recording Control Service support

Recording Control Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.



Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 29.

Note: If GetServicesResponse contains several services with “http://www.onvif.org/ver10/recording/wsd1” namespace ONVIF Client will use service with the latest version.

Note: If Recording Control service is not supported, the following feature discovery (Dynamic Recordings, Dynamic Tracks and Audio Recording features support) will be skipped.

Table 29 Recording Control Service (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
Recording Control Service	Includes service with “http://www.onvif.org/ver10/recording/wsd1” namespace	Does not include service with “http://www.onvif.org/ver10/recording/wsd1” namespace

Recording Control features support

Dynamic Recordings, Dynamic Tracks, Audio Recording, and Recording Options support under Recording Control Service is determined according to the following procedure in conjunction with the above procedure.

Discovery Procedure:

1. ONVIF Client invokes GetServiceCapabilitiesRequest message to check Dynamic Recording capability support by the DUT.
2. The DUT returns GetServiceCapabilitiesResponse. ONVIF Client checks features support as defined in Table 30.

Note: If the DUT does not return GetServiceCapabilitiesResponse then Dynamic Recordings feature, Dynamic Tracks feature, Audio Recording feature, Recording Options and Metadata Recording feature will be marked as undefined.

Table 30 Recording Control features support (GetServices)

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
Dynamic Recordings	Capabilities.DynamicRecordings = true	Skipped Capabilities. DynamicRecordings or Capabilities.DynamicRecordings = false

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
Dynamic Tracks	Capabilities.DynamicTracks = true	Skipped Capabilities. DynamicTracks or Capabilities. DynamicTracks = false
Audio Recording	Includes Capabilities.Encoding with at least one audio codec (AAC, G711, or G726)	Does not include Capabilities.Encoding with at least one audio codec (AAC, G711, or G726)
Recording Options	Capabilities.Options = true	Skipped Capabilities.Options or Capabilities.Options = false
tns1:RecordingConfig/DeleteTrackData	GetEventProperties contains tns1:RecordingConfig/DeleteTrackData topic	GetEventProperties doesn't contain tns1:RecordingConfig/DeleteTrackData topic
Metadata Recording	Capabilities.MetadataRecording = true	Skipped Capabilities.MetadataRecording or Capabilities.MetadataRecording = false

5.5.12 Recording Search Service support

Recording Search Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 31.

Note: If GetServicesResponse contains several services with “http://www.onvif.org/ver10/search/wsd1” namespace ONVIF Client will use service with the latest version.

Note: If Recording Search service is not supported, the following feature discovery (Metadata Search and PTZ search features support) will be skipped.

Table 31 Recording Search Service (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
Recording Search Service	Includes service with “http://www.onvif.org/ver10/search/wsd1” namespace	Does not include service with “http://www.onvif.org/ver10/search/wsd1” namespace

Metadata search support

Metadata Search support under Recording Search Service is determined according to the following procedure in conjunction with the above procedure.

Discovery Procedure:

1. ONVIF Client invokes GetServiceCapabilitiesRequest message to check Metadata Search capability support by DUT.
2. The DUT returns GetServiceCapabilitiesResponse. ONVIF Client checks features support as defined in Table 32.

Note: If the DUT does not return GetServiceCapabilitiesResponse then Metadata Search feature will be marked as undefined.

Table 32 Metadata search support (GetServices)

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
Metadata Search	Capabilities.MetadataSearch = true	Skipped Capabilities. MetadataSearch or Capabilities. MetadataSearch = false

PTZ Position search support

PTZ Position Search support under Recording Search Service is determined according to the following procedure in conjunction with the above procedure.

Pre-requisite

- A Recording which is used in the function discovery procedure should be provided via GetRecordingInformation command prior to the execution of the procedure (see Annex A.3 Recording Environment Pre-Requisite in the Replay Control Test Specification).

Discovery Procedure:

1. ONVIF Client invokes FindPTZPositionRequest message (StartPoint = [start point of recording], Scope.IncludedRecordings = [recording token], SearchFilter = [any], KeepAliveTime) to check PTZ Search support by DUT.
2. If the DUT returns any SOAP fault, ONVIF Client assumes that PTZ Search feature is not supported by DUT. Otherwise, ONVIF Client marks PTZ Search will be defined as supported.

Note: If the DUT does not return GetRecordingInformationResponse, then PTZ Position Search feature will be marked as undefined.

Note: If RecordingInformation.EarliestRecording is not included in GetRecordingInformationResponse message, then minimum value of Track.DataFrom will be used as StartPoint.

Table 33 PTZ Position search support (GetServices)

Criterion Item	FindPTZPositionResponse	
Feature	Supported	Not Supported
PTZ Position Search	DUT returns FindPTZPositionResponse	DUT returns SOAP fault

5.5.13 Replay Service support

Replay Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 34.

Note: If GetServicesResponse contains several services with “http://www.onvif.org/ver10/replay/wsd!” namespace, ONVIF Client will use service with the latest version.

Note: If Replay service is not supported, the following feature discovery (Reverse Replay features support) will be skipped.

Table 34 Replay Service (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
Replay Service	Includes service with “http://www.onvif.org/ver10/replay/wsd1” namespace	Does not include service with “http://www.onvif.org/ver10/replay/wsd1” namespace

Replay features support

Reverse Replay and RTP/RTSP/TCP support under Replay Service is determined according to the following procedure in conjunction with the above procedure.

Discovery Procedure:

1. ONVIF Client invokes GetServiceCapabilitiesRequest message to check Reverse Replay capability support by DUT.
2. The DUT returns GetServiceCapabilitiesResponse. ONVIF Client checks features support as defined in Table 35.

Note: If the DUT does not return GetServiceCapabilitiesResponse then Reverse Replay feature and RTP/RTSP/TCP feature will be marked as undefined.


Table 35 Replay Control features support (GetServices)

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
Reverse Replay	Capabilities.ReversePlayback = true	Skipped Capabilities.ReversePlayback or Capabilities.ReversePlayback = false
RTP/RTSP/TCP	Capabilities.RTP_RTSP_TCP = true	Skipped Capabilities.RTP_RTSP_TCP or Capabilities.RTP_RTSP_TCP = false

5.5.14 Receiver Service support

Receiver Service support is defined according to the following procedure.

Pre-requisite



- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 34.

Note: If GetServicesResponse contains several services with “http://www.onvif.org/ver10/receiver/wsd1” namespace, ONVIF Client will use service with the latest version.

Table 36 Receiver Service (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
Receiver Service	Includes service with “http://www.onvif.org/ver10/receiver/wsd1” namespace	Does not include service with “http://www.onvif.org/ver10/receiver/wsd1” namespace

5.5.15 Door Control Service support

Door Control Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 37.

Note: If GetServicesResponse contains several services with “http://www.onvif.org/ver10/doorcontrol/wsd1” namespace, ONVIF Client will use service with the latest version.

Note: If Door Control service is not supported, the following feature discovery (Door Entity support, Door Control Events support) will be skipped.

Table 37 Door Control Service (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
Door Control Service	Includes service with “http://www.onvif.org/ver10/doorcontrol/wsd1” namespace	Does not include service with “http://www.onvif.org/ver10/doorcontrol/wsd1” namespace

Door Entity support


Door Entity support under Door Control Service is determined according to the following procedure in conjunction with the above procedure.

Discovery Procedure:

1. Door Entity shall be defined as supported as it is a mandatory feature to be supported by the DUT.
2. ONVIF Client gets all DoorInfos from the DUT using Annex A.3 to check Door Entity sub-feature support by the DUT.
3. ONVIF Client checks features support as defined in Table 38.

Note: If the DUT does not return GetDoorInfoListResponse message, then the following features will be marked as undefined:

- Access Door
- Lock Door
- Unlock Door
- Double Lock Door
- Block Door
- Lock Down Door
- Lock Open Door
- Door Monitor
- Lock Monitor
- Double Lock Monitor
- Alarm
- Tamper
- Fault



Note: Lock Down Door feature support means that both LockDownDoor and LockDownReleaseDoor command are expected to be supported by the DUT.

Note: Lock Open Door feature support means that both LockOpenDoor and LockOpenReleaseDoor command are expected to be supported by the DUT.

Table 38 Door Entity support (GetServices)

Criterion Item	All DoorInfos	
Feature	Supported	Not Supported
Door Entity	Mandatory	-
Access Door	Contains at least one Door with Capabilities.Access = true	Contains no Doors with Capabilities.Access = true
Lock Door	Contains at least one Door with Capabilities.Lock = true	Contains no Doors with Capabilities.Lock = true
Unlock Door	Contains at least one Door with Capabilities.Unlock = true	Contains no Doors with Capabilities.Unlock = true
Double Lock Door	Contains at least one Door with Capabilities.DoubleLock = true	Contains no Doors with Capabilities.DoubleLock = true
Block Door	Contains at least one Door with Capabilities.Block = true	Contains no Doors with Capabilities.Block = true
Lock Down Door	Contains at least one Door with Capabilities.LockDown = true	Contains no Doors with Capabilities.LockDown = true
Lock Open Door	Contains at least one Door with Capabilities.LockOpen = true	Contains no Doors with Capabilities.LockOpen = true
Door Monitor	Contains at least one Door with Capabilities.DoorMonitor = true	Contains no Doors with Capabilities.DoorMonitor = true
Lock Monitor	Contains at least one Door with Capabilities.LockMonitor = true	Contains no Doors with Capabilities.LockMonitor = true

Criterion Item	All DoorInfos	
Feature	Supported	Not Supported
Double Lock Monitor	Contains at least one Door with Capabilities. DoubleLockMonitor = true	Contains no Doors with Capabilities. DoubleLockMonitor = true
Alarm	Contains at least one Door with Capabilities. Alarm = true	Contains no Doors with Capabilities. Alarm = true
Tamper	Contains at least one Door with Capabilities. Tamper = true	Contains no Doors with Capabilities. Tamper = true
Fault	Contains at least one Door with Capabilities. Fault = true	Contains no Doors with Capabilities. Fault = true

Door Control Events support

Door Control Events support under Door Control Service is determined according to the following procedure in conjunction with the above procedure.

Pre-requisite

- This procedure assumes that GetEventPropertiesResponse has already been retrieved via preceding procedure described in Section 5.5.6.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 39.

Note: If the DUT does not return Event Service or GetEventPropertiesResponse message, then the following features will be marked as undefined:

- Door/State/DoorMode
- Door/State/DoorPhysicalState
- Door/State/LockPhysicalState
- Door/State/DoubleLockPhysicalState
- Door/State/DoorAlarm
- Door/State/DoorTamper



- Door/State/DoorFault
- Configuration/Door/Changed
- Configuration/Door/Removed

Table 39 Door Control Events support (GetServices)

Criterion Item	GetEventPropertiesResponse	
Feature	Supported	Not Supported
Door/State/DoorMode	Contains tns1:Door/State/DoorMode Event topic	Does not contain tns1:Door/State/DoorMode Event topic
Door/State/DoorPhysicalState	Contains tns1:Door/State/DoorPhysicalState Event topic	Does not contain tns1:Door/State/DoorPhysicalState Event topic
Door/State/LockPhysicalState	Contains tns1:Door/State/LockPhysicalState Event topic	Does not contain tns1:Door/State/LockPhysicalState Event topic
Door/State/DoubleLockPhysicalState	Contains tns1:Door/State/DoubleLockPhysicalState Event topic	Does not contain tns1:Door/State/DoubleLockPhysicalState Event topic
Door/State/DoorAlarm	Contains tns1:Door/State/DoorAlarm Event topic	Does not contain tns1:Door/State/DoorAlarm Event topic
Door/State/DoorTamper	Contains tns1:Door/State/DoorTamper Event topic	Does not contain tns1:Door/State/DoorTamper Event topic
Door/State/DoorFault	Contains tns1:Door/State/DoorFault Event topic	Does not contain tns1:Door/State/DoorFault Event topic
Configuration/Door/Changed	Contains tns1:Configuration/Door/Changed Event topic	Does not contain tns1:Configuration/Door/Changed Event topic
Configuration/Door/Removed	Contains tns1:Configuration/Door/Removed Event topic	Does not contain tns1:Configuration/Door/Removed Event topic

5.5.16 Access Control Service support

Access Control Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 40.

Note: If GetServicesResponse contains several services with “http://www.onvif.org/ver10/accesscontrol/wsd!” namespace, ONVIF Client will use service with the latest version.

Note: If Access Control service is not supported, the following feature discovery (Area Entity support, Access Point Entity support and sub-features support, Access Control Events support) will be skipped.

Table 40 Access Control Service (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
Access Control Service	Includes service with “http://www.onvif.org/ver10/accesscontrol/wsd1” namespace	Does not include service with “http://www.onvif.org/ver10/accesscontrol/wsd1” namespace

Area Entity support

Area Entity support under Access Control Service is determined according to the following procedure in conjunction with the above procedure.

Discovery Procedure:

1. ONVIF Client gets all AreaInfos from the DUT using Annex A.5 to check Area Entity feature support by DUT.
2. ONVIF Client checks features support as defined in Table 41.

Note: If DUT does not return at least one GetAreaInfoListResponse message, then Area entity feature will be marked as undefined.

Table 41 Area Entity support (GetServices)

Criterion Item	GetAreaInfoListResponse messages	
Feature	Supported	Not Supported
Area Entity	Contains at least one AreaInfo	Contains no AreaInfos

Access Point Entity support and sub-features support

Access Point Entity support and sub-features support under Access Control Service is determined according to the following procedure in conjunction with the above procedure.

Discovery Procedure:

1. Access Point Entity shall be defined as supported as it is a mandatory feature to be supported by DUT.
2. ONVIF Client gets all AccessPointInfos from the DUT using Annex A.4 to check Access Point Entity sub-feature support by DUT.
3. ONVIF Client checks features support as defined in Table 42.



Note: If the DUT does not return at least one GetAccessPointInfoListResponse message, then the following features will be marked as undefined:

- Enable/Disable Access Point feature
- Duress feature
- Access Taken feature
- External Authorization feature
- Anonymous Access feature

Table 42 Access Control Entity support (GetServices)

Criterion Item	All AccessPointInfos	
Feature	Supported	Not Supported
Access Point Entity	Mandatory	-
Enable/Disable Access Point	Contains at least one Access Point Info with Capabilities.DisableAccessPoint = true	Contains no Access Point Info with Capabilities.DisableAccessPoint = true
Duress	Contains at least one Access Point Info with Capabilities.Duress = true	Contains no Access Point Info with Capabilities.Duress = true
Access Taken	Contains at least one Access Point Info with Capabilities.AccessTaken = true	Contains no Access Point Info with Capabilities.AccessTaken = true
External Authorization	Contains at least one Access Point Info with Capabilities.ExternalAuthorization = true	Contains no Access Point Info with Capabilities.ExternalAuthorization = true
Anonymous Access	Contains at least one Access Point Info with Capabilities.AnonymousAccess = true	Contains no Access Point Info with Capabilities.AnonymousAccess = true

Access Control Events support

Access Control Events support under Access Control Service is determined according to the following procedure in conjunction with the above procedure.

Pre-requisite



- This procedure assumes that `GetEventPropertiesResponse` has already been retrieved via preceding procedure described in Section 5.5.6.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 33.

Note: If the DUT does not return Event Service or `GetEventPropertiesResponse` message, then the following features will be marked as undefined:

- `AccessControl/AccessGranted/Anonymous`
- `AccessControl/AccessGranted/Credential`
- `AccessControl/AccessTaken/Anonymous`
- `AccessControl/AccessTaken/Credential`
- `AccessControl/AccessNotTaken/Anonymous`
- `AccessControl/AccessNotTaken/Credential`
- `AccessControl/Denied/Anonymous`
- `AccessControl/Denied/Credential`
- `AccessControl/Denied/CredentialNotFound/Card`
- `AccessControl/Duress`
- `AccessControl/Request/Anonymous`
- `AccessControl/Request/Credential`
- `AccessControl/Request/Timeout`
- `AccessPoint/State/Enabled`
- `Configuration/AccessPoint/Changed`
- `Configuration/AccessPoint/Removed`
- `Configuration/Area/Changed`
- `Configuration/Area/Removed`

Table 43 Access Control Events support (GetServices)

Criterion Item	GetEventPropertiesResponse	
Feature	Supported	Not Supported
AccessControl/AccessGranted/Anonymous	Contains tns1:AccessControl/ AccessGranted/Anonymous Event topic	Does not contain tns1:AccessControl/ AccessGranted/Anonymous Event topic
AccessControl/AccessGranted/Credential	Contains tns1:AccessControl/ AccessGranted/Credential Event topic	Does not contain tns1:AccessControl/ AccessGranted/Credential Event topic
AccessControl/AccessTaken/Anonymous	Contains tns1:AccessControl/ AccessTaken/Anonymous Event topic	Does not contain tns1:AccessControl/ AccessTaken/Anonymous Event topic
AccessControl/AccessTaken/Credential	Contains tns1:AccessControl/ AccessTaken/Credential Event topic	Does not contain tns1:AccessControl/ AccessTaken/Credential Event topic
AccessControl/AccessNotTaken/Anonymous	Contains tns1:AccessControl/ AccessNotTaken/Anonymous Event topic	Does not contain tns1:AccessControl/ AccessNotTaken/Anonymous Event topic
AccessControl/AccessNotTaken/Credential	Contains tns1:AccessControl/ AccessNotTaken/Credential Event topic	Does not contain tns1:AccessControl/ AccessNotTaken/Credential Event topic
AccessControl/Denied/Anonymous	Contains tns1:AccessControl/Denied/ Anonymous Event topic	Does not contain tns1:AccessControl/Denied/ Anonymous Event topic
AccessControl/Denied/Credential	Contains tns1:AccessControl/Denied/ Credential Event topic	Does not contain tns1:AccessControl/Denied/ Credential Event topic
AccessControl/Denied/CredentialNotFound/Card	Contains tns1:AccessControl/Denied/ CredentialNotFound/Card Event topic	Does not contain tns1:AccessControl/Denied/ CredentialNotFound/Card Event topic
AccessControl/Duress	Contains tns1:AccessControl/Duress Event topic	Does not contain tns1:AccessControl/Duress Event topic

Criterion Item	GetEventPropertiesResponse	
Feature	Supported	Not Supported
AccessControl/Request/Anonymous	Contains tns1:AccessControl/Request/Anonymous Event topic	Does not contain tns1:AccessControl/Request/Anonymous Event topic
AccessControl/Request/Credential	Contains tns1:AccessControl/Request/Credential Event topic	Does not contain tns1:AccessControl/Request/Credential Event topic
AccessControl/Request/Timeout	Contains tns1:AccessControl/Request/Timeout Event topic	Does not contain tns1:AccessControl/Request/Timeout Event topic
AccessPoint/State/Enabled	Contains tns1:AccessPoint/State/Enabled Event topic	Does not contain tns1:AccessPoint/State/Enabled Event topic
Configuration/AccessPoint/Changed	Contains tns1:Configuration/AccessPoint/Changed Event topic	Does not contain tns1:Configuration/AccessPoint/Changed Event topic
Configuration/AccessPoint/Removed	Contains tns1:Configuration/AccessPoint/Removed Event topic	Does not contain tns1:Configuration/AccessPoint/Removed Event topic
Configuration/Area/Changed	Contains tns1:Configuration/Area/Changed Event topic	Does not contain tns1:Configuration/Area/Changed Event topic
Configuration/Area/Removed	Contains tns1:Configuration/Area/Removed Event topic	Does not contain tns1:Configuration/Area/Removed Event topic

5.5.17 Advanced Security Service support

Advanced Security Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:



1. ONVIF Client checks features support as defined in Table 44.

Note: If `GetServicesResponse` contains several services with “`http://www.onvif.org/ver10/advancedsecurity/wsd1`” namespace ONVIF Client will use service with the latest version.

Note: If Advanced Security service is not supported, the following feature discovery (Advanced Security features support) will be skipped.

Table 44 Advanced Security Service (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
Advanced Security Service	Includes service with “<code>http://www.onvif.org/ver10/advancedsecurity/wsd1</code>” namespace	Does not include service with “<code>http://www.onvif.org/ver10/advancedsecurity/wsd1</code>” namespace

Advanced Security features support

Keystore, TLS Server, and 802.1X configuration capabilities support under Advanced Security Service is determined according to the following procedure in conjunction with the above procedure.

Discovery Procedure:

1. ONVIF Client invokes `GetServiceCapabilitiesRequest` message to check Advanced Security capabilities support by the DUT.
2. The DUT returns `GetServiceCapabilitiesResponse`. ONVIF Client checks features support as defined in Table 45.

Note: If the DUT does not return `GetServiceCapabilitiesResponse`, then all features defined in Table 45 will be marked as undefined.

Table 45 Advanced Security features support (GetServices)

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
RSA Key Pair Generation	Capabilities. KeystoreCapabilities. RSAKeyPairGeneration = true	Skipped Capabilities. KeystoreCapabilities. RSAKeyPairGeneration or Capabilities.KeystoreCapabilities. RSAKeyPairGeneration = false
PKCS10 External Certification with RSA	Capabilities. KeystoreCapabilities.	Skipped Capabilities. KeystoreCapabilities. PKCS10ExternalCertification

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
	PKCS10ExternalCertificationWithRSA = true	WithRSA or Capabilities. KeystoreCapabilities. PKCS10ExternalCertificationWithRSA = false
Self-Signed Certificate Creation with RSA	Capabilities. KeystoreCapabilities. SelfSignedCertificateCreationWithRSA = true	Skipped Capabilities. KeystoreCapabilities. SelfSignedCertificateCreationWithRSA or Capabilities. KeystoreCapabilities. SelfSignedCertificateCreationWithRSA = false
Passphrase Management	Capabilities. KeystoreCapabilities. MaximumNumberOfPassphrases > 0	Skipped Capabilities. KeystoreCapabilities. MaximumNumberOfPassphrases or Capabilities. KeystoreCapabilities. MaximumNumberOfPassphrases = 0
PKCS8 Container Upload	Capabilities. KeystoreCapabilities. PKCS8RSAKeyPairUpload = true	Skipped Capabilities. KeystoreCapabilities. PKCS8RSAKeyPairUpload or Capabilities. KeystoreCapabilities. PKCS8RSAKeyPairUpload = false
PKCS12 Container Upload	Capabilities. KeystoreCapabilities. PKCS12CertificateWithRSAPrivateKeyUpload = true	Skipped Capabilities. KeystoreCapabilities. PKCS12CertificateWithRSAPrivateKeyUpload or Capabilities. KeystoreCapabilities. PKCS12CertificateWithRSAPrivateKeyUpload = false
CRLs	Capabilities. KeystoreCapabilities. MaximumNumberOfCRLs > 0	Skipped Capabilities. KeystoreCapabilities. MaximumNumberOfCRLs or Capabilities. KeystoreCapabilities. MaximumNumberOfCRLs = 0
Certification path validation policies	Capabilities. KeystoreCapabilities. MaximumNumberOfCertificationPathValidationPolicies > 0	Skipped Capabilities. KeystoreCapabilities. MaximumNumberOfCertificationPathValidationPolicies or Capabilities. KeystoreCapabilities.



Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
		MaximumNumberOfCertificationPathValidationPolicies = 0
TLS WWW client auth extended key usage extension	Capabilities. KeystoreCapabilities. EnforceTLSWebClientAuthExtendedKeyUsage = true	Skipped Capabilities. KeystoreCapabilities. EnforceTLSWebClientAuthExtendedKeyUsage or Capabilities. KeystoreCapabilities. EnforceTLSWebClientAuthExtendedKeyUsage = false
TLS Server Support	Capabilities. TLSServerCapabilities. TLSServerSupported list is not empty	Skipped Capabilities. TLSServerCapabilities. TLSServerSupported or empty Capabilities. TLSServerCapabilities. TLSServerSupported list
TLS client authentication	Capabilities. TLSServerCapabilities. TLSClientAuthSupported = true	Skipped Capabilities. TLSServerCapabilities. TLSClientAuthSupported or Capabilities. TLSServerCapabilities. TLSClientAuthSupported = false

5.5.18 Credential Service support

Credential Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 44.

Note: If GetServicesResponse contains several services with "http://www.onvif.org/ver10/credential/wsd1" namespace, ONVIF Client will use service with the latest version.

Note: If Credential service is not supported, the following feature discovery (Credential features support) will be skipped.

Table 46 Credential Service (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
Credential Service	Includes service with “http://www.onvif.org/ver10/credential/wsd1” namespace	Does not include service with “http://www.onvif.org/ver10/credential/wsd1” namespace

Credential features support

Credential capabilities support under Credential Service is determined according to the following procedure in conjunction with the above procedure.

Discovery Procedure:

1. ONVIF Client invokes GetServiceCapabilitiesRequest message to check Credential capabilities support by the DUT.
2. The DUT returns GetServiceCapabilitiesResponse. ONVIF Client checks features support as defined in Table 47.

Note: If the DUT does not return GetServiceCapabilitiesResponse, then all features defined in Table 47 will be marked as undefined.

Table 47 Credential features support (GetServices)

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
pt:Card	Capabilities. SupportedIdentifierType contains pt:Card	Capabilities. SupportedIdentifierType does not contain pt:Card
pt:PIN	Capabilities. SupportedIdentifierType contains pt:PIN	Capabilities. SupportedIdentifierType does not contain pt:PIN
pt:Fingerprint	Capabilities. SupportedIdentifierType contains pt:Fingerprint	Capabilities. SupportedIdentifierType does not contain pt:Fingerprint
pt:Face	Capabilities. SupportedIdentifierType contains pt:Face	Capabilities. SupportedIdentifierType does not contain pt:Face
pt:Iris	Capabilities. SupportedIdentifierType contains pt:Iris	Capabilities. SupportedIdentifierType does not contain pt:Iris

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
pt:Vein	Capabilities. SupportedIdentifierType contains pt:Vein	Capabilities. SupportedIdentifierType does not contain pt:Vein
Credential Validity	Capabilities. CredentialValiditySupported = true	Capabilities. CredentialValiditySupported = false
Credential Access Profile Validity	Capabilities. CredentialAccessProfileVali ditySupported = true	Capabilities. CredentialAccessProfileValidit ySupported = false
Validity Supports Time Value	Capabilities. ValiditySupportsTimeValue = true	Capabilities. ValiditySupportsTimeValue = false
Reset Antipassback Violation	Capabilities. ResetAntipassbackSupporte d = true	Capabilities. ResetAntipassbackSupported = false

5.5.19 Access Rules Service support

Access Rules Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 48.

Note: If GetServicesResponse contains several services with "http://www.onvif.org/ver10/accessrules/wsd" namespace, ONVIF Client will use service with the latest version.

Note: If Access Rules service is not supported, the following feature discovery (Access Rules features support) will be skipped.

Table 48 Access Rules Service (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
Access Rules Service	Includes service with “http://www.onvif.org/ver10/accessrules/wsd1” namespace	Does not include service with “http://www.onvif.org/ver10/accessrules/wsd1” namespace

Access Rules features support

Access Rules capabilities support under Access Rules Service is determined according to the following procedure in conjunction with the above procedure.

Discovery Procedure:

1. ONVIF Client invokes GetServiceCapabilitiesRequest message to check Access Rules capabilities support by the DUT.
2. The DUT returns GetServiceCapabilitiesResponse. ONVIF Client checks features support as defined in Table 49.

Note: If the DUT does not return GetServiceCapabilitiesResponse, then all features defined in Table 49 will be marked as undefined.

Table 49 Access Rules features support (GetServices)

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
Multiple Schedules per Access Point	Capabilities. MultipleSchedulesPerAccessPointSupported = true	Capabilities. MultipleSchedulesPerAccessPointSupported = false

5.5.20 Schedule Service support

Schedule Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetServicesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:



1. ONVIF Client checks features support as defined in Table 50.

Note: If GetServicesResponse contains several services with “http://www.onvif.org/ver10/schedule/wsd1” namespace, ONVIF Client will use service with the latest version.

Note: If Schedule service is not supported, the following feature discovery (Schedule features support) will be skipped.

Table 50 Schedule Service (GetServices)

Criterion Item	GetServicesResponse	
Feature	Supported	Not Supported
Schedule Service	Includes service with “http://www.onvif.org/ver10/schedule/wsd1” namespace	Does not include service with “http://www.onvif.org/ver10/schedule/wsd1” namespace

Schedule features support

Schedule capabilities support under Schedule Service is determined according to the following procedure in conjunction with the above procedure.

Discovery Procedure:

1. ONVIF Client invokes GetServiceCapabilitiesRequest message to check Schedule capabilities support by the DUT.
2. The DUT returns GetServiceCapabilitiesResponse. ONVIF Client checks features support as defined in Table 51.

Note: If the DUT does not return GetServiceCapabilitiesResponse, then all features defined in Table 51 will be marked as undefined.

Table 51 Schedule features support (GetServices)

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
Extended Recurrence	Capabilities. ExtendedRecurrenceSupported = true	Capabilities. ExtendedRecurrenceSupported = false
Special Days	Capabilities. SpecialDaysSupported = true	Capabilities. SpecialDaysSupported = false

Criterion Item	GetServiceCapabilitiesResponse message	
Feature	Supported	Not Supported
State Reporting	Capabilities. StateReportingSupported = true	Capabilities. StateReportingSupported = false

5.6 Discovery Procedure (GetCapabilities)

If only GetCapabilities is supported by the DUT, then GetCapabilities command will be used for feature discovery procedure. The following provides with the functionality discovery procedure for this case.

5.6.1 Device Service Capabilities configuration functionality in Device Management Service

There are various network configuration functions defined in [ONVIF Core] as a part of ONVIF Device Management Service. The following provides with the functionality discovery procedure which is related to network configuration.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 52.

Note: Absence of Capabilities.Device or Capabilities.Device.Network element in GetCapabilitiesResponse will be regarded as no support for the following functionalities:

- ZeroConfiguration
- IPv6
- IP Filter
- Dynamic DNS
- DHCPv6

Note: Absence of Capabilities.Device or Capabilities.Device.System or Capabilities.Device.Security element in GetCapabilitiesResponse will be regarded as no support for the following functionalities:

- BYE Message
- System logging
- HttpFirmwareUpgrade

Note: Since the DUT does not support GetServices feature, Maximum Users, Maximum Username Length, Maximum Password Length and DefaultAccessPolicy are defined as not supported

Table 52 Device Service Capabilities configuration functionality in Device Management**Service (GetCapabilities)**

Criterion Item	GetCapabilitiesResponse message	
Feature	Supported	Not Supported
IPv6	Capabilities.Device.Network . IPv6Version = true	Skipped Capabilities.Device.Network. IPv6Version or Capabilities.Device.Network. IPv6Version = false
Zero Configuration	Capabilities.Device.Network . ZeroConfiguration = true	Skipped Capabilities.Device.Network. ZeroConfiguration or Capabilities.Device.Network. ZeroConfiguration = false
Dynamic DNS	Capabilities.Device.Network . DynDNS = true	Skipped Capabilities.Device.Network. DynDNS or Capabilities.Device.Network. DynDNS = false
IP Filter	Capabilities.Device.Network . IPFilter = true	Skipped Capabilities.Device. Network.IPFilter or Capabilities.Device.Network. IPFilter = false
Stateful IPv6 DHCP	Capabilities.Device.Network . DHCPv6 = true	Skipped Capabilities.Device. Network.DHCPv6 or Capabilities.Device.Network. DHCPv6 = false
Remote User Handling	Capabilities.Device.Security . Extension.Extension. RemoteUserHandling = true	Skipped Capabilities.Device. Security. Extension.Extension. RemoteUserHandling or Capabilities.Security. Extension.Extension. RemoteUserHandling = false
Bye Message	Capabilities.Device.System. DiscoveryBye = true	Skipped Capabilities.Device. System.DiscoveryBye or Capabilities.Device.System. DiscoveryBye = false
System logging	Capabilities.Device.System. SystemLogging = true	Skipped Capabilities.Device. System.SystemLogging or Capabilities.Device.System. SystemLogging = false

Criterion Item	GetCapabilitiesResponse message	
Feature	Supported	Not Supported
Http Firmware Upgrade	Capabilities.System.Extension.HttpFirmwareUpgrade = true	Skipped Capabilities.System.Extension.HttpFirmwareUpgrade or Capabilities.System.Extension.HttpFirmwareUpgrade = false
Http System Backup	Capabilities.System.Extension.HttpSystemBackup = true	Skipped Capabilities.System.Extension.HttpSystemBackup or Capabilities.System.Extension.HttpSystemBackup = false
Http System Logging	Capabilities.System.Extension.HttpSystemLogging = true	Skipped Capabilities.System.Extension.HttpSystemLogging or Capabilities.System.Extension.HttpSystemLogging = false
Http Support Information	Capabilities.System.Extension.HttpSupportInformation = true	Skipped Capabilities.System.Extension.HttpSupportInformation or Capabilities.System.Extension.HttpSupportInformation = false

5.6.2 Security (HTTP digest authentication) support

In the first version of [ONVIF Core], WS-UsernameToken support was the only method defined as a mandatory feature for user authentication. This has been changed in the later version of [ONVIF Core] where it also defines the HTTP digest authentication support as a mandatory feature.

The following discovery procedure will be performed for ONVIF Client to determine which user authentication function will be used in conformance testing.

Discovery Procedure:

1. ONVIF Client invokes request message for command with security support without any user authentication (no WS-Security and no HTTP digest authentication) to check HTTP digest authentication support.
2. ONVIF Client checks features support as defined in Table 53.

Note: The command which is being used for this discovery procedure should be provided before performing the steps.

Note: If HTTP digest authentication is assumed as supported, the HTTP digest authentication scheme will be used in the following feature discovery procedure whenever necessary as well as in conformance testing.

Table 53 HTTP digest authentication (GetCapabilities)

Criterion Item	Command with security support response message	
Feature	Supported	Not Supported
HTTP digest	HTTP 401 Unauthorized error	Not HTTP 401 Unauthorized error

5.6.3 NTP support

Whether the DUT supports NTP functionality is determined by the following discovery procedure.

Discovery Procedure:

1. ONVIF Client invokes GetNTPRequest.
2. ONVIF Client checks features support as defined in Table 54.

Note: In any other case than the above, NTP function support will be marked as undefined.

Table 54 NTP functionality (GetCapabilities)

Criterion Item	GetNTPResponse	
Feature	Supported	Not Supported
NTP	DUT returns GetNTP Response	DUT returns any SOAP fault

5.6.4 I/O functionality in Device Management Service

I/O related functionality support can be retrieved by checking correspondent element of GetCapabilitiesResponse. The following is the procedure to determine the function support.

Pre-requisite

- This procedure assumes that GetCapabilitiesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client invokes GetCapabilitiesRequest to check I/O functionality support.
2. ONVIF Client receives GetCapabilitiesResponse and checks features support as defined in Table 55.
3. ONVIF Client invokes GetRelayOutputsRequest message to retrieve a relay output list.
4. The DUT returns GetRelayOutputsResponse with a list of relay outputs.



5. ONVIF Client invokes SetRelayOutputSettingsRequest message (RelayOutputToken = “[first token from GetRelayOutputsResponse]”, Properties.Mode = “Bistable”, Properties.DelayTime = “PT30S”, Properties.IdleState = “open”).
6. ONVIF Client receives SetRelayOutputSettingsResponse.
7. ONVIF Client invokes SetRelayOutputSettingsRequest message (RelayOutputToken = “[first token from GetRelayOutputsResponse]”, Properties.Mode = “Bistable”, Properties.DelayTime = “PT30S”, Properties.IdleState = “closed”).
8. ONVIF Client receives SetRelayOutputSettingsResponse.
9. ONVIF Client invokes SetRelayOutputSettingsRequest message (RelayOutputToken = “[first token from GetRelayOutputsResponse]”, Properties.Mode = “Monostable”, Properties.DelayTime = “PT30S”, Properties.IdleState = “open”).
10. ONVIF Client receives SetRelayOutputSettingsResponse.
11. ONVIF Client invokes SetRelayOutputSettingsRequest message (RelayOutputToken = “[first token from GetRelayOutputsResponse]”, Properties.Mode = “Monostable”, Properties.DelayTime = “PT30S”, Properties.IdleState = “closed”).
12. ONVIF Client receives SetRelayOutputSettingsResponse.
13. ONVIF Client checks features support as defined in Table 56.

Note: Absence of Capabilities.Device.IO element in the GetCapabilitiesResponse will be defined as absence of Capabilities.Device.IO.RelayOutputs.

Note: If Capabilities.Device element is not included in the GetCapabilitiesResponse, Relay Outputs feature will be marked as unsupported.

Note: If DUT does not return GetRelayOutputsResponse or a list of relay outputs in the GetRelayOutputsResponse is empty, Relay Outputs features will be marked as undefined.

Note: If GetCapabilities command is not supported by the DUT, I/O feature for Device Management Service will be defined as unsupported.

Table 55 Relay Outputs in Device Management Service (GetCapabilities)

Criterion Item	GetCapabilitiesResponse message	
Feature	Supported	Not Supported
RelayOutputs	Capabilities.Device.IO. RelayOutputs > 0	Skipped Capabilities.Device.IO. RelayOutputs or Capabilities. Device.IO.RelayOutputs = 0

Table 56 Relay Outputs Mode and Idle State in Device Management Service (GetCapabilities)

Criterion Item	SetRelayOutputSettingsResponse	
Feature	Supported	Not Supported
Bistable Mode/Open Idle State	DUT returns SetRelayOutputSettings Response for step 6	DUT returns any SOAP fault for step 6
Bistable Mode/Closed Idle State	DUT returns SetRelayOutputSettings Response for step 8	DUT returns any SOAP fault for step 8
Bistable Mode	DUT returns SetRelayOutputSettings Response for step 6 or 8	DUT returns any SOAP fault for step 6 and 8
Monostable Mode/Open Idle State	DUT returns SetRelayOutputSettings Response for step 9	DUT returns any SOAP fault for step 9
Monostable Mode/Closed Idle State	DUT returns SetRelayOutputSettings Response for step 11	DUT returns any SOAP fault for step 11
Monostable Mode	DUT returns SetRelayOutputSettings Response for step 9 or 11	DUT returns any SOAP fault for step 9 and 11

5.6.5 Monitoring Events support

Monitoring Events support under Device Control Service is determined according to the following procedure.

Pre-requisite

- This procedure assumes that GetEventPropertiesResponse has already been retrieved via preceding procedure described in Section 5.5.6.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 57.

Note: If the DUT does not return Event Service or GetEventPropertiesResponse message, then the following features will be marked as undefined:

- Monitoring/ProcessorUsage
- Monitoring/OperatingTime/LastReset



- Monitoring/OperatingTime/LastReboot
- Monitoring/OperatingTime/LastClockSynchronization
- Monitoring/Backup/Last
- Device/HardwareFailure/TemperatureCritical
- Device/HardwareFailure/FanFailure
- Device/HardwareFailure/PowerSupplyFailure
- Device/HardwareFailure/StorageFailure

Table 57 Monitoring Events support (GetCapabilities)

Criterion Item	GetEventPropertiesResponse	
Feature	Supported	Not Supported
Monitoring/ProcessorUsage	Contains tns1:Monitoring/ProcessorUsage Event topic	Does not contain tns1:Monitoring/ProcessorUsage Event topic
Monitoring/OperatingTime/LastReset	Contains tns1:Monitoring/OperatingTime/LastReset Event topic	Does not contain tns1:Monitoring/OperatingTime/LastReset Event topic
Monitoring/OperatingTime/LastReboot	Contains tns1:Monitoring/OperatingTime/LastReboot Event topic	Does not contain tns1:Monitoring/OperatingTime/LastReboot Event topic
Monitoring/OperatingTime/LastClockSynchronization	Contains tns1:Monitoring/OperatingTime/LastClockSynchronization Event topic	Does not contain tns1:Monitoring/OperatingTime/LastClockSynchronization Event topic
Monitoring/Backup/Last	Contains tns:Monitoring/Backup/Last Event topic	Does not contain tns:Monitoring/Backup/Last Event topic
Device/HardwareFailure/TemperatureCritical	Contains tns1:Device/HardwareFailure/TemperatureCritical Event topic	Does not contain tns1:Device/HardwareFailure/TemperatureCritical Event topic
Device/HardwareFailure/FanFailure	Contains tns1:Device/HardwareFailure/FanFailure Event topic	Does not contain tns1:Device/HardwareFailure/FanFailure Event topic

Criterion Item	GetEventPropertiesResponse	
Feature	Supported	Not Supported
Device/HardwareFailure/PowerSupplyFailure	Contains tns1:Device/HardwareFailure/PowerSupplyFailure Event topic	Does not contain tns1:Device/HardwareFailure/PowerSupplyFailure Event topic
Device/HardwareFailure/StorageFailure	Contains tns1:Device/HardwareFailure/StorageFailure Event topic	Does not contain tns1:Device/HardwareFailure/StorageFailure Event topic

5.6.6 Media Service – general

Media Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetCapabilitiesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

ONVIF Client checks features support as defined in

1. Table 58.

Note: If Media service is not supported, the following feature discovery (Media Service features support) will be skipped.

Table 58 Media Service – general (GetCapabilities)

Criterion Item	GetCapabilitiesResponse	
Feature	Supported	Not Supported
Media Service	Includes Capabilities.Media element	Does not include Capabilities.Media element

Media Service – Video encoding support

Video encoding function support in Media Service is determined according to the following procedure.

Discovery Procedure:



1. ONVIF Client invokes `GetVideoEncoderConfigurationOptionsRequest` (no `ConfigurationToken`, no `ProfileToken`) message to retrieve all supported codecs.
2. The DUT returns `GetVideoEncoderConfigurationOptionsResponse` with a list of supported codecs. ONVIF Client checks features support as defined in Table 59.

Note: If the DUT does not return `GetVideoEncoderConfigurationOptionsResponse`, MPEG4 and H.264 feature will be marked as undefined.

Table 59 Media Service – Video encoding support (GetCapabilities)

Criterion Item	GetVideoEncoderConfigurationOptionsResponse	
Feature	Supported	Not Supported
JPEG	Mandatory functionality	-
MPEG-4	Includes Options.MPEG4	Does not include Options.MPEG4
H.264	Includes Options.H264	Does not include Options.H264

Media Service – Audio encoding support

Audio encoding function support in Media Service is determined according to the following procedure.

Discovery Procedure:

1. ONVIF Client invokes `GetAudioEncoderConfigurationOptionsRequest` (no `ConfigurationToken`, no `ProfileToken`) message to retrieve all supported audio codecs.
2. The DUT returns `GetAudioEncoderConfigurationOptionsResponse` with a list of supported codecs or SOAP fault. ONVIF Client checks features support as defined in Table 60.

Note: If the DUT returns no response for `GetAudioEncoderConfigurationOptionsRequest`, Audio encoding feature will be marked as undefined.

Table 60 Media Service – Audio encoding support (GetCapabilities)

Criterion Item	GetAudioEncoderConfigurationOptionsResponse	
Feature	Supported	Not Supported
Audio encoding	DUT returns GetAudioEncoder ConfigurationOptions Response	DUT returns any SOAP fault
G.711	DUT returns GetAudioEncoder	DUT returns any SOAP fault

Criterion Item	GetAudioEncoderConfigurationOptionsResponse	
Feature	Supported	Not Supported
	ConfigurationOptions Response	
G.726	Includes Options.Options.Encoding = "G726"	Does not include Options.Options.Encoding = "G726"
AAC	Includes Options.Options.Encoding = "AAC"	Does not include Options.Options.Encoding = "AAC"

Media Service – Real-time streaming

Since the DUT does not support GetServices feature Real-time streaming feature will be defined as supported.

Media Service – Supported Real-time streaming Setup

Which Real-time streaming Setup is supported under Real-time Streaming is determined according to the following procedure.

Discovery Procedure:

1. ONVIF Client invokes GetCapabilitiesRequest message to check Multicast streaming capability support by the DUT.
2. The DUT returns GetCapabilitiesResponse. ONVIF Client checks features support as defined in Table 61.

Note: If DUT does not return GetCapabilitiesResponse then RTP Multicast streaming (UDP) and RTP/RTSP/TCP Setup features will be marked as undefined.

Table 61 Media Service – Supported Real-time streaming Setup (GetCapabilities)

Criterion Item	GetCapabilitiesResponse message	
Feature	Supported	Not Supported
RTP/UDP	Mandatory functionality	-
RTP/RTSP/HTTP	Mandatory functionality	-
RTP/RTSP/TCP	Capabilities. Media.StreamingCapabilities. RTP_RTSP_TCP = true	Skipped Capabilities. Media.StreamingCapabilities. RTP_RTSP_TCP or Capabilities.

Criterion Item	GetCapabilitiesResponse message	
Feature	Supported	Not Supported
		StreamingCapabilities.RTP_RTSP_TCP = false
RTP-Multicast/UDP	Capabilities.Media.StreamingCapabilities.RTPMulticast = true	Skipped Capabilities.Media.StreamingCapabilities.RTPMulticast or Capabilities.Media.StreamingCapabilities.RTPMulticast = false

Media Service - GetSnapshotUri

GetSnapshotUri function support is determined according to the following procedure.

Discovery Procedure:

1. ONVIF Client invokes GetProfilesRequest message to retrieve an existing Media Profiles list.
2. The DUT returns GetProfilesResponse with the list of existing Media Profiles.
3. ONVIF Client looks for ready-to-use profile (a profile with VideoSourceConfiguration and VideoEncoderConfiguration in the GetProfilesResponse. If there are no ready-to-use profiles found in the GetProfilesResponse, ONVIF Client marks GetSnapshotUri support by the DUT as undefined.
4. ONVIF Client invokes GetSnapshotUriRequest (ProfileToken = found ready-to-use profile token) message to get Snapshot URI.
5. The DUT returns GetSnapshotUriResponse or SOAP fault. ONVIF Client checks features support as defined in Table 62.

Note: If no GetProfilesResponse is returned by the DUT, GetSnapshotUri function support by the DUT is marked as undefined.

Note: If no GetSnapshotUriResponse or SOAP fault is returned by the DUT, GetSnapshotUri function support by the DUT is marked as undefined.

Table 62 Media Service – GetSnapshotUri (GetCapabilities)

Criterion Item	GetSnapshotUriResponse	
Feature	Supported	Not Supported
GetSnapshotUri	DUT returns GetSnapshotUriResponse	DUT returns any SOAP fault

Media Service – Audio outputs support

Audio outputs support in conjunction with its Audio decoding function is determined according to the following procedure.

Discovery Procedure:

1. ONVIF Client invokes GetAudioOutputsRequest message to retrieve an Audio outputs list.
2. The DUT returns GetAudioOutputsResponse or SOAP fault. ONVIF Client checks features support as defined in Table 63. Go to the next feature definition.
3. ONVIF Client invokes GetAudioDecoderConfigurationOptionsRequest (no ConfigurationToken, no ProfileToken) message to retrieve all supported Audio codecs for decoding by the DUT.
4. The DUT returns GetAudioDecoderConfigurationOptionsResponse. ONVIF Client checks features support as defined in Table 64.

Note: If the DUT does not return GetAudioDecoderConfigurationOptionsResponse, ONVIF Client assumes that G.711, G.726 and AAC Audio decoding function support is marked as undefined.

Table 63 Media Service – Audio outputs support (GetCapabilities)

Criterion Item	GetAudioOutputsResponse	
Feature	Supported	Not Supported
Audio output	DUT returns GetAudioOutputsResponse and there are at least one AudioOutput on the list	DUT returns any SOAP fault or GetAudioOutputsResponse and there are no AudioOutput on the list

Table 64 Media Service – Audio outputs decoding support (GetCapabilities)

Criterion Item	GetAudioDecoderConfigurationOptionsResponse	
Feature	Supported	Not Supported
G.711	Includes Options.G711DecOptions	Does not include Options.G711DecOptions
G.726	Includes Options.G726DecOptions	Does not include Options.G726DecOptions
AAC	Includes Options.AACDecOptions	Does not include Options.AACDecOptions

5.6.7 Event Service

Event Service shall be defined as supported as it is a mandatory feature to be supported by the DUT. The following procedure will be used as pre-requisite for other features support check.

Since the DUT does not support GetServices feature, Event Service sub-features will be defined as described below:

- Persistent Notification Storage under Event Service is not supported by the DUT.
- WS Basic Notification under Event Service is supported by the DUT.
- GetServiceCapabilities\MaxPullPoints capability is not supported by the DUT.

5.6.8 Device IO Service

Device IO Service feature support is determined according to the following procedure.

Since the DUT does not support GetServices feature, the following Device IO Service sub-features will be defined as described below:



- Digital Inputs under Device IO Service is not supported by the DUT.

Pre-requisite

- This procedure assumes that GetCapabilitiesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 65.

Note: If the Device IO Service feature is not supported by the DUT, the following feature discovery (Relay outputs support) will be skipped.

Table 65 Device IO Service (GetCapabilities)

Criterion Item	GetCapabilitiesResponse	
Feature	Supported	Not Supported
Device IO Service	Includes Extension.DeviceIO element	Does not include Extension.DeviceIO element

Relay outputs support

Relay outputs support under Device IO Service is determined according to the following procedure in conjunction with the above procedure.

Pre-requisite

- This procedure assumes that GetCapabilitiesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 66.

Table 66 Relay outputs support (GetCapabilities)

Criterion Item	GetCapabilitiesResponse message	
Feature	Supported	Not Supported
Relay Outputs	Capabilities.Extension.DevicelO.RelayOutputs > 0	Capabilities.Extension.DevicelO.RelayOutputs = 0



5.6.9 PTZ Service support

PTZ Service support is defined according to the following procedure.

Pre-requisite

- This procedure assumes that GetCapabilitiesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 67.

Note: If PTZ service is not supported, the following feature discovery (Various functions support and Fixed / Configurable Home Position support) will be skipped.

Table 67 PTZ Service (GetCapabilities)

Criterion Item	GetCapabilitiesResponse	
Feature	Supported	Not Supported
PTZ Service	Includes Capabilities.PTZ element	Does not include Capabilities.PTZ element

Various functions support in PTZ Service

The number of function support in PTZ Service is determined according to the following procedure.

Pre-requisite

- A PTZNode which is used in the function discovery procedure should be provided prior to the execution of the procedure. Otherwise, ONVIF Client will invoke GetNodesRequest message to get the PTZNodes that can be used for the procedure and the first PTZNode present in GetNodesResponse will be used in the procedure. In case PTZNode token is provided, ONVIF Client will use the provided PTZNode token to derive PTZNode via GetNodeRequest.
- Continuous move function is considered as supported if the DUT supports PTZ Service feature.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 68.

Note: If neither GetPTZNodesResponse nor GetPTZNodeResponse is returned correctly by the DUT, all functions support under PTZ Service is marked as undefined.

Table 68 Various functions support in PTZ Service (GetCapabilities)

Criterion Item	First PTZNode from GetNodesResponse or PTZNode from GetNodeResponse	
Feature	Supported	Not Supported
Continuous Pan/Tilt movement	SupportedPTZSpaces. ContinuousPanTiltVelocitySpace element is present	SupportedPTZSpaces. ContinuousPanTiltVelocitySpace element is not present
Continuous Zoom movement	SupportedPTZSpaces. ContinuousZoomVelocitySpace element is present	SupportedPTZSpaces. ContinuousZoomVelocitySpace element is not present
Continuous movement	Mandatory	-
Absolute Pan/Tilt movement	SupportedPTZSpaces. AbsolutePanTiltPositionSpace element is present	SupportedPTZSpaces. AbsolutePanTiltPositionSpace element is not present
Absolute Zoom movement	SupportedPTZSpaces. AbsoluteZoomPositionSpace element is present	SupportedPTZSpaces. AbsoluteZoomPositionSpace element is not present
Absolute movement	Absolute Pan/Tilt movement or Absolute Zoom movement is supported	Absolute Pan/Tilt movement and Absolute Zoom movement is not supported
Relative Pan/Tilt movement	SupportedPTZSpaces. RelativePanTiltTranlationSpace element is present	SupportedPTZSpaces. RelativePanTiltTranlationSpace element is not present
Relative Zoom movement	SupportedPTZSpaces. RelativeZoomTranlationSpace element is present	SupportedPTZSpaces. RelativeZoomTranlationSpace element is not present
Relative movement	Relative Pan/Tilt movement or Relative Zoom movement is supported	Relative Pan/Tilt movement and Relative Zoom movement is not supported
Speed configuration function for Pan/Tilt movement	SupportedPTZSpaces. PanTiltSpeedSpace element is present	SupportedPTZSpaces. PanTiltSpeedSpace element is not present
Speed configuration function for Zoom movement	SupportedPTZSpaces. ZoomSpeedSpace element is present	SupportedPTZSpaces. ZoomSpeedSpace element is not present
Preset position	MaximumNumberOfPresets > 0	MaximumNumberOfPresets = 0

Criterion Item	First PTZNode from GetNodesResponse or PTZNode from GetNodeResponse	
Feature	Supported	Not Supported
Auxiliary operation	AuxiliaryCommands element is present	AuxiliaryCommands element is not present
Home Position	HomeSupported = true	HomeSupported = false

Fixed / Configurable Home Position support

In case Home Position function is supported by the DUT, either Fixed or Configurable Home Position shall be supported by DUT. The following defines the discovery procedure to determine which Home Position function is supported by the DUT.

Pre-requisite

- This procedure assumes that Media Service has already been retrieved via preceding procedure described in Section 5.2.
- A PTZNode which is used in the function discovery procedure should be provided prior to the execution of the procedure. Otherwise, ONVIF Client will invoke GetNodesRequest message to get the PTZNodes that can be used for the procedure and the first PTZNode present in GetNodesResponse will be used in the procedure. In case PTZNode token is provided, ONVIF Client will use the provided PTZNode token to derive PTZNode via GetNodeRequest.

Discovery Procedure:

1. ONVIF Client invokes GetConfigurationsRequest message to retrieve PTZNodes list.
2. The DUT returns GetConfigurationsResponse with the list of PTZConfiguration that contains PTZNode. ONVIF Client identifies the first PTZConfiguration which has the corresponding PTZNode with the provided PTZNode.
3. ONVIF Client either selects or creates Media Profile anew along with the identified PTZConfiguration. Refer to Annex A.1 for the details.
4. ONVIF Client invokes SetHomePositionRequest (ProfileToken = selected or newly created profile token) message to check Configurable Home Position is supported by the DUT.
5. ONVIF Client checks features support as defined in Table 69.
6. ONVIF Client restores Media Profiles setting in case it changes some of the Media Profiles configuration.

Note: If Media Service is not supported by the DUT Fixed and Configurable Home Position features will be marked as undefined.

Table 69 Fixed / Configurable Home Position support (GetCapabilities)

Criterion Item	SetHomePositionResponse	
Feature	Supported	Not Supported
Configurable Home Position	DUT returns SetHomePositionResponse	DUT returns SOAP fault
Fixed Home Position	DUT returns SOAP fault	DUT returns SetHomePositionResponse

5.6.10 Imaging Service support

Imaging Service feature support is determined according to the following procedure.

Pre-requisite

- This procedure assumes that GetCapabilitiesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 70.

Table 70 Imaging Service (GetCapabilities)

Criterion Item	GetCapabilitiesResponse	
Feature	Supported	Not Supported
Imaging Service	Includes Capabilities.Imaging element	Does not include Capabilities.Imaging element

IrCutfilterConfiguration function support in Imaging Service

IrCutfilterConfiguration function support in Imaging Service is determined according to the following procedure.

Pre-requisite

- This procedure assumes that Media Service address or DeviceIO Service address were received from the DUT

Discovery Procedure:

1. ONVIF Client invokes GetVideoSourcesRequest message to retrieve all video sources from the DUT.



2. The DUT returns GetVideoSourcesResponse message with a list of existing Video Sources.
3. ONVIF Client invokes GetOptionsRequest message (VideoSourceToken = VideoSourceToken1, where VideoSourceToken1 is the first token of the Video Source in GetVideoSourcesResponse) to retrieve all supported parameters from the DUT.
4. The DUT returns GetOptionsResponse message.
5. ONVIF Client checks IrCutfilterConfiguration feature support as defined in Table 71.
6. If IrCutfilterConfiguration is supported by the VideoSourceToken1, ONVIF Client skips other steps and assumes that IrCutfilterConfiguration feature is supported by the DUT.
7. If IrCutfilterConfiguration is not supported by the VideoSourceToken1, then ONVIF Client repeats steps 3-7 for the next not tested VideoSourceToken. If there is no untested VideoSourceToken, then ONVIF Client assumes that IrCutfilterConfiguration feature is not supported by the DUT.

Note: If neither Media service, nor DeviceIO service are supported, the following feature discovery (IrCutfilter Configuration) will be skipped and assumed as not supported.

Table 71 IrCutfilterConfiguration function support in Imaging Service (GetCapabilities)

Criterion Item	At least one VideoSourceToken from GetVideoSources	
Feature	Supported	Not Supported
IrCutfilter	At least two IrCutFilterModes elements are present in GetOptionsResponse.ImagingOptions and one of them equal to OFF	GetOptionsResponse.ImagingOptions does not contain at least two IrCutFilterModes elements or GetOptionsResponse.ImagingOptions does not contain IrCutFilterModes equal to OFF

5.6.11 Video Analytics Service support

Video Analytics Service feature support is determined according to the following procedure.

Pre-requisite

- This procedure assumes that GetCapabilitiesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 72.

Table 72 Video Analytics Service (GetCapabilities)

Criterion Item	GetCapabilitiesResponse	
Feature	Supported	Not Supported
Video Analytics Service	Includes Capabilities.Analytics element	Does not include Capabilities.Analytics element

5.6.12 Recording Control Service support

Recording Control Service feature support is determined according to the following procedure.

Pre-requisite

- This procedure assumes that GetCapabilitiesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

- ONVIF Client checks features support as defined in Table 73.

Note: If Recording Control service is not supported, the following feature discovery (Dynamic Recordings, Dynamic Tracks, Recording Options and Audio Recording features support) will be skipped.

Table 73 Recording Control Service (GetCapabilities)

Criterion Item	GetCapabilitiesResponse	
Feature	Supported	Not Supported
Recording Control Service	Includes Capabilities.Extension.Recording	Does not include Capabilities.Extension.Recording
Dynamic Recordings	Extension.Recording.DynamicRecordings = true	Extension.Recording.DynamicRecordings = false
Dynamic Tracks	Extension.Recording.DynamicTracks = true	Extension.Recording.DynamicTracks = false
Audio Recording	-	Not supported
Recording Options	-	Not supported

Criterion Item	GetCapabilitiesResponse	
Feature	Supported	Not Supported
tns1:RecordingConfig/DeleteTrackData	GetEventProperties contains tns1:RecordingConfig/DeleteTrackData topic	GetEventProperties doesn't contain tns1:RecordingConfig/DeleteTrackData topic

5.6.13 Recording Search Service support

Recording Search Service feature support is determined according to the following procedure.

Pre-requisite

- This procedure assumes that GetCapabilitiesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

ONVIF Client checks features support as defined in

Table 74.

Note: If Recording Search service is not supported, the following feature discovery (Metadata Search and PTZ search features support) will be skipped.

Table 74 Recording Search Service (GetCapabilities)

Criterion Item	GetCapabilitiesResponse	
Feature	Supported	Not Supported
Recording Search Service	Includes Capabilities.Extension.Search	Does not include Capabilities.Extension.Search
Metadata Search	Capabilities.Extension.Search.MetadataSearch = true	Capabilities.Extension.Search.MetadataSearch = false

Metadata Recording support

Metadata Recording support is determined according to the following procedure in conjunction with the above procedure.

Pre-requisite



- This procedure assumes that GetCapabilitiesResponse has already been retrieved via preceding procedure described in Section 5.2.
- A Recording which is used in the function discovery procedure should be provided prior to the execution of the procedure (see Annex A.3 Recording Environment Pre-Requisite in the Replay Control Test Specification).

Discovery Procedure:

1. ONVIF Client invokes GetRecordingInformationRequest message for recording to check that this recording contains metadata track with data.
2. The DUT returns GetRecordingInformationResponse. ONVIF Client checks features support as defined in.

Note: If the DUT does not return GetRecordingInformationResponse, then Metadata Recording feature will be marked as undefined.

Note: If the DUT does not support Recording Search Service, then Metadata Recording feature will be marked as undefined.

Note: If the DUT does not support Recording Search Service and Recording Control Service, then Metadata Recording feature will be defined as not supported.

Table 75 Metadata Recording support (GetCapabilities)

Criterion Item	GetRecordingInformationResponse	
Feature	Supported	Not Supported
Metadata Search	Contains at least one Track with TrackType = “Metadata” and DataFrom is less than DataTo for this Track	Does not contain at any Track with TrackType = “Metadata” or for all Tracks with TrackType = “Metadata” DataFrom is not less than DataTo for this Track

PTZ Position search support

PTZ Position Search support under Recording Search Service is determined according to the following procedure in conjunction with the above procedure.

Pre-requisite

- A Recording which is used in the function discovery procedure should be provided via GetRecordingInformation command prior to the execution of the procedure (see Annex A.3 Recording Environment Pre-Requisite in the Replay Control Test Specification).

Discovery Procedure:



1. ONVIF Client invokes FindPTZPositionRequest message (StartPoint = [start point of recording], Scope.IncludedRecordings = [recording token], SearchFilter = [any], KeepAliveTime) to check PTZ Search support by the DUT.
2. If the DUT returns any SOAP fault, ONVIF Client assumes that PTZ Search feature is not supported by the DUT. Otherwise, ONVIF Client marks PTZ Search will be defined as supported.

Note: If the DUT does not return GetRecordingInformationResponse, then PTZ Position Search feature will be marked as undefined.

Note: If RecordingInformation.EarliestRecording is not included in GetRecordingInformationResponse message, then minimum value of Track.DataFrom will be used as StartPoint.

Table 76 PTZ Position search support (GetCapabilities)

Criterion Item	FindPTZPositionResponse	
Feature	Supported	Not Supported
Metadata Search	DUT returns FindPTZPositionResponse	DUT returns SOAP fault

5.6.14 Replay Service support

Replay Service feature support is determined according to the following procedure.

Pre-requisite

- This procedure assumes that GetCapabilitiesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 77.

Note: If Replay service is not supported, the following feature discovery (Reverse Replay features support) will be skipped.

Table 77 Replay Service (GetCapabilities)

Criterion Item	GetCapabilitiesResponse	
Feature	Supported	Not Supported
Replay Service	Includes Capabilities.Extension.Replay element	Does not include Capabilities.Extension.Replay element

Criterion Item	GetCapabilitiesResponse	
Feature	Supported	Not Supported
Reverse Replay	-	Not Supported
RTP/RTSP/TCP	-	Not Supported

5.6.15 Receiver Service support

Receiver Service feature support is determined according to the following procedure.

Pre-requisite

- This procedure assumes that GetCapabilitiesResponse has already been retrieved via preceding procedure described in Section 5.2.

Discovery Procedure:

1. ONVIF Client checks features support as defined in Table 78.

Table 78 Receiver Service (GetCapabilities)

Criterion Item	GetCapabilitiesResponse	
Feature	Supported	Not Supported
Receiver Service	Includes Capabilities.Extension.Receiver element	Does not include Capabilities.Extension.Receiver element

5.6.16 Door Control Service support

Since the DUT does not support GetServices feature Door Control Service feature will be defined as not supported.

5.6.17 Access Control Service support

Since the DUT does not support GetServices feature Access Control Service feature will be defined as not supported.



5.6.18 Advanced Security Service support

Since the DUT does not support GetServices feature Advanced Security Service feature will be defined as not supported.

5.6.19 Credential Service support

Since the DUT does not support GetServices feature Credential Service feature will be defined as not supported.

5.6.20 Access Rules Service support

Since the DUT does not support GetServices feature Access Rules Service feature will be defined as not supported.

5.6.21 Schedule Service support

Since the DUT does not support GetServices feature Schedule Service feature will be defined as not supported.

5.7 Devices scopes retrieval via GetDeviceScopes

Device scopes provided via GetDeviceScopes may indicate referenced Profiles by the DUT in case the DUT supports a certain profile. The following is the procedure to identify referenced Profile(s) by the DUT. For the details on how the retrieved scope will be used for Profile checking, refer to the specific document.

Discovery Procedure:

1. ONVIF Client invokes GetScopesRequest message to retrieve a device scope list.
2. ONVIF Client preserves the device scope list to determine the referenced Profiles.

Note: If the DUT does not return GetScopesResponse, ONVIF Client regards that the device scope is defined as empty.

5.8 Devices information retrieval via GetDeviceInformation

General device information provided via GetDeviceScopes is required for report generation. The following is the procedure to identify DUT information.

Discovery Procedure:



1. ONVIF Client invokes `GetDeviceInformationRequest` message to retrieve device information.
2. ONVIF Client preserves the device information.

Note: If the DUT does not return `GetDeviceInformationResponse`, ONVIF Client regards the device information as undefined.



Annex A

This chapter details out some specific topic which is related to feature discovery procedure described above.

A.1 Selection / Creation of Media Profile that contains PTZConfiguration

The following procedure describes the way to either select or create Media Profile which adds PTZConfiguration.

Procedure:

1. Retrieve media profiles by invoking GetProfilesRequest message. Check whether a list of profiles in the GetProfilesResponse contains identified PTZConfiguration.
2. If no media profile contains identified PTZConfiguration, select one media profile whose fixed attribute is set to false and which already adds VideoSourceConfiguration and VideoEncoderConfiguration. Add PTZConfiguration to the media profile by invoking AddPTZConfiguration command.
3. If no media profile is present to meet the above condition, create new media profile with VideoSourceConfiguration and VideoEncoderConfiguration by invoking CreateProfile, AddVideoSourceConfiguration and AddVideoEncoderConfiguration command. After that, add PTZConfiguration to the media profile by invoking AddPTZConfiguration command.

A.2 Media2 Service - Media Profile Configuration for PTZ Control

For the execution of PTZ control test cases, ONVIF Client has to select and configure the media profile as follows.


1. ONVIF Client invokes GetProfilesRequest with Type="PTZ" as input parameter in Media2 Service address.
2. The DUT sends GetProfilesResponse with list of profiles.
3. ONVIF Client selects a profile with PTZ Configuration is not empty in GetProfilesResponse and returns this profile to the test.
4. If there is no profile with PTZ Configuration in GetProfilesResponse then ONVIF Client selects first profile in GetProfilesResponse, saves this profile in **Profile1** variable and runs the following steps:
 - 4.1. ONVIF Client invokes GetConfigurationsRequest in PTZ Service address.
 - 4.2. The DUT sends GetConfigurationsResponse with the list of PTZ Configurations.
 - 4.3. ONVIF Client selects first PTZ Configuration in the GetConfigurationsResponse, saves this configuration in **PTZConfiguration1** variable and runs the following steps:
 - 4.4. ONVIF Client invokes AddConfigurationRequest with ProfileToken = **Profile1** token, Configuration Type = "PTZ" and Configuration Token = **PTZConfiguration1** token in Media2 Service address.
 - 4.5. The DUT sends AddConfigurationResponse.



4.6. ONVIF Client invokes GetConfigurationOptions with ConfigurationToken = **PTZConfiguration1** token.

4.7. The DUT sends GetConfigurationOptionsResponse.

4.8. ONVIF Client stops the annex and return **Profile1** variable to the test.



A.3 Get Complete Door Info List

The following algorithm will be used to get a complete list of Doors:

1. ONVIF Client will invoke GetDoorInfoListRequest message (no Limit, no StartReference) to retrieve the first part of Door Information list from the DUT.
2. Verify the GetDoorInfoListResponse message from the DUT.



3. If GetDoorInfoListResponse message contains NextStartReference, repeat steps 1-2 with StartReference = **[current NextStartReference]**. Otherwise, skip other steps and finalize getting complete door list.

The complete ordered list of doors with information will be made by the means of uniting all GetDoorInfoListResponse messages. Also, the total number of doors will be calculated.

A.4 Get Complete Access Point Info List

The following algorithm will be used to get a complete list of Access Points:

1. ONVIF Client will invoke GetAccessPointInfoListRequest message (no Limit, no StartReference) to retrieve the first part of Access Point Information list from the DUT.
2. Verify the GetAccessPointInfoListResponse message from the DUT.
3. If GetAccessPointInfoListResponse message contains NextStartReference, repeat steps 1-2 with **StartReference = [current NextStartReference]**. Otherwise, skip other steps and finalize getting complete access point list.

The complete ordered list of access points with information will be made by the means of uniting all GetAccessPointInfoListResponse messages. Also, the total number of access points will be calculated.

A.5 Get Complete Area Info List

The following algorithm will be used to get a complete list of Areas:

1. ONVIF Client will invoke GetAreaInfoListRequest message (no Limit, no StartReference) to retrieve the first part of Area Information list from the DUT.
2. Verify the GetAreaInfoListResponse message from the DUT.
3. If GetAreaInfoListResponse message contains NextStartReference, repeat steps 1-2 with StartReference = [current NextStartReference]. Otherwise, skip other steps and finalize getting complete area list.

The complete ordered list of areas with information will be made by the means of uniting all GetAreaInfoListResponse messages. Also, the total number of areas will be calculated.