

# ONVIF™

# **Imaging Client Test Specification**

Version 18.06

June 2018

www.onvif.org

#### © 2018 ONVIF, Inc. All rights reserved.

Recipients of this document may copy, distribute, publish, or display this document so long as this copyright notice, license and disclaimer are retained with all copies of the document. No license is granted to modify this document.

THIS DOCUMENT IS PROVIDED "AS IS," AND THE CORPORATION AND ITS MEMBERS AND THEIR AFFILIATES, MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THIS DOCUMENT ARE SUITABLE FOR ANY PURPOSE; OR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

IN NO EVENT WILL THE CORPORATION OR ITS MEMBERS OR THEIR AFFILIATES BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES, ARISING OUT OF OR RELATING TO ANY USE OR DISTRIBUTION OF THIS DOCUMENT, WHETHER OR NOT (1) THE CORPORATION, MEMBERS OR THEIR AFFILIATES HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, OR (2) SUCH DAMAGES WERE REASONABLY FORESEEABLE, AND ARISING OUT OF OR RELATING TO ANY USE OR DISTRIBUTION OF THIS DOCUMENT. THE FOREGOING DISCLAIMER AND LIMITATION ON LIABILITY DO NOT APPLY TO, INVALIDATE, OR LIMIT REPRESENTATIONS AND WARRANTIES MADE BY THE MEMBERS AND THEIR RESPECTIVE AFFILIATES TO THE CORPORATION AND OTHER MEMBERS IN CERTAIN WRITTEN POLICIES OF THE CORPORATION.



# **REVISION HISTORY**

Vers.	Date	Description		
18.06	Jun 21, 2018	Reformatting document using new template		
18.06	May 22, 2018	Tampering feature updated according to #246		
18.06	Apr 28, 2018	Tampering feature updated according to #246		
18.06	Apr 05, 2018	'Required Number of Devices Summary' Annex added according to #241		
18.06	Feb 14, 2018	The following were updated in the scope of #241:		
		Feature Level Requirement (updated with new rules)		
		Each Feature Level Requirement (updated with Check Condition based on Device Features and Required Number of Devices)		
17.12 Aug 15, 2017		, 2017 Requirement level of Profile T of the following features was changed from Mandatory to Cconditional according to #220:		
		Focus Move Capabilities		
		Focus Control		
17.06	Jun 15, 2017	Links in Normative references section were updated.		
17.06	May 22, 2017	Motion Alarm Test Cases added.		
17.06	Mar 22, 2017	Tampering Test Cases added.		
Intr		Introduction section updated.		
17.06 Mar 17, 2017 Profile T Normative Reference were added for features:		Profile T Normative Reference were added for the following features:		
		Get Imaging Setting, Imaging Settings Configuration, Focus Move Capabilities		
16.07	Mar 14, 2016	www.onvif.org was removed from Copyright section.		
te		The following step was removed from SETIMAGINGSETTINGS-2 test case: [S4] It invoked for the same Device as for the Client SetImagingSettings request		
		Steps with checking that settings from the SetImagingSettings request correspond options from GetOptionsResponse were removed from SETIMAGINGSETTINGS-2 test case		
16.01	Dec 21, 2016	16 Focus Control Test Cases was splitted on two parts (Focus Move Capabilities Test Cases and Focus Control Test Cases) to handle Device capabilities issue.		
16.01	Dec 18, 2016	Get Imaging Capabilities Test Cases feature definition was updated		
15.10	Oct 20, 2016	Initial version:		
		General parts added		
		Get Imaging Capabilities Test Cases added		
		Video Sources List Test Cases added		



Get Imaging Settings Test Cases added
Imaging Settings Configuration Test Cases added
Focus Control Test Cases added

### **Table of Contents**

1	Intro	ductior	۱	. 7
	1.1	Scop	e	7
	1.2	Get Ir	naging Capabilities	7
	1.3	Get Ir	naging Settings	8
	1.4	Imagi	ng Settings Configuration	8
	1.5	Focus	Move Capabilities	8
	1.6	Focus	s Control	8
	1.7	Tamp	ering	. 8
	1.8	Motio	n Alarm	8
2	Norm	native r	eferences	9
3	Term	s and I	Definitions	10
	3.1	Conv	entions	10
	3.2	Defin	itions	10
	3.3	Abbre	eviations	10
	3.4	Name	espaces	11
4	Test	Overvi	ew	12
	4.1	Gene	ral	12
	4	4.1.1	Feature Level Requirement	12
	4	4.1.2	Expected Scenarios Under Test 1	12
	4	4.1.3	Test Cases	13
	4.2	Test	Setup	13
	4.3	Prere	quisites	13
5	Get l	maging	Capabilities Test Cases 1	15
	5.1	Featu	re Level Requirement:	15
	5.2	Expec	ted Scenarios Under Test: 1	15
	5.3	GET	CAPABILITIES	15
	5.4	GET	SERVICE CAPABILITIES 1	16
6	Get I	maging	Settings Test Cases	18
	6.1	Featu	re Level Requirement:	18
	6.2	Expec	ted Scenarios Under Test: 1	18

# **ONVIF**<sup>®</sup> | Standardizing IP Connectivity for Physical Security

	6.3	GET IMAGING SETTINGS	18
7	Imagiı	ng Settings Configuration Test Cases	20
	7.1	Feature Level Requirement:	20
	7.2	Expected Scenarios Under Test:	20
	7.3	GET OPTIONS	20
	7.4	SET IMAGING SETTINGS	21
8	Focus	Move Capabilities Test Cases	23
	8.1	Feature Level Requirement:	23
	8.2	Expected Scenarios Under Test:	23
	8.3	GET FOCUS MOVE OPTIONS	23
9	Focus	S Control Test Cases	25
	9.1	Feature Level Requirement:	25
	9.2	Expected Scenarios Under Test:	25
	9.3	ABSOLUTE FOCUS MOVE	25
	9.4	RELATIVE FOCUS MOVE	27
	9.5	CONTINUOUS FOCUS MOVE	29
	9.6	STOP	. 31
10	Tam	pering Test Cases	. 33
	10.1	Feature Level Normative Reference:	33
	10.2	Expected Scenarios Under Test:	33
11	Moti	on Alarm Test Cases	34
	11.1	Feature Level Normative Reference:	34
	11.2	Expected Scenarios Under Test:	34
Α	Test	for Appendix A	35
	A.1	Required Number of Devices Summary	35

# **1** Introduction

The goal of the ONVIF Test Specification set is to make it possible to realize fully interoperable IP physical security implementations from different vendors. This specification also acts as an input document to the development of a test tool which will be used to test the ONVIF Client implementation conformance towards ONVIF standard. This Client Test Tool analyzes network communications between ONVIF Devices and Clients being tested and determines whether a specific Client is ONVIF conformant (see ONVIF Conformance Process Specification).

This particular document defines test cases required for testing Imaging Service features of a Client application e.g. Get Imaging Capabilities, Video Sources List, Get Imaging Settings, Imaging Settings Configuration, Focus Control. It also describes the test framework, test setup, prerequisites, test policies needed for the execution of the described test cases.

### 1.1 Scope

This ONVIF Imaging Client Test Specification defines and regulates the conformance testing procedure for the ONVIF conformant Clients in the scope of Imaging Service features. Conformance testing is meant to be black-box network traces analysis and verification. The objective of this specification is to provide the test cases to test individual requirements of ONVIF Clients in the scope of Imaging Service features according to ONVIF Imaging Service Specification.

The principal intended purposes are:

- Provide self-assessment tool for implementations.
- Provide comprehensive test suite coverage for Imaging Service features.

This specification **does not** address the following:

- 3rd parties Client use cases
- Non-functional (performance and regression) testing and analysis.
- SOAP Implementation Interoperability test i.e. Web Services Interoperability Basic Profile version 2.0 (WS-I BP2.0).
- Network protocol implementation Conformance test for HTTPS and HTTP protocols.

The following sections cover test cases needed for the verification of relevant features as mentioned in the ONVIF Profile Specifications.

## 1.2 Get Imaging Capabilities

Get Imaging Capabilities section specifies Client ability to request imaging capabilities from Device.

### 1.3 Get Imaging Settings

Get Imaging Settings section specifies Client ability to request imaging settings from Device.

### 1.4 Imaging Settings Configuration

Imaging Settings Configuration section specifies Client ability to change imaging settings on Device.

### 1.5 Focus Move Capabilities

Focus Move Capabilities section specifies Client ability to retrieve focus move capabilities from Device.

### 1.6 Focus Control

Focus Control section specifies Client ability to control focus on Device.

### 1.7 Tampering

Tampering section specifies Client ability to receive notifications of Tampering events.

### 1.8 Motion Alarm

Motion Alarm section specifies Client ability to receive notifications of motion alarm event.

#### Standardizing IP Connectivity for Physical Security

## 2 Normative references

ONVIF Conformance Process Specification:

https://www.onvif.org/profiles/conformance/

• ONVIF Profile Policy:

https://www.onvif.org/profiles/

• ONVIF Core Specifications:

https://www.onvif.org/profiles/specifications/

ONVIF Core Client Test Specification:

https://www.onvif.org/profiles/conformance/client-test/

• ONVIF Imaging Specification:

https://www.onvif.org/profiles/specifications/

ISO/IEC Directives, Part 2, Annex H:

http://www.iso.org/directives

• ISO 16484-5:2014-09 Annex P:

https://www.iso.org/obp/ui/#!iso:std:63753:en

• W3C SOAP 1.2, Part 1, Messaging Framework:

http://www.w3.org/TR/soap12-part1/

• W3C XML Schema Part 1: Structures Second Edition:

http://www.w3.org/TR/xmlschema-1/

• W3C XML Schema Part 2: Datatypes Second Edition:

http://www.w3.org/TR/xmlschema-2/

# **3** Terms and Definitions

### 3.1 Conventions

The key words "shall", "shall not", "should", "should not", "may", "need not", "can", "cannot" in this specification are to be interpreted as described in [ISO/IEC Directives Part 2].

### 3.2 Definitions

This section describes terms and definitions used in this document.

Profile	See ONVIF Profile Policy.		
ONVIF Device	Computer appliance or software program that exposes one or multiple ONVIF Web Services.		
ONVIF Client	Computer appliance or software program that uses ONVIF Web Services.		
Conversation	A Conversation is all exchanges between two MAC addresses that contains SOAP request and response.		
Network	A network is an interconnected group of devices communicating using the Internet protocol.		
Network Trace Capture file	Data file created by a network protocol analyzer software (such as Wireshark). Contains network packets data recorded during a live network communications.		
SOAP	SOAP is a lightweight protocol intended for exchanging structured information in a decentralized, distributed environment. It uses XML technologies to define an extensible messaging framework providing a message construct that can be exchanged over a variety of underlying protocols.		
Client Test Tool	ONVIF Client Test Tool that tests ONVIF Client implementation towards the ONVIF Test Specification set.		
Imaging Service	Services for exposure time, gain and white balance parameters among others.		
Image Stabilization	Functionality used to avoid blurring of images due to movement of the device or its objects.		
Tone Compensation	Functionality used to make the image with dark or bright areas to be more visible.		
Defogging	Functionality used to make the image more detailed in presence of fog.		
Valid Device Response	Device has responded to specific request with code HTTP or RTSP 200 OK and SOAP fault message has not appeared.		

### 3.3 Abbreviations

This section describes abbreviations used in this document.

- HTTP Hyper Text Transport Protocol.
- HTTPS Hyper Text Transport Protocol over Secure Socket Layer.
- **URI** Uniform Resource Identifier.
- **WSDL** Web Services Description Language.
- **XML** eXtensible Markup Language.

### 3.4 Namespaces

Prefix and namespaces used in this test specification are listed in Table 1. These prefixes are not part of the standard and an implementation can use any prefix.

### Table 3.1. Defined namespaces in this specification

Prefix	Namespace URI	Description
soapenv	http://www.w3.org/2003/05/soap- envelope	Envelope namespace as defined by SOAP 1.2 [SOAP 1.2, Part 1]
xs	http://www.w3.org/2001/XMLSchema	Instance namespace as defined by XS [XML- Schema, Part1] and [XMLSchema,Part 2]
xsi	http://www.w3.org/2001/XMLSchema- instance	XML schema instance namespace
tns1	http://www.onvif.org/ver10/topics	The namespace for the ONVIF topic namespace
tt	http://www.onvif.org/ver10/schema	ONVIF XML schema descriptions
tds	http://www.onvif.org/ver10/device/wsdl	The namespace for the WSDL device service
trt	http://www.onvif.org/ver10/media/wsdl	The namespace for the WSDL media service
timg	http://www.onvif.org/ver20/imaging/wsd	The namespace for the WSDL imaging service

# 4 Test Overview

This section provides information for the test setup procedure and required prerequisites that should be followed during test case execution.

An ONVIF client with Imaging features support can provide image settings configuration and focus control.

An ONVIF Profile is described by a fixed set of functionalities through a number of services that are provided by the ONVIF standard. A number of services and functionalities are mandatory for each type of ONVIF Profile. An ONVIF Device and ONVIF Client may support any combination of Profiles and other optional services and functionalities.

### 4.1 General

Test Cases are grouped depending on features. Each Test Cases group provides description of feature requirement level for Profiles, expected scenario under test and related test cases:

- Feature Level Normative Reference
- Expected Scenarios Under Test
- List of Test Cases

### 4.1.1 Feature Level Requirement

Feature Level Requirement item contains a feature ID, check condition based on Device features, required number of Devices and feature requirement level for the Profiles, which will be used for Profiles conformance.

To claim this Feature as supported Client shall pass Expected Scenario Under Test:

- · for each Device, which supports Device Features defined in Check Condition Based on **Device Features**
- · for at least with number of Devices specified in Required Number of Devices

If Feature Level Requirement is defined as Mandatory for some Profile, Client shall support this Feature to claim this Profile Conformance.

### 4.1.2 Expected Scenarios Under Test

Expected Scenarios Under Test item contains expected scenario under test, conditions when the feature will be defined as supported and as not supported.

### 4.1.3 Test Cases

Test Case items contain list of test cases which are related to feature. Test cases provide exact procedure of testing feature support conditions.

Each Test Case contains the following parts:

- Test Label Unique label for each test
- Test Case ID Unique ID for each test
- Profile Normative References Normative Reference level for the feature under test is defined in Profile Specification. This reference is informative and will not be used in conformance procedure.
- Feature Under Test Feature which is under current test. Typically a particular command or an event.
- Test Purpose The purpose of current test case.
- Pre-Requisite The pre-requisite defines when the test should be performed. In case if prerequisite does not match, the test result will be NOT DETECTED.
- Test Procedure scenario expected to be reflected in network trace file.
- Test Result Passed and failed criteria of the test case. Depending on these criteria test result will be defined as PASSED or FAILED.
- Validated Feature List list of features ID related to this test case.

### 4.2 Test Setup

Collect Network Traces files required by the test cases.

Collect Feature List XML files for Devices detected in the Network Trace files.

Client shall support all mandatory and conditional features listed in the Device Feature List XML file supplied for the Profiles supported by the Client.

For ONVIF compatibility, the ONVIF Client shall follow the requirements of the conformance process. For details please see the latest ONVIF Conformance Process Specification.

### 4.3 Prerequisites

The pre-requisites for executing the test cases described in this Test Specification include:



The Device shall be configured with an IPv4 address.

The Device shall be able to be discovered by the Client.

# **5** Get Imaging Capabilities Test Cases

### 5.1 Feature Level Requirement:

Validated Feature: GetImagingCapabilities

Check Condition based on Device Features: Imaging Service is supported by Device.

### **Required Number of Devices:** 1

### 5.2 Expected Scenarios Under Test:

- 1. Client connects to Device to retrieve a imaging capabilities.
- 2. Client is considered as supporting Get Imaging Capabilities if the following conditions are met:
  - Client is able to retrieve a imaging capabilities using GetCapabilities operation OR GetServiceCapabilities operation (Imaging Service) OR supports get\_services\_capabilities.get\_services feature.
- 3. Client is considered as NOT supporting Get Imaging Capabilities if ANY of the following is TRUE:
  - No valid responses for **GetCapabilities** request if detected AND Device supportes GetCapabilities feature OR
  - No valid responses for **GetServiceCapabilities** request (Imaging Service) if detected AND Device supportes GetServices feature
  - No **GetCapabilities** valid responses for request AND no valid **GetServiceCapabilities** responses for request (Imaging Service) AND get services capabilities.get services feature is not supported by Client.

### 5.3 GET CAPABILITIES

Test Label: Get Imaging Capabilities - Get Capabilities

Test Case ID: GETIMAGINGCAPABILITIES-1

Feature Under Test: Get Capabilities

**Test Purpose:** To verify that imaging capabilities provided by Device is received by Client using the **GetCapabilities** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with GetCapabilities operation with tds:Category element equal to "All" OR "Imaging" OR without any tds:Category element present.
- Device supports Imaging Service.

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetCapabilities request message with tds:Category element equal to "All" OR "Imaging" OR without any tds:Category element to retrieve imaging capabilities from the Device.
- 2. Device responds with code HTTP 200 OK and GetCapabilitiesResponse message.

#### **Test Result:**

### PASS -

- Client GetCapabilities request messages are valid according to XML Schemas listed in Namespaces AND
- Client GetCapabilities request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tds:GetCapabilities AND
  - [S2] IF it contains any tds:Category element THEN it contains tds:Category element equal to "All" OR "Imaging" AND
- Device response on the **GetCapabilities** request fulfills the following requirements:
  - · [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element tds:GetCapabilitiesResponse.

### FAIL -

• The Client failed PASS criteria.

Validated Feature List: GetImagingCapabilities.GetImgCapabilities

### 5.4 GET SERVICE CAPABILITIES

Test Label: Get Imaging Capabilities - Get Service Capabilities

Test Case ID: GETIMAGINGCAPABILITIES-2

Feature Under Test: Get Services

**Test Purpose:** To verify that imaging capabilities provided by Device is received by Client using the **GetServiceCapabilities** operation.

### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetServiceCapabilities** operation for Imaging Service present.
- Device supports Imaging Service.

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetServiceCapabilities** request message to retrieve imaging capabilities from the Device.
- 2. Device responds with code HTTP 200 OK and **GetServiceCapabilitiesResponse** message.

#### **Test Result:**

### PASS -

- Client GetServiceCapabilities request messages are valid according to XML Schemas listed in Namespaces AND
- Client GetServiceCapabilities request in Test Procedure fulfills the following requirements:
  [S1] soapenv:Body element has child element timg:GetServiceCapabilities AND
- Device response on the **GetServiceCapabilities** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element timg:GetServiceCapabilitiesResponse.

#### FAIL -

• The Client failed PASS criteria.

Validated Feature List: GetImagingCapabilities.GetImgServiceCapabilities

# 6 Get Imaging Settings Test Cases

### 6.1 Feature Level Requirement:

Validated Feature: GetImagingSettings

Check Condition based on Device Features: Imaging Service is supported by Device.

**Required Number of Devices:** 3

Profile T Requirement: Mandatory

### 6.2 Expected Scenarios Under Test:

- 1. Client connects to Device to retrieve a current imaging settings.
- 2. Client is considered as supporting Get Imaging Settings if the following conditions are met:
  - Client is able to retrieve a current imaging settings using **GetImagingSettings** operation.
- 3. Client is considered as NOT supporting Get Imaging Settings if ANY of the following is TRUE:
  - No valid responses for GetImagingSettings request.

### 6.3 GET IMAGING SETTINGS

Test Label: Get Imaging Settings - Get Imaging Settings

Test Case ID: GETIMAGINGSETTINGS-1

Profile T Normative Reference: Mandatory

Feature Under Test: Get Imaging Settings

**Test Purpose:** To verify that imaging settings for Device is received by Client using the **GetImagingSettings** operation.

Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetImagingSettings** operation present.
- Device supports Imaging Service.

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetImagingSettings** request message to retrieve imaging settings for specified video source from the Device.
- 2. Device responds with code HTTP 200 OK and GetImagingSettingsResponse message.

#### **Test Result:**

#### PASS -

- Client GetImagingSettings request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetImagingSettings** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element timg:GetImagingSettings AND
- Device response on the GetImagingSettings request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element timg:GetImagingSettingsResponse.

### FAIL -

• The Client failed PASS criteria.

Validated Feature List: GetImagingSettings.GetImgSettings

# 7 Imaging Settings Configuration Test Cases

### 7.1 Feature Level Requirement:

Validated Feature: SetImagingSettings

Check Condition based on Device Features: Imaging Service is supported by Device.

#### **Required Number of Devices:** 3

Profile T Requirement: Mandatory

### 7.2 Expected Scenarios Under Test:

- 1. Client connects to Device to change imaging settings.
- 2. Client is considered as supporting Imaging Settings Configuration if the following conditions are met:
  - · Client is able to retrieve a imaging options using GetOptions operation AND
  - Client is able to change a imaging settings using **SetImagingSettings** operation.
- 3. Client is considered as NOT supporting Imaging Settings Configuration if ANY of the following is TRUE:
  - No valid responses for GetOptions request OR
  - No valid responses for SetImagingSettings request OR
  - There is no **GetOptions** request for the same video source token as used in **SetImagingSettings** request.

### 7.3 GET OPTIONS

Test Label: Get Imaging Settings - Get Options

Test Case ID: SETIMAGINGSETTINGS-1

Profile T Normative Reference: Mandatory

Feature Under Test: Get Options

**Test Purpose:** To verify that imaging options for Device is received by Client using the **GetOptions** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetOptions** operation present.
- Device supports Imaging Service.

### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetOptions** request message to retrieve imaging options for specified video source from the Device.
- 2. Device responds with code HTTP 200 OK and GetOptionsResponse message.

#### Test Result:

### PASS -

- Client GetOptions request messages are valid according to XML Schemas listed in Namespaces AND
- Client GetOptions request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element timg:GetOptions AND
- Device response on the **GetOptions** request fulfills the following requirements:
  - · [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element timg:GetOptionsResponse.

#### FAIL -

• The Client failed PASS criteria.

Validated Feature List: GetImagingSettings.GetOptions

### 7.4 SET IMAGING SETTINGS

Test Label: Set Imaging Settings - Set Imaging Settings

Test Case ID: SETIMAGINGSETTINGS-2

Profile T Normative Reference: Mandatory

Feature Under Test: Set Imaging Settings

**Test Purpose:** To verify that Client is able to change imaging settings on Device using the **SetImagingSettings** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **SetImagingSettings** operation present.
- Device supports Imaging Service.

### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetOptions** request message to retrieve imaging options for specified video source from the Device.
- 2. Device responds with code HTTP 200 OK and GetOptionsResponse message.
- 3. Client invokes **SetImagingSettings** request message to change imaging settings for specified video source which correspond to the retrieved options on the Device.
- 4. Device responds with code HTTP 200 OK and SetImagingSettingsResponse message.

### **Test Result:**

#### PASS -

- Client SetImagingSettings request messages are valid according to XML Schemas listed in Namespaces AND
- Client SetImagingSettings request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element timg:SetImagingSettings AND
- Device response on the **SetImagingSettings** request fulfills the following requirements:
  - · [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element timg:SetImagingSettingsResponse AND
- There is a Client GetOptions request in Test Procedure that fulfills the following requirements:
  - [S4] **timg:VideoSourceToken** element value is equal to **timg:VideoSourceToken** element from the **SetImagingSettings** request AND
  - [S5] It is invoked before the Client SetImagingSettings request AND
- Device response on the GetOptions request fulfills the following requirements:
  - [S6] It has HTTP 200 response code AND
  - [S7] soapenv:Body element has child element timg:GetOptionsResponse.

### FAIL -

• The Client failed PASS criteria.

Validated Feature List: GetImagingSettings.SetImagingSettingsRequest

# 8 Focus Move Capabilities Test Cases

### 8.1 Feature Level Requirement:

Validated Feature: GetMoveOptions

Check Condition based on Device Features: Imaging Service is supported by Device.

#### **Required Number of Devices:** 1

Profile T Requirement: Conditional

### 8.2 Expected Scenarios Under Test:

- 1. Client connects to Device to get focus move capabilities.
- Client is considered as supporting Focus Move Capabilities if the following conditions are met:
  - · Client is able to retrieve a focus move options using GetMoveOptions operation AND
- 3. Client is considered as NOT supporting Focus Move Capabilities if ANY of the following is TRUE:
  - No valid responses for GetMoveOptions request OR

### 8.3 GET FOCUS MOVE OPTIONS

Test Label: Get Move Options

Test Case ID: GETMOVEOPTIONS-1

Profile T Normative Reference: Conditional

Feature Under Test: Get Move Options

**Test Purpose:** To verify that Client is able retrive focus move capabilities from Device using the **GetMoveOptions** operation.

### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetMoveOptions** operation present.
- Device supports Imaging Service.

www.onvif.org

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetMoveOptions** request message to retrieve focus move options for specified video source from the Device.
- 2. Device responds with code HTTP 200 OK and GetMoveOptionsResponse message.

#### **Test Result:**

#### PASS -

- Client GetMoveOptions request messages are valid according to XML Schemas listed in Namespaces AND
- Client GetMoveOptions request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element timg:GetMoveOptions AND
- Device response on the GetMoveOptions request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element timg:GetMoveOptionsResponse.

### FAIL -

• The Client failed PASS criteria.

Validated Feature List: GetMoveOptions.GetFocusMoveOptions

# 9 Focus Control Test Cases

### 9.1 Feature Level Requirement:

Validated Feature: FocusControl

Check Condition based on Device Features: Focus Control is supported by Device.

### **Required Number of Devices:** 1

Profile T Requirement: Conditional

### 9.2 Expected Scenarios Under Test:

- 1. Client connects to Device to control focus.
- 2. Client is considered as supporting Focus Control if the following conditions are met:
  - Client supports get\_move\_options feature AND
  - Client is able to invoke Absolute OR Relative OR Continuous focus move using Move operation AND
  - If Client is able to invoke Continuous focus move Client is able to invoke stop focus move using **Stop** operation.
- 3. Client is considered as NOT supporting Focus Control if ANY of the following is TRUE:
  - Client does not support get\_move\_options feature OR
  - No valid responses for Move request OR
  - Move request contains settings which does not correspong to GetMoveOptions message for the same video source token OR
  - No valid responses for Stop request if Stop request is supported by the Client OR
  - **Stop** request is not supported, in the case Continuous focus move is supported by the Client.

### 9.3 ABSOLUTE FOCUS MOVE

Test Label: Focus Control - Absolute Focus Move

Test Case ID: FOCUSCONTROL-1

www.onvif.org

#### Profile T Normative Reference: Conditional

#### Feature Under Test: Absolute Focus Move

**Test Purpose:** To verify that Client is able retrive absolute focus move on Device using the **Move** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **Move** operation with **tt:Absolute** element present.
- Device supports Imaging Service.

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetMoveOptions** request message to retrieve focus move options for specified video source from the Device.
- 2. Device responds with code HTTP 200 OK and GetMoveOptionsResponse message.
- 3. If **GetMoveOptionsResponse** message contains **tt:Absolute** element Client invokes **Move** request message for specified video source with **tt:Absolute** element with parameters which are correspond to the resieved focus move options to start absolute focus movement on the Device.
- 4. Device responds with code HTTP 200 OK and MoveResponse message.

#### **Test Result:**

#### PASS -

- Client Move request messages are valid according to XML Schemas listed in Namespaces AND
- Client **Move** request in Test Procedure fulfills the following requirements:
  - [S1] **soapenv:Body** element has child element **timg:Move** AND
  - [S2] It contains timg:Focus/tt:Absolute element AND
- Device response on the **Move** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element timg:MoveResponse AND
- There is a Client **GetMoveOptions** request in Test Procedure fulfills the following requirements:
  - [S5] It invoked for the same Device as for the Client Move request AND
  - [S6] It invoked before the Client Move request AND

- [S7] **timg:VideoSourceToken** element value is equal to **timg:VideoSourceToken** element from the **Move** request AND
- Device response on the **GetMoveOptions** request fulfills the following requirements:
  - [S8] It has HTTP 200 response code AND
  - [S9] soapenv:Body element has child element timg:GetMoveOptionsResponse AND
  - [S10] It contains timg:MoveOptions\tt:Absolute element AND
- Settings from the **Move** request corresponds options recieved in the **GetMoveOptionsResponse** message:
  - [S11] timg:Focus/tt:Absolute/tt:Position element value from the Move request is less or equal to timg:MoveOptions/tt:Absolute/tt:Position/tt:Max from the the GetMoveOptionsResponse message AND
  - [S12] timg:Focus/tt:Absolute/tt:Position element value from the Move request is greater or equal to timg:MoveOptions/tt:Absolute/tt:Position/tt:Min from the the GetMoveOptionsResponse message AND
  - [S13] IF the Move request contains timg:Focus/tt:Absolute/tt:Speed element THEN:
    - The GetMoveOptionsResponse message contains timg:MoveOptions/tt:Absolute/ tt:Speed element AND
    - timg:Focus/tt:Absolute/tt:Speed element value from the Move request is less or equal to timg:MoveOptions/tt:Absolute/tt:Speed/tt:Max from the the GetMoveOptionsResponse message AND
    - timg:Focus/tt:Absolute/tt:Speed element value from the Move request is greater or equal to timg:MoveOptions/tt:Absolute/tt:Speed/tt:Min from the the GetMoveOptionsResponse message.

### FAIL -

• The Client failed PASS criteria.

Validated Feature List: FocusControl.AbsoluteFocusMove

### 9.4 RELATIVE FOCUS MOVE

Test Label: Focus Control - Relative Focus Move

Test Case ID: FOCUSCONTROL-2

Profile T Normative Reference: Conditional

Feature Under Test: Relative Focus Move

**Test Purpose:** To verify that Client is able retrive relative focus move on Device using the **Move** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **Move** operation with **tt:Relative** element present.
- Device supports Imaging Service.

### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetMoveOptions** request message to retrieve focus move options for specified video source from the Device.
- 2. Device responds with code HTTP 200 OK and GetMoveOptionsResponse message.
- If GetMoveOptionsResponse message contains tt:Relative element Client invokes Move request message for specified video source with tt:Relative element with parameters which are correspond to the resieved focus move options to start relative focus movement on the Device.
- 4. Device responds with code HTTP 200 OK and MoveResponse message.

### **Test Result:**

### PASS -

- Client Move request messages are valid according to XML Schemas listed in Namespaces AND
- Client **Move** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element timg:Move AND
  - [S2] It contains timg:Focus/tt:Relative element AND
- Device response on the **Move** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element timg:MoveResponse AND
- There is a Client **GetMoveOptions** request in Test Procedure fulfills the following requirements:
  - [S5] It invoked for the same Device as for the Client Move request AND
  - [S6] It invoked before the Client Move request AND
  - [S7] **timg:VideoSourceToken** element value is equal to **timg:VideoSourceToken** element from the **Move** request AND
- Device response on the **GetMoveOptions** request fulfills the following requirements:
  - [S8] It has HTTP 200 response code AND

- [S9] soapenv:Body element has child element timg:GetMoveOptionsResponse AND
- [S10] It contains timg:MoveOptions\tt:Relative element AND
- Settings from the **Move** request corresponds options recieved in the **GetMoveOptionsResponse** message:
  - [S11] timg:Focus/tt:Relative/tt:Distance element value from the Move request is less or equal to timg:MoveOptions/tt:Relative/tt:Distance/tt:Max from the the GetMoveOptionsResponse message AND
  - [S12] timg:Focus/tt:Relative/tt:Distance element value from the Move request is greater or equal to timg:MoveOptions/tt:Relative/tt:Distance/tt:Min from the the GetMoveOptionsResponse message AND
  - [S13] IF the Move request contains timg:Focus/tt:Relative/tt:Speed element THEN:
    - The GetMoveOptionsResponse message contains timg:MoveOptions/tt:Relative/ tt:Speed element AND
    - timg:Focus/tt:Relative/tt:Speed element value from the Move request is less or equal to timg:MoveOptions/tt:Relative/tt:Speed/tt:Max from the the GetMoveOptionsResponse message AND
    - timg:Focus/tt:Relative/tt:Speed element value from the Move request is greater or equal to timg:MoveOptions/tt:Relative/tt:Speed/tt:Min from the the GetMoveOptionsResponse message.

#### FAIL -

• The Client failed PASS criteria.

Validated Feature List: FocusControl.RelativeFocusMove

### 9.5 CONTINUOUS FOCUS MOVE

Test Label: Focus Control - Continuous Focus Move

Test Case ID: FOCUSCONTROL-3

Profile T Normative Reference: Conditional

Feature Under Test: Continuous Focus Move

**Test Purpose:** To verify that Client is able retrive continuous focus move on Device using the **Move** operation.

#### Pre-Requisite:

• The Network Trace Capture files contains at least one Conversation between Client and Device with **Move** operation with **tt:Continuous** element present.

• Device supports Imaging Service.

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetMoveOptions request message to retrieve focus move options for specified video source from the Device.
- 2. Device responds with code HTTP 200 OK and GetMoveOptionsResponse message.
- If GetMoveOptionsResponse message contains tt:Continuous element Client invokes Move request message for specified video source with tt:Relative element with parameters which are correspond to the resieved focus move options to start continuous focus movement on the Device.
- 4. Device responds with code HTTP 200 OK and MoveResponse message.

#### Test Result:

#### PASS -

- Client Move request messages are valid according to XML Schemas listed in Namespaces AND
- Client **Move** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element timg:Move AND
  - [S2] It contains timg:Focus/tt:Continuous element AND
- Device response on the Move request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element timg:MoveResponse AND
- There is a Client **GetMoveOptions** request in Test Procedure fulfills the following requirements:
  - [S5] It invoked for the same Device as for the Client Move request AND
  - [S6] It invoked before the Client Move request AND
  - [S7] **timg:VideoSourceToken** element value is equal to **timg:VideoSourceToken** element from the **Move** request AND
- Device response on the GetMoveOptions request fulfills the following requirements:
  - [S8] It has HTTP 200 response code AND
  - [S9] soapenv:Body element has child element timg:GetMoveOptionsResponse AND
  - [S10] It contains timg:MoveOptions\tt:Continuous element AND
- Settings from the **Move** request corresponds options recieved in the **GetMoveOptionsResponse** message:

- [S11] timg:Focus/tt:Continuous/tt:Speed element value from the Move request is less or equal to timg:MoveOptions/tt:Continuous/tt:Speed/tt:Max from the the GetMoveOptionsResponse message AND
- [S12] timg:Focus/tt:Continuous/tt:Speed element value from the Move request is greater or equal to timg:MoveOptions/tt:Continuous/tt:Speed/tt:Min from the the GetMoveOptionsResponse message.

FAIL -

• The Client failed PASS criteria.

Validated Feature List: FocusControl.ContinuousFocusMove

### 9.6 STOP

Test Label: Focus Control - Stop

Test Case ID: FOCUSCONTROL-4

Profile T Normative Reference: Conditional

Feature Under Test: Stop

**Test Purpose:** To verify that Client is able retrivefocus move options from Device using the **Stop** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **Stop** operation present.
- Device supports Imaging Service.

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **Stop** request message to stop focus move for specified video source for the Device.
- 2. Device responds with code HTTP 200 OK and StopResponse message.

#### Test Result:

#### PASS -

 Client Stop request messages are valid according to XML Schemas listed in Namespaces AND

- Client Stop request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element timg:Stop AND
- Device response on the **Stop** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element timg:StopResponse.

### FAIL -

• The Client failed PASS criteria.

Validated Feature List: FocusControl.FocusStop

# **10 Tampering Test Cases**

### 10.1 Feature Level Normative Reference:

Validated Feature: Tampering

Check Condition based on Device Features: None (ONVIF Profile T Simulator is used as device).

**Required Number of Devices:** 1

Profile T Requirement: Conditional

### 10.2 Expected Scenarios Under Test:

- 1. Client subscribes to ONVIF Profile T Simulator using **CreatePullPointSubscription** operation to get tampering notifications.
- 2. Client uses Pull Point event mechanism to retrieve the following notification events from ONVIF Profile T Simulator:
  - tns1:VideoSource/ImageTooBlurry/AnalyticsService
  - tns1:VideoSource/ImageTooBlurry/ImagingService
  - tns1:VideoSource/ImageTooDark/AnalyticsService
  - tns1:VideoSource/ImageTooDark/ImagingService
  - tns1:VideoSource/ImageTooBright/AnalyticsService
  - tns1:VideoSource/ImageTooBright/ImagingService
  - tns1:VideoSource/GlobalSceneChange/AnalyticsService
  - tns1:VideoSource/GlobalSceneChange/ImagingService
- 3. Client is considered as supporting Tampering if the following conditions are met:
  - ONVIF Profile T Simulator detects **Tampering** feature as supported.
- 4. Client is considered as NOT supporting Tampering if ANY of the following is TRUE:
  - ONVIF Profile T Simulator detects Tampering feature as not supported.

# **11 Motion Alarm Test Cases**

### 11.1 Feature Level Normative Reference:

Validated Feature: MotionAlarm

Check Condition based on Device Features: Motion Alarm is supported by Device.

**Required Number of Devices:** 3

Profile T Requirement: Mandatory

### 11.2 Expected Scenarios Under Test:

- 1. Client subscribes to device messages using **CreatePullPointSubscription** operation to get motion alarm notifications.
- 2. Client uses Pull Point event mechanism to retrieve notification events from Device.
- 3. Client is considered as supporting Motion Alarm if the following conditions are met:
  - · Client supports EventHandling\_Pullpoint feature AND
  - Client is able to retrieve tns1:VideoSource/MotionAlarm notifications if Device supports Motion Alarm feature.
- 4. Client is considered as NOT supporting Motion Alarm if ANY of the following is TRUE:
  - · Client does not support EventHandling\_Pullpoint feature OR
  - Client is not able to retrieve tns1:VideoSource/MotionAlarm.

## Annex A Test for Appendix A

## A.1 Required Number of Devices Summary

Required number of devices and Device feature dependency used in this test specification are listed in the Table.

### Table A.1. Required Number of Devices Summary

Feature ID	Feature Name	Required Number of Devices	Check Condition based on Device Features	Check Condition based on Device Features ID
tc.GetImagin gCapabilities	Get Imaging Capabilities	1	Imaging Service is supported by Device.	ImagingService
tc.GetImagin gSettings	Get Imaging Settings	3	Imaging Service is supported by Device.	ImagingService
tc.SetImagin gSettings	Imaging Settings Configuration	3	Imaging Service is supported by Device.	ImagingService
tc.GetMoveOp tions	Focus Move Capabilities	1	Imaging Service is supported by Device.	ImagingService
tc.FocusControl	Focus Control	1	Focus Control is supported by Device.	FocusControl
tc.Tampering	Tampering	1	Check Condition based on Device Features: None (ONVIF Profile T Simulator is used as device).	
tc.MotionAlarm	Motion Alarm	3	Check Condition based on Device Features: Motion Alarm is supported by Device.	MotionAlarm