

# ONVIF<sup>™</sup> Profile T Client Test Specification

Version 18.06

June 2018



© 2018 ONVIF, Inc. All rights reserved.

Recipients of this document may copy, distribute, publish, or display this document so long as this copyright notice, license and disclaimer are retained with all copies of the document. No license is granted to modify this document.

THIS DOCUMENT IS PROVIDED "AS IS," AND THE CORPORATION AND ITS MEMBERS AND THEIR AFFILIATES, MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THIS DOCUMENT ARE SUITABLE FOR ANY PURPOSE; OR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

IN NO EVENT WILL THE CORPORATION OR ITS MEMBERS OR THEIR AFFILIATES BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES, ARISING OUT OF OR RELATING TO ANY USE OR DISTRIBUTION OF THIS DOCUMENT, WHETHER OR NOT (1) THE CORPORATION, MEMBERS OR THEIR AFFILIATES HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, OR (2) SUCH DAMAGES WERE REASONABLY FORESEEABLE, AND ARISING OUT OF OR RELATING TO ANY USE OR DISTRIBUTION OF THIS DOCUMENT. THE FOREGOING DISCLAIMER AND LIMITATION ON LIABILITY DO NOT APPLY TO, INVALIDATE, OR LIMIT REPRESENTATIONS AND WARRANTIES MADE BY THE MEMBERS AND THEIR RESPECTIVE AFFILIATES TO THE CORPORATION AND OTHER MEMBERS IN CERTAIN WRITTEN POLICIES OF THE CORPORATION.



# **REVISION HISTORY**

Vers.	Date	Description
18.06	Jun 21, 2018	Reformatting document using new template
18.06	Jun 15, 2018	Audio Backchannel Streaming Using Media2 updated to exclude multicast streaming according to #274
18.06	May 22, 2018	HTTPS Streaming Using Media2 feature was added according to #224
18.06	May 15, 2018	Audio Output Configuration Using Media2 feature requirement level was changed from Conditional to Optional according to #261
18.06	Apr 28, 2018	Get Snapshot Uri Using Media2 feature requirement level was changed from Conditional to Optional according to #253
18.06	Apr 27, 2018	Video Streaming Using Media2 feature was replaced with H264 Video Streaming Using Media2 and H265 Video Streaming Using Media2 features according to #242
		Audio Streaming Using Media2 feature was replaced with G.711 Audio Streaming Using Media2 and AAC Audio Streaming Using Media2 features according to #243
18.06	Apr 05, 2018	'Required Number of Devices Summary' Annex added according to #241
18.06	Feb 16, 2018	The following were updated in the scope of #241:
		Feature Level Requirement (updated with new rules)
		Each Feature Level Requirement (updated with Check Condition based on Device Features and Required Number of Devices)
17.12	Sept 1, 2017	The following test cases added according to #226:
		Media Profile Management Test Cases
17.12	Aug 15, 2017	Requirement level of Profile T of the following features was changed to Optional according to #220:
		Audio Source Configuration Using Media2
		Audio Decoder Configuration Using Media2
17.12	Aug 15, 2017	Requirement level of Profile T of the following features was changed from Mandatory to Conditional according to #220:
		Audio Streaming Using Media2
		Audio Profile Configuration Using Media2
		Audio Backchannel Streaming Using Media2
		Audio Output Profile Configuration Using Media2
17.12	Aug 14, 2017	The following test cases added according to #222:
		<ul> <li>Multicast Streaming Test Cases</li> <li>Video Source Configuration Using Media2 Test Cases</li> <li>Metadata Configuration Using Media2 Test Cases</li> <li>Metadata Profile Configuration Using Media2 Test Cases</li> </ul>



		<ul> <li>Video Profile Configuration Using Media2 Test Cases</li> </ul>
17.06	Jun 15, 2017	Links in Normative references section were updated.
17.06	Jun 13, 2017	The following test cases added according to #201:
		Get Snapshot Uri Using Media2.
17.06	Jun 9, 2017	The following test cases added according to #201:
		Analytics Profile Configuration Using Media2 Test Cases
		Video Source Mode Test Cases
		Audio Source Configuration Using Media2 Test Cases
		Audio Output Configuration Using Media2 Test Cases
		Audio Decoder Configuration Using Media2 Test Cases
		List Video Source Configurations Using Media2 Test Cases
		OSD Configuration Using Media2 Test Cases
17.06	Jun 07, 2017	The following Device IO test cases moved into ONVIF Device IO Client Test Specification according to #194:
		Relay Outputs Using Device IO
		Get Digital Inputs
17.06	Jun 06, 2017	The following PTZ test cases moved into ONVIF PTZ Client Test Specification according to #194:
		PTZ Using Media2 Absolute Positioning
		PTZ Using Media2 Continuous Positioning
		PTZ - Set Preset
		Annex A.1 Get default PTZ space of PTZ Configuration corresponding to Move Operation
17.06	May 29, 2017	<ul> <li>Audio Profile Configuration Using Media Test Cases updated according to #191</li> <li>Audio Output Profile Configuration Using Media2 Test Cases updated according to #193</li> <li>Get Audio Output Configurations Using Media2 Test Cases removed according to #193</li> </ul>
17.06	Apr 04, 2017	<ul> <li>PTZ - Set Preset Test Cases added</li> <li>Audio Profile Configuration Using Media2 Test Cases added</li> </ul>
17.06	Apr 03, 2017	PTZ Using Media2 Continuous Positioning Test Cases added
17.06	Mar 29, 2017	Audio Output Profile Configuration Using Media2 added
17.06	Mar 28, 2017	<ul> <li>Get Audio Output Configurations Using Media2 Test Cases added</li> </ul>
17.06	Mar 27, 2017	PTZ Using Media2 Absolute Positioning Test Cases added
17.06	Mar 24, 2017	<ul> <li>Digital Inputs Test Cases added</li> <li>Audio Backchannel Streaming Using Media2 Test Cases added</li> </ul>
Ì		



17.06	Mar 21, 2017	<ul> <li>Media2 Media Streaming Test Cases added</li> </ul>
17.06	Mar 20, 2017	<ul> <li>Media2 Audio Encoder Configuration Test Cases added</li> </ul>
17.06	Mar 17, 2017	<ul> <li>Media2 Video Streaming Test Cases added</li> <li>Media2 Video Encoder Configuration Test Cases added</li> </ul>
17.06	Feb 06, 2017	Initial version:
		General parts added



## **Table of Contents**

1	Intro	duction	. 13
	1.1	Scope	13
	1.2	Get Profiles Using Media2	14
	1.3	Get Stream Uri Using Media2	14
	1.4	Media Streaming Using Media2	14
	1.5	H264 Video Streaming Using Media2	14
	1.6	H265 Video Streaming Using Media2	14
	1.7	Multicast Streaming Using Media2	14
	1.8	Video Encoder Configuration Using Media2	14
	1.9	Audio Encoder Configuration Using Media2	14
	1.10	G711 Audio Streaming Using Media2	15
	1.11	AAC1 Audio Streaming Using Media2	15
	1.12	Audio Profile Configuration Using Media2	15
	1.13	Audio Backchannel Streaming Using Media2	15
	1.14	Audio Output Profile Configuration Using Media2	15
	1.15	Analytics Profile Configuration Using Media2	15
	1.16	Video Source Mode	15
	1.17	Audio Source Configuration Using Media2	15
	1.18	Audio Output Configuration Using Media2	16
	1.19	Audio Decoder Configuration Using Media2	16
	1.20	List Video Source Configurations Using Media2	16
	1.21	OSD Configuration Using Media2	16
	1.22	Get Snapshot Uri Using Media2	16
	1.23	Metadata Configuration Using Media2	16
	1.24	Video Source Configuration Using Media2	16
	1.25	Metadata Profile Configuration Using Media2	16
	1.26	Video Profile Configuration Using Media2	17
	1.27	Media Profile Management	17
2	Norm	ative references	18
3	Terms	s and Definitions	19

	3.1	Conv	entions	. 19
	3.2	Defini	itions	. 19
	3.3	Abbre	eviations	. 20
	3.4	Name	espaces	. 20
4	Tes	t Overvi	ew	. 21
	4.1	Gene	ral	. 21
		4.1.1	Feature Level Requirement	21
		4.1.2	Expected Scenarios Under Test	21
		4.1.3	Test Cases	22
	4.2	Test S	Setup	. 22
	4.3	Prere	quisites	. 22
5	Get	Profiles	Using Media2 Test Cases	24
	5.1	Featu	re Level Normative Reference:	24
	5.2	Exped	cted Scenarios Under Test:	24
	5.3	GET I	PROFILES USING MEDIA2	24
6	Get	Stream	Uri Using Media2 Test Cases	26
	6.1	Featu	re Level Normative Reference:	26
	6.2	Exped	ted Scenarios Under Test:	26
	6.3	GET S	STREAM URI USING MEDIA2	26
7	Med	lia Strea	ming Using Media2 Test Cases	28
	7.1	Featu	re Level Requirement:	28
	7.2	Exped	ted Scenarios Under Test:	28
	7.3	STRE	AMING OVER RTSP USING MEDIA2	28
	7.4	STRE	AMING OVER UDP USING MEDIA2	31
	7.5	STRE	AMING OVER HTTP USING MEDIA2	34
8	H26	4 Video	Streaming Using Media2 Test Cases	38
	8.1	Featu	re Level Normative Reference:	38
	8.2	Exped	ted Scenarios Under Test:	38
	8.3	H264	VIDEO STREAMING USING MEDIA2	38
9	H26	5 Video	Streaming Using Media2 Test Cases	42
	9.1	Featu	re Level Normative Reference:	42



	9.2	Expected Scenarios Under Test:	. 42
	9.3	H265 VIDEO STREAMING USING MEDIA2	. 42
10	Mult	icast Streaming Using Media2 Test Cases	. 46
	10.1	Feature Level Requirement:	. 46
	10.2	Expected Scenarios Under Test:	. 46
	10.3	MULTICAST STREAMING USING RTSP USING MEDIA2	. 46
11	Vide	o Encoder Configuration Using Media2 Test Cases	50
	11.1	Feature Level Normative Reference:	. 50
	11.2	Expected Scenarios Under Test:	50
	11.3	GET VIDEO ENCODER CONFIGURATION OPTIONS USING MEDIA2	50
	11.4	SET VIDEO ENCODER CONFIGURATION USING MEDIA2	. 52
12	Audi	o Encoder Configuration Using Media2 Test Cases	. 54
	12.1	Feature Level Normative Reference:	. 54
	12.2	Expected Scenarios Under Test:	. 54
	12.3	GET AUDIO ENCODER CONFIGURATIONS USING MEDIA2	. 54
	12.4	GET AUDIO ENCODER CONFIGURATION OPTIONS USING MEDIA2	56
	12.5	SET AUDIO ENCODER CONFIGURATION USING MEDIA2	57
13	G.71	1 Audio Streaming Using Media2 Test Cases	. 59
	13.1	Feature Level Requirement:	. 59
	13.2	Expected Scenarios Under Test:	. 59
	13.3	G.711 AUDIO STREAMING USING MEDIA2	. 59
14	AAC	Audio Streaming Using Media2 Test Cases	. 63
	14.1	Feature Level Requirement:	. 63
	14.2	Expected Scenarios Under Test:	. 63
	14.3	AAC AUDIO STREAMING USING MEDIA2	. 63
15	Audi	o Profile Configuration Using Media2 Test Cases	. 67
	15.1	Feature Level Requirement:	. 67
	15.2	Expected Scenarios Under Test:	. 67
	15.3	ADD AUDIO SOURCE CONFIGURATION USING MEDIA2	68
	15.4	CREATE MEDIA PROFILE WITH AUDIO SOURCE CONFIGURATION USING	
	MEDI	Δ2	70

	15.5	GET AUDIO ENCODER CONFIGURATIONS COMPATIBLE WITH PROFILE	
	USING	6 MEDIA2	. 71
	15.6	ADD AUDIO ENCODER CONFIGURATION USING MEDIA2	72
16	Audi	o Backchannel Streaming Using Media2 Test Cases	. 75
	16.1	Feature Level Requirement:	75
	16.2	Expected Scenarios Under Test:	75
	16.3	G.711 AUDIO BACKCHANNEL STREAMING USING MEDIA2	. 75
	16.4	AAC AUDIO BACKCHANNEL STREAMING USING MEDIA2	. 79
17	Audio	Output Profile Configuration Using Media2 Test Cases	. 83
	17.1	Feature Level Requirement:	83
	17.2	Expected Scenarios Under Test:	83
	17.3	ADD AUDIO OUTPUT CONFIGURATION USING MEDIA2	84
	17.4	CREATE MEDIA PROFILE WITH AUDIO OUTPUT CONFIGURATION USING	
	MEDIA	A2	. 86
	17.5	GET AUDIO DECODER CONFIGURATIONS COMPATIBLE WITH PROFILE	
	USING	MEDIA2	. 87
	17.6	ADD AUDIO DECODER CONFIGURATION USING MEDIA2	88
18	Analy	tics Profile Configuration Using Media2 Test Cases	. 91
	18.1	Feature Level Requirement:	91
	18.2	Expected Scenarios Under Test:	91
	18.3	GET ANALYTICS CONFIGURATIONS COMPATIBLE WITH PROFILE USING	
	MEDIA	N2	. 91
	18.4	ADD ANALYTICS CONFIGURATION USING MEDIA2	93
19	Vide	o Source Mode Test Cases	95
	19.1	Feature Level Normative Reference:	95
	19.2	Expected Scenarios Under Test:	95
	19.3	GET VIDEO SOURCE MODES	95
	19.4	SET VIDEO SOURCE MODE	96
20	Audi	o Source Configuration Using Media2 Test Cases	<b>9</b> 8
	20.1	Feature Level Normative Reference:	98
	20.2	Expected Scenarios Under Test:	98



	20.3	GET AUDIO SOURCE CONFIGURATIONS USING MEDIA2	98
	20.4	GET AUDIO SOURCE CONFIGURATION OPTIONS USING MEDIA2	100
	20.5	SET AUDIO SOURCE CONFIGURATION USING MEDIA2	101
21	Audio	Output Configuration Using Media2 Test Cases	103
	21.1	Feature Level Normative Reference:	. 103
	21.2	Expected Scenarios Under Test:	103
	21.3	GET AUDIO OUTPUT CONFIGURATIONS USING MEDIA2	104
	21.4	GET AUDIO OUTPUT CONFIGURATION OPTIONS USING MEDIA2	105
	21.5	SET AUDIO OUTPUT CONFIGURATION USING MEDIA2	106
22	Audio	Decoder Configuration Using Media2 Test Cases	108
	22.1	Feature Level Normative Reference:	. 108
	22.2	Expected Scenarios Under Test:	108
	22.3	GET AUDIO DECODER CONFIGURATIONS USING MEDIA2	109
	22.4	GET AUDIO DECODER CONFIGURATION OPTIONS USING MEDIA2	110
	22.5	SET AUDIO DECODER CONFIGURATION USING MEDIA2	111
23	List V	/ideo Source Configurations Using Media2 Test Cases	113
	23.1	Feature Level Normative Reference:	. 113
	23.2	Expected Scenarios Under Test:	113
	23.3	LIST VIDEO SOURCE CONFIGURATIONS USING MEDIA2	113
24	OSD	Configuration Using Media2 Test Cases	. 116
	24.1	Feature Level Normative Reference:	. 116
	24.2	Expected Scenarios Under Test:	116
	24.3	GET OSD CONFIGURATIONS USING MEDIA2	117
	24.4	CREATE TEXT OSD USING MEDIA2	. 118
	24.5	CREATE IMAGE OSD USING MEDIA2	. 119
	24.6	GET OSD OPTIONS USING MEDIA2	. 120
	24.7	SET OSD USING MEDIA2	. 121
25	Get S	Snapshot Uri Using Media2 Test Cases	. 123
	25.1	Feature Level Normative Reference:	. 123
	25.2	Expected Scenarios Under Test:	123
	25.3	GET SNAPSHOT LIRLUSING MEDIA?	123



26	Meta	data Configuration Using Media2 Test Cases	. 126
	26.1	Feature Level Normative Reference:	126
	26.2	Expected Scenarios Under Test:	126
	26.3	GET METADATA CONFIGURATIONS USING MEDIA2	. 126
	26.4	GET METADATA CONFIGURATION OPTIONS USING MEDIA2	. 127
	26.5	SET METADATA CONFIGURATION USING MEDIA2	129
27	Vide	o Source Configuration Using Media2 Test Cases	. 131
	27.1	Feature Level Normative Reference:	131
	27.2	Expected Scenarios Under Test:	131
	27.3	GET VIDEO SOURCE CONFIGURATIONS USING MEDIA2	. 131
	27.4	GET VIDEO SOURCE CONFIGURATION OPTIONS USING MEDIA2	. 133
	27.5	SET VIDEO SOURCE CONFIGURATION USING MEDIA2	. 134
28	Meta	data Profile Configuration Using Media2 Test Cases	136
	28.1	Feature Level Requirement:	136
	28.2	Expected Scenarios Under Test:	136
	28.3	GET METADATA CONFIGURATIONS COMPATIBLE WITH PROFILE USING	
	MEDI	A2	. 136
	28.4	ADD METADATA CONFIGURATION USING MEDIA2	. 138
29	Vide	o Profile Configuration Using Media2 Test Cases	. 140
	29.1	Feature Level Requirement:	140
	29.2	Expected Scenarios Under Test:	140
	29.3	ADD VIDEO ENCODER CONFIGURATION USING MEDIA2	. 140
30	Med	ia Profile Management Test Cases	143
	30.1	Feature Level Requirement:	143
	30.2	Expected Scenarios Under Test:	143
	30.3	CREATE MEDIA PROFILE WITH VIDEO SOURCE CONFIGURATION USING	
	MEDI	A2	. 144
	30.4	GET VIDEO ENCODER INSTANCES USING MEDIA2	. 145
31	нтт	PS Streaming Using Media2 Test Cases	147
	31.1	Feature Level Requirement:	147
	31.2	Expected Scenarios Under Test:	147



Α	Test 1	for Appendix A	148
	A.1	Required Number of Devices Summary	148



## 1 Introduction

The goal of the ONVIF Test Specification set is to make it possible to realize fully interoperable IP physical security implementations from different vendors. This specification also acts as an input document to the development of a test tool which will be used to test the ONVIF Client implementation conformance towards ONVIF standard. This Client Test Tool analyzes network communications between ONVIF Devices and Clients being tested and determines whether a specific Client is ONVIF conformant (see ONVIF Conformance Process Specification).

This particular document defines test cases required for testing Profile T features of a Client application e.g. Video Streaming, Video Encoder Configuration, Audio Streaming, Configuration of Audio Profile, Audio Source Configuration, Audio Encoder Configuration, Audio Output Streaming, Configuration of Audio Output Profile, Audio Output Configuration, Metadata Configuration, Relay Outputs, Digital Inputs, and Tampering. It also describes the test framework, test setup, prerequisites, test policies needed for the execution of the described test cases.

# 1.1 Scope

This ONVIF Profile T Client Test Specification defines and regulates the conformance testing procedure for the ONVIF conformant Clients in the scope of Profile T features. Conformance testing is meant to be black-box network traces analysis and verification. The objective of this specification is to provide the test cases to test individual requirements of ONVIF Clients in the scope of Profile T features according to ONVIF Profile Specifications.

The principal intended purposes are:

- · Provide self-assessment tool for implementations.
- Provide comprehensive test suite coverage for Profile T features.

This specification does not address the following:

- 3rd parties Client use cases
- Non-functional (performance and regression) testing and analysis.
- SOAP Implementation Interoperability test i.e. Web Services Interoperability Basic Profile version 2.0 (WS-I BP2.0).
- Network protocol implementation Conformance test for HTTPS and HTTP protocols.

The following sections cover test cases needed for the verification of relevant features as mentioned in the ONVIF Profile Specifications.



# 1.2 Get Profiles Using Media2

Get Profiles Using Media2 section specifies Client ability to retrieve a list of Media2 profiles from Device.

# 1.3 Get Stream Uri Using Media2

Get Stream Uri Using Media2 section specifies Client ability to retrieve a Media2 stream URI from Device.

# 1.4 Media Streaming Using Media2

Media Streaming Using Media2 section defines different streaming options based on RTP protocol which are required for all types of streams of video, audio and metadata. Media control is done using RTSP protocol.

# 1.5 H264 Video Streaming Using Media2

H264 Media Streaming Using Media2 section specifies Client ability to establish specific video streams in H264 video format.

# 1.6 H265 Video Streaming Using Media2

H265 Media Streaming Using Media2 section specifies Client ability to establish specific video streams in H265 video format.

# 1.7 Multicast Streaming Using Media2

Multicast Streaming Using Media2 section specifies Client ability to stream multicast to Device.

# 1.8 Video Encoder Configuration Using Media2

Video Encoder Configuration Using Media2 section specifies modification of video encoder configurations on Device.

# 1.9 Audio Encoder Configuration Using Media2

Audio Encoder Configuration Using Media2 section specifies listing and modification of audio encoder configurations on Device.



# 1.10 G711 Audio Streaming Using Media2

G711 Audio Streaming Using Media2 section specifies Client ability to establish specific audio streams in G.711 audio format.

# 1.11 AAC1 Audio Streaming Using Media2

AAC Audio Streaming Using Media2 section specifies Client ability to establish specific audio streams in AAC audio format.

# 1.12 Audio Profile Configuration Using Media2

Audio Profile Configuration Using Media2 section specifies Client ability to configure or create media profile with audio source configuration and to add audio encoder configuration to a media profile.

# 1.13 Audio Backchannel Streaming Using Media2

Audio Backchannel Streaming Using Media2 section specifies Client ability to stream audio for backchannel to Device.

# 1.14 Audio Output Profile Configuration Using Media2

Audio Output Profile Configuration Using Media2 section specifies Client ability to configure or create media profile with audio output configuration and to add audio decoder configuration to a media profile.

# 1.15 Analytics Profile Configuration Using Media2

Analytics Profile Configuration Using Media2 section specifies Client ability to add analytics configuration to a media profile.

## 1.16 Video Source Mode

Video Source Mode section specifies Client ability to request the information for current video source mode and settable video source modes and to change current video source mode on device.

# 1.17 Audio Source Configuration Using Media2

Audio Source Configuration Using Media2 section specifies listing and modification of audio source configurations on Device.



# 1.18 Audio Output Configuration Using Media2

Audio Output Configuration Using Media2 section specifies listing and modification of audio output configurations on Device.

# 1.19 Audio Decoder Configuration Using Media2

Audio Decoder Configuration Using Media2 section specifies listing and modification of audio decoder configurations on Device.

# 1.20 List Video Source Configurations Using Media2

List Video Source Configurations Using Media2 section specifies listing of video source configurations on Device.

# 1.21 OSD Configuration Using Media2

OSD Configuration Using Media2 section specifies listing and modification of OSD configurations on Device.

# 1.22 Get Snapshot Uri Using Media2

Get Snapshot Uri Using Media2 section specifies Client ability to obtain a JPEG snapshot from the device.

# 1.23 Metadata Configuration Using Media2

Metadata Configuration Using Media2 section specifies listing and modification of metadata configurations on Device.

# 1.24 Video Source Configuration Using Media2

Video Source Configuration Using Media2 section specifies listing and modification of video source configurations on Device.

# 1.25 Metadata Profile Configuration Using Media2

Metadata Profile Configuration Using Media2 section specifies Client ability to add metadata configuration to a media profile.



# 1.26 Video Profile Configuration Using Media2

Video Profile Configuration Using Media2 section specifies Client ability to add video encoder configuration to a media profile.

# 1.27 Media Profile Management

Media Profile Management section specifies Client ability to create media profile with video source configuration or audio source configuration or audio output configuration and to list video source configurations and video encoder instances on Device.

## 2 Normative references

• ONVIF Conformance Process Specification:

https://www.onvif.org/profiles/conformance/

ONVIF Profile Policy:

https://www.onvif.org/profiles/

ONVIF Core Specifications:

https://www.onvif.org/profiles/specifications/

ONVIF Core Client Test Specification:

https://www.onvif.org/profiles/conformance/client-test/

ONVIF Profile T Specification:

https://www.onvif.org/profiles/profile-t/

· ONVIF Media2 Service Specification:

https://www.onvif.org/profiles/specifications/

ISO/IEC Directives, Part 2, Annex H:

http://www.iso.org/directives

• ISO 16484-5:2014-09 Annex P:

https://www.iso.org/obp/ui/#!iso:std:63753:en

· WS-BaseNotification:

http://docs.oasis-open.org/wsn/wsn-ws\_base\_notification-1.3-spec-os.pdf

• W3C SOAP 1.2, Part 1, Messaging Framework:

http://www.w3.org/TR/soap12-part1/

• W3C XML Schema Part 1: Structures Second Edition:

http://www.w3.org/TR/xmlschema-1/

• W3C XML Schema Part 2: Datatypes Second Edition:

"http://www.w3.org/TR/xmlschema-2/ [http://www.w3.org/TR/xmlschema-2/]



## 3 Terms and Definitions

## 3.1 Conventions

The key words "shall", "shall not", "should", "should not", "may", "need not", "can", "cannot" in this specification are to be interpreted as described in [ISO/IEC Directives Part 2].

## 3.2 Definitions

This section describes terms and definitions used in this document.

**Profile** See ONVIF Profile Policy.

Profile T The Profile T Specification.

ONVIF Device Computer appliance or software program that exposes one or

multiple ONVIF Web Services.

ONVIF Client Computer appliance or software program that uses ONVIF

Web Services.

Conversation A Conversation is all exchanges between two MAC

addresses that contains SOAP request and response.

Network A network is an interconnected group of devices

communicating using the Internet protocol.

Network Trace Capture file Data file created by a network protocol analyzer software

(such as Wireshark). Contains network packets data recorded

during a live network communications.

SOAP is a lightweight protocol intended for exchanging

structured information in a decentralized, distributed environment. It uses XML technologies to define an extensible messaging framework providing a message construct that can be exchanged over a variety of underlying

protocols.

Client Test Tool ONVIF Client Test Tool that tests ONVIF Client

implementation towards the ONVIF Test Specification set.

Configuration Entity A network video device media abstract component that

produces or consumes a media stream on the network, i.e.

video and/or audio stream.

Configuration Entity A network video device media abstract component that

produces or consumes a media stream on the network, i.e.

video and/or audio stream.

Digital PTZ Function that diminishes or crops an image to adjust the

image position and ratio.

**GZIP** GNU data format for lossless compression.

Media Profile Maps a video and audio sources and outputs encoders as

well as PTZ and analytics configurations.



Metadata All streaming data except video and audio, including video

analytics results, PTZ position data and other metadata (such as textual data from POS applications).

**Reference Token** Token provided by the device to uniquely reference an

instance of a physicalIO, configuration or profile.

**Video Analytics** Algorithms or programs used to analyze video data and to

generate data describing object location and behaviour.

## 3.3 Abbreviations

This section describes abbreviations used in this document.

**RTCP** RTP Control Protocol.

**RTP** Realtime Transport Protocol.

**RTSP** Real Time Streaming Protocol.

**TCP** Transmission Control Protocol.

**UDP** User Datagram Protocol.

**XML** eXtensible Markup Language.

**HTTP** Hyper Text Transport Protocol.

**HTTPS** Hyper Text Transport Protocol over Secure Socket Layer.

URI Uniform Resource Identifier.

WSDL Web Services Description Language.

**XML** eXtensible Markup Language.

# 3.4 Namespaces

Prefix and namespaces used in this test specification are listed in Table 1. These prefixes are not part of the standard and an implementation can use any prefix.

Table 3.1. Defined namespaces in this specification

Prefix	Namespace URI	Description
soapenv	http://www.w3.org/2003/05/soap- envelope	Envelope namespace as defined by SOAP 1.2 [SOAP 1.2, Part 1]
tt	http://www.onvif.org/ver10/schema	ONVIF XML schema descriptions
tr2	http://www.onvif.org/ver20/media/wsdl	The namespace for the WSDL Media2 service



# **4 Test Overview**

This section provides information for the test setup procedure and required prerequisites that should be followed during test case execution.

An ONVIF client compliant to Profile T can configure, request, and control streaming of video, audio, and audio output data over an IP network from an ONVIF Device compliant to the Profile T. The client can also retrieve and receive standardized Tampering related events.

An ONVIF Profile is described by a fixed set of functionalities through a number of services that are provided by the ONVIF standard. A number of services and functionalities are mandatory for each type of ONVIF Profile. An ONVIF Device and ONVIF Client may support any combination of Profiles and other optional services and functionalities.

## 4.1 General

Test Cases are grouped depending on features. Each Test Cases group provides description of feature requirement level for Profiles, expected scenario under test and related test cases:

- Feature Level Normative Reference
- Expected Scenarios Under Test
- · List of Test Cases

# 4.1.1 Feature Level Requirement

Feature Level Requirement item contains a feature ID, check condition based on Device features, required number of Devices and feature requirement level for the Profiles, which will be used for Profiles conformance.

To claim this Feature as supported Client shall pass Expected Scenario Under Test:

- for each Device, which supports Device Features defined in Check Condition Based on Device Features
- for at least with number of Devices specified in Required Number of Devices

If Feature Level Requirement is defined as Mandatory for some Profile, Client shall support this Feature to claim this Profile Conformance.

# 4.1.2 Expected Scenarios Under Test

Expected Scenarios Under Test item contains expected scenario under test, conditions when the feature will be defined as supported and as not supported.



## 4.1.3 Test Cases

Test Case items contain list of test cases which are related to feature. Test cases provide exact procedure of testing feature support conditions.

Each Test Case contains the following parts:

- · Test Label Unique label for each test
- · Test Case ID Unique ID for each test
- Profile Normative References Normative Reference level for the feature under test is defined in Profile Specification. This reference is informative and will not be used in conformance procedure.
- Feature Under Test Feature which is under current test. Typically a particular command or an event.
- Test Purpose The purpose of current test case.
- Pre-Requisite The pre-requisite defines when the test should be performed. In case if pre-requisite does not match, the test result will be NOT DETECTED.
- Test Procedure scenario expected to be reflected in network trace file.
- Test Result Passed and failed criteria of the test case. Depending on these criteria test result
  will be defined as PASSED or FAILED.
- Validated Feature List list of features ID related to this test case.

# 4.2 Test Setup

Collect Network Traces files required by the test cases.

Collect Feature List XML files for Devices detected in the Network Trace files.

Client shall support all mandatory and conditional features listed in the Device Feature List XML file supplied for the Profiles supported by the Client.

For compatibility with the Profile T, the ONVIF Client shall follow the requirements of the conformance process. For details please see the latest ONVIF Conformance Process Specification.

# 4.3 Prerequisites

The pre-requisites for executing the test cases described in this Test Specification include:



The Device shall be configured with an IPv4 address.

The Device shall be able to be discovered by the Client.

www.onvif.org

23



# 5 Get Profiles Using Media2 Test Cases

## 5.1 Feature Level Normative Reference:

Validated Feature: GetProfiles

Check Condition based on Device Features: Media2 Service is supported by Device.

**Required Number of Devices:** 3

Profile T Requirement: Mandatory

# 5.2 Expected Scenarios Under Test:

- 1. Client connects to Device to retrive media profiles from the DUT.
- 2. Client is considered as supporting Get Profiles if the following conditions are met:
  - Client is able to retrieve media profiles using **GetProfiles** operation (Media2 Service).
- 3. Client is considered as NOT supporting Get Profiles if ANY of the following is TRUE:
  - · No valid response to GetProfiles request (Media2 Service).

## 5.3 GET PROFILES USING MEDIA2

Test Label: GetProfiles

Test Case ID: MEDIA2\_GETPROFILES-1

**Profile T Normative Reference:** Mandatory

Feature Under Test: Get Profiles

Test Purpose: To verify that media profiles provided by Device are received by Client using the

GetProfiles operation.

## Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetProfiles** operation for Media2 Service present.
- Device supports Media2 Service (Media2 Service).

Test Procedure (expected to be reflected in network trace file):



- 1. Client invokes **GetProfiles** request message to retrieve a media profile or a list of media profiles from the Device.
- 2. Device responds with code HTTP 200 OK and **GetProfilesResponse** message.

## **Test Result:**

## PASS -

- Client GetProfiles request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetProfiles** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetProfiles AND
- Device response on the **GetProfiles** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetProfilesResponse.

## FAIL -

· The Client failed PASS criteria.

Validated Feature List: Media2\_GetProfiles.Media2\_GetProfilesRequest



# 6 Get Stream Uri Using Media2 Test Cases

## 6.1 Feature Level Normative Reference:

Validated Feature: GetStreamUri

Check Condition based on Device Features: Real Time Streaming (Media2 Service) is supported

by Device.

**Required Number of Devices:** 3

Profile T Requirement: Mandatory

# 6.2 Expected Scenarios Under Test:

- 1. Client connects to Device to retrive stream uri.
- 2. Client is considered as supporting Get Stream Uri if the following conditions are met:
  - Client is able to get the stream URI for the selected media profile using GetStreamURI operation (Media2 Service).
- 3. Client is considered as NOT supporting Get Stream Uri if ANY of the following is TRUE:
  - No valid response to GetStreamURI request (Media2 Service).

# 6.3 GET STREAM URI USING MEDIA2

Test Label: GetStreamUri

Test Case ID: MEDIA2\_GETSTREAMURI-1

**Profile T Normative Reference:** Mandatory

Feature Under Test: Get Stream URI

Test Purpose: To verify that stream URI provided by Device is received by Client using the

GetStreamUri operation.

## **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetStreamUri** operation for Media2 Service present.
- Device supports Media2 Service (Media2 Service).



## Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes GetStreamUri request message to retrieve a stream URI from the Device.
- 2. Device responds with code HTTP 200 OK and **GetStreamUriResponse** message.

#### **Test Result:**

## PASS -

- Client GetStreamUri request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetStreamUri** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetStreamUri AND
- Device response on the **GetStreamUri** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetStreamUriResponse.

## FAIL -

· The Client failed PASS criteria.

Validated Feature List: media2\_get\_stream\_uri.get\_stream\_uri



# 7 Media Streaming Using Media2 Test Cases

# 7.1 Feature Level Requirement:

Validated Feature: MediaStreaming

Validated Feature: GetStreamUri

Check Condition based on Device Features: Real Time Streaming (Media2 Service) is supported

by Device.

**Required Number of Devices:** 3

Profile T Requirement: Mandatory

## 7.2 Expected Scenarios Under Test:

- 1. Client connects to Device to initiate Media Streaming.
- 2. Client is considered as supporting Media Streaming if the following conditions are met:
  - Device supports media2\_get\_profiles.get\_profiles feature AND
  - Device supports media2 get stream uri.get stream uri feature AND
  - Stream was successfully established by Client using UDP protocol OR HTTP protocol.
  - · Stream was successfully established by Client using RTSP protocol (if supported).
- 3. Client is considered as NOT supporting Media Streaming if the following is TRUE:
  - Device does not support media2\_get\_profiles.get\_profiles feature OR
  - Device does not support media2 get stream uri get stream uri feature OR
  - Client is unable to establish stream using UDP protocol OR HTTP protocol OR
  - · Client is unable to establish stream using RTSP protocol if detected.

## 7.3 STREAMING OVER RTSP USING MEDIA2

Test Label: Media Streaming - RTSP

Test Case ID: MEDIA2\_MEDIASTREAMING-1



Profile T Normative Reference: Optional

Feature Under Test: Media Streaming using Media2

**Test Purpose**: To verify that stream over RTSP protocol was successfully established between Client and Device using RTSP commands and then successfully stopped.

## **Pre-Requisite:**

- Device supports RTSP streaming for Media2 Service (Media2\_RTPRTSPTCP).
- The Network Trace Capture files contains at least one Conversation between Client and Device with RTSP SETUP request with transport parameter as "RTP/AVP/TCP" and which does not contain Require header with "onvif-replay" value and which is not tunneled in HTTP present.
- The Network Trace Capture files contains at least one Conversation between Client and Device with GetStreamUri for Media2 Service with rt2:Protocol element value equals to RTSP.

## Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetStreamUri** request message for media profile with Transport element with "RTSP" value.
- 2. Device responds with code HTTP 200 OK and **GetStreamUriResponse** message.
- 3. Client invokes RTSP DESCRIBE request to retrieve media stream description.
- 4. Device responds with code RTSP 200 OK.
- 5. Client invokes **RTSP SETUP** request with **Transport** tag in RTSP header that contains "RTP/AVP/TCP" and without "onvif-replay" Require header to set media session parameters.
- 6. Device responds with code RTSP 200 OK.
- 7. Client invokes **RTSP PLAY** request without "onvif-replay" Require header to start media stream.
- 8. Device responds with code RTSP 200 OK.
- 9. Client invokes RTSP TEARDOWN request to terminate the RTSP session.
- 10. If Device sends response to RTSP TEARDOWN, it has code RTSP 200 OK or RTSP 454.

#### **Test Result:**



#### PASS -

- Client RTSP SETUP request in Test Procedure fulfills the following requirements:
  - [S1] It contains **Transport** request header field with value is equal to "RTP/AVP/TCP" (transport=RTP, profile=AVP, lower-transport=TCP) (see [RFC 2326]) AND
  - [S2] It does not contain Require request header field with value is equal to "onvif-replay"
     AND
  - · [S3] It is not tunneled in HTTP AND
- Device response on the RTSP SETUP request fulfills the following requirements:
  - [S4] It has RTSP 200 response code AND
- There is Client RTSP DESCRIBE request in Test Procedure fulfills the following requirements:
  - [S5] It invoked for the same Device as for the Client RTSP SETUP request AND
  - [S6] It invoked before the Client RTSP SETUP request AND
  - [S7] It is not tunneled in HTTP AND
- Device response on the RTSP DESCRIBE request fulfills the following requirements:
  - [S8] SDP packet contains media type with Control URL that was used to send RTSP SETUP (see [RFC 2326, C.1.1 Control URL]) AND
  - [S9] It has RTSP 200 response code AND
- There is a Client **GetStreamUri** request in Test Procedure fulfills the following requirements:
  - [S10] It invoked for the same Device as for the Client RTSP DESCRIBE request AND
  - [S11] It invoked before the Client RTSP DESCRIBE request AND
  - [S12] tr2:GetStreamUri/tr2:Protocol element value is equal to "RTSP"
- Device response on the **GetStreamUri** request to Media2 Service fulfills the following requirements:
  - [S13] It has HTTP 200 response code AND
  - [S14] It contains **tr2:Uri** element which value is equal to RTSP address that was used to send the **RTSP DESCRIBE** request AND
- There is Client RTSP PLAY request in Test Procedure fulfills the following requirements:



- [S15] It is invoked for the same RTSP session as the Client RTSP SETUP request AND
- [S16] It invoked after the Client RTSP SETUP request AND
- [S17] RTSP address that was used to send it is correspond to any media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
- [S18] It does not contain Require request header field with value is equal to "onvif-replay"
   AND
- · [S19] It is not tunneled in HTTP AND
- Device response on the RTSP PLAY request fulfills the following requirements:
  - [S20] It has RTSP 200 response code AND
- There is Client **RTSP TEARDOWN** request in Test Procedure fulfills the following requirements:
  - [S21] It invoked for the same RTSP session as the Client RTSP SETUP request AND
  - [S22] It invoked after the Client RTSP PLAY request AND
  - [S23] RTSP address that was used to send it is correspond to any media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
  - · [S24] It is not tunneled in HTTP AND
- If there is Device response on the **RTSP TEARDOWN** request then it fulfills the following requirements:
  - [S25] It has RTSP 200 response code.

## FAIL -

· The Client failed PASS criteria.

Validated Feature List: media2\_media\_streaming.RTP\_RTSP\_TCP

## 7.4 STREAMING OVER UDP USING MEDIA2

Test Label: Media Streaming - UDP

Test Case ID: MEDIA2 MEDIASTREAMING-2



**Profile T Normative Reference:** Mandatory

Feature Under Test: Media Streaming using Media2

**Test Purpose:** To verify that stream over UDP protocol was successfully established between Client and Device using RTSP commands and then successfully stopped.

## **Pre-Requisite:**

- Device supports Media2 Real Time Streaming (Media2\_RealTimeStreaming).
- The Network Trace Capture files contains at least one Conversation between Client and Device with RTSP SETUP request with transport parameter as "RTP/AVP/UDP" or "RTP/ AVP" and which does not contain Require header with "onvif-replay" value present.
- The Network Trace Capture files contains at least one Conversation between Client and Device with GetStreamUri for Media2 Service with rt2:Protocol element value equals to "RtspUnicast" or "RtspMulticast".

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetStreamUri** request message for media profile with Transport element with "RtspUnicast" value or "RtspMulticast" value.
- 2. Device responds with code HTTP 200 OK and **GetStreamUriResponse** message.
- 3. Client invokes RTSP DESCRIBE request to retrieve media stream description.
- 4. Device responds with code RTSP 200 OK.
- 5. Client invokes **RTSP SETUP** request with **Transport** tag in RTSP header that contains "RTP/AVP/UDP" or "RTP/AVP" and without "onvif-replay" Require header to set media session parameters.
- 6. Device responds with code RTSP 200 OK.
- 7. Client invokes **RTSP PLAY** request without "onvif-replay" Require header to start media stream.
- 8. Device responds with code RTSP 200 OK.
- 9. Client invokes RTSP TEARDOWN request to terminate the RTSP session.
- 10. If Device sends response to RTSP TEARDOWN, it has code RTSP 200 OK or RTSP 454.

## Test Result:

PASS -



- Client RTSP SETUP request in Test Procedure fulfills the following requirements:
  - [S1] It contains Transport request header field with value is equal to "RTP/AVP/UDP" OR "RTP/AVP" (transport=RTP, profile=AVP, lower-transport=TCP or skipped) (see [RFC 2326]) AND
  - [S2] It does not contain Require request header field with value is equal to "onvif-replay"
     AND
- Device response on the RTSP SETUP request fulfills the following requirements:
  - [S3] It has RTSP 200 response code AND
- There is Client **RTSP DESCRIBE** request in Test Procedure fulfills the following requirements:
  - [S4] It invoked for the same Device as for the Client RTSP SETUP request AND
  - [S5] It invoked before the Client RTSP SETUP request AND
- Device response on the RTSP DESCRIBE request fulfills the following requirements:
  - [S6] SDP packet contains media type with Control URL that was used to send RTSP SETUP (see [RFC 2326, C.1.1 Control URL]) AND
  - [S7] It has RTSP 200 response code AND
- There is a Device GetStreamUri request in Test Procedure fulfills the following requirements:
  - [S8] It invoked for the same Device as for the Client RTSP DESCRIBE request AND
  - [S9] It invoked before the Client RTSP DESCRIBE request AND
  - [S10] tr2:GetStreamUri/tr2:Protocol element value is equal to "RtspUnicast" or "RtspMulticast"
- Device response on the GetStreamUri request to Media2 Service fulfills the following requirements:
  - [S11] It contains tr2:Uri element which value is equal to RTSP address that was used to send the RTSP DESCRIBE request AND
  - [S12] It has HTTP 200 response code AND
- There is Client RTSP PLAY request in Test Procedure fulfills the following requirements:
  - [S13] It invoked for the same RTSP session as the Client RTSP SETUP request AND
  - [S14] It invoked after the Client RTSP SETUP request AND



- [S15] RTSP address that was used to send it is correspond to any media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
- [S16] It does not contain Require request header field with value is equal to "onvif-replay"
   AND
- Device response on the RTSP PLAY request fulfills the following requirements:
  - [S17] It has RTSP 200 response code AND
- There is Client **RTSP TEARDOWN** request in Test Procedure fulfills the following requirements:
  - [S18] It invoked for the same RTSP session as the Client RTSP SETUP request AND
  - [S19] It invoked after the Client RTSP PLAY request AND
  - [S20] RTSP address that was used to send it is correspond to any media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
- If there is Device response on the **RTSP TEARDOWN** request then it fulfills the following requirements:
  - [S21] It has RTSP 200 response code.

## FAIL -

34

· The Client failed PASS criteria.

Validated Feature List: media2\_media\_streaming.RTP\_UDP

## 7.5 STREAMING OVER HTTP USING MEDIA2

Test Label: Media Streaming - HTTP

Test Case ID: MEDIA2\_MEDIASTREAMING-3

**Profile T Normative Reference:** Mandatory

Feature Under Test: Media Streaming using Media2

Test Purpose: To verify that stream over HTTP protocol was successfully established between

Client and Device using RTSP commands and then successfully stopped.



#### **Pre-Requisite:**

- Device supports HTTP streaming for Media2 Service (Media2\_RTPRTSPHTTP).
- The Network Trace Capture files contains at least one Conversation between Client and Device with RTSP SETUP request with transport parameter as "RTP/AVP/TCP" and which does not contain Require header with "onvif-replay" value and which is tunneled in HTTP present.
- The Network Trace Capture files contains at least one Conversation between Client and Device with GetStreamUri for Media2 Service with rt2:Protocol element value equals to RtspOverHttp.

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetStreamUri** request message for media profile with Protocol element with "RtspOverHttp" value.
- 2. Device responds with code HTTP 200 OK and GetStreamUriResponse message.
- 3. Client invokes **RTSP DESCRIBE** request in HTTP tunnel to retrieve media stream description.
- 4. Device responds with code RTSP 200 OK.
- 5. Client invokes **RTSP SETUP** request without "onvif-replay" Require header in HTTP tunnel with **Transport** tag in RTSP header that contains "RTP/AVP/TCP" to set media session parameters.
- 6. Device responds with code RTSP 200 OK.
- 7. Client invokes **RTSP PLAY** request without "onvif-replay" Require header in HTTP tunnel to start media stream.
- 8. Device responds with code RTSP 200 OK.
- 9. Client invokes **RTSP TEARDOWN** request in HTTP tunnel to terminate the RTSP session.
- 10. If Device sends response to RTSP TEARDOWN, it has code RTSP 200 OK or RTSP 454.

#### **Test Result:**

#### PASS -

• Client RTSP SETUP request in Test Procedure fulfills the following requirements:

١	www.onvif.org		

35



- [S1] It contains **Transport** request header field with value is equal to "RTP/AVP/TCP" (transport=RTP, profile=AVP, lower-transport=TCP) (see [RFC 2326]) AND
- [S2] It does not contain Require request header field with value is equal to "onvif-replay"
   AND
- [S3] It is tunneled in HTTP AND
- Device response on the RTSP SETUP request fulfills the following requirements:
  - [S4] It has RTSP 200 response code AND
- There is Client RTSP DESCRIBE request in Test Procedure fulfills the following requirements:
  - [S5] It invoked for the same Device as for the Client RTSP SETUP request AND
  - [S6] It invoked before the Client RTSP SETUP request AND
  - [S7] It is tunneled in HTTP AND
- Device response on the RTSP DESCRIBE request fulfills the following requirements:
  - [S8] SDP packet contains media type with Control URL that was used to send **RTSP SETUP** (see [RFC 2326, C.1.1 Control URL]) AND
  - [S9] It has RTSP 200 response code AND
- There is a Device **GetStreamUri** request in Test Procedure fulfills the following requirements:
  - [S10] It invoked for the same Device as for the Client RTSP DESCRIBE request AND
  - [S11] It invoked before the Client RTSP DESCRIBE request AND
  - [S12] tr2:GetStreamUri/tr2:Protocol element value is equal to "RtspOverHttp"
- Device response on the **GetStreamUri** request to Media2 Service fulfills the following requirements:
  - [S13] It has HTTP 200 response code AND
  - [S14] It contains **tr2:Uri** element which value is equal to RTSP address that was used to send the **RTSP DESCRIBE** request AND
- There is Client RTSP PLAY request in Test Procedure fulfills the following requirements:
  - [S15] It invoked for the same RTSP session as the Client RTSP SETUP request AND
  - [S16] It invoked after the Client RTSP SETUP request AND



- [S17] RTSP address that was used to send it is correspond to any media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
- [S18] It does not contain Require request header field with value is equal to "onvif-replay"
   AND
- [S19] It is tunneled in HTTP AND
- Device response on the RTSP PLAY request fulfills the following requirements:
  - [S20] It has RTSP 200 response code AND
- There is Client **RTSP TEARDOWN** request in Test Procedure fulfills the following requirements:
  - [S21] It invoked for the same RTSP session as the Client RTSP SETUP request AND
  - [S22] It invoked after the Client RTSP PLAY request AND
  - [S23] RTSP address that was used to send it is correspond to any media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
  - [S24] It is tunneled in HTTP AND
- If there is Device response on the **RTSP TEARDOWN** request then it fulfills the following requirements:
  - [S25] It has RTSP 200 response code.

· The Client failed PASS criteria.

Validated Feature List: media2\_media\_streaming.RTP\_RTSP\_HTTP



## 8 H264 Video Streaming Using Media2 Test Cases

#### 8.1 Feature Level Normative Reference:

Validated Feature: H264 VideoStreaming

Check Condition based on Device Features: Real Time Streaming (Media2 Service) and H264

(Media2 Service) are supported by Device.

**Required Number of Devices:** 3

Profile T Requirement: Mandatory

### 8.2 Expected Scenarios Under Test:

- 1. Client connects to Device to setup and control of H264 video streaming.
- 2. Client is considered as supporting H264 Video Streaming if the following conditions are met:
  - Client supports media2\_get\_profiles.get\_profiles feature AND
  - Client supports media2\_get\_stream\_uri.get\_stream\_uri feature AND
  - Client is able to receive a stream using Media2 and decode H.264 video using the selected Media Profile over RTSP.
- 3. Client is considered as NOT supporting H264 Video Streaming if ANY of the following is TRUE:
  - · Client does not support media2 get profiles get profiles feature OR
  - · Client does not support media2 get stream uri.get stream uri feature OR
  - Client is unable to initiate and retrieve video stream using Media2 with H.264 encoding type.

#### 8.3 H264 VIDEO STREAMING USING MEDIA2

Test Label: Video Streaming - H264

Test Case ID: MEDIA2\_VIDEOSTREAMING\_H264-1

**Profile T Normative Reference:** Mandatory

Feature Under Test: Video Streaming



**Test Purpose:** To verify that the Client is able to initiate and retrieve a video stream with H264 encoding type.

#### Pre-Requisite:

- Device supports H264 encoding for Video Streaming for Media2 Service (Media2\_H264).
- The Network Trace Capture files contains at least one Conversation between Client and Device with Video Streaming of H264 encoding type.
- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetStreamUri** for Media2 Service.
- Device supports H264 encoding for Video Streaming using Media2.

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetStreamUri request message for media profile that contains Video Source Configuration and Video Encoder Configuration with H264 Encoding value. GetStreamUri request is set for RtspUnicast OR RtspMulticast OR RTSP OR RtspOverHttp transport.
- 2. Device responds with code HTTP 200 OK and GetStreamUriResponse message.
- 3. Client invokes RTSP DESCRIBE request to retrieve media stream description.
- 4. Device responds with code RTSP 200 OK and SDP information with Media Type: "video" and with encoding name "H264".
- 5. Client invokes **RTSP SETUP** request without "onvif-replay" Require header and with transport parameter element to to set media session parameters for H264 video streaming.
- 6. Device responds with code RTSP 200 OK.
- 7. Client invokes **RTSP PLAY** request without "onvif-replay" Require header to start media stream.
- 8. Device responds with code RTSP 200 OK.
- 9. Client invokes RTSP TEARDOWN request to terminate the RTSP session.
- 10. If Device sends response to RTSP TEARDOWN, it has code RTSP 200 OK or RTSP 454.

#### **Test Result:**

**Note:** RTSP requests and RTSP response could be tunneled in HTTP if RTP-Unicast/RTSP/HTTP/TCP transport is used.



- There is Client RTSP DESCRIBE request in Test Procedure
- Device response on the RTSP DESCRIBE request fulfills the following requirements:
  - [S1] It has RTSP 200 response code AND
  - [S2] SDP packet contains media type "video" (m=video) with sessions attribute "rtpmap" with encoding name "H264" (see [RFC 3984], item 8.2.1. Mapping of MIME Parameters to SDP) AND
- There is Client RTSP SETUP request in Test Procedure fulfills the following requirements:
  - [S3] It invoked for the same Device as for the Client RTSP DESCRIBE request AND
  - [S4] It invoked after the Client RTSP DESCRIBE request AND
  - [S5] RTSP address that was used to send RTSP SETUP is correspond to corresponding media Control URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
  - [S6] It does not contain Require request header field with value is equal to "onvif-replay"
     AND
- Device response on the RTSP SETUP request fulfills the following requirements:
  - [S7] It has RTSP 200 response code AND
- There is a Device response on the **GetStreamUri** request for Media2 Service in Test Procedure fulfills the following requirements:
  - · [S8] It has HTTP 200 response code AND
  - [S9] It received for the same Device as for the Client RTSP DESCRIBE request AND
  - [S10] It received before the Client RTSP DESCRIBE request AND
  - [S11] It contains **tr2:Uri** element which value is equal to RTSP address that was used to send the **RTSP DESCRIBE** request AND
- There is Client RTSP PLAY request in Test Procedure fulfills the following requirements:
  - [S12] It invoked for the same RTSP session as the Client RTSP SETUP request AND
  - [S13] It invoked after the Client RTSP SETUP request AND
  - [S14] RTSP address that was used to send it is correspond to corresponding media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND



- [S15] It does not contain Require request header field with value is equal to "onvif-replay" AND
- Device response on the RTSP PLAY request fulfills the following requirements:
  - [S16] It has RTSP 200 response code AND
- There is Client RTSP TEARDOWN request in Test Procedure fulfills the following requirements:
  - [S17] It invoked for the same RTSP session as the Client RTSP SETUP request AND
  - [S18] It invoked after the Client RTSP PLAY request AND
  - [S19] RTSP address that was used to send it is correspond to corresponding media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
- If there is Device response on the **RTSP TEARDOWN** request then it fulfills the following requirements:
  - [S20] It has RTSP 200 response code.

· The Client failed PASS criteria.

Validated Feature List: Media2\_H264VideoStreaming



## 9 H265 Video Streaming Using Media2 Test Cases

#### 9.1 Feature Level Normative Reference:

Validated Feature: H265 VideoStreaming

Check Condition based on Device Features: Real Time Streaming (Media2 Service) and H265

(Media2 Service) are supported by Device.

**Required Number of Devices:** 3

Profile T Requirement: Mandatory

## 9.2 Expected Scenarios Under Test:

- 1. Client connects to Device to setup and control of H265 video streaming.
- 2. Client is considered as supporting H265 Video Streaming if the following conditions are met:
  - Client supports media2\_get\_profiles.get\_profiles feature AND
  - Client supports media2\_get\_stream\_uri.get\_stream\_uri feature AND
  - Client is able to receive a stream using Media2 and decode H.265 video using the selected Media Profile over RTSP.
- 3. Client is considered as NOT supporting H265 Video Streaming if ANY of the following is TRUE:
  - · Client does not support media2 get profiles get profiles feature OR
  - · Client does not support media2 get stream uri.get stream uri feature OR
  - Client is unable to initiate and retrieve video stream using Media2 with H.265 encoding type.

#### 9.3 H265 VIDEO STREAMING USING MEDIA2

Test Label: Video Streaming - H265

Test Case ID: MEDIA2 VIDEOSTREAMING H265-1

**Profile T Normative Reference:** Mandatory

Feature Under Test: Video Streaming



**Test Purpose:** To verify that the Client is able to initiate and retrieve a video stream with H265 encoding type.

#### Pre-Requisite:

- Device supports H265 encoding for Video Streaming for Media2 Service (Media2\_H265).
- The Network Trace Capture files contains at least one Conversation between Client and Device with Video Streaming of H265 encoding type.
- The Network Trace Capture files contains at least one Conversation between Client and Device with GetStreamUri for Media2 Service.
- Device supports H265 encoding for Video Streaming using Media2.

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetStreamUri request message for media profile that contains Video Source Configuration and Video Encoder Configuration with H265 Encoding value. GetStreamUri request is set for RtspUnicast OR RtspMulticast OR RTSP OR RtspOverHttp transport.
- 2. Device responds with code HTTP 200 OK and GetStreamUriResponse message.
- 3. Client invokes RTSP DESCRIBE request to retrieve media stream description.
- 4. Device responds with code RTSP 200 OK and SDP information with Media Type: "video" and with encoding name "H265".
- 5. Client invokes **RTSP SETUP** request without "onvif-replay" Require header and with transport parameter element to to set media session parameters for H265 video streaming.
- 6. Device responds with code RTSP 200 OK.
- 7. Client invokes **RTSP PLAY** request without "onvif-replay" Require header to start media stream.
- 8. Device responds with code RTSP 200 OK.
- 9. Client invokes RTSP TEARDOWN request to terminate the RTSP session.
- 10. If Device sends response to RTSP TEARDOWN, it has code RTSP 200 OK or RTSP 454.

#### **Test Result:**

**Note:** RTSP requests and RTSP response could be tunneled in HTTP if RTP-Unicast/RTSP/HTTP/TCP transport is used.



- There is Client RTSP DESCRIBE request in Test Procedure
- Device response on the RTSP DESCRIBE request fulfills the following requirements:
  - [S1] It has RTSP 200 response code AND
  - [S2] SDP packet contains media type "video" (m=video) with sessions attribute "rtpmap" with encoding name "H265" (see [RFC 3984], item 8.2.1. Mapping of MIME Parameters to SDP) AND
- There is Client RTSP SETUP request in Test Procedure fulfills the following requirements:
  - [S3] It invoked for the same Device as for the Client RTSP DESCRIBE request AND
  - [S4] It invoked after the Client RTSP DESCRIBE request AND
  - [S5] RTSP address that was used to send RTSP SETUP is correspond to corresponding media Control URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
  - [S6] It does not contain Require request header field with value is equal to "onvif-replay"
     AND
- Device response on the RTSP SETUP request fulfills the following requirements:
  - [S7] It has RTSP 200 response code AND
- There is a Device response on the **GetStreamUri** request for Media2 Service in Test Procedure fulfills the following requirements:
  - · [S8] It has HTTP 200 response code AND
  - [S9] It received for the same Device as for the Client RTSP DESCRIBE request AND
  - [S10] It received before the Client RTSP DESCRIBE request AND
  - [S11] It contains **tr2:Uri** element which value is equal to RTSP address that was used to send the **RTSP DESCRIBE** request AND
- There is Client RTSP PLAY request in Test Procedure fulfills the following requirements:
  - [S12] It invoked for the same RTSP session as the Client RTSP SETUP request AND
  - [S13] It invoked after the Client RTSP SETUP request AND
  - [S14] RTSP address that was used to send it is correspond to corresponding media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND



- [S15] It does not contain Require request header field with value is equal to "onvif-replay" AND
- Device response on the RTSP PLAY request fulfills the following requirements:
  - [S16] It has RTSP 200 response code AND
- There is Client RTSP TEARDOWN request in Test Procedure fulfills the following requirements:
  - [S17] It invoked for the same RTSP session as the Client RTSP SETUP request AND
  - [S18] It invoked after the Client RTSP PLAY request AND
  - [S19] RTSP address that was used to send it is correspond to corresponding media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
- If there is Device response on the **RTSP TEARDOWN** request then it fulfills the following requirements:
  - [S20] It has RTSP 200 response code.

· The Client failed PASS criteria.

Validated Feature List: Media2\_VideoStreaming\_H265



## 10 Multicast Streaming Using Media2 Test Cases

### 10.1 Feature Level Requirement:

Validated Feature: Media2\_MulticastStreaming

Check Condition based on Device Features: RTP-Multicast/UDP (Media2 Service) is supported

by Device.

**Required Number of Devices: 1** 

Profile T Requirement: Conditional

### 10.2 Expected Scenarios Under Test:

- 1. Client connects to Device and initiates Multicast Streaming using RTSP.
- 2. Client is considered as supporting Multicast Streaming Using Media2 if the following conditions are met:
  - · Client is able to start and stop a multicast stream by using RTSP.
- 3. Client is considered as NOT supporting Multicast Streaming Using Media2 if ANY of the following is TRUE:
  - Client is not able to start and stop a multicast stream by using RTSP.

#### 10.3 MULTICAST STREAMING USING RTSP USING MEDIA2

Test Label: Multicast Streaming Using Media2 - RTSP multicast setup

Test Case ID: MEDIA2\_MULTICASTSTREAMING-1

Profile T Normative Reference: Conditional

Feature Under Test: Multicast Streaming

Test Purpose: To verify that the Client is able to setup and initiate a multicast stream with RTSP

commands for stream control.

#### Pre-Requisite:

 The Network Trace Capture files contains at least one Conversation between Client and Device with RTSP SETUP request with transport parameter as "RTP/AVP/UDP;multicast" or "RTP/AVP;multicast" and without "onvif-replay" Require header present.



- The Network Trace Capture files contains at least one Conversation between Client and Device with GetStreamUri for Media2 Service with rt2:Protocol element with "RtspMulticast" value.
- Device supports RTPMulticastUDP feature.

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetStreamUri** request message for media profile with Protocol element with "RtspMulticast" value.
- 2. Device responds with code HTTP 200 OK and **GetStreamUriResponse** message. message.
- 3. Client invokes **RTSP DESCRIBE** request to retrieve media stream description.
- 4. Device responds with code RTSP 200 OK.
- 5. Client invokes RTSP SETUP request without "onvif-replay" Require header and with Transport tag in RTSP header that contains "RTP/AVP/UDP;multicast" or "RTP/AVP;multicast" to set media session parameters.
- 6. Device responds with code RTSP 200 OK.
- 7. Client invokes **RTSP PLAY** request without "onvif-replay" Require header to start media stream.
- 8. Device responds with code RTSP 200 OK.
- 9. Client invokes RTSP TEARDOWN request to terminate the RTSP session.
- 10. If Device sends response to RTSP TEARDOWN, it has code RTSP 200 OK or RTSP 454.

#### **Test Result:**

- Client RTSP SETUP request in Test Procedure fulfills the following requirements:
  - [S1] It contains Transport request header field with value is equal to "RTP/AVP/UDP"
     OR "RTP/AVP" and with "multicast" parameter value (transport=RTP, profile=AVP, lower-transport=TCP or skipped, parameter=multicast) (see [RFC 2326]) AND
  - [S2] It does not contain Require request header field with value is equal to "onvif-replay"
     AND



- Device response on the RTSP SETUP request fulfills the following requirements:
  - · [S3] It has RTSP 200 response code AND
- There is Client **RTSP DESCRIBE** request in Test Procedure that fulfills the following requirements:
  - [S4] It invoked for the same Device as for the Client RTSP SETUP request AND
  - [S5] It invoked before the Client RTSP SETUP request AND
  - [S6] SDP packet contains media type with Control URL that was used to send RTSP SETUP (see [RFC 2326, C.1.1 Control URL]) AND
- Device response on the RTSP DESCRIBE request fulfills the following requirements:
  - [S7] It has RTSP 200 response code AND
- There is a Device GetStreamUri request in Test Procedure that fulfills the following requirements:
  - [S8] It invoked for the same Device as for the Client RTSP DESCRIBE request AND
  - [S9] It invoked before the Client RTSP DESCRIBE request AND
  - [S10] tr2:GetStreamUri/tr2:Protocol element value is equal to "RtspMulticast"
- Device response on the GetStreamUri request fulfills the following requirements:
  - [S11] It has HTTP 200 response code AND
  - [S12] It contains tr2:Uri element which value is equal to RTSP address that was used to send the RTSP DESCRIBE request AND
- There is Client RTSP PLAY request in Test Procedure that fulfills the following requirements:
  - [S13] It invoked for the same RTSP session as the Client RTSP SETUP request AND
  - [S14] It invoked after the Client RTSP SETUP request AND
  - [S15] RTSP address that was used to send it is correspond to any media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
  - [S16] It does not contain Require request header field with value is equal to "onvif-replay"
     AND
- Device response on the RTSP PLAY request fulfills the following requirements:



- [S17] It has RTSP 200 response code AND
- There is Client **RTSP TEARDOWN** request in Test Procedure that fulfills the following requirements:
  - [S18] It invoked for the same RTSP session as the Client RTSP SETUP request AND
  - [S19] It invoked after the Client RTSP PLAY request AND
  - [S20] RTSP address that was used to send it is correspond to any media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
- If there is Device response on the **RTSP TEARDOWN** request then it fulfills the following requirements:
  - [S21] It has RTSP 200 response code.

• The Client failed PASS criteria.

Validated Feature List: MulticastStreaming.RTSP



# 11 Video Encoder Configuration Using Media2 Test Cases

#### 11.1 Feature Level Normative Reference:

Validated Feature: VideoEncoderConfiguration

Check Condition based on Device Features: Video (Media2 Service) is supported by Device.

**Required Number of Devices:** 3

Profile T Requirement: Mandatory

## 11.2 Expected Scenarios Under Test:

- 1. Client connects to Device to modify Video Encoder Configuration.
- 2. Client is considered as supporting Video Encoder Configuration if the following conditions are met:
  - Client is able to retrieve video encoder configuration options using GetVideoEncoderConfigurationOptions operation (Media2 Service) AND
  - Client is able to modify video encoder configuration using SetVideoEncoderConfiguration operation (Media2 Service) AND
- 3. Client is considered as NOT supporting Video Encoder Configuration if ANY of the following is TRUE:
  - No valid response to GetVideoEncoderConfigurationOptions request (Media2 Service) OR
  - No valid response to SetVideoEncoderConfiguration request (Media2 Service) OR

## 11.3 GET VIDEO ENCODER CONFIGURATION OPTIONS USING MEDIA2

Test Label: Video Encoder Configuration - Get Video Encoder Configuration Options

Test Case ID: MEDIA2\_VIDEOENCODERCONFIGURATION-1

**Profile T Normative Reference:** Mandatory

50 www.onvif.org



Feature Under Test: Get Video Encoder Configuration Options

**Test Purpose:** To verify that video encoder configuration options provided by Device is received by Client using the **GetVideoEncoderConfigurationOptions** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetVideoEncoderConfigurationOptions** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetVideoEncoderConfigurationOptions** request message to retrieve a video encoder configuration options from the Device.
- 2. Device responds with code HTTP 200 OK and **GetVideoEncoderConfigurationOptionsResponse** message.

#### **Test Result:**

#### PASS -

- Client GetVideoEncoderConfigurationOptions request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetVideoEncoderConfigurationOptions** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetVideoEncoderConfigurationOptions AND
- Device response on the **GetVideoEncoderConfigurationOptions** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetVideoEncoderConfigurationOptionsResponse.

#### FAIL -

· The Client failed PASS criteria.

Validated	Feature	List:
media2_video_encoder_configu	uration.get_video_encoder_configuration_opt	ions

www.onvif.org



## 11.4 SET VIDEO ENCODER CONFIGURATION USING MEDIA2

Test Label: Video Encoder Configuration - Set Video Encoder Configuration

Test Case ID: MEDIA2\_VIDEOENCODERCONFIGURATION-2

**Profile T Normative Reference:** Mandatory

Feature Under Test: Set Video Encoder Configuration

**Test Purpose:** To verify that Client is able to change video encoder configuration provided by Device using the **SetVideoEncoderConfiguration** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with SetVideoEncoderConfiguration operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **SetVideoEncoderConfiguration** request message to change a video encoder configuration on the Device.
- 2. Device responds with code HTTP 200 OK and **SetVideoEncoderConfigurationResponse** message.

#### **Test Result:**

- Client SetVideoEncoderConfiguration request messages are valid according to XML Schemas listed in Namespaces AND
- Client **SetVideoEncoderConfiguration** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:SetVideoEncoderConfiguration AND
- Device response on the **SetVideoEncoderConfiguration** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND



• [S3] soapenv:Body element has child element tr2:SetVideoEncoderConfigurationResponse.

#### FAIL -

• The Client failed PASS criteria.

Validated Feature List: media2\_video\_encoder\_configuration.set\_video\_encoder\_configuration

www.onvif.org

53



# 12 Audio Encoder Configuration Using Media2 Test Cases

#### 12.1 Feature Level Normative Reference:

Validated Feature: AudioEncoderConfiguration

Check Condition based on Device Features: Audio (Media2 Service) is supported by Device.

**Required Number of Devices: 1** 

Profile T Requirement: Conditional

### 12.2 Expected Scenarios Under Test:

- 1. Client connects to Device to modify Audio Encoder Configuration.
- 2. Client is considered as supporting Audio Encoder Configuration if the following conditions are met:
  - Client is able to retrieve audio encoder configurations using GetAudioEncoderConfigurations operation (Media2 Service) AND
  - Client is able to retrieve audio encoder configuration options using GetAudioEncoderConfigurationOptions operation (Media2 Service) AND
  - Client is able to modify audio encoder configuration using SetAudioEncoderConfiguration operation (Media2 Service) AND
- 3. Client is considered as NOT supporting Audio Encoder Configuration if ANY of the following is TRUE:
  - No valid response to **GetAudioEncoderConfigurations** request (Media2 Service) OR
  - No valid response to GetAudioEncoderConfigurationOptions request (Media2 Service) OR
  - No valid response to SetAudioEncoderConfiguration request (Media2 Service) OR

## 12.3 GET AUDIO ENCODER CONFIGURATIONS USING MEDIA2

Test Label: Audio Encoder Configuration - Get Audio Encoder Configurations

54	www.onvif.org



Test Case ID: MEDIA2\_AUDIOENCODERCONFIGURATION-1

Profile T Normative Reference: Conditional

Feature Under Test: GetAudioEncoderConfigurations

**Test Purpose:** To verify that audio encoder configuration provided by Device is received by Client using the **GetAudioEncoderConfigurations** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetAudioEncoderConfigurations** operation for Media2 Service present.
- Device supports Media2 Service (Media2 Service).
- Device supports Audio feature for Media2 Service (Media2\_Audio).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetAudioEncoderConfigurations request message to retrieve an audio encoder configuration or a list of audio encoder configurations from the Device.
- 2. Device responds with code HTTP 200 OK and **GetAudioEncoderConfigurationsResponse** message.

#### **Test Result:**

- Client GetAudioEncoderConfigurations request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetAudioEncoderConfigurations** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetAudioEncoderConfigurations
     AND
- Device response on the **GetAudioEncoderConfigurations** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetAudioEncoderConfigurationsResponse.

ı	F	Δ	ı	ı	
н	_	_		_	•

www.onvif.org	55



· The Client failed PASS criteria.

Validated Feature List: media2 audio encoder configuration get audio encoder configurations

## 12.4 GET AUDIO ENCODER CONFIGURATION OPTIONS USING MEDIA2

Test Label: Audio Encoder Configuration - Get Audio Encoder Configuration Options

Test Case ID: MEDIA2 AUDIOENCODERCONFIGURATION-2

Profile T Normative Reference: Conditional

Feature Under Test: GetAudioEncoderConfigurationOptions

**Test Purpose**: To verify that audio encoder configuration options provided by Device is received by Client using the **GetAudioEncoderConfigurationOptions** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetAudioEncoderConfigurationOptions** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Audio feature for Media2 Service (Media2\_Audio).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetAudioEncoderConfigurationOptions** request message to retrieve an audio encoder configuration options from the Device.
- 2. Device responds with code HTTP 200 OK and **GetAudioEncoderConfigurationOptionsResponse** message.

#### **Test Result:**

#### PASS -

- Client GetAudioEncoderConfigurationOptions request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetAudioEncoderConfigurationOptions** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetAudioEncoderConfigurationOptions AND

56



- Device response on the GetAudioEncoderConfigurations request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetAudioEncoderConfigurationOptionsResponse.

· The Client failed PASS criteria.

Validated Feature List: media2\_audio\_encoder\_configuration.get\_audio\_encoder\_configuration\_options

## 12.5 SET AUDIO ENCODER CONFIGURATION USING MEDIA2

**Test Label:** Audio Encoder Configuration - Set Audio Encoder Configuration

Test Case ID: MEDIA2\_AUDIOENCODERCONFIGURATION-3

Profile T Normative Reference: Conditional

Feature Under Test: SetAudioEncoderConfiguration

**Test Purpose:** To verify that Client is able to change audio encoder configuration provided by Device using the **SetAudioEncoderConfiguration** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **SetAudioEncoderConfiguration** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Audio feature for Media2 Service (Media2 Audio).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes SetAudioEncoderConfiguration request message to change an audio encoder configuration on the Device.
- 2. Device responds with code HTTP 200 OK and **SetAudioEncoderConfigurationResponse** message.

www.onvif.org	57
www.onvii.org	57



#### **Test Result:**

#### PASS -

- Client SetAudioEncoderConfiguration request messages are valid according to XML Schemas listed in Namespaces AND
- Client **SetAudioEncoderConfiguration** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:SetAudioEncoderConfiguration AND
- Device response on the **SetAudioEncoderConfiguration** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:SetAudioEncoderConfigurationResponse.

#### FAIL -

· The Client failed PASS criteria.

Validated Feature List: media2\_audio\_encoder\_configuration.set\_audio\_encoder\_configuration



## 13 G.711 Audio Streaming Using Media2 Test Cases

## 13.1 Feature Level Requirement:

Validated Feature: AudioStreaming

**Check Condition based on Device Features:** Real Time Streaming (Media2 Service) and Audio G711 (Media2 Service) are supported by Device.

**Required Number of Devices: 1** 

**Profile T Requirement:** Conditional

### 13.2 Expected Scenarios Under Test:

- 1. Client connects to Device to configure a media profile and initiate Audio Streaming with G.711 encoding type.
- 2. Client is considered as supporting G711 Audio Streaming if the following conditions are met:
  - Client supports media2 get profiles get profiles feature AND
  - Client supports media2\_get\_stream\_uri.get\_stream\_uri feature AND
  - Client is able to initiate and retrieve audio stream using Media2 with G.711 encoding type.
- 3. Client is considered as NOT supporting G711 Audio Streaming if ANY of the following is TRUE:
  - Client does not support media2\_get\_profiles.get\_profiles feature OR
  - · Client does not support media2 get stream uri.get stream uri feature OR
  - Client is unable to initiate and retrieve audio stream using Media2 with G.711 encoding type.

#### 13.3 G.711 AUDIO STREAMING USING MEDIA2

Test Label: Audio Streaming using Media2 - G.711

Test Case ID: MEDIA2\_G711AUDIOSTREAMING-1

Profile T Normative Reference: Conditional



Feature Under Test: AudioStreaming

**Test Purpose:** To verify that the Client is able to initiate and retrieve audio stream with G.711 encoding type.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one conversation between Client and Device with Audio Streaming of G.711 encoding type.
- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetStreamUri** for Media2 Service.
- Device supports G.711 encoding for Audio streaming using Media2 (Media2\_G711).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetStreamUri request message for media profile that contains Audio Source Configuration and Audio Encoder Configuration with G711 Encoding value. GetStreamUri request is set for RTP-Unicast/UDP OR RTP-Multicast/UDP OR RTP/RTSP/TCP OR RTP-Unicast/RTSP/HTTP/TCP transport.
- 2. Device responds with code HTTP 200 OK and **GetStreamUriResponse** message.
- 3. Client invokes RTSP DESCRIBE request to retrieve media stream description.
- 4. Device responds with code RTSP 200 OK and SDP information with Media Type: "audio" and with encoding name "PCMU" or with payload type number "0".
- 5. Client invokes **RTSP SETUP** request without "onvif-replay" Require header and with transport parameter element to set media session parameters for G711 audio streaming.
- 6. Device responds with code RTSP 200 OK.
- 7. Client invokes **RTSP PLAY** request without "onvif-replay" Require header to start media stream.
- 8. Device responds with code RTSP 200 OK.
- 9. Client invokes RTSP TEARDOWN request to terminate the RTSP session.
- 10. If Device sends response to RTSP TEARDOWN, it has code RTSP 200 OK or RTSP 454.

#### Test Result:

**Note:** RTSP requests and RTSP response could be tunneled in HTTP if RTP-Unicast/RTSP/HTTP/TCP transport is used.



- There is Client RTSP DESCRIBE request in Test Procedure
- Device response on the RTSP DESCRIBE request fulfills the following requirements:
  - [S1] It has RTSP 200 response code AND
  - [S2] IF SDP packet contains media type "audio" (m=audio) without session attribute "sendonly" (a=sendonly) AND with sessions attribute "rtpmap" THEN encoding name is "PCMU"
  - [S3] ELSE IF SDP packet contains media type "audio" (m=audio) without session attribute
    "sendonly" (a=sendonly) AND without sessions attribute "rtpmap" THEN payload type
    number is "0" (see [RFC 3551]) AND
- There is Client RTSP SETUP request in Test Procedure fulfills the following requirements:
  - [S4] It invoked for the same Device as for the Client RTSP DESCRIBE request AND
  - [S5] It invoked after the Client RTSP DESCRIBE request AND
  - [S6] RTSP address that was used to send RTSP SETUP is correspond to corresponding media Control URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
  - [S7] It does not contain Require request header field with value is equal to "onvif-replay"
     AND
- Device response on the RTSP SETUP request fulfills the following requirements:
  - [S8] It has RTSP 200 response code AND
- There is a Device response on the **GetStreamUri** request to Media2 Service in Test Procedure fulfills the following requirements:
  - [S9] It has HTTP 200 response code AND
  - [S10] It received for the same Device as for the Client RTSP DESCRIBE request AND
  - [S11] It received before the Client RTSP DESCRIBE request AND
  - [S12] It contains **tr2:Uri** element which value is equal to RTSP address that was used to send the **RTSP DESCRIBE** request AND
- There is Client RTSP PLAY request in Test Procedure fulfills the following requirements:
  - [S13] It invoked for the same Device as for the Client RTSP SETUP request AND



- [S14] It invoked after the Client RTSP SETUP request AND
- [S15] RTSP address that was used to send it is correspond to corresponding media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
- [S16] It does not contain Require request header field with value is equal to "onvif-replay"
   AND
- Device response on the RTSP PLAY request fulfills the following requirements:
  - [S17] It has RTSP 200 response code AND
- There is Client **RTSP TEARDOWN** request in Test Procedure fulfills the following requirements:
  - [S18] It invoked for the same Device as for the Client RTSP SETUP request AND
  - [S19] It invoked after the Client RTSP PLAY request AND
  - [S20] RTSP address that was used to send it is correspond to corresponding media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
- If there is Device response on the **RTSP TEARDOWN** request then it fulfills the following requirements:
  - [S21] It has RTSP 200 response code.

· The Client failed PASS criteria.

Validated Feature List: media2\_audio\_streaming.g711



## 14 AAC Audio Streaming Using Media2 Test Cases

### 14.1 Feature Level Requirement:

Validated Feature: AudioStreaming

Check Condition based on Device Features: Real Time Streaming (Media2 Service) and Audio

AAC (Media2 Service) are supported by Device.

**Required Number of Devices: 1** 

**Profile T Requirement:** Conditional

## 14.2 Expected Scenarios Under Test:

- 1. Client connects to Device to configure a media profile and initiate Audio Streaming with AAC encoding type.
- 2. Client is considered as supporting AAC Audio Streaming if the following conditions are met:
  - Client supports media2\_get\_profiles.get\_profiles feature AND
  - Client supports media2\_get\_stream\_uri.get\_stream\_uri feature AND
  - Client is able to initiate and retrieve audio stream using Media2 with AAC encoding type.
- 3. Client is considered as NOT supporting AAC Audio Streaming if ANY of the following is TRUE:
  - · Client does not support media2 get profiles.get profiles feature OR
  - · Client does not support media2 get stream uri.get stream uri feature OR
  - Client is unable to initiate and retrieve audio stream using Media2 with AAC encoding type.

#### 14.3 AAC AUDIO STREAMING USING MEDIA2

Test Label: Audio Streaming using Media2 - AAC

Test Case ID: MEDIA2 AACAUDIOSTREAMING-1

**Profile T Normative Reference:** Conditional

Feature Under Test: AudioStreaming



**Test Purpose:** To verify that the Client is able to initiate and retrieve audio stream with AAC encoding type.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with Audio Streaming of AAC encoding type.
- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetStreamUri** for Media2 Service.
- Device supports AAC encoding for Audio streaming using Media2 (Media2 AAC).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetStreamUri request message for media profile that contains Audio Source Configuration and Audio Encoder Configuration with AAC Encoding value. GetStreamUri request is set for RTP-Unicast/UDP OR RTP-Multicast/UDP OR RTP/RTSP/TCP OR RTP-Unicast/RTSP/HTTP/TCP transport.
- 2. Device responds with code HTTP 200 OK and **GetStreamUriResponse** message.
- 3. Client invokes RTSP DESCRIBE request to retrieve media stream description.
- 4. Device responds with code RTSP 200 OK and SDP information with Media Type: "audio" and with encoding name "MPEG4-GENERIC".
- 5. Client invokes **RTSP SETUP** request without "onvif-replay" Require header and with transport parameter element to to set media session parameters for AAC audio streaming.
- 6. Device responds with code RTSP 200 OK.
- 7. Client invokes **RTSP PLAY** request without "onvif-replay" Require header to start media stream.
- 8. Device responds with code RTSP 200 OK.
- 9. Client invokes RTSP TEARDOWN request to terminate the RTSP session.
- 10. If Device sends response to RTSP TEARDOWN, it has code RTSP 200 OK or RTSP 454.

#### **Test Result:**

**Note:** RTSP requests and RTSP response could be tunneled in HTTP if RTP-Unicast/RTSP/HTTP/TCP transport is used.



- There is Client RTSP DESCRIBE request in Test Procedure
- Device response on the RTSP DESCRIBE request fulfills the following requirements:
  - [S1] It has RTSP 200 response code AND
  - [S2] SDP packet contains media type "audio" (m=audio) without session attribute "sendonly" (a=sendonly) AND with sessions attribute "rtpmap" with encoding name "MPEG4-GENERIC" (see [RFC 3640]) AND
- There is Client RTSP SETUP request in Test Procedure fulfills the following requirements:
  - [S3] It invoked for the same Device as for the Client RTSP DESCRIBE request AND
  - [S4] It invoked after the Client RTSP DESCRIBE request AND
  - [S5] RTSP address that was used to send RTSP SETUP is correspond to corresponding media Control URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
  - [S6] It does not contain Require request header field with value is equal to "onvif-replay"
     AND
- Device response on the RTSP SETUP request fulfills the following requirements:
  - [S7] It has RTSP 200 response code AND
- There is a Device response on the **GetStreamUri** request to Media2 Service in Test Procedure fulfills the following requirements:
  - · [S8] It has HTTP 200 response code AND
  - [S9] It received for the same Device as for the Client RTSP DESCRIBE request AND
  - [S10] It received before the Client RTSP DESCRIBE request AND
  - [S11] It contains **tr2:Uri** element which value is equal to RTSP address that was used to send the **RTSP DESCRIBE** request AND
- There is Client RTSP PLAY request in Test Procedure fulfills the following requirements:
  - [S12] It invoked for the same Device as for the Client RTSP SETUP request AND
  - [S13] It invoked after the Client RTSP SETUP request AND
  - [S14] RTSP address that was used to send it is correspond to corresponding media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND



- [S15] It does not contain Require request header field with value is equal to "onvif-replay" AND
- Device response on the RTSP PLAY request fulfills the following requirements:
  - [S16] It has RTSP 200 response code AND
- There is Client **RTSP TEARDOWN** request in Test Procedure fulfills the following requirements:
  - [S17] It invoked for the same Device as for the Client RTSP SETUP request AND
  - [S18] It invoked after the Client RTSP PLAY request AND
  - [S19] RTSP address that was used to send it is correspond to corresponding media Control URL or session Control URL or Content-Base URL from SDP packet (see [RFC 2326, C.1.1 Control URL]) AND
- If there is Device response on the **RTSP TEARDOWN** request then it fulfills the following requirements:
  - [S20] It has RTSP 200 response code.

• The Client failed PASS criteria.

Validated Feature List: media2\_audio\_streaming.aac



# 15 Audio Profile Configuration Using Media2 Test Cases

## 15.1 Feature Level Requirement:

Validated Feature: Media2AudioProfileConfiguration

Check Condition based on Device Features: Audio (Media2 Service) is supported by Device.

**Required Number of Devices: 1** 

**Profile T Requirement:** Conditional

## 15.2 Expected Scenarios Under Test:

- 1. Client connects to Device to add compatible audio source configuration and audio encoder configuration to a Media Profile.
- 2. Client is considered as supporting Audio Profile Configuration if the following conditions are met:
  - Client is able to add an audio source configuration to profile using EITHER
     AddConfiguration operation with Type element value is equal to AudioSource OR
     CreateProfile operation with Type element value is equal to AudioSource.
  - Client is able to retrieve audio encoder configurations compatible with media profile using **GetAudioEncoderConfigurations** operation with specified ProfileToken element.
  - Client is able to add an audio encoder configuration using **AddConfiguration** operation with Type element value is equal to AudioEncoder.
- 3. Client is considered as NOT supporting Audio Profile Configuration if ANY of the following is TRUE:
  - Client unable to add an audio source configuration to profile using AddConfiguration operation and CreateProfile operation OR
  - No valid responses for CreateProfile request Type element value is equal to AudioSource if detected OR
  - No valid responses for GetAudioEncoderConfigurations request with ProfileToken element OR



- No valid responses for AddConfiguration request with Type element value is equal to AudioEncoder OR
- No valid responses for AddConfiguration request with Type element value is equal to AudioSource is detected.

## 15.3 ADD AUDIO SOURCE CONFIGURATION USING MEDIA2

Test Label: Add Audio Source Configuration

Test Case ID: MEDIA2 AUDIOPROFILECONFIGURATION-1

Profile T Normative Reference: Conditional

Feature Under Test: AddConfiguration

**Test Purpose:** To verify that Client is able to add an audio source configuration to a media profile using the **GetAudioSourceConfigurations** and **AddConfiguration** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with AddConfiguration operation with Type = AudioSource present.
- Device supports Media2 Audio feature (Media2 Audio).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetAudioSourceConfigurations request message with specified ProfileToken to retrieve compatible audio source configurations for specified media profile from the Device.
- 2. Device responds with code HTTP 200 OK and **GetAudioSourceConfigurationsResponse** message.
- 3. Client invokes AddConfiguration request message with Type element value is equal to AudioSource and with Configuration token that was recieved in GetAudioSourceConfigurationsResponse message for the same media profile to add an audio source configuration to specified media profile on the Device.
- 4. Device responds with code HTTP 200 OK and AddConfigurationResponse message.

#### **Test Result:**

68 www.onvif.org	



#### PASS -

- Client AddConfiguration request messages are valid according to XML Schemas listed in Namespaces AND
- Client AddConfiguration request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:AddConfiguration AND
  - [S2] It has tr2:Configuration/tr2:Type element with value is equal to "AudioSource" AND
- Device response to the **AddConfiguration** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element tr2:AddConfigurationResponse.
- There is Client **GetAudioSourceConfigurations** request in Test Procedure that fulfills the following requirements:
  - [S5] It is invoked before the Client AddConfiguration request AND
  - [S6] It has **tr2:ProfileToken** element with value is equal to **tr2:ProfileToken** element value from the **AddConfiguration** request AND
  - [S7] It is the last **GetAudioSourceConfigurations** request which corresponds to [S5], AND [S6] AND
- Device response to the **GetAudioSourceConfigurations** request fulfills the following requirements:
  - [S8] It has HTTP 200 response code AND
  - [S9] soapenv:Body element has child element tr2:GetAudioSourceConfigurationsResponse AND
  - [S10] It contains tr2:Configurations element with @token attribute value equal to tr2:Configuration/tr2:Token value for Configuration with tr2:Configuration/tr2:Type value is equal to AudioSource from the AddConfiguration request message.

#### FAIL -

· The Client failed PASS criteria.

Validated Feature List: Media2AudioProfileConfiguration.AddAudioSourceConfiguration

www.onvif.org	69



## 15.4 CREATE MEDIA PROFILE WITH AUDIO SOURCE CONFIGURATION USING MEDIA2

Test Label: Create Media2 Profile with Audio Source Configuration

Test Case ID: MEDIA2\_AUDIOPROFILECONFIGURATION-2

Profile T Normative Reference: Conditional

Feature Under Test: CreateProfile

**Test Purpose:** To verify that Client is able to create media profile with audio source configuration using the **CreateProfile** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **CreateProfile** operation with Type = **AudioSource** present.
- Device supports Media2 Audio feature (Media2 Audio).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes CreateProfile request message with tr2:Configuration\tr2:Type = AudioSource and with specified tr2:Token element for this Configuration to create profile with audio source configuration on the Device.
- 2. Device responds with code HTTP 200 OK and **CreateProfileResponse** message.

#### Test Result:

- Client CreateProfile request messages are valid according to XML Schemas listed in Namespaces AND
- Client **CreateProfile** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:CreateProfile AND
  - [S2] It has tr2:Configuration/tr2:Type element with value is equal to "AudioSource" AND
  - [S3] tr2:Configuration element with tr2:Type value is equal to "AudioSource" has tr2:Token element AND
- Device response to the **CreateProfile** request fulfills the following requirements:



- [S3] It has HTTP 200 response code AND
- [S4] soapenv:Body element has child element tr2:CreateProfileResponse.

· The Client failed PASS criteria.

Validated Feature List:

Media 2 Audio Profile Configuration. Create Profile With Audio Source Configuration

## 15.5 GET AUDIO ENCODER CONFIGURATIONS COMPATIBLE WITH PROFILE USING MEDIA2

Test Label: Get Audio Encoder Configurations

Test Case ID: MEDIA2\_AUDIOPROFILECONFIGURATION-3

Profile T Normative Reference: Conditional

Feature Under Test: Media2\_GetCompatibleAudioEncoderConfigurations

**Test Purpose:** To verify that list of audio encoder configurations compatible with a media profile is received by Client using the **GetAudioEncoderConfigurations** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with GetAudioEncoderConfigurations operation with specified ProfileToken element present.
- Device supports Media2 Audio feature (Media2 Audio).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetAudioEncoderConfigurations request message with ProfileToken element to retrieve a list of audio encoder configurations compatible with requested media profile from the Device.
- Device responds with code HTTP 200 OK and GetAudioEncoderConfigurationsResponse message.

T4	D		14.
Test	Res	u	IT:

www.onvif.org	71



- Client GetAudioEncoderConfigurations request messages are valid according to XML Schemas listed in Namespaces AND
- Client GetAudioEncoderConfigurations request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetAudioEncoderConfigurations
     AND
  - [S2] It has tr2:ProfileToken element AND
- Device response to the **GetAudioEncoderConfigurations** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element tr2:GetAudioEncoderConfigurationsResponse.

· The Client failed PASS criteria.

Validated Feature List:

 $Media 2 Audio Profile Configuration. Media 2\_Get Compatible Audio Encoder Configurations$ 

## 15.6 ADD AUDIO ENCODER CONFIGURATION USING MEDIA2

Test Label: Add Audio Encoder Configuration

Test Case ID: MEDIA2\_AUDIOPROFILECONFIGURATION-4

Profile T Normative Reference: Conditional

Feature Under Test: AddConfiguration

**Test Purpose:** To verify that Client is able to add an audio encoder configuration to a media profile using the **AddConfiguration** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **AddConfiguration** operation with Type value is equal to "VideoEncoder" present.
- Device supports Media2 Audio feature (Media2\_Audio).



#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetAudioEncoderConfigurations request message with specified ProfileToken to retrieve compatible audio encoder configurations for specified media profile from the Device.
- 2. Device responds with code HTTP 200 OK and **GetAudioEncoderConfigurationsResponse** message.
- 3. Client invokes AddConfiguration request message with Type element value is equal to AudioEncoder and with Configuration token that was recieved in GetAudioEncoderConfigurationsResponse message for the same media profile to add an audio encoder configuration to specified media profile on the Device.
- 4. Device responds with code HTTP 200 OK and AddConfigurationResponse message.

#### **Test Result:**

- Client AddConfiguration request messages are valid according to XML Schemas listed in Namespaces AND
- Client AddConfiguration request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:AddConfiguration AND
  - [S2] It has tr2:Configuration/tr2:Type element with value is equal to "AudioEncoder" AND
- Device response to the **AddConfiguration** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element tr2:AddConfigurationResponse.
- There is Client **GetAudioEncoderConfigurations** request in Test Procedure that fulfills the following requirements:
  - [S5] It is invoked before the Client AddConfiguration request AND
  - [S6] It has tr2:ProfileToken element with value is equal to tr2:ProfileToken element value from the AddConfiguration request AND
  - [S7] It is the last GetAudioEncoderConfigurations request which corresponds to [S5],
     AND [S6] AND
- Device response to the **GetAudioEncoderConfigurations** request fulfills the following requirements:

www.onvif.org	73



- [S8] It has HTTP 200 response code AND
- [S9] **soapenv:Body** element has child element **tr2:GetAudioEncoderConfigurationsResponse** AND
- [S10] It contains tr2:Configurations element with @token attribute value equal to tr2:Configuration/tr2:Token value for Configuration with tr2:Configuration/tr2:Type value is equal to AudioEncoder from the AddConfiguration request message.

· The Client failed PASS criteria.

Validated Feature List: Media2AudioProfileConfiguration.AddAudioEncoderConfiguration



# 16 Audio Backchannel Streaming Using Media2 Test Cases

### 16.1 Feature Level Requirement:

Validated Feature: AudioBackchannelStreaming

Check Condition based on Device Features: Real Time Streaming (Media2 Service) and Audio

Output (Media2 Service) are supported by Device.

**Required Number of Devices: 1** 

Profile T Requirement: Conditional

### 16.2 Expected Scenarios Under Test:

- 1. Client connects to Device to stream audio for backchannel using Media2.
- 2. Client is considered as supporting Audio Backchannel Streaming if the following conditions are met:
  - Client is able to stream unicast audio for backchannel using G.711 AND
  - Client is able to stream unicast audio for backchannel using AAC if supported.
- 3. Client is considered as NOT supporting Audio Backchannel Streaming if ANY of the following is TRUE:
  - · No unicast G.711 Audio Backchannel Streaming attempts were found OR
  - Unicast G.711 Audio Backchannel Streaming attempts have failed OR
  - Detected unicast AAC Audio Backchannel Streaming attempts have failed.

## 16.3 G.711 AUDIO BACKCHANNEL STREAMING USING MEDIA2

Test Label: Audio Backchannel Streaming Using Media2 - G.711

Test Case ID: MEDIA2 AUDIOBACKCHANNELSTREAMING-1

Profile A Normative Reference: None



Profile C Normative Reference: None

Profile G Normative Reference: None

Profile Q Normative Reference: None

Profile S Normative Reference: None

Profile T Normative Reference: Conditional

Feature Under Test: Audio Backchannel Streaming

**Test Purpose:** To verify that unicast audio backchannel streaming to Device was successfully started by Client.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with unicast audio backchannel streaming using Media2 with G.711 encoding.
- The Network Trace Capture files contains at least one Conversation between Client and Device with GetStreamUri for Media2 Service.
- Device supports G.711 decoding for Media2 Audio Outputs (Media2 AudioOutputG711).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetStreamUri request message to Media2 Service for media profile that contains Audio Output Configuration and Audio Decoder Configuration with RTP-Unicast/ UDP OR RTP/RTSP/TCP OR RTP-Unicast/RTSP/HTTP/TCP transport.
- 2. Device responds with code HTTP 200 OK and **GetStreamUriResponse** message.
- 3. Client invokes **RTSP DESCRIBE** request to retrieve media stream description with **Require** tag in RTSP header that contains "www.onvif.org/ver20/backchannel".
- 4. Device responds with code RTSP 200 OK with SDP that contains media type "audio" with session attribute "sendonly".
- 5. Client invokes **RTSP SETUP** request with transport parameter element to set media session parameters for audio backchannel with **Require** tag in RTSP header that contains "www.onvif.org/ver20/backchannel".
- 6. Device responds with code RTSP 200 OK.
- 7. Client invokes **RTSP PLAY** request to start media stream with **Require** tag in RTSP header that contains "www.onvif.org/ver20/backchannel".



- 8. Device responds with code RTSP 200 OK.
- 9. Client invokes **RTSP TEARDOWN** request to terminate the RTSP session with **Require** tag in RTSP header that contains "www.onvif.org/ver20/backchannel".
- 10. If Device sends response to RTSP TEARDOWN, it has code RTSP 200 OK or RTSP 454.

**Note:** RTSP requests and RTSP response could be tunneled in HTTP if RTP-Unicast/RTSP/HTTP/TCP transport is used.

#### **Test Result:**

- Client RTSP DESCRIBE request in Test Procedure fulfills the following requirements:
  - [S1] Require tag in RTSP header contains "www.onvif.org/ver20/backchannel" AND
- Device response to the RTSP DESCRIBE request fulfills the following requirements:
  - [S2] It has RTSP 200 response code AND
  - [S3] SDP packet contains media type "audio" (m=audio) with session attribute "sendonly" (a=sendonly) and sessions attribute "rtpmap" with encoding name "PCMU" AND
- There is Client RTSP SETUP request in Test Procedure that fulfills the following requirements:
  - [S5] It is invoked after the Client RTSP DESCRIBE request AND
  - [S6] RTSP address that was used to send RTSP SETUP is corresponds to media type
    "audio" with session attribute "sendonly" depending on media session attribute, general
    session attribute and address that was used for the RTSP DESCRIBE request (see [RFC
    2326]) AND
  - [S7] Require tag in RTSP header contains "www.onvif.org/ver20/backchannel" AND
- Device response to the RTSP SETUP request fulfills the following requirements:
  - [S8] It has RTSP 200 response code AND
- There is GetStreamUri request to Media2 Service in Test Procedure that fulfills the following requirements:
  - [S9] tr2:Protocol element value is equal EITHER RtspUnicast OR RTSP OR RtspOverHttp AND
- There is a Device response to the **GetStreamUri** request to Media2 Service in Test Procedure that fulfills the following requirements:

www.onvif.org	77



- [S10] It has HTTP 200 response code AND
- [S11] It is received from the same Device as the response for RTSP DESCRIBE request AND
- [S12] It is received before the Client RTSP DESCRIBE request AND
- [S13] It contains **tr2:Uri** element which value is equal to RTSP address that was used to send the **RTSP DESCRIBE** request AND
- There is Client RTSP PLAY request in Test Procedure that fulfills the following requirements:
  - [S14] It is invoked for the same Device as the response for RTSP SETUP request AND
  - [S15] It is invoked after the Client RTSP SETUP request AND
  - [S16] RTSP address that was used to send it should be equal to address that was used for the RTSP DESCRIBE request AND
  - [S17] Require tag in RTSP header contains "www.onvif.org/ver20/backchannel" AND
- Device response to the RTSP PLAY request fulfills the following requirements:
  - [S18] It has RTSP 200 response code AND
- There is Client **RTSP TEARDOWN** request in Test Procedure that fulfills the following requirements:
  - [S19] It is invoked for the same Device as the response for RTSP SETUP request AND
  - [S20] It is invoked after the Client RTSP PLAY request AND
  - [S21] RTSP address that was used to send it should be equal to address that was used for the RTSP DESCRIBE request AND
  - [S22] Require tag in RTSP header contains "www.onvif.org/ver20/backchannel" AND
- If there is Device response on the **RTSP TEARDOWN** request then it fulfills the following requirements:
  - [S23] It has RTSP 200 response code.

· The Client failed PASS criteria.

Validated Feature List: media2\_audio\_backchannel\_streaming.g711



## 16.4 AAC AUDIO BACKCHANNEL STREAMING USING MEDIA2

Test Label: Audio Backchannel Streaming - AAC

Test Case ID: MEDIA2\_AUDIOBACKCHANNELSTREAMING-2

Profile A Normative Reference: None

Profile C Normative Reference: None

Profile G Normative Reference: None

Profile Q Normative Reference: None

Profile S Normative Reference: None

Profile T Normative Reference: Conditional

Feature Under Test: Audio Backchannel Streaming

**Test Purpose:** To verify that audio backchannel streaming to Device was successfully started by Client.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with unicast audio backchannel streaming using Media2 with AAC encoding.
- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetStreamUri** for Media2 Service.
- Device supports AAC encoding for Media2 Audio Outputs (Media2 AudioOutputAAC).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetStreamUri request message to Media2 Service for media profile that contains Audio Output Configuration and Audio Decoder Configuration with RTP-Unicast/ UDP OR RTP/RTSP/TCP OR RTP-Unicast/RTSP/HTTP/TCP transport.
- 2. Device responds with code HTTP 200 OK and GetStreamUriResponse message.
- 3. Client invokes **RTSP DESCRIBE** request to retrieve media stream description with **Require** tag in RTSP header that contains "www.onvif.org/ver20/backchannel".



- 4. Device responds with code RTSP 200 OK with SDP that contains media type "audio" with session attribute "sendonly".
- 5. Client invokes **RTSP SETUP** request with transport parameter element to set media session parameters for audio backchannel with **Require** tag in RTSP header that contains "www.onvif.org/ver20/backchannel".
- 6. Device responds with code RTSP 200 OK.
- 7. Client invokes **RTSP PLAY** request to start media stream with **Require** tag in RTSP header that contains "www.onvif.org/ver20/backchannel".
- 8. Device responds with code RTSP 200 OK.
- 9. Client invokes **RTSP TEARDOWN** request to terminate the RTSP session with **Require** tag in RTSP header that contains "www.onvif.org/ver20/backchannel".
- 10. If Device sends response to RTSP TEARDOWN, it has code RTSP 200 OK or RTSP 454.

**Note:** RTSP requests and RTSP response could be tunneled in HTTP if RTP-Unicast/RTSP/HTTP/TCP transport is used.

#### **Test Result:**

- Client RTSP DESCRIBE request in Test Procedure fulfills the following requirements:
  - [S1] Require tag in RTSP header contains "www.onvif.org/ver20/backchannel" AND
- Device response to the RTSP DESCRIBE request fulfills the following requirements:
  - [S2] It has RTSP 200 response code AND
  - [S3] SDP packet contains media type "audio" (m=audio) with session attribute "sendonly" (a=sendonly) and sessions attribute "rtpmap" with encoding name "mpeg4-generic" AND
- There is Client RTSP SETUP request in Test Procedure that fulfills the following requirements:
  - [S5] It is invoked after the Client RTSP DESCRIBE request AND
  - [S6] RTSP address that was used to send RTSP SETUP is corresponds to media type
    "audio" with session attribute "sendonly" depending on media session attribute, general
    session attribute and address that was used for the RTSP DESCRIBE request (see [RFC
    2326]) AND
  - [S7] Require tag in RTSP header contains "www.onvif.org/ver20/backchannel" AND



- Device response to the RTSP SETUP request fulfills the following requirements:
  - [S8] It has RTSP 200 response code AND
- There is GetStreamUri request to Media2 Service in Test Procedure that fulfills the following requirements:
  - [S9] tr2:Protocol element value is equal EITHER RtspUnicast OR RTSP OR RtspOverHttp AND
- There is a Device response to the **GetStreamUri** request to Media2 Service in Test Procedure that fulfills the following requirements:
  - [S10] It has HTTP 200 response code AND
  - [S11] It is received from the same Device the response for RTSP DESCRIBE request AND
  - [S12] It is received before the Client RTSP DESCRIBE request AND
  - [S13] It contains **tr2:Uri** element which value is equal to RTSP address that was used to send the **RTSP DESCRIBE** request AND
- There is Client RTSP PLAY request in Test Procedure that fulfills the following requirements:
  - [S14] It is invoked for the same Device as the response for RTSP SETUP request AND
  - [S15] It is invoked after the Client RTSP SETUP request AND
  - [S16] RTSP address that was used to send it should be equal to address that was used for the RTSP DESCRIBE request AND
  - [S17] Require tag in RTSP header contains "www.onvif.org/ver20/backchannel" AND
- Device response to the RTSP PLAY request fulfills the following requirements:
  - [S18] It has RTSP 200 response code AND
- There is Client **RTSP TEARDOWN** request in Test Procedure that fulfills the following requirements:
  - [S19] It is invoked for the same Device the response for RTSP SETUP request AND
  - [S20] It is invoked after the Client RTSP PLAY request AND
  - [S21] RTSP address that was used to send it should be equal to address that was used for the RTSP DESCRIBE request AND
  - [S22] Require tag in RTSP header contains "www.onvif.org/ver20/backchannel" AND



- If there is Device response on the **RTSP TEARDOWN** request then it fulfills the following requirements:
  - [S23] It has RTSP 200 response code.

• The Client failed PASS criteria.

Validated Feature List: media2\_audio\_backchannel\_streaming.aac



# 17 Audio Output Profile Configuration Using Media2 Test Cases

### 17.1 Feature Level Requirement:

Validated Feature: Media2AudioOutputProfileConfiguration

Check Condition based on Device Features: Audio Output (Media2 Service) is supported by Device.

**Required Number of Devices: 1** 

**Profile T Requirement:** Conditional

### 17.2 Expected Scenarios Under Test:

- 1. Client connects to Device to add compatible audio output configuration and decoder configuration to a Media Profile.
- 2. Client is considered as supporting Audio Output Profile Configuration if the following conditions are met:
  - Client is able to add an audio output configuration to profile using EITHER
     AddConfiguration operation with Type element value is equal to AudioOutput OR
     CreateProfile operation with Type element value is equal to AudioOutput.
  - Client is able to retrieve audio decoder configurations compatible with media profile using GetAudioDecoderConfigurations operation with specified ProfileToken element.
  - Client is able to add an audio decoder configurations using **AddConfiguration** operation with Type element value is equal to AudioDecoder.
- 3. Client is considered as NOT supporting Audio Output Profile Configuration if ANY of the following is TRUE:
  - Client unable to add an audio output configuration to profile using AddConfiguration operation and CreateProfile operation OR
  - No valid responses for CreateProfile request Type element value is equal to AudioOutput if detected OR
  - No valid responses for GetAudioDecoderConfigurations request with ProfileToken element OR



- No valid responses for AddConfiguration request with Type element value is equal to AudioDecoder OR
- No valid responses for AddConfiguration request with Type element value is equal to AudioOutput is detected.

## 17.3 ADD AUDIO OUTPUT CONFIGURATION USING MEDIA2

Test Label: Add Audio Output Configuration

Test Case ID: MEDIA2\_AUDIOOUTPUTPROFILECONFIGURATION-1

Profile T Normative Reference: Conditional

Feature Under Test: AddConfiguration

**Test Purpose:** To verify that Client is able to add an audio output configuration to a media profile using the **GetAudioOutputConfigurations** and **AddConfiguration** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with AddConfiguration operation with Type = AudioOutput present.
- Device supports Media2 Audio Output feature (Media2 AudioOutput).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetAudioOutputConfigurations request message with specified ProfileToken to retrieve compatible audio output configurations for specified media profile from the Device.
- 2. Device responds with code HTTP 200 OK and **GetAudioOutputConfigurationsResponse** message.
- 3. Client invokes AddConfiguration request message with Type element value is equal to AudioOutput and with Configuration token that was recieved in GetAudioOutputConfigurationsResponse message for the same media profile to add an audio output configuration to specified media profile on the Device.
- 4. Device responds with code HTTP 200 OK and AddConfigurationResponse message.

#### Test Result:

84	www.onvif.org	



#### PASS -

- Client AddConfiguration request messages are valid according to XML Schemas listed in Namespaces AND
- Client AddConfiguration request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:AddConfiguration AND
  - [S2] It has tr2:Configuration/tr2:Type element with value is equal to "AudioOutput" AND
- Device response to the **AddConfiguration** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element tr2:AddConfigurationResponse.
- There is Client **GetAudioOutputConfigurations** request in Test Procedure that fulfills the following requirements:
  - [S5] It is invoked before the Client AddConfiguration request AND
  - [S6] It has **tr2:ProfileToken** element with value is equal to **tr2:ProfileToken** element value from the **AddConfiguration** request AND
  - [S7] It is the last **GetAudioOutputConfigurations** request which corresponds to [S5], AND [S6] AND
- Device response to the **GetAudioOutputConfigurations** request fulfills the following requirements:
  - [S8] It has HTTP 200 response code AND
  - [S9] soapenv:Body element has child element tr2:GetAudioOutputConfigurationsResponse AND
  - [S10] It contains tr2:Configurations element with @token attribute value equal to tr2:Configuration/tr2:Token value for Configuration with tr2:Configuration/tr2:Type value is equal to AudioOutput from the AddConfiguration request message.

#### FAIL -

· The Client failed PASS criteria.

**Validated Feature List:** Media2AudioProfileConfiguration.AddAudioOutputConfiguration

www.onvif.org	8



## 17.4 CREATE MEDIA PROFILE WITH AUDIO OUTPUT CONFIGURATION USING MEDIA2

Test Label: Create Media2 Profile with Audio Output Configuration

Test Case ID: MEDIA2\_AUDIOOUTPUTPROFILECONFIGURATION-2

Profile T Normative Reference: Conditional

Feature Under Test: CreateProfile

**Test Purpose**: To verify that Client is able to create media profile with audio output configuration using the **CreateProfile** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **CreateProfile** operation with Type = **AudioOutput** present.
- Device supports Media2 Audio Output feature (Media2\_AudioOutput).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes CreateProfile request message with tr2:Configuration\tr2:Type = AudioOutput and with specified tr2:Token element for this Configuration to create profile with audio output configuration on the Device.
- 2. Device responds with code HTTP 200 OK and **CreateProfileResponse** message.

#### Test Result:

- Client CreateProfile request messages are valid according to XML Schemas listed in Namespaces AND
- Client CreateProfile request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:CreateProfile AND
  - [S2] It has tr2:Configuration/tr2:Type element with value is equal to "AudioOutput" AND
  - [S3] tr2:Configuration element with tr2:Type value is equal to "AudioOutput" has tr2:Token element AND
- Device response to the **CreateProfile** request fulfills the following requirements:

36	www.onvif.org
	· · · · · · · · · · · · · · · · · · ·



- [S3] It has HTTP 200 response code AND
- [S4] soapenv:Body element has child element tr2:CreateProfileResponse.

· The Client failed PASS criteria.

Validated Feature List:

Media2AudioProfileConfiguration.CreateProfileWithAudioOutputConfiguration

## 17.5 GET AUDIO DECODER CONFIGURATIONS COMPATIBLE WITH PROFILE USING MEDIA2

**Test Label:** Get Audio Decoder Configurations

Test Case ID: MEDIA2 AUDIOOUTPUTPROFILECONFIGURATION-3

Profile T Normative Reference: Conditional

Feature Under Test: GetAudioDecoderConfigurationsUsingMedia2

**Test Purpose:** To verify that list of audio decoder configurations compatible with a media profile is received by Client using the **GetAudioDecoderConfigurations** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetAudioDecoderConfigurations** operation present.
- Device supports Media2 Audio Output feature (Media2 AudioOutput).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetAudioDecoderConfigurations request message with ProfileToken element to retrieve a list of audio decoder configurations compatible with requested media profile from the Device.
- Device responds with code HTTP 200 OK and GetAudioDecoderConfigurationsResponse message.

Toot	Resu	.14.	
iest	Kest	JIT:	

www.onvif.org	87



- Client GetAudioDecoderConfigurations request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetAudioDecoderConfigurations** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetAudioDecoderConfigurations
     AND
  - [S2] It has tr2:ProfileToken element AND
- Device response to the **GetAudioDecoderConfigurations** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element tr2:GetAudioDecoderConfigurationsResponse.

· The Client failed PASS criteria.

Validated Feature List:

Media 2 Audio Output Profile Configuration. Get Compatible Audio Decoder Configurations

## 17.6 ADD AUDIO DECODER CONFIGURATION USING MEDIA2

Test Label: Add Audio Decoder Configuration

Test Case ID: MEDIA2\_AUDIOOUTPUTPROFILECONFIGURATION-4

Profile T Normative Reference: Conditional

Feature Under Test: AddConfiguration

**Test Purpose:** To verify that Client is able to add an audio decoder configuration to a media profile using the **AddConfiguration** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **AddConfiguration** operation present.
- Device supports Media2 Audio Output feature (Media2\_AudioOutput).

88	www.onvif.org	



#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetAudioDecoderConfigurations request message with specified ProfileToken to retrieve compatible audio decoder configurations for specified media profile from the Device.
- 2. Device responds with code HTTP 200 OK and **GetAudioDecoderConfigurationsResponse** message.
- 3. Client invokes AddConfiguration request message with Type element value is equal to AudioDecoder and with Configuration token that was recieved in GetAudioDecoderConfigurationsResponse message for the same media profile to add an audio decoder configuration to specified media profile on the Device.
- 4. Device responds with code HTTP 200 OK and **AddConfigurationResponse** message.

#### **Test Result:**

- Client AddConfiguration request messages are valid according to XML Schemas listed in Namespaces AND
- Client AddConfiguration request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:AddConfiguration AND
  - [S2] It has tr2:Configuration/tr2:Type element with value is equal to "AudioDecoder" AND
- Device response to the **AddConfiguration** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element tr2:AddConfigurationResponse.
- There is Client **GetAudioDecoderConfigurations** request in Test Procedure that fulfills the following requirements:
  - [S5] It is invoked before the Client AddConfiguration request AND
  - [S6] It has tr2:ProfileToken element with value is equal to tr2:ProfileToken element value from the AddConfiguration request AND
  - [S7] It is the last GetAudioDecoderConfigurations request which corresponds to [S5],
     AND [S6] AND
- Device response to the **GetAudioDecoderConfigurations** request fulfills the following requirements:

www.onvif.org	89



- [S8] It has HTTP 200 response code AND
- [S9] **soapenv:Body** element has child element **tr2:GetAudioDecoderConfigurationsResponse** AND
- [S10] It contains tr2:Configurations element with @token attribute value equal to tr2:Configuration/tr2:Token value for Configuration with tr2:Configuration/tr2:Type value is equal to AudioDecoder from the AddConfiguration request message.

· The Client failed PASS criteria.

Validated Feature List: Media2AudioOutputProfileConfiguration.AddAudioDecoderConfiguration



# 18 Analytics Profile Configuration Using Media2 Test Cases

### 18.1 Feature Level Requirement:

Validated Feature: Media2AnalyticsProfileConfiguration

Check Condition based on Device Features: Analytics (Media2 Service) is supported by Device.

**Required Number of Devices: 1** 

**Profile T Requirement:** Conditional

### 18.2 Expected Scenarios Under Test:

- 1. Client connects to Device to add compatible analytics configuration to a Media Profile.
- 2. Client is considered as supporting Analytics Profile Configuration if the following conditions are met:
  - Client is able to retrieve analytics configurations compatible with media profile using **GetAnalyticsConfigurations** operation with specified ProfileToken element.
  - Client is able to add an analytics configuration using **AddConfiguration** operation with Type element value is equal to **Analytics**.
- 3. Client is considered as NOT supporting Analytics Profile Configuration if ANY of the following is TRUE:
  - No valid responses for GetAnalyticsConfigurations request with ProfileToken element OR
  - No valid responses for AddConfiguration request with Type element value is equal to Analytics.

## 18.3 GET ANALYTICS CONFIGURATIONS COMPATIBLE WITH PROFILE USING MEDIA2

Test Label: Get Analytics Configurations

Test Case ID: MEDIA2\_ANALYTICSPROFILECONFIGURATION-1

Profile T Normative Reference: Conditional



Feature Under Test: Media2\_GetCompatibleAnalyticsConfigurations

Test Purpose: To verify that list of analytics configurations compatible with a media profile is received by Client using the **GetAnalyticsConfigurations** operation.

#### Pre-Requisite:

- · The Network Trace Capture files contains at least one Conversation between Client and Device with GetAnalyticsConfigurations operation with specified ProfileToken element present.
- Device supports Media2 Analytics feature (Media2\_Analytics).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes GetAnalyticsConfigurations request message with ProfileToken element to retrieve a list of analytics configurations compatible with requested media profile from the Device.
- 2. Device responds with code HTTP 200 OK and GetAnalyticsConfigurationsResponse message.

#### **Test Result:**

#### PASS -

- Client **GetAnalyticsConfigurations** request messages are valid according to XML Schemas listed in Namespaces AND
- Client GetAnalyticsConfigurations request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetAnalyticsConfigurations AND
  - [S2] It has tr2:ProfileToken element AND
- Device response to the GetAnalyticsConfigurations request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element tr2:GetAnalyticsConfigurationsResponse.

#### FAIL -

· The Client failed PASS criteria.



Validated Feature List:

Media2AnalyticsProfileConfiguration.Media2\_GetCompatibleAnalyticsConfigurations

## 18.4 ADD ANALYTICS CONFIGURATION USING MEDIA2

Test Label: Add Analytics Configuration

Test Case ID: MEDIA2 ANALYTICSPROFILECONFIGURATION-2

Profile T Normative Reference: Conditional

Feature Under Test: AddConfiguration

**Test Purpose:** To verify that Client is able to add an analytics configuration to a media profile using the **GetAnalyticsConfigurations** and **AddConfiguration** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **AddConfiguration** operation with Type = **Analytics** present.
- Device supports Media2 Analytics feature (Media2 Analytics).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetAnalyticsConfigurations** request message with specified **ProfileToken** to retrieve compatible analytics configurations for specified media profile from the Device.
- 2. Device responds with code HTTP 200 OK and **GetAnalyticsConfigurationsResponse** message.
- Client invokes AddConfiguration request message with Type element value is equal to Analytics and with Configuration token that was recieved in GetAnalyticsConfigurationsResponse message for the same media profile to add an analytics configuration to specified media profile on the Device.
- 4. Device responds with code HTTP 200 OK and AddConfigurationResponse message.

#### **Test Result:**

- Client AddConfiguration request messages are valid according to XML Schemas listed in Namespaces AND
- Client **AddConfiguration** request in Test Procedure fulfills the following requirements:

www.onvif.org	Q?



- [S1] soapenv:Body element has child element tr2:AddConfiguration AND
- [S2] It has tr2:Configuration/tr2:Type element with value is equal to Analytics AND
- Device response to the **AddConfiguration** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element tr2:AddConfigurationResponse.
- There is Client GetAnalyticsConfigurations request in Test Procedure that fulfills the following requirements:
  - [S5] It is invoked before the Client AddConfiguration request AND
  - [S6] It has tr2:ProfileToken element with value is equal to tr2:ProfileToken element value from the AddConfiguration request AND
  - [S7] It is the last GetAnalyticsConfigurations request which corresponds to [S5], AND
     [S6] AND
- Device response to the **GetAnalyticsConfigurations** request fulfills the following requirements:
  - [S8] It has HTTP 200 response code AND
  - [S9] soapenv:Body element has child element tr2:GetAnalyticsConfigurationsResponse AND
  - [S10] It contains tr2:Configurations element with @token attribute value equal to tr2:Configuration/tr2:Token value for Configuration with tr2:Configuration/tr2:Type value is equal to Analytics from the AddConfiguration request message.

· The Client failed PASS criteria.

Validated Feature List: Media2AnalyticsProfileConfiguration.AddAnalyticsConfiguration



### 19 Video Source Mode Test Cases

#### 19.1 Feature Level Normative Reference:

Validated Feature: VideoSourceMode

Check Condition based on Device Features: Video Source Mode (Media2 Service) is supported

by Device.

**Required Number of Devices: 1** 

Profile T Requirement: Conditional

### 19.2 Expected Scenarios Under Test:

- Client connects to Device to request the information for current video source mode and settable video source modes of specified video source using GetVideoSourceModes operation.
- 2. Client changes current video source mode using the **SetVideoSourceMode** operation.
- 3. Client is considered as supporting Video Source Mode if the following conditions are met:
  - Client is able to retrieve current video source mode and settable video source modes using GetVideoSourceModes operation AND
  - Client is able to modify source mode using **SetVideoSourceMode** operation.
- 4. Client is considered as NOT supporting Video Source Mode if ANY of the following is TRUE:
  - No valid response to GetVideoSourceModes request OR
  - No valid response to **SetVideoSourceMode** request.

#### 19.3 GET VIDEO SOURCE MODES

Test Label: Get Video Source Modes

Test Case ID: VIDEOSOURCEMODE-1

Profile T Normative Reference: Conditional

Feature Under Test: GetVideoSourceModes



**Test Purpose:** To verify that video source modes provided by Device is received by Client using the **GetVideoSourceModes** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with GetVideoSourceModes operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Video Source Mode feature (Media2 VideoSourceMode).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetVideoSourceModes** request message to retrieve a video source modes from the Device.
- 2. Device responds with code HTTP 200 OK and **GetVideoSourceModesResponse** message.

#### **Test Result:**

#### PASS -

- Client GetVideoSourceModes request messages are valid according to XML Schemas listed in Namespaces AND
- Client GetVideoSourceModes request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetVideoSourceModes AND
- Device response on the GetVideoSourceModes request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetVideoSourceModesResponse.

#### FAIL -

· The Client failed PASS criteria.

Validated Feature List: video\_source\_mode.get\_video\_source\_modes

### 19.4 SET VIDEO SOURCE MODE

Test Label: Set Video Source Mode

Test Case ID: VIDEOSOURCEMODE-2



Profile T Normative Reference: Conditional

Feature Under Test: SetVideoSourceMode

**Test Purpose**: To verify that current video source mode can be changed by Client using the **SetVideoSourceMode** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **SetVideoSourceMode** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Video Source Mode feature (Media2\_VideoSourceMode).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **SetVideoSourceMode** request message to change a video source mode on the Device.
- 2. Device responds with code HTTP 200 OK and **SetVideoSourceModeResponse** message.

#### **Test Result:**

#### PASS -

- Client SetVideoSourceMode request messages are valid according to XML Schemas listed in Namespaces AND
- Client **SetVideoSourceMode** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:SetVideoSourceMode AND
- Device response on the **SetVideoSourceMode** request fulfills the following requirements:
  - · [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:SetVideoSourceModeResponse.

#### FAIL -

· The Client failed PASS criteria.

Validated Feature List: video source mode.set video source mode



# 20 Audio Source Configuration Using Media2 Test Cases

#### 20.1 Feature Level Normative Reference:

Validated Feature: AudioSourceConfiguration

Check Condition based on Device Features: Audio (Media2 Service) is supported by Device.

Required Number of Devices: 1

Profile T Requirement: Optional

### 20.2 Expected Scenarios Under Test:

- 1. Client connects to Device to modify Audio Source Configuration.
- 2. Client is considered as supporting Audio Source Configuration if the following conditions are met:
  - Client is able to retrieve audio source configurations using GetAudioSourceConfigurations operation (Media2 Service) AND
  - Client is able to retrieve audio source configuration options using GetAudioSourceConfigurationOptions operation (Media2 Service) AND
  - Client is able to modify audio source configuration using SetAudioSourceConfiguration operation (Media2 Service) AND
- 3. Client is considered as NOT supporting Audio Source Configuration if ANY of the following is TRUE:
  - No valid response to GetAudioSourceConfigurations request (Media2 Service) OR
  - No valid response to GetAudioSourceConfigurationOptions request (Media2 Service)
     OR
  - No valid response to SetAudioSourceConfiguration request (Media2 Service) OR

## 20.3 GET AUDIO SOURCE CONFIGURATIONS USING MEDIA2

Test Label: Audio Source Configuration - Get Audio Source Configurations



Test Case ID: MEDIA2\_AUDIOSOURCECONFIGURATION-1

Profile T Normative Reference: Optional

Feature Under Test: GetAudioSourceConfigurations

**Test Purpose**: To verify that audio source configuration provided by Device is received by Client using the **GetAudioSourceConfigurations** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetAudioSourceConfigurations** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Audio feature for Media2 Service (Media2\_Audio).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetAudioSourceConfigurations** request message to retrieve an audio source configuration or a list of audio source configurations from the Device.
- 2. Device responds with code HTTP 200 OK and **GetAudioSourceConfigurationsResponse** message.

#### **Test Result:**

- Client GetAudioSourceConfigurations request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetAudioSourceConfigurations** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetAudioSourceConfigurations AND
- Device response on the **GetAudioSourceConfigurations** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetAudioSourceConfigurationsResponse.

FΔ	ı	ı	_
-		_	

www.onvif.org	99



· The Client failed PASS criteria.

Validated Feature List: media2 audio source configuration.get audio source configurations

## 20.4 GET AUDIO SOURCE CONFIGURATION OPTIONS USING MEDIA2

Test Label: Audio Source Configuration - Get Audio Source Configuration Options

Test Case ID: MEDIA2\_AUDIOSOURCECONFIGURATION-2

Profile T Normative Reference: Optional

Feature Under Test: GetAudioSourceConfigurationOptions

**Test Purpose:** To verify that audio source configuration options provided by Device is received by Client using the **GetAudioSourceConfigurationOptions** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetAudioSourceConfigurationOptions** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Audio feature for Media2 Service (Media2\_Audio).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetAudioSourceConfigurationOptions** request message to retrieve an audio source configuration options from the Device.
- 2. Device responds with code HTTP 200 OK and **GetAudioSourceConfigurationOptionsResponse** message.

#### **Test Result:**

#### PASS -

- Client GetAudioSourceConfigurationOptions request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetAudioSourceConfigurationOptions** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetAudioSourceConfigurationOptions AND

100



- Device response on the **GetAudioSourceConfigurations** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetAudioSourceConfigurationOptionsResponse.

· The Client failed PASS criteria.

Validated Feature List: media2 audio source configuration.get audio source configuration options

## 20.5 SET AUDIO SOURCE CONFIGURATION USING MEDIA2

Test Label: Audio Source Configuration - Set Audio Source Configuration

Test Case ID: MEDIA2 AUDIOSOURCECONFIGURATION-3

Profile T Normative Reference: Optional

Feature Under Test: SetAudioSourceConfiguration

**Test Purpose:** To verify that Client is able to change audio source configuration provided by Device using the **SetAudioSourceConfiguration** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **SetAudioSourceConfiguration** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Audio feature for Media2 Service (Media2 Audio).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes SetAudioSourceConfiguration request message to change an audio source configuration on the Device.
- 2. Device responds with code HTTP 200 OK and **SetAudioSourceConfigurationResponse** message.

www.onvif.org	101



#### **Test Result:**

#### PASS -

- Client SetAudioSourceConfiguration request messages are valid according to XML Schemas listed in Namespaces AND
- Client **SetAudioSourceConfiguration** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:SetAudioSourceConfiguration AND
- Device response on the **SetAudioSourceConfiguration** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:SetAudioSourceConfigurationResponse.

#### FAIL -

· The Client failed PASS criteria.

Validated Feature List: media2\_audio\_source\_configuration.set\_audio\_source\_configuration



# 21 Audio Output Configuration Using Media2 Test Cases

#### 21.1 Feature Level Normative Reference:

Validated Feature: AudioOutputConfiguration

Check Condition based on Device Features: Audio Output (Media2 Service) is supported by Device.

**Required Number of Devices: 1** 

Profile T Requirement: Optional

### 21.2 Expected Scenarios Under Test:

- 1. Client connects to Device to modify Audio Output Configuration.
- 2. Client is considered as supporting Audio Output Configuration if the following conditions are met:
  - Client is able to retrieve audio output configurations using GetAudioOutputConfigurations operation (Media2 Service) AND
  - Client is able to retrieve audio output configuration options using GetAudioOutputConfigurationOptions operation (Media2 Service) AND
  - Client is able to modify audio output configuration using SetAudioOutputConfiguration operation (Media2 Service) AND
- 3. Client is considered as NOT supporting Audio Output Configuration if ANY of the following is TRUE:
  - No valid response to **GetAudioOutputConfigurations** request (Media2 Service) OR
  - No valid response to GetAudioOutputConfigurationOptions request (Media2 Service)
     OR
  - No valid response to SetAudioOutputConfiguration request (Media2 Service) OR



## 21.3 GET AUDIO OUTPUT CONFIGURATIONS USING MEDIA2

Test Label: Audio Output Configuration - Get Audio Output Configurations

Test Case ID: MEDIA2 AUDIOOUTPUTCONFIGURATION-1

Profile T Normative Reference: Optional

Feature Under Test: GetAudioOutputConfigurations

**Test Purpose:** To verify that audio output configuration provided by Device is received by Client using the **GetAudioOutputConfigurations** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetAudioOutputConfigurations** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Audio outputs feature for Media2 Service (Media2\_AudioOutput).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetAudioOutputConfigurations** request message to retrieve an audio output configuration or a list of audio output configurations from the Device.
- 2. Device responds with code HTTP 200 OK and **GetAudioOutputConfigurationsResponse** message.

#### **Test Result:**

- Client GetAudioOutputConfigurations request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetAudioOutputConfigurations** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetAudioOutputConfigurations AND
- Device response on the **GetAudioOutputConfigurations** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND



• [S3] soapenv:Body element has child element tr2:GetAudioOutputConfigurationsResponse.

#### FAIL -

· The Client failed PASS criteria.

Validated Feature List: media2\_audio\_output\_configuration.get\_audio\_output\_configurations

## 21.4 GET AUDIO OUTPUT CONFIGURATION OPTIONS USING MEDIA2

Test Label: Audio Output Configuration - Get Audio Output Configuration Options

Test Case ID: MEDIA2\_AUDIOOUTPUTCONFIGURATION-2

Profile T Normative Reference: Optional

Feature Under Test: GetAudioOutputConfigurationOptions

**Test Purpose:** To verify that audio output configuration options provided by Device is received by Client using the **GetAudioOutputConfigurationOptions** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetAudioOutputConfigurationOptions** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Audio outputs feature for Media2 Service (Media2\_AudioOutput).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetAudioOutputConfigurationOptions** request message to retrieve an audio output configuration options from the Device.
- 2. Device responds with code HTTP 200 OK and **GetAudioOutputConfigurationOptionsResponse** message.

#### **Test Result:**

#### PASS -

 Client GetAudioOutputConfigurationOptions request messages are valid according to XML Schemas listed in Namespaces AND

www.onvif.org 105



- Client GetAudioOutputConfigurationOptions request in Test Procedure fulfills the following requirements:
  - [S1] **soapenv:Body** element has child element **tr2:GetAudioOutputConfigurationOptions** AND
- Device response on the **GetAudioOutputConfigurations** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetAudioOutputConfigurationOptionsResponse.

· The Client failed PASS criteria.

Validated Feature List: media2\_audio\_output\_configuration.get\_audio\_output\_configuration\_options

#### 21.5 SET AUDIO OUTPUT CONFIGURATION USING MEDIA2

**Test Label:** Audio Output Configuration - Set Audio Output Configuration

Test Case ID: MEDIA2 AUDIOOUTPUTCONFIGURATION-3

Profile T Normative Reference: Optional

Feature Under Test: SetAudioOutputConfiguration

**Test Purpose:** To verify that Client is able to change audio output configuration provided by Device using the **SetAudioOutputConfiguration** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **SetAudioOutputConfiguration** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Audio outputs feature for Media2 Service (Media2\_AudioOutput).

#### Test Procedure (expected to be reflected in network trace file):

1. Client invokes **SetAudioOutputConfiguration** request message to change an audio output configuration on the Device.



2. Device responds with code HTTP 200 OK and **SetAudioOutputConfigurationResponse** message.

#### **Test Result:**

#### PASS -

- Client SetAudioOutputConfiguration request messages are valid according to XML Schemas listed in Namespaces AND
- Client **SetAudioOutputConfiguration** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:SetAudioOutputConfiguration AND
- Device response on the **SetAudioOutputConfiguration** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:SetAudioOutputConfigurationResponse.

#### FAIL -

• The Client failed PASS criteria.

Validated Feature List: media2\_audio\_output\_configuration.set\_audio\_output\_configuration

www.onvif.org 107



# 22 Audio Decoder Configuration Using Media2 Test Cases

#### 22.1 Feature Level Normative Reference:

Validated Feature: AudioDecoderConfiguration

Check Condition based on Device Features: Audio Output (Media2 Service) is supported by Device.

**Required Number of Devices: 1** 

Profile T Requirement: Optional

### 22.2 Expected Scenarios Under Test:

- 1. Client connects to Device to modify Audio Decoder Configuration.
- 2. Client is considered as supporting Audio Decoder Configuration if the following conditions are met:
  - Client is able to retrieve audio decoder configurations using GetAudioDecoderConfigurations operation (Media2 Service) AND
  - Client is able to retrieve audio decoder configuration options using GetAudioDecoderConfigurationOptions operation (Media2 Service) AND
  - Client is able to modify audio decoder configuration using SetAudioDecoderConfiguration operation (Media2 Service) AND
- 3. Client is considered as NOT supporting Audio Decoder Configuration if ANY of the following is TRUE:
  - No valid response to **GetAudioDecoderConfigurations** request (Media2 Service) OR
  - No valid response to GetAudioDecoderConfigurationOptions request (Media2 Service) OR
  - No valid response to SetAudioDecoderConfiguration request (Media2 Service) OR



## 22.3 GET AUDIO DECODER CONFIGURATIONS USING MEDIA2

Test Label: Audio Decoder Configuration - Get Audio Decoder Configurations

Test Case ID: MEDIA2\_AUDIODECODERCONFIGURATION-1

Profile T Normative Reference: Optional

Feature Under Test: GetAudioDecoderConfigurations

**Test Purpose:** To verify that audio decoder configuration provided by Device is received by Client using the **GetAudioDecoderConfigurations** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetAudioDecoderConfigurations** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Audio outputs feature for Media2 Service (Media2\_AudioOutput).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetAudioDecoderConfigurations request message to retrieve an audio decoder configuration or a list of audio decoder configurations from the Device.
- 2. Device responds with code HTTP 200 OK and **GetAudioDecoderConfigurationsResponse** message.

#### **Test Result:**

- Client GetAudioDecoderConfigurations request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetAudioDecoderConfigurations** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetAudioDecoderConfigurations
     AND
- Device response on the **GetAudioDecoderConfigurations** request fulfills the following requirements:



- [S2] It has HTTP 200 response code AND
- [S3] soapenv:Body element has child element tr2:GetAudioDecoderConfigurationsResponse.

· The Client failed PASS criteria.

Validated Feature List: media2 audio decoder configuration get audio decoder configurations

# 22.4 GET AUDIO DECODER CONFIGURATION OPTIONS USING MEDIA2

Test Label: Audio Decoder Configuration - Get Audio Decoder Configuration Options

Test Case ID: MEDIA2\_AUDIODECODERCONFIGURATION-2

Profile T Normative Reference: Optional

Feature Under Test: GetAudioDecoderConfigurationOptions

**Test Purpose:** To verify that audio decoder configuration options provided by Device is received by Client using the **GetAudioDecoderConfigurationOptions** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with GetAudioDecoderConfigurationOptions operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Audio outputs feature for Media2 Service (Media2\_AudioOutput).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetAudioDecoderConfigurationOptions request message to retrieve an audio decoder configuration options from the Device.
- 2. Device responds with code HTTP 200 OK and **GetAudioDecoderConfigurationOptionsResponse** message.

#### **Test Result:**



- Client GetAudioDecoderConfigurationOptions request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetAudioDecoderConfigurationOptions** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetAudioDecoderConfigurationOptions AND
- Device response on the **GetAudioDecoderConfigurationOptions** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetAudioDecoderConfigurationOptionsResponse.

The Client failed PASS criteria.

**Validated Feature List:** media2\_audio\_decoder\_configuration.get\_audio\_decoder\_configuration\_options

## 22.5 SET AUDIO DECODER CONFIGURATION USING MEDIA2

Test Label: Audio Decoder Configuration - Set Audio Decoder Configuration

Test Case ID: MEDIA2\_AUDIODECODERCONFIGURATION-3

**Profile T Normative Reference:** Optional

Feature Under Test: SetAudioDecoderConfiguration

**Test Purpose:** To verify that Client is able to change audio decoder configuration provided by Device using the **SetAudioDecoderConfiguration** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **SetAudioDecoderConfiguration** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Audio outputs feature for Media2 Service (Media2\_AudioOutput).



#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **SetAudioDecoderConfiguration** request message to change an audio decoder configuration on the Device.
- 2. Device responds with code HTTP 200 OK and **SetAudioDecoderConfigurationResponse** message.

#### **Test Result:**

#### PASS -

- Client SetAudioDecoderConfiguration request messages are valid according to XML Schemas listed in Namespaces AND
- Client **SetAudioDecoderConfiguration** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:SetAudioDecoderConfiguration AND
- Device response on the **SetAudioDecoderConfiguration** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:SetAudioDecoderConfigurationResponse.

#### FAIL -

· The Client failed PASS criteria.

**Validated Feature List:** media2\_audio\_decoder\_configuration.set\_audio\_decoder\_configuration



# 23 List Video Source Configurations Using Media2 Test Cases

#### 23.1 Feature Level Normative Reference:

Validated Feature: GetVideoSourceConfigurations

Check Condition based on Device Features: Video (Media2 Service) is supported by Device.

**Required Number of Devices: 1** 

**Profile T Requirement:** Conditional

### 23.2 Expected Scenarios Under Test:

- 1. Client connects to Device to retrieve all Video Source Configurations available on device.
- 2. Client is considered as supporting List Video Source Configurations if the following conditions are met:
  - Client is able to retrieve full list of video source configurations using GetVideoSourceConfigurations operation with skipped ConfigurationToken and ProfileToken in request (Media2 Service).
- 3. Client is considered as NOT supporting List Video Source Configurations if ANY of the following is TRUE:
  - No valid response to GetVideoSourceConfigurations request that does not contain ConfigurationToken and ProfileToken elements (Media2 Service) OR

# 23.3 LIST VIDEO SOURCE CONFIGURATIONS USING MEDIA2

Test Label: Video Source Configuration - Get Video Source Configurations

Test Case ID: MEDIA2\_LISTVIDEOSOURCECONFIGURATIONS-1

**Profile T Normative Reference:** Conditional

Feature Under Test: Get Video Source Configurations

**Test Purpose:** To verify that video source configurations provided by Device is received by Client

using the  ${\bf GetVideoSourceConfigurations}$  operation.



#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with GetVideoSourceConfigurations operation with skipped ConfigurationToken element and with skipped ProfileToken element present.
- Device supports Media2 Service (Media2Service).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetVideoSourceConfigurations** request message with skipped ConfigurationToken element and with skipped ProfileToken element to retrieve a list of video source configurations from the Device.
- 2. Device responds with code HTTP 200 OK and **GetVideoSourceConfigurationsResponse** message.

#### **Test Result:**

#### PASS -

- Client GetVideoSourceConfigurations request messages are valid according to XML Schemas listed in Namespaces AND
- Client GetVideoSourceConfigurations request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetVideoSourceConfigurations AND
  - [S2] tr2:GetVideoSourceConfigurations element does not have child element tr2:ConfigurationToken AND
  - [S3] tr2:GetVideoSourceConfigurations element does not have child element tr2:ProfileToken AND
- Device response on the **GetVideoSourceConfigurations** request fulfills the following requirements:
  - [S4] It has HTTP 200 response code AND
  - [S5] soapenv:Body element has child element tr2:GetVideoSourceConfigurationsResponse.

#### FAIL -

· The Client failed PASS criteria.

114	www.onvif.org



Validated Feature List:

media2\_list\_video\_source\_configurations.list\_video\_source\_configurations

www.onvif.org 115



## 24 OSD Configuration Using Media2 Test Cases

### 24.1 Feature Level Normative Reference:

Validated Feature: OSD Configuration

Check Condition based on Device Features: OSD (Media2 Service) is supported by Device.

**Required Number of Devices: 1** 

**Profile T Requirement:** Conditional

### 24.2 Expected Scenarios Under Test:

- 1. Client connects to Device to list OSDs, create OSD, and modify OSD on the device.
- 2. Client is considered as supporting OSD Configuration if the following conditions are met:
  - Client supports List video source configurations feature AND
  - Client is able to retrieve OSD configurations using GetOSDs operation (Media2 Service)
     AND
  - Client is able to create OSD text configurations using CreateOSD operation with Type = Text (Media2 Service) AND
  - If supported, Client is able to create OSD image configurations using CreateOSD operation with Type = Image (Media2 Service) AND
  - Client is able to retrieve OSD options using **GetOSDOptions** operation (Media2 Service).
  - Client is able to modify OSD using SetOSD operation (Media2 Service).
- 3. Client is considered as NOT supporting OSD Configuration if ANY of the following is TRUE:
  - · Client does not support List video source configurations feature OR
  - No valid response to **GetOSDs** request (Media2 Service) OR
  - No valid response to CreateOSD operation with Type = Text (Media2 Service) OR
  - No valid response to CreateOSD operation with Type = Image if detected (Media2 Service) OR
  - No valid response to **GetOSDOptions** operation (Media2 Service) OR



• No valid response to **SetOSD** operation (Media2 Service).

#### 24.3 GET OSD CONFIGURATIONS USING MEDIA2

Test Label: OSD Configuration - Get OSDs

Test Case ID: MEDIA2 OSDCONFIGURATION-1

**Profile T Normative Reference:** Conditional

Feature Under Test: GetOSDs

**Test Purpose:** To verify that existing OSD configurations is received by Client using the **GetOSDs** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with GetOSDs operation with skipped OSDToken element for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Media2 OSD feature (Media2\_OSD).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetOSDs** request message to retrieve OSD configurations from the Device.
- 2. Device responds with code HTTP 200 OK and GetOSDsResponse message.

#### **Test Result:**

- Client GetOSDs request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetOSDs** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetOSDs AND
  - [S2] tr2:GetOSDs element does not contain child element tr2:OSDToken AND
- Device response on the **GetOSDs** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND



• [S4] soapenv:Body element has child element tr2:GetOSDsResponse.

#### FAIL -

· The Client failed PASS criteria.

Validated Feature List: media2\_osd\_configuration.get\_osds

#### 24.4 CREATE TEXT OSD USING MEDIA2

Test Label: OSD Configuration - Create OSD

Test Case ID: MEDIA2\_OSDCONFIGURATION-2

Profile T Normative Reference: Conditional

Feature Under Test: CreateOSD

**Test Purpose:** To verify that Client is able to create text OSD using the **CreateOSD** operation with

Type value is equal to Text

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with CreateOSD operation for Media2 Service with Type value is equal to Text present.
- Device supports Media2 Service (Media2Service).
- Device supports Media2 OSD feature (Media2\_OSD).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **CreateOSD** with Type = **Text** request message to create text OSD on the Device.
- 2. Device responds with code HTTP 200 OK and CreateOSDResponse message.

#### **Test Result:**

- Client CreateOSD request messages are valid according to XML Schemas listed in Namespaces AND
- Client **CreateOSD** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:CreateOSD AND



- [S2] tr2:CreateOSD/tr2:OSD/tt:Type element value is equal to Text AND
- Device response on the **CreateOSD** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element tr2:CreateOSDResponse.

· The Client failed PASS criteria.

Validated Feature List: media2\_osd\_configuration.create\_text\_osd

#### 24.5 CREATE IMAGE OSD USING MEDIA2

Test Label: OSD Configuration - Create OSD

Test Case ID: MEDIA2 OSDCONFIGURATION-3

Profile T Normative Reference: Conditional

Feature Under Test: CreateOSD

**Test Purpose**: To verify that Client is able to create image OSD using the **CreateOSD** operation

with Type value is equal to Image

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with CreateOSD operation for Media2 Service with Type value is equal to Image present.
- Device supports Media2 Service (Media2 Service).
- Device supports Media2 OSD feature (Media2\_OSD).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **CreateOSD** with Type = **Image** request message to create image OSD on the Device.
- 2. Device responds with code HTTP 200 OK and **CreateOSDResponse** message.

#### **Test Result:**



- Client CreateOSD request messages are valid according to XML Schemas listed in Namespaces AND
- Client CreateOSD request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:CreateOSD AND
  - [S2] tr2:CreateOSD/tr2:OSD/tt:Type element value is equal to Image AND
- Device response on the **CreateOSD** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element tr2:CreateOSDResponse.

· The Client failed PASS criteria.

Validated Feature List: media2 osd configuration.create image osd

#### 24.6 GET OSD OPTIONS USING MEDIA2

Test Label: OSD Configuration - Get OSD Options

Test Case ID: MEDIA2\_OSDCONFIGURATION-4

Profile T Normative Reference: Conditional

Feature Under Test: GetOSDOptions

**Test Purpose:** To verify that OSD options provided by Device is received by Client using the **GetOSDOptions** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetOSDOptions** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Media2 OSD feature (Media2\_OSD).

#### Test Procedure (expected to be reflected in network trace file):

 Client invokes GetOSDOptions request message to retrieve an OSD options from the Device.



2. Device responds with code HTTP 200 OK and GetOSDOptionsResponse message.

#### **Test Result:**

#### PASS -

- Client GetOSDOptions request messages are valid according to XML Schemas listed in Namespaces AND
- Client GetOSDOptions request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetOSDOptions AND
- Device response on the **GetOSDOptions** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetOSDOptionsResponse.

#### FAIL -

· The Client failed PASS criteria.

Validated Feature List: media2 osd configuration.get osd options

### 24.7 SET OSD USING MEDIA2

Test Label: OSD Configuration - Set OSD Configuration

Test Case ID: MEDIA2\_OSDCONFIGURATION-5

Profile T Normative Reference: Conditional

Feature Under Test: SetOSD

**Test Purpose:** To verify that Client is able to change OSD configuration provided by Device using the **SetOSD** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with SetOSD operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Media2 OSD feature (Media2\_OSD).

Test Procedure (expected to be reflected in network trace file):

www.onvif.org	121



- 1. Client invokes SetOSD request message to change an OSD configuration on the Device.
- 2. Device responds with code HTTP 200 OK and **SetOSDResponse** message.

#### **Test Result:**

#### PASS -

- Client SetOSD request messages are valid according to XML Schemas listed in Namespaces AND
- Client **SetOSD** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:SetOSD AND
- Device response on the **SetOSD** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:SetOSDResponse.

#### FAIL -

· The Client failed PASS criteria.

Validated Feature List: media2\_osd\_configuration.set\_osd



## 25 Get Snapshot Uri Using Media2 Test Cases

#### 25.1 Feature Level Normative Reference:

Validated Feature: GetSnapshotUri

Check Condition based on Device Features: Snapshot Uri (Media2 Service) is supported by

Device.

**Required Number of Devices: 1** 

Profile T Requirement: Optional

### 25.2 Expected Scenarios Under Test:

- 1. Client connects to Device to obtain a JPEG snapshot uri from the device using **GetSnapshotUri** operation.
- 2. Client gets JPEG images from the device using **HTTP GET** sent to the Uri provided by the Device in GetSnapshotUriResponse.
- 3. Client is considered as supporting Snapshot Uri if the following conditions are met:
  - Client is able to retrieve JPEG snapshot URI using GetSnapshotUri operation (Media2 Service) AND
  - Client is able to retrieve JPEG images using HTTP GET.
- 4. Client is considered as NOT supporting JPEG snapshot URI if ANY of the following is TRUE:
  - No valid response to **GetSnapshotUri** request (Media2 Service).
  - No valid response for HTTP GET request the Uri provided by the Device in GetSnapshotUriResponse.

#### 25.3 GET SNAPSHOT URI USING MEDIA2

Test Label: SnapshotUri - Get Snapshot Uri

Test Case ID: MEDIA2\_GETSNAPSHOTURI-1

Profile T Normative Reference: Optional

Feature Under Test: Get Snapshot Uri



**Test Purpose:** To verify that snapshot URI provided by Device is received by Client using the **GetSnapshotUri** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetSnapshotUri** operation present.
- Device supports SnapshotUri feature for Media2 Service (Media2 SnapshotUri).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetSnapshotUri** request message to retrieve snapshot Uri from the Device.
- 2. Device responds with code HTTP 200 OK and GetSnapshotUriResponse message.
- 3. Client invokes HTTP GET request to snapshot Uri.
- 4. Client responds with code HTTP 200 OK.

#### **Test Result:**

#### PASS -

- Client GetSnapshotUri request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetSnapshotUri** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetSnapshotUri AND
- Device response on the **GetSnapshotUri** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetSnapshotUriResponse AND
- There is **HTTP GET** request in Test Procedure that fulfills the following requirements:
  - [S4] It invoked to address which equal to **tr2:GetSnapshotUriResponse/tr2:Uri** value from the Device response to GetSnapshotUri request AND
  - [S5] It invoked after the Client GetSnapshotUri request AND
- Device response on the **HTTP GET** request fulfills the following requirements:
  - [S6] It has **HTTP 200** response code.

#### FAIL -



• The Client failed PASS criteria.

Validated Feature List: media2\_snapshot\_uri.get\_snapshot\_uri

www.onvif.org 125



## 26 Metadata Configuration Using Media2 Test Cases

#### 26.1 Feature Level Normative Reference:

Validated Feature: MetadataConfiguration

Check Condition based on Device Features: Media2 Service is supported by Device.

**Required Number of Devices: 1** 

Profile T Requirement: Conditional

### 26.2 Expected Scenarios Under Test:

- 1. Client connects to Device to modify Metadata Configuration.
- 2. Client is considered as supporting Metadata Configuration if the following conditions are met:
  - Client is able to retrieve metadata configurations using GetMetadataConfigurations operation (Media2 Service) AND
  - Client is able to retrieve metadata configuration options using GetMetadataConfigurationOptions operation (Media2 Service) AND
  - Client is able to modify metadata configuration using SetMetadataConfiguration operation (Media2 Service) AND
- 3. Client is considered as NOT supporting Metadata Configuration if ANY of the following is TRUE:
  - No valid response to **GetMetadataConfigurations** request (Media2 Service) OR
  - No valid response to GetMetadataConfigurationOptions request (Media2 Service) OR
  - No valid response to SetMetadataConfiguration request (Media2 Service) OR

#### 26.3 GET METADATA CONFIGURATIONS USING MEDIA2

Test Label: Metadata Configuration - Get Metadata Configurations

Test Case ID: MEDIA2\_METADATACONFIGURATION-1

Profile T Normative Reference: Conditional

Feature Under Test: GetMetadataConfigurations



**Test Purpose:** To verify that metadata configuration provided by Device is received by Client using the **GetMetadataConfigurations** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetMetadataConfigurations** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetMetadataConfigurations** request message to retrieve an metadata configuration or a list of metadata configurations from the Device.
- 2. Device responds with code HTTP 200 OK and **GetMetadataConfigurationsResponse** message.

#### **Test Result:**

#### PASS -

- Client GetMetadataConfigurations request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetMetadataConfigurations** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetMetadataConfigurations AND
- Device response on the **GetMetadataConfigurations** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetMetadataConfigurationsResponse.

#### FAIL -

· The Client failed PASS criteria.

Validated Feature List: media2\_metadata\_configuration.get\_metadata\_configurations

## 26.4 GET METADATA CONFIGURATION OPTIONS USING MEDIA2

Test Label: Metadata Configuration - Get Metadata Configuration Options

www.onvif.org	127
www.onvii.org	121



Test Case ID: MEDIA2\_METADATACONFIGURATION-2

Profile T Normative Reference: Conditional

Feature Under Test: GetMetadataConfigurationOptions

**Test Purpose:** To verify that metadata configuration options provided by Device is received by Client using the **GetMetadataConfigurationOptions** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetMetadataConfigurationOptions** operation for Media2 Service present.
- Device supports Media2 Service (Media2 Service).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetMetadataConfigurationOptions request message to retrieve an metadata configuration options from the Device.
- 2. Device responds with code HTTP 200 OK and **GetMetadataConfigurationOptionsResponse** message.

#### **Test Result:**

#### PASS -

- Client GetMetadataConfigurationOptions request messages are valid according to XML Schemas listed in Namespaces AND
- Client GetMetadataConfigurationOptions request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetMetadataConfigurationOptions
     AND
- Device response on the **GetMetadataConfigurationOptions** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetMetadataConfigurationOptionsResponse.

#### FAIL -

· The Client failed PASS criteria.

128	www.onvif.org



Validated Feature List: media2\_metadata\_configuration.get\_metadata\_configuration\_options

#### 26.5 SET METADATA CONFIGURATION USING MEDIA2

**Test Label:** Metadata Configuration - Set Metadata Configuration

Test Case ID: MEDIA2\_METADATACONFIGURATION-3

**Profile T Normative Reference:** Conditional

Feature Under Test: SetMetadataConfiguration

**Test Purpose:** To verify that Client is able to change metadata configuration provided by Device using the **SetMetadataConfiguration** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **SetMetadataConfiguration** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **SetMetadataConfiguration** request message to change an metadata configuration on the Device.
- 2. Device responds with code HTTP 200 OK and **SetMetadataConfigurationResponse** message.

#### **Test Result:**

- Client SetMetadataConfiguration request messages are valid according to XML Schemas listed in Namespaces AND
- Client **SetMetadataConfiguration** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:SetMetadataConfiguration AND
- Device response on the **SetMetadataConfiguration** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND



• [S3] soapenv:Body element has child element tr2:SetMetadataConfigurationResponse.

#### FAIL -

• The Client failed PASS criteria.

Validated Feature List: media2\_metadata\_configuration.set\_metadata\_configuration



# 27 Video Source Configuration Using Media2 Test Cases

#### 27.1 Feature Level Normative Reference:

Validated Feature: VideoSourceConfiguration

Check Condition based on Device Features: Video (Media2 Service) is supported by Device.

**Required Number of Devices: 1** 

Profile T Requirement: Conditional

### 27.2 Expected Scenarios Under Test:

- 1. Client connects to Device to modify Video Source Configuration.
- 2. Client is considered as supporting Video Source Configuration if the following conditions are met:
  - Client is able to retrieve video source configurations using GetVideoSourceConfigurations operation (Media2 Service) AND
  - Client is able to retrieve video source configuration options using GetVideoSourceConfigurationOptions operation (Media2 Service) AND
  - Client is able to modify video source configuration using SetVideoSourceConfiguration operation (Media2 Service) AND
- 3. Client is considered as NOT supporting Video Source Configuration if ANY of the following is TRUE:
  - No valid response to GetVideoSourceConfigurations request (Media2 Service) OR
  - No valid response to GetVideoSourceConfigurationOptions request (Media2 Service)
     OR
  - No valid response to SetVideoSourceConfiguration request (Media2 Service) OR

# 27.3 GET VIDEO SOURCE CONFIGURATIONS USING MEDIA2

Test Label: Video Source Configuration - Get Video Source Configurations



Test Case ID: MEDIA2\_VIDEOSOURCECONFIGURATION-1

**Profile T Normative Reference:** Conditional

Feature Under Test: GetVideoSourceConfigurations

**Test Purpose:** To verify that video source configuration provided by Device is received by Client using the **GetVideoSourceConfigurations** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetVideoSourceConfigurations** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Video feature for Media2 Service (Media2\_Video).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetVideoSourceConfigurations** request message to retrieve an video source configuration or a list of video source configurations from the Device.
- 2. Device responds with code HTTP 200 OK and **GetVideoSourceConfigurationsResponse** message.

#### **Test Result:**

#### PASS -

- Client GetVideoSourceConfigurations request messages are valid according to XML Schemas listed in Namespaces AND
- Client GetVideoSourceConfigurations request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetVideoSourceConfigurations AND
- Device response on the **GetVideoSourceConfigurations** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetVideoSourceConfigurationsResponse.

#### FAIL -

132	www.onvif.org



· The Client failed PASS criteria.

Validated Feature List: media2 video source configuration.get video source configurations

## 27.4 GET VIDEO SOURCE CONFIGURATION OPTIONS USING MEDIA2

Test Label: Video Source Configuration - Get Video Source Configuration Options

Test Case ID: MEDIA2\_VIDEOSOURCECONFIGURATION-2

Profile T Normative Reference: Conditional

Feature Under Test: GetVideoSourceConfigurationOptions

**Test Purpose:** To verify that video source configuration options provided by Device is received by Client using the **GetVideoSourceConfigurationOptions** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetVideoSourceConfigurationOptions** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Video feature for Media2 Service (Media2\_Video).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetVideoSourceConfigurationOptions** request message to retrieve an video source configuration options from the Device.
- 2. Device responds with code HTTP 200 OK and **GetVideoSourceConfigurationOptionsResponse** message.

#### **Test Result:**

- Client GetVideoSourceConfigurationOptions request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetVideoSourceConfigurationOptions** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetVideoSourceConfigurationOptions AND



- Device response on the **GetVideoSourceConfigurations** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetVideoSourceConfigurationOptionsResponse.

· The Client failed PASS criteria.

Validated Feature List: media2 video source configuration.get video source configuration options

## 27.5 SET VIDEO SOURCE CONFIGURATION USING MEDIA2

**Test Label:** Video Source Configuration - Set Video Source Configuration

Test Case ID: MEDIA2 VIDEOSOURCECONFIGURATION-3

Profile T Normative Reference: Conditional

Feature Under Test: SetVideoSourceConfiguration

**Test Purpose:** To verify that Client is able to change video source configuration provided by Device using the **SetVideoSourceConfiguration** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **SetVideoSourceConfiguration** operation for Media2 Service present.
- Device supports Media2 Service (Media2Service).
- Device supports Video feature for Media2 Service (Media2\_Video).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **SetVideoSourceConfiguration** request message to change an video source configuration on the Device.
- 2. Device responds with code HTTP 200 OK and **SetVideoSourceConfigurationResponse** message.



#### **Test Result:**

#### PASS -

- Client SetVideoSourceConfiguration request messages are valid according to XML Schemas listed in Namespaces AND
- Client **SetVideoSourceConfiguration** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:SetVideoSourceConfiguration AND
- Device response on the **SetVideoSourceConfiguration** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:SetVideoSourceConfigurationResponse.

#### FAIL -

· The Client failed PASS criteria.

Validated Feature List: media2\_video\_source\_configuration.set\_video\_source\_configuration



# 28 Metadata Profile Configuration Using Media2 Test Cases

### 28.1 Feature Level Requirement:

Validated Feature: Media2MetadataProfileConfiguration

**Check Condition based on Device Features:** Media2 Service is supported by Device.

**Required Number of Devices: 1** 

Profile T Requirement: Conditional

### 28.2 Expected Scenarios Under Test:

- 1. Client connects to Device to add compatible Metadata configuration to a Media Profile.
- 2. Client is considered as supporting Metadata Profile Configuration if the following conditions are met:
  - Client is able to retrieve Metadata configurations compatible with media profile using **GetMetadataConfigurations** operation with specified ProfileToken element.
  - Client is able to add an Metadata configuration using **AddConfiguration** operation with Type element value is equal to Metadata.
- 3. Client is considered as NOT supporting Metadata Profile Configuration if ANY of the following is TRUE:
  - No valid responses for GetMetadataConfigurations request with ProfileToken element OR
  - No valid responses for AddConfiguration request with Type element value is equal to Metadata is detected.

# 28.3 GET METADATA CONFIGURATIONS COMPATIBLE WITH PROFILE USING MEDIA2

Test Label: Get Metadata Configurations

Test Case ID: MEDIA2\_METADATAPROFILECONFIGURATION-1

Profile T Normative Reference: Conditional



Feature Under Test: Media2\_GetCompatibleMetadataConfigurations

**Test Purpose:** To verify that list of metadata configurations compatible with a media profile is received by Client using the **GetMetadataConfigurations** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with GetMetadataConfigurations operation with specified ProfileToken element present.
- Device supports Media2 Service (Media2Service).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetMetadataConfigurations request message with ProfileToken element to retrieve a list of metadata configurations compatible with requested media profile from the Device.
- 2. Device responds with code HTTP 200 OK and **GetMetadataConfigurationsResponse** message.

#### **Test Result:**

#### PASS -

- Client GetMetadataConfigurations request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetMetadataConfigurations** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetMetadataConfigurations AND
  - [S2] It has tr2:ProfileToken element AND
- Device response to the **GetMetadataConfigurations** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element tr2:GetMetadataConfigurationsResponse.

#### FAIL -

· The Client failed PASS criteria.

www.onvif.org	137



Validated Feature List:

Media2MetadataProfileConfiguration.Media2 GetCompatibleMetadataConfigurations

### 28.4 ADD METADATA CONFIGURATION USING MEDIA2

Test Label: Add Metadata Configuration

Test Case ID: MEDIA2 METADATAPROFILECONFIGURATION-2

Profile T Normative Reference: Conditional

Feature Under Test: AddConfiguration

**Test Purpose:** To verify that Client is able to add an metadata configuration to a media profile using the **AddConfiguration** operation.

#### Pre-Requisite:

- The Network Trace Capture files contains at least one Conversation between Client and Device with **AddConfiguration** operation with Type value is equal to "Metadata" present.
- Device supports Media2 Service (Media2Service).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **GetMetadataConfigurations** request message with specified **ProfileToken** to retrieve compatible metadata configurations for specified media profile from the Device.
- 2. Device responds with code HTTP 200 OK and **GetMetadataConfigurationsResponse** message.
- 3. Client invokes AddConfiguration request message with Type element value is equal to Metadata and with Configuration token that was recieved in GetMetadataConfigurationsResponse message for the same media profile to add an metadata configuration to specified media profile on the Device.
- 4. Device responds with code HTTP 200 OK and AddConfigurationResponse message.

#### **Test Result:**

- Client AddConfiguration request messages are valid according to XML Schemas listed in Namespaces AND
- Client **AddConfiguration** request in Test Procedure fulfills the following requirements:

138	www.onvif.org
130	www.onvii.org



- [S1] soapenv:Body element has child element tr2:AddConfiguration AND
- [S2] It has tr2:Configuration/tr2:Type element with value is equal to "Metadata" AND
- Device response to the **AddConfiguration** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element tr2:AddConfigurationResponse.
- There is Client **GetMetadataConfigurations** request in Test Procedure that fulfills the following requirements:
  - [S5] It is invoked before the Client AddConfiguration request AND
  - [S6] It has tr2:ProfileToken element with value is equal to tr2:ProfileToken element value from the AddConfiguration request AND
  - [S7] It is the last **GetMetadataConfigurations** request which corresponds to [S5], AND [S6] AND
- Device response to the **GetMetadataConfigurations** request fulfills the following requirements:
  - [S8] It has HTTP 200 response code AND
  - [S9] **soapenv:Body** element has child element **tr2:GetMetadataConfigurationsResponse** AND
  - [S10] It contains tr2:Configurations element with @token attribute value equal to tr2:Configuration/tr2:Token value for Configuration with tr2:Configuration/tr2:Type value is equal to Metadata from the AddConfiguration request message.

· The Client failed PASS criteria.

Validated Feature List: Media2MetadataProfileConfiguration.AddMetadataConfiguration

www.onvif.org 139



# 29 Video Profile Configuration Using Media2 Test Cases

## 29.1 Feature Level Requirement:

Validated Feature: Media2VideoProfileConfiguration

Check Condition based on Device Features: Video (Media2 Service) is supported by Device.

**Required Number of Devices: 1** 

Profile T Requirement: Conditional

### 29.2 Expected Scenarios Under Test:

- 1. Client connects to Device to add video encoder configuration to a Media Profile.
- 2. Client is considered as supporting Video Profile Configuration if the following conditions are met:
  - Client is able to add an video encoder configuration using **AddConfiguration** operation with Type element value is equal to VideoEncoder.
- 3. Client is considered as NOT supporting Video Profile Configuration if ANY of the following is TRUE:
  - No valid responses for AddConfiguration request with Type element value is equal to VideoEncoder is detected.

# 29.3 ADD VIDEO ENCODER CONFIGURATION USING MEDIA2

Test Label: Add Video Encoder Configuration

Test Case ID: MEDIA2\_VIDEOPROFILECONFIGURATION-1

**Profile T Normative Reference:** Conditional

Feature Under Test: AddConfiguration

**Test Purpose:** To verify that Client is able to add an video encoder configuration to a media profile

using the AddConfiguration operation.

Pre-Requisite:



- The Network Trace Capture files contains at least one Conversation between Client and Device with AddConfiguration operation with Type value is equal to "VideoEncoder" present.
- Device supports Media2 Video feature (Media2\_Video).

#### Test Procedure (expected to be reflected in network trace file):

- Client invokes GetVideoEncoderConfigurations request message with specified ProfileToken to retrieve compatible video encoder configurations for specified media profile from the Device.
- Device responds with code HTTP 200 OK and GetVideoEncoderConfigurationsResponse message.
- 3. Client invokes AddConfiguration request message with Type element value is equal to VideoEncoder and with Configuration token that was recieved in GetVideoEncoderConfigurationsResponse message for the same media profile to add an video encoder configuration to specified media profile on the Device.
- 4. Device responds with code HTTP 200 OK and **AddConfigurationResponse** message.

#### **Test Result:**

- Client AddConfiguration request messages are valid according to XML Schemas listed in Namespaces AND
- Client AddConfiguration request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:AddConfiguration AND
  - [S2] It has tr2:Configuration/tr2:Type element with value is equal to "VideoEncoder" AND
- Device response to the **AddConfiguration** request fulfills the following requirements:
  - [S3] It has HTTP 200 response code AND
  - [S4] soapenv:Body element has child element tr2:AddConfigurationResponse.
- There is Client **GetVideoEncoderConfigurations** request in Test Procedure that fulfills the following requirements:
  - [S5] It is invoked before the Client AddConfiguration request AND
  - [S6] It has **tr2:ProfileToken** element with value is equal to **tr2:ProfileToken** element value from the **AddConfiguration** request AND

www.onvif.org	141



- [S7] It is the last GetVideoEncoderConfigurations request which corresponds to [S5],
   AND [S6] AND
- Device response to the **GetVideoEncoderConfigurations** request fulfills the following requirements:
  - [S8] It has HTTP 200 response code AND
  - [S9] **soapenv:Body** element has child element **tr2:GetVideoEncoderConfigurationsResponse** AND
  - [S10] It contains tr2:Configurations element with @token attribute value equal to tr2:Configuration/tr2:Token value for Configuration with tr2:Configuration/tr2:Type value is equal to VideoEncoder from the AddConfiguration request message.

• The Client failed PASS criteria.

**Validated Feature List:** Media2VideoProfileConfiguration.AddVideoEncoderConfiguration



## 30 Media Profile Management Test Cases

### 30.1 Feature Level Requirement:

Validated Feature: Media2MediaProfileManagement

**Check Condition based on Device Features:** Real Time Streaming (Media2 Service) and Video (Media2 Service) are supported by Device.

**Required Number of Devices: 1** 

**Profile T Requirement:** Conditional

### 30.2 Expected Scenarios Under Test:

- Client connects to Device to create media profile and query the maximum number of concurrent streams using the GetVideoSourceConfigurations and GetVideoEncoderInstances operations.
- 2. Client is considered as supporting Media Profile Management if the following conditions are met:
  - Client is able to create media profile using CreateProfile operation with Type element value is equal to EITHER VideoSource OR AudioSource (Media2AudioProfileConfiguration.CreateProfileWithAudioSourceConfiguration)
     OR AudioOutput

(Media2AudioProfileConfiguration.CreateProfileWithAudioOutputConfiguration) AND

- Client is able to retrieve minimum number of guaranteed video encoder instances for video source configuration using **GetVideoEncoderInstances** operation.
- Client supports media2\_video\_source\_configuration.get\_video\_source\_configurations feature.
- 3. Client is considered as NOT supporting Video Profile Configuration if ANY of the following is TRUE:
  - No valid responses for CreateProfile request Type element value is equal to VideoSource if detected OR
  - Client does not support the following features:
     Media2MediaProfileManagement.CreateProfileWithVideoSourceConfiguration
     AND

www.onvif.ora



 ${\bf Media 2 Audio Profile Configuration. Create Profile With Audio Source Configuration} \\ {\bf AND}$ 

Media2AudioProfileConfiguration.CreateProfileWithAudioOutputConfiguration

No valid responses for GetVideoEncoderInstances request OR

 Client does not support media2\_video\_source\_configuration.get\_video\_source\_configurations feature OR

# 30.3 CREATE MEDIA PROFILE WITH VIDEO SOURCE CONFIGURATION USING MEDIA2

Test Label: Create Media2 Profile with Video Source Configuration

Test Case ID: MEDIA2 MEDIAPROFILEMANAGEMENT-1

**Profile T Normative Reference:** Conditional

Feature Under Test: CreateProfile

**Test Purpose:** To verify that Client is able to create media profile with video source configuration using the **CreateProfile** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **CreateProfile** operation with Type = **VideoSource** present.
- Device supports Media2 Video feature (Media2 Video).

#### Test Procedure (expected to be reflected in network trace file):

- 1. Client invokes **CreateProfile** request message with **tr2:Configuration\tr2:Type** = **VideoSource** and with specified **tr2:Token** element for this Configuration to create profile with video source configuration on the Device.
- 2. Device responds with code HTTP 200 OK and CreateProfileResponse message.

#### **Test Result:**

#### PASS -

 Client CreateProfile request messages are valid according to XML Schemas listed in Namespaces AND



- Client CreateProfile request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:CreateProfile AND
  - [S2] It has tr2:Configuration/tr2:Type element with value is equal to "VideoSource" AND
  - [S3] tr2:Configuration element with tr2:Type value is equal to "VideoSource" has tr2:Token element AND
- Device response to the **CreateProfile** request fulfills the following requirements:
  - [S4] It has HTTP 200 response code AND
  - [S5] soapenv:Body element has child element tr2:CreateProfileResponse.

· The Client failed PASS criteria.

Validated Feature List:

Media2MediaProfileManagement.CreateProfileWithVideoSourceConfiguration

#### 30.4 GET VIDEO ENCODER INSTANCES USING MEDIA2

Test Label: Get Video Encoder Instances

Test Case ID: MEDIA2\_MEDIAPROFILEMANAGEMENT-2

Profile T Normative Reference: Conditional

Feature Under Test: Media2\_GetVideoEncoderInstances

**Test Purpose:** To verify that list of video encoder instances is received by Client using the **GetVideoEncoderInstances** operation.

#### **Pre-Requisite:**

- The Network Trace Capture files contains at least one Conversation between Client and Device with **GetVideoEncoderInstances** operation present.
- Device supports Media2 Video feature (Media2\_Video).

#### Test Procedure (expected to be reflected in network trace file):

1. Client invokes **GetVideoEncoderInstances** request message to retrieve a list of video encoder instances from the Device.

www.onvif.org	145



2. Device responds with code HTTP 200 OK and **GetVideoEncoderInstancesResponse** message.

#### **Test Result:**

#### PASS -

- Client GetVideoEncoderInstances request messages are valid according to XML Schemas listed in Namespaces AND
- Client **GetVideoEncoderInstances** request in Test Procedure fulfills the following requirements:
  - [S1] soapenv:Body element has child element tr2:GetVideoEncoderInstances AND
- Device response to the **GetVideoEncoderInstances** request fulfills the following requirements:
  - [S2] It has HTTP 200 response code AND
  - [S3] soapenv:Body element has child element tr2:GetVideoEncoderInstancesResponse.

#### FAIL -

• The Client failed PASS criteria.

Validated Feature List: Media2MediaProfileManagement.Media2\_GetVideoEncoderInstances



## 31 HTTPS Streaming Using Media2 Test Cases

### 31.1 Feature Level Requirement:

Validated Feature: HTTPSStreaming

Check Condition based on Device Features: No (ONVIF Profile T Simulator is used as device).

**Required Number of Devices: 1** 

**Profile T Requirement:** Conditional

### 31.2 Expected Scenarios Under Test:

- 1. Client connects to ONVIF Profile T Simulator to initiate HTTPS H264 video Streaming.
- 2. Client is considered as supporting HTTPS Streaming if the following conditions are met:
  - ONVIF Profile T Simulator detects Streaming over RTP/RTSP/HTTPS/TCP feature as supported.
- 3. Client is considered as NOT supporting HTTPS Streaming if the following is TRUE:
  - ONVIF Profile T Simulator detects Streaming over RTP/RTSP/HTTPS/TCP feature as not supported.



## **Annex A Test for Appendix A**

## A.1 Required Number of Devices Summary

Required number of devices and Device feature dependency used in this test specification are listed in the Table.

**Table A.1. Required Number of Devices Summary** 

Feature ID	Feature Name	Required Number of Devices	Check Condition based on Device Features	Check Condition based on Device Features ID
tc.Media2_Ge tProfiles	Get Profiles Using Media2	3	Media2 Service is supported by Device.	Media2Service
tc.Media2_Ge tStreamURI	Get Stream Uri Using Media2	3	Real Time Streaming (Media2 Service) is supported by Device.	Media2_RealT imeStreaming
tc.Media2_Me diaStreaming	Media Streaming Using Media2	3	Real Time Streaming (Media2 Service) is supported by Device.	Media2_RealT imeStreaming
tc.Media2_Vi deoStreaming_ H264	H264 Video Streaming Using Media2	3	Real Time Streaming (Media2 Service) and H264 (Media2 Service) are supported by Device.	Media2_RealT imeStreaming AND Media2_H264
tc.Media2_Vi deoStreaming_ H265	H265 Video Streaming Using Media2	3	Real Time Streaming (Media2 Service) and H265 (Media2 Service) are supported by Device.	Media2_RealT imeStreaming AND Media2_H265



Feature ID	Feature Name	Required Number of Devices	Check Condition based on Device Features	Check Condition based on Device Features ID
tc.Media2_Mu IticastStreaming	Multicast Streaming Using Media2	1	RTP-Multicast/ UDP (Media2 Service) is supported by Device.	Media2_RTPMu IticastUDP
tc.Media2_Vi deoEncoderCon figuration	Video Encoder Configuration Using Media2	3	Video (Media2 Service) is supported by Device.	Media2_Video
tc.Media2_Au dioEncoderCon figuration	Audio Encoder Configuration Using Media2	1	Audio (Media2 Service) is supported by Device.	Media2_Audio
tc.Media2_Au dioStreaming_ G711	G.711 Audio Streaming Using Media2	1	Real Time Streaming (Media2 Service) and Audio G711 (Media2 Service) are supported by Device.	Media2_RealT imeStreaming AND Media2_G711
tc.Media2_Au dioStreaming_ AAC	AAC Audio Streaming Using Media2	1	Real Time Streaming (Media2 Service) and Audio AAC (Media2 Service) are supported by Device.	Media2_RealT imeStreaming AND Media2_AAC
tc.Media2_Au dioProfileCon figuration	Audio Profile Configuration Using Media2	1	Audio (Media2 Service) is supported by Device.	Media2_Audio
tc.Media2_Au dioBackchanne IStreaming	Audio Backchannel Streaming Using Media2	1	Real Time Streaming (Media2 Service) and Audio Output (Media2 Service)	Media2_RealT imeStreaming AND Media2_Audio Output



Feature ID	Feature Name	Required Number of Devices	Check Condition based on Device Features	Check Condition based on Device Features ID
			are supported by Device.	
tc.Media2_Au dioOutputProf ileConfiguration	Audio Output Profile Configuration Using Media2	1	Audio Output (Media2 Service) is supported by Device.	Media2_Audio Output
tc.Media2_An alyticsProfil eConfiguration	Analytics Profile Configuration Using Media2	1	Analytics (Media2 Service) is supported by Device.	Media2_Analytics
tc.VideoSour ceMode	Video Source Mode	1	Video Source Mode (Media2 Service) is supported by Device.	Media2_Video SourceMode
tc.Media2_Au dioSourceConf iguration	Audio Source Configuration Using Media2	1	Audio (Media2 Service) is supported by Device.	Media2_Audio
tc.Media2_Au dioOutputConf iguration	Audio Output Configuration Using Media2	1	Audio Output (Media2 Service) is supported by Device.	Media2_Audio Output
tc.Media2_Au dioDecoderCon figuration	Audio Decoder Configuration Using Media2	1	Audio Output (Media2 Service) is supported by Device.	Media2_Audio Output
tc.Media2_Li stVideoSource Configurations	List Video Source Configurations Using Media2	1	Video (Media2 Service) is supported by Device.	Media2_Video
tc.Media2_OS DConfiguration	OSD Configuration Using Media2	1	OSD (Media2 Service) is supported by Device.	Media2_OSD
tc.Media2_Ge tSnapshotUri	Get Snapshot Uri Using Media2	1	Snapshot Uri (Media2 Service)	Media2_Snaps hotUri



Feature ID	Feature Name	Required Number of Devices	Check Condition based on Device Features	Check Condition based on Device Features ID
			is supported by Device.	
tc.Media2_Me tadataConfigu ration	Metadata Configuration Using Media2	1	Media2 Service is supported by Device.	Media2Service
tc.Media2_Vi deoSourceConf iguration	Video Source Configuration Using Media2	1	Video (Media2 Service) is supported by Device.	Media2_Video
tc.Media2_Me tadataProfile Configuration	Metadata Profile Configuration Using Media2	1	Media2 Service is supported by Device.	Media2Service
tc.Media2_Vi deoProfileCon figuration	Video Profile Configuration Using Media2	1	Video (Media2 Service) is supported by Device.	Media2_Video
tc.Media2_Me diaProfileMan agement	Media Profile Management	1	Real Time Streaming (Media2 Service) and Video (Media2 Service) are supported by Device.	Media2_RealT imeStreaming AND Media2_Video
tc.Media2_HT TPSStreaming	HTTPS Streaming Using Media2	1	No (ONVIF Profile T Simulator is used as device).	