



ONVIF™

ONVIF Profiles Conformance Test Specification

Version 17.01

January 2017



© 2017 by ONVIF, Inc. All rights reserved.

Recipients of this document may copy, distribute, publish, or display this document so long as this copyright notice, license and disclaimer are retained with all copies of the document. No license is granted to modify this document.

THIS DOCUMENT IS PROVIDED "AS IS," AND THE CORPORATION AND ITS MEMBERS AND THEIR AFFILIATES, MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THIS DOCUMENT ARE SUITABLE FOR ANY PURPOSE; OR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

IN NO EVENT WILL THE CORPORATION OR ITS MEMBERS OR THEIR AFFILIATES BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES, ARISING OUT OF OR RELATING TO ANY USE OR DISTRIBUTION OF THIS DOCUMENT, WHETHER OR NOT (1) THE CORPORATION, MEMBERS OR THEIR AFFILIATES HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, OR (2) SUCH DAMAGES WERE REASONABLY FORESEEABLE, AND ARISING OUT OF OR RELATING TO ANY USE OR DISTRIBUTION OF THIS DOCUMENT. THE FOREGOING DISCLAIMER AND LIMITATION ON LIABILITY DO NOT APPLY TO, INVALIDATE, OR LIMIT REPRESENTATIONS AND WARRANTIES MADE BY THE MEMBERS AND THEIR RESPECTIVE AFFILIATES TO THE CORPORATION AND OTHER MEMBERS IN CERTAIN WRITTEN POLICIES OF THE CORPORATION.



Revision History

Ver.	Date	Description
17.01	Jan, 2017	First issue



Table of Contents

1	Introduction	5
1.1	Scope	5
1.2	Normative References.....	5
1.3	Informative References	5
1.4	Requirement by the Profile.....	5
2	Terms and Definitions	6
2.1	Definitions.....	6
2.2	Abbreviations.....	6
3	Profile S Conformance	7
3.1	Feature category classification for ONVIF Profile S.....	7
3.2	Profile S support check	12
4	Profile G Conformance	16
4.1	Feature category classification for ONVIF Profile G	16
4.2	Profile G support check.....	23
5	Profile C Conformance.....	31
5.1	Feature category classification for ONVIF Profile C	31
5.2	Profile C support check	35
6	Profile Q Conformance	42
6.1	Feature category classification for ONVIF Profile Q	42
6.2	Profile Q support check.....	46
6.3	Profile Q testing preparation.....	53
7	Profile A Conformance	57
7.1	Feature category classification for ONVIF Profile A.....	57
7.2	Profile A support check.....	62



1 Introduction

The goal of the ONVIF Profiles Conformance Test Specification document is to provide some details about logic of profiles' supporting check.

Profile S Conformance item focuses on ONVIF Profile S specification ([ONVIF Profile S]) as a referenced Profile by an ONVIF device implementation under test.

Profile G Conformance item focuses on ONVIF Profile G specification ([ONVIF Profile G]) as a referenced Profile by an ONVIF device implementation under test.

Profile C Conformance item focuses on ONVIF Profile C specification ([ONVIF Profile C]) as a referenced Profile by an ONVIF device implementation under test.

Profile Q Conformance item focuses on ONVIF Profile Q specification ([ONVIF Profile Q]) as a referenced Profile by an ONVIF device implementation under test.

Profile A Conformance item focuses on ONVIF Profile A specification ([ONVIF Profile A]) as a referenced Profile by an ONVIF device implementation under test.

1.1 Scope

This ONVIF Profiles Conformance Test Specification document defines and regulates the conformance testing procedure for the ONVIF conformant devices. The objective of this specification is to provide the logic of ONVIF Profiles detection according to ONVIF Profile S Specification, ONVIF Profile G Specification, ONVIF Profile C Specification, ONVIF Profile Q Specification, and ONVIF Profile A Specification.

1.2 Normative References

[ONVIF Network Interface Specs] ONVIF Network Interface Specification documents
<http://www.onvif.org/Documents/Specifications.aspx>

[ONVIF Conformance] ONVIF Conformance Process Specification
<http://www.onvif.org/Documents/Specifications.aspx>

1.3 Informative References

[ONVIF Feature Discovery] ONVIF Feature Discovery Specification version 17.01, Jan 2017
<http://www.onvif.org/Documents/Specifications.aspx>

1.4 Requirement by the Profile

The following define denotations to indicate the required level by the Profile towards ONVIF device implementation (DUT).

M = mandatory function that shall be SUPPORTED by DUT

C = conditional mandatory function that shall be SUPPORTED by DUT if they support that functionality. On the list of test cases such functionalities are described after C – the content of parenthesis.



2 Terms and Definitions

2.1 Definitions

Profile See ONVIF Profile Policy.

2.2 Abbreviations

This section describes abbreviations used in this document.

DHCP	Dynamic Host Configuration Protocol
DNS	Domain Name System
DUT	Device Under Test
HTTP	Hyper Text Transport Protocol
IP	Internet Protocol
IPv4	Internet Protocol version 4
IPv6	Internet Protocol version 6
NTP	Network Time Protocol
RTP	Real-time Transport Protocol
RTSP	Real Time Streaming Protocol
UDP	User Datagram Protocol
URI	Uniform Resource Identifier
UTC	Coordinated Universal Time



3 Profile S Conformance

3.1 Feature category classification for ONVIF Profile S

In order for ONVIF Device Test Tool to conduct conformance testing toward [ONVIF Profile S], it would need to identify whether DUT implements the expected feature set.

This section classifies supported features as multiple categories that are related to [ONVIF Profile S] conformance. Those category classifications will be used to do some preliminary checking prior to the test case execution and also they will be used to determine whether DUT can be considered to be [ONVIF Profile S] conformant device.

The following discovery scope is defined as the scope that signals that DUT is [ONVIF Profile S] product.

Table 1: Profile S Discovery Scope

<code>onvif://www.onvif.org/Profile/Streaming</code>
--

The following table shows the classified feature categories based on commands and/or functional blocks that are referenced by DUT.

Table 2: Profile S Features Categories

Media Streaming	GetStreamUri
	SetSynchronizationPoint
	Media Streaming RTSP
	Media Streaming RTSP (JPEG RTP Header Extension)
Video Encoder Configuration	GetVideoEncoderConfiguration
	GetVideoEncoderConfigurations
	AddVideoEncoderConfiguration
	RemoveVideoEncoderConfiguration
	SetVideoEncoderConfiguration
	GetCompatibleVideoEncoderConfigurations
	GetVideoEncoderConfigurationOptions



	GetGuaranteedNumberOfVideoEncoderInstances
User Authentication	WS-UsernameToken Authentication
	HTTP Digest Authentication
Capabilities	GetCapabilities
	GetWsdUrl
PTZ	AddPTZConfiguration
	RemovePTZConfiguration
	GetNodes
	GetNode
	GetConfigurations
	GetConfiguration
	GetConfigurationOptions
	SetConfiguration
	ContinuousMove
	Stop
	GetStatus
PTZ – Absolute Positioning	AbsoluteMove
PTZ – Relative Positioning	RelativeMove
PTZ – Presets	SetPreset
	GetPresets
	GotoPreset
	RemovePreset
PTZ – Home Position	GotoHomePosition



	SetHomePosition
PTZ – Auxiliary Command	SendAuxiliaryCommand
Audio Streaming	GetAudioSources
	GetAudioSourceConfiguration
	GetAudioSourceConfigurations
	AddAudioSourceConfiguration
	RemoveAudioSourceConfiguration
	SetAudioSourceConfiguration
	GetCompatibleAudioSourceConfigurations
	GetAudioSourceConfigurationOptions
	GetAudioEncoderConfiguration
	GetAudioEncoderConfigurations
	AddAudioEncoderConfiguration
	RemoveAudioEncoderConfiguration
	SetAudioEncoderConfiguration
	GetCompatibleAudioEncoderConfigurations
GetAudioEncoderConfigurationOptions	
Media Streaming - Multicast	StartMulticastStreaming
	StopMulticastStreaming
Relay Outputs	GetRelayOutputs
	SetRelayOutputSettings
	SetRelayOutputState
NTP	GetNTP
	SetNTP



Dynamic DNS	GetDynamicDNS
	SetDynamicDNS
Zero Configuration	GetZeroConfiguration
	SetZeroConfiguration
IP Address Filtering	GetIPAddressFilter
	SetIPAddressFilter
	AddIPAddressFilter
	RemoveIPAddressFilter
Discovery	WS-Discovery
	GetDiscoveryMode
	SetDiscoveryMode
	GetScopes
	SetScopes
	AddScopes
	RemoveScopes
Network Configuration	GetHostname
	SetHostname
	GetDNS
	SetDNS
	GetNetworkInterfaces
	SetNetworkInterfaces
	GetNetworkProtocols
	SetNetworkProtocols
	GetNetworkDefaultGateway



	SetNetworkDefaultGateway
System	GetDeviceInformation
	GetSystemDateAndTime
	SetSystemDateAndTime
	SetSystemFactoryDefault
	Reboot
User Handling	GetUsers
	CreateUsers
	DeleteUsers
	SetUser
Event Handling	Notify
	Subscribe
	Renew
	Unsubscribe
	SetSynchronizationPoint (Event Service)
	CreatePullPointSubscription
	PullMessage
	GetEventProperties
	TopicFilter
	MessageContentFilter
Media Profile Configuration	GetProfiles
	GetProfile
	CreateProfile
	DeleteProfile



Video Source Configuration	GetVideoSources
	GetVideoSourceConfiguration
	GetVideoSourceConfigurations
	AddVideoSourceConfiguration
	RemoveVideoSourceConfiguration
	SetVideoSourceConfiguration
	GetCompatibleVideoSourceConfigurations
	GetVideoSourceConfigurationOptions
Metadata Configuration	GetMetadataConfiguration
	GetMetadataConfigurations
	AddMetadataConfiguration
	RemoveMetadataConfiguration
	SetMetadataConfiguration
	GetCompatibleMetadataConfigurations
	GetMetadataConfigurationOptions

3.2 Profile S support check

Preliminary checking for feature discovery will be performed prior to the test execution. For the details of the preliminary feature discovery, refer to [ONVIF Feature Discovery].

According to the result of test case execution, final determination of [ONVIF Profile S] support toward DUT is performed based on the following procedure.

Procedure:

1. Check that scope list contains the scope given in Table 1 **Error! Reference source not found.** If there is no such scope in the scope list of the DUT, then it is determined that [ONVIF Profile S] is not supported.
2. Check Capabilities feature.
 - a. Check that GetCapabilities command is supported by the DUT. If GetCapabilities is not supported by the DUT, then it is determined that [ONVIF Profile S] is not



supported by DUT. Otherwise, it is determined that Capabilities category is supported.

3. Check Discovery feature. If Discovery feature is regarded as unsupported, then it is determined that [ONVIF Profile S] is not supported by DUT. This is mandatory feature for any of ONVIF device implementation.
4. Check Discovery Types support. If Discovery/Types/dn:NetworkVideoTransmitter feature is not supported by the DUT, then it is determined that [ONVIF Profile S] is not supported by DUT and certification will be failed.
5. Check Network Configuration feature of ONVIF profile support. If Network Configuration feature is regarded as unsupported, then it is determined that [ONVIF Profile S] is not supported by DUT. This is a mandatory feature for any of ONVIF device implementation.
6. Check System feature of ONVIF profile support. If System feature is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. This feature is mandatory for any of ONVIF device implementation.
7. Check User Handling feature of ONVIF profile support. If User Handling feature is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. This is a mandatory feature for any of ONVIF device implementation.
8. Check Event Handling feature of ONVIF profile support. If Event Handling feature is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. This is a mandatory feature for any of ONVIF device implementation.
 - a. Check that WS-BasicNotification is supported by the DUT. If WS-BasicNotification is not supported by the DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that WS-BasicNotification is supported.
9. Check NTP feature.
 - a. Check that NTP is supported by the DUT. If NTP is regarded as supported, then it is determined that NTP feature category is supported by DUT.
10. Check Dynamic DNS feature.
 - a. Check that Dynamic DNS is supported by the DUT. If Dynamic DNS is regarded as supported, then Dynamic DNS feature category is supported by DUT.
11. Check Zero Configuration feature.
 - a. Check that Zero Configuration is supported by the DUT. If Zero Configuration is regarded as supported by DUT, then it is determined that Zero Configuration feature category is supported by DUT.
12. Check IP Address Filtering feature.
 - a. Check that IP Address Filter is supported by the DUT. If IP Address Filter is regarded as supported, then it is determined that IP Address Filtering feature category is supported by DUT.
13. Check User Authentication feature.
 - a. Check that WS-UsernameToken Authentication is supported by the DUT. If WS-UsernameToken is regarded as unsupported by DUT, then it is determined that



[ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that WS-UsernameToken Authentication feature is supported by DUT.

- b. Check that HTTP Digest Authentication is supported by the DUT.

14. Check Media Profile Configuration feature.

- a. Check that Media Service is supported by DUT. If Media Service is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that Media Profile Configuration feature category is supported by DUT.

15. Check Media Streaming feature of ONVIF profile support.

- a. Check that Real-time Streaming is supported by DUT. If Real-time Streaming is regarded unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that Media Streaming feature category is supported by DUT.

16. Check Video Source Configuration feature of ONVIF profile support.

- a. Check that Media Service is supported by DUT. If Media Service is regarded unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that Video Source Configuration feature category is supported by DUT.

17. Check Video Encoder Configuration feature.

- a. Check that Media Service is supported by the DUT. If Media Service is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that Video Encoder Configuration feature category is supported by DUT.

18. Check Metadata Configuration feature.

- a. Check that Media Service is supported by the DUT. If Media Service is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that Metadata Configuration feature category is supported by DUT.

19. Check Media Streaming - Multicast feature.

- a. Check that RTP-Multicast/UDP is supported by the DUT. If RTP-Multicast/UDP is regarded as supported, then it is determined that Media Streaming - Multicast feature category is supported by DUT.

20. Check PTZ feature.

- a. Check that PTZ Service and Preset position are supported by DUT. If PTZ Service and Preset position are regarded as supported then, it is determined that PTZ - Presets feature category is supported by DUT.

21. Check PTZ – Home Position feature.

- a. Check that PTZ Service and Home Position are supported by DUT. If PTZ Service and Home Position are regarded as supported, then it is determined that PTZ - Home Position feature category is supported by DUT.

22. Check PTZ – Absolute Positioning feature.



- a. Check that PTZ Service and Absolute Move are supported by DUT. If PTZ Service and Absolute Move are regarded as supported, then it is determined that PTZ - Absolute Positioning feature category is supported by DUT.

23. Check PTZ – Relative Positioning feature.

- a. Check that PTZ Service and Relative Move are supported by the DUT. If PTZ Service and Relative Move are regarded as supported, then it is determined that PTZ - Relative Positioning feature category is supported by DUT.

24. Check PTZ – Auxiliary Commands feature.

- a. Check that PTZ Service and Auxiliary Commands are supported by DUT. If PTZ Service and Auxiliary Commands are regarded as supported, then it is determined that PTZ - Auxiliary Commands feature category is supported by DUT.

25. Check Audio Streaming feature.

- a. Check that Audio feature is supported by DUT. If Audio feature is regarded as supported, then it is determined that Audio Streaming feature category is supported by DUT.

26. Check Relay Outputs feature.

- a. Check that Relay Outputs from Device Service are supported by the DUT. If Relay Outputs are regarded as supported, then it is determined that Relay Outputs feature category is supported by DUT.



4 Profile G Conformance

4.1 Feature category classification for ONVIF Profile G

In order for ONVIF Device Test Tool to conduct conformance testing toward [ONVIF Profile G], it would need to identify whether DUT implements the expected feature set.

This section classifies supported features as multiple categories that are related to [ONVIF Profile G] conformance. Those category classifications will be used to do some preliminary checking prior to the test case execution and also they will be used to determine whether DUT can be considered to be [ONVIF Profile G] conformant device.

The following discovery scope is defined as the scope that signals that DUT is [ONVIF Profile G] product.

Table 3: Profile G Discovery Scope

onvif://www.onvif.org/Profile/G

The following table shows the classified feature categories based on commands and/or functional blocks that are referenced by DUT.

Table 4: Profile G Features Categories

Profile Mandatory Features	
Security	HTTP Digest
Capabilities	GetServices (Device)
	GetServiceCapabilities (Device)
	GetServiceCapabilities (Recording Control)
	GetServiceCapabilities (Replay)
	GetServiceCapabilities (Recording Search)
	GetServiceCapabilities (Receiver)
	GetServiceCapabilities (Event)
	MaxPullPoint capability is supported and value is not less than 2
	GetServiceCapabilities (Media)



	GetWsdUrl (Device)
Recording Search – Media Search	FindRecordings (Recording Search)
	GetRecordingSearchResults (Recording Search)
	EndSearch (Recording Search)
	FindEvents (Recording Search)
	GetEventSearchResults (Recording Search)
	GetRecordingSummary (Recording Search)
	GetRecordingInformation (Recording Search)
	GetMediaAttributes (Recording Search)
	tns1:RecordingHistory/Track/State
	tns1:RecordingHistory/Recording/State
	XPath dialect filtering
Replay Control	RTP header extension
	“onvif-replay” RTSP feature tag
	Media Replay
	Reverse Replay
	GetReplayUri (Replay)
	SetReplayConfiguration (Replay)
	GetReplayConfiguration (Replay)
Profile Conditional Features	
Recording Search – Metadata Search	FindMetadata (Recording Search)
	GetMetadataSearchResults (Recording Search)
Recording Control – Dynamic	Create Recording (Recording Control)



Recording	Delete Recording (Recording Control)
	tns1:RecordingConfig/CreateRecording
	tns1:RecordingConfig/DeleteRecording
	CreateTrack (Recording Control)
	DeleteTrack (Recording Control)
	tns1:RecordingConfig/CreateTrack
	tns1:RecordingConfig/DeleteTrack
Recording Search – PTZ Position Search	FindPTZPosition (Recording Search)
	GetPTZPositionSearchResults (Recording Search)
Device Mandatory Features	
Recording Control	GetRecordings (Recording Control)
	CreateRecordingJob (Recording Control)
	DeleteRecordingJob (Recording Control)
	GetRecordingJobs (Recording Control)
	GetRecordingJobState (Recording Control)
	SetRecordingJobMode (Recording Control)
	GetRecordingOptions (Recording Control)
	tns1:RecordingConfig/JobState
	tns1:RecordingConfig/DeleteTrackData
Recording Control – Using an on-board media source	GetProfiles (Media)
	GetProfile (Media)
	CreateProfile (Media)
	DeleteProfile (Media)



	GetVideoSources (Media)
	GetVideoSourceConfiguration (Media)
	GetVideoSourceConfigurations (Media)
	AddVideoSourceConfiguration (Media)
	RemoveVideoSourceConfiguration (Media)
	SetVideoSourceConfiguration (Media)
	GetCompatibleVideoSourceConfigurations (Media)
	GetVideoSourceConfigurationOptions (Media)
	GetVideoEncoderConfiguration (Media)
	GetVideoEncoderConfigurations (Media)
	AddVideoEncoderConfiguration (Media)
	RemoveVideoEncoderConfiguration (Media)
	SetVideoEncoderConfiguration (Media)
	GetCompatibleVideoEncoderConfigurations (Media)
	GetVideoEncoderConfigurationOptions (Media)
	GetGuaranteedNumberOfVideoEncoderInstances (Media)
	GetMetadataConfiguration (Media)
	GetMetadataConfigurations (Media)
	AddMetadataConfiguration (Media)
	RemoveMetadataConfiguration (Media)
	SetMetadataConfiguration (Media)
	GetCompatibleMetadataConfigurations (Media)
	GetMetadataConfigurationOptions (Media)



	GetAudioSources (Media)
	GetAudioSourceConfiguration (Media)
	GetAudioSourceConfigurations (Media)
	AddAudioSourceConfiguration (Media)
	RemoveAudioSourceConfiguration (Media)
	SetAudioSourceConfiguration (Media)
	GetCompatibleAudioSourceConfigurations (Media)
	GetAudioSourceConfigurationOptions (Media)
	GetAudioEncoderConfiguration (Media)
	GetAudioEncoderConfigurations (Media)
	AddAudioEncoderConfiguration (Media)
	RemoveAudioEncoderConfiguration (Media)
	SetAudioEncoderConfiguration (Media)
	GetCompatibleAudioEncoderConfigurations (Media)
	GetAudioEncoderConfigurationOptions (Media)
Recording Control – Using a Receiver as Source	GetReceivers (Receiver)
	GetReceiver (Receiver)
	CreateReceiver (Receiver)
	DeleteReceiver (Receiver)
	ConfigureReceiver (Receiver)
	SetReceiverMode (Receiver)
	GetReceiverState (Receiver)
	tns1:Receiver/ChangeState



	tns1:Receiver/ConnectionFailed
	Media Streaming using RTSP
Recording Configuration/Configuration of the Recording Source	SetRecordingConfiguration (Recording Control)
	GetRecordingConfiguration (Recording Control)
	GetTrackConfiguration (Recording Control)
	SetTrackConfiguration (Recording Control)
	SetRecordingJobConfiguration (Recording Control)
	GetRecordingJobConfiguration (Recording Control)
	tns1:RecordingConfig/RecordingConfiguration
	tns1:RecordingConfig/TrackConfiguration
	tns1:RecordingConfig/RecordingJobConfiguration
Discovery	WS-Discovery
	GetDiscoveryMode (Device)
	SetDiscoveryMode (Device)
	GetScopes (Device)
	SetScopes (Device)
	AddScopes (Device)
	RemoveScopes (Device)
Network Configuration	GetHostname (Device)
	SetHostname (Device)
	GetDNS (Device)
	SetDNS (Device)
	GetNetworkInterfaces (Device)



	SetNetworkInterfaces (Device)
	GetNetworkProtocols (Device)
	SetNetworkProtocols (Device)
	GetNetworkDefaultGateway (Device)
	SetNetworkDefaultGateway (Device)
System	GetDeviceInformation (Device)
	GetSystemDateAndTime (Device)
	SetSystemDateAndTime (Device)
	SetSystemFactoryDefault (Device)
	Reboot (Device)
User Handling	GetUsers (Device)
	CreateUsers (Device)
	DeleteUsers (Device)
	SetUser (Device)
Event Handling	SetSynchronizationPoint (Event)
	CreatePullPointSubscription (Event)
	PullMessage (Event)
	GetEventProperties (Event)
	Renew (Event)
	Unsubscribe (Event)
	TopicFilter (Event)
	MessageContentFilter
	At least two PullPoint subscriptions



4.2 Profile G support check

Preliminary checking for feature discovery will be performed prior to the test execution. For the details of the preliminary feature discovery, refer to [ONVIF Feature Discovery].

According to the result of test case execution, final determination of [ONVIF Profile G] support toward DUT is performed based on the following procedure.

Procedure:

1. Check that scope list contains the scope given in Table 3. **Error! Reference source not found.** If there is no such scope in the scope list of the DUT, then it is determined that [ONVIF Profile G] is not supported.
2. Check Capabilities feature.
 - a. Check that GetServices command is supported by the DUT. If **Device Service/Capabilities/GetServices** is not supported by the DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that Capabilities category is supported with the following features included:
 - i. GetServices (Device Management Service)
 - ii. GetServiceCapabilities (Device Management Service)
 - iii. GetServiceCapabilities (Event Service)
3. Check Discovery feature category of ONVIF profile support. This is a mandatory feature for any of ONVIF device implementation. The following features are defined as supported:
 - WS-Discovery
 - GetDiscoveryMode (Device Management Service)
 - SetDiscoveryMode (Device Management Service)
 - GetScopes (Device Management Service)
 - SetScopes (Device Management Service)
 - AddScopes (Device Management Service)
 - RemoveScopes (Device Management Service)
4. Check Discovery Types support. If **Discovery/Types/tds:Device** is not supported by the DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed.
5. Check Network Configuration feature category of ONVIF profile support. This is a mandatory feature for any of ONVIF device implementation. The following features are defined as supported:
 - GetHostname (Device Management Service)
 - SetHostname (Device Management Service)
 - GetDNS (Device Management Service)



- SetDNS (Device Management Service)
 - GetNetworkInterfaces (Device Management Service)
 - SetNetworkInterfaces (Device Management Service)
 - GetNetworkProtocols (Device Management Service)
 - SetNetworkProtocols (Device Management Service)
 - GetNetworkDefaultGateway (Device Management Service)
 - SetNetworkDefaultGateway (Device Management Service)
6. Check System feature category of ONVIF profile support. This feature is a mandatory for any of ONVIF device implementation. The following features are defined as supported:
- GetDeviceInformation (Device Management Service)
 - GetSystemDateAndTime (Device Management Service)
 - SetSystemDateAndTime (Device Management Service)
 - SetSystemFactoryDefault (Device Management Service)
 - Reboot (Device Management Service)
7. Check User Handling feature category of ONVIF profile support. This is a mandatory feature for any of ONVIF device implementation. The following features are defined as supported:
- GetUsers (Device Management Service)
 - CreateUsers (Device Management Service)
 - DeleteUsers (Device Management Service)
 - SetUser (Device Management Service)
8. Check Event Handling feature category of ONVIF profile support. This is a mandatory feature for any of ONVIF device implementation. The following features are defined as supported:
- Renew (Event Service)
 - Unsubscribe (Event Service)
 - SetSynchronizationPoint (Event Service)
 - CreatePullPointSubscription (Event Service)
 - PullMessage (Event Service)
 - GetEventProperties (Event Service)
 - TopicFilter (Event Service)
 - MessageContentFilter (Event Service)



9. Check that at least two PullPoint subscriptions are supported by the DUT. If **Device Service/Event/MaxPullPoints** is not supported by the DUT or it has value less than 2, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that Event Handling is supported with the following feature category included:
 - a. At least two PullPoint subscriptions
10. Check Security feature category.
 - a. Check that HTTP Digest Authentication is supported by the DUT. If **Security\Digest** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that HTTP Digest Authentication feature is supported by DUT.
11. Check Recording Search Service related features.
 - a. Check that Recording Search Service is supported by DUT. If **Recording Search Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that Recording Search related features are supported by DUT. Those features are:
 - i. Capabilities feature category
 - GetServiceCapabilities (Recording Search Service)
 - ii. Recording Control
 - FindRecordings (Recording Search)
 - GetRecordingSearchResults (Recording Search)
 - EndSearch (Recording Search)
 - FindEvents (Recording Search)
 - GetEventSearchResults (Recording Search)
 - GetRecordingSummary (Recording Search)
 - GetRecordingInformation (Recording Search)
 - GetMediaAttributes (Recording Search)
 - tns1:RecordingHistory/Track/State
 - tns1:RecordingHistory/Recording/State
 - XPath dialect filtering
 - b. Check that Recording Search – Metadata Search feature category is supported by the DUT. If **Recording Search Service\Metadata Search** is regarded as supported by DUT, then it is determined that the following features are supported by the DUT:
 - FindMetadata (Recording Search)
 - GetMetadataSearchResults (Recording Search)



- c. Check that Recording Search – PTZ Position Search feature category is supported by the DUT. If **Recording Search Service\PTZ Position Search** is regarded as supported by DUT, then it is determined that the following features are supported by the DUT:

- FindPTZPosition (Recording Search)
- GetPTZPositionSearchResults (Recording Search)

12. Check Replay Service related features.

- a. Check that Replay Service is supported by DUT. If **Replay Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that Replay related features are supported by DUT. Those features are:

i. Capabilities feature category

- GetServiceCapabilities (Replay Service)

ii. Replay Control

- RTP header extension
- “onvif-replay” RTSP feature tag
- Media Replay
- Reverse Replay
- GetReplayUri (Replay)
- SetReplayConfiguration (Replay)
- GetReplayConfiguration (Replay)

- b. Check that Reverse Replay feature is supported by the DUT. If **Replay Service\Reverse Replay** is regarded as supported by DUT, then it is determined that Reverse Replay feature is supported by the DUT:

13. Check Recording Control Service related features.

- a. Check that Recording Service is supported by DUT. If **Recording Control Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that Recording control related features are supported by DUT. Those features are:

i. Capabilities feature category

- GetServiceCapabilities (Recording Control Service)

ii. Recording Control

- GetRecordings (Recording Control)
- CreateRecordingJob (Recording Control)
- DeleteRecordingJob (Recording Control)



- GetRecordingJobs (Recording Control)
 - GetRecordingJobState (Recording Control)
 - SetRecordingJobMode (Recording Control)
 - GetRecordingOptions (Recording Control)
 - tns1:RecordingConfig/JobState
- iii. Recording Configuration/Configuration of the Recording Source
- SetRecordingConfiguration (Recording Control)
 - GetRecordingConfiguration (Recording Control)
 - GetTrackConfiguration (Recording Control)
 - SetRecordingJobConfiguration (Recording Control)
 - GetRecordingJobConfiguration (Recording Control)
- b. Check that tns1:RecordingConfig/DeleteTrackData event is supported by the DUT. If **Recording Control/Recording Control Events/RecordingConfig/DeleteTrackData** is regarded as supported by DUT, then it is determined that the following feature is supported by the DUT:
- tns1:RecordingConfig/DeleteTrackData
- c. Check that tns1:RecordingConfig/RecordingConfiguration event is supported by the DUT. If **Recording Control/Recording Control Events/RecordingConfig/RecordingConfiguration** is regarded as supported by DUT, then it is determined that the following feature is supported by the DUT:
- tns1:RecordingConfig/RecordingConfiguration
- d. Check that tns1:RecordingConfig/RecordingJobConfiguration event is supported by the DUT. If **Recording Control/Recording Control Events/RecordingConfig/RecordingJobConfiguration** is regarded as supported by DUT, then it is determined that the following feature is supported by the DUT:
- tns1:RecordingConfig/RecordingJobConfiguration
- e. Check that tns1:RecordingConfig/TrackConfiguration event is supported by the DUT. If **Recording Control/Recording Control Events/RecordingConfig/TrackConfiguration** is regarded as supported by DUT, then it is determined that the following feature is supported by the DUT:
- tns1:RecordingConfig/TrackConfiguration
- f. Check that GetRecordingOptions is supported by DUT. If **Recording Control Service/Recording Options** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that GetRecordingOptions is supported by DUT.

14. Check Receiver Service related features.



- a. Check that Receiver Service is supported by DUT. If **Receiver Service** is regarded as supported by DUT, then it is determined that Receiver related features are supported by DUT. Those features are:
 - i. Capabilities feature category
 - GetServiceCapabilities (Receiver Service)
 - ii. Recording Control – Using a Receiver as Source
 - GetReceivers (Receiver)
 - GetReceiver (Receiver)
 - CreateReceiver (Receiver)
 - DeleteReceiver (Receiver)
 - ConfigureReceiver (Receiver)
 - SetReceiverMode (Receiver)
 - GetReceiverState (Receiver)
 - tns1:Receiver/ChangeState
 - tns1:Receiver/ConnectionFailed
 - Media Streaming using RTSP

15. Check Media Service related features.

- a. Check that Media Service is supported by DUT. If **Media Service** is regarded as supported by DUT, then it is determined that Media related features are supported by DUT. Those features are:
 - i. Capabilities feature category
 - GetServiceCapabilities (Media)
 - ii. Recording Control – Using an on-board media source
 - GetProfiles (Media)
 - GetProfile (Media)
 - CreateProfile (Media)
 - DeleteProfile (Media)
 - GetVideoSourceConfigurations (Media)
 - AddVideoSourceConfiguration (Media)
 - RemoveVideoSourceConfiguration (Media)
 - GetCompatibleVideoSourceConfigurations (Media)
 - GetVideoEncoderConfiguration (Media)



- GetVideoEncoderConfigurations (Media)
 - AddVideoEncoderConfiguration (Media)
 - RemoveVideoEncoderConfiguration (Media)
 - SetVideoEncoderConfiguration (Media)
 - GetCompatibleVideoEncoderConfigurations (Media)
 - GetVideoEncoderConfigurationOptions (Media)
 - GetGuaranteedNumberOfVideoEncoderInstances (Media)
 - GetMetadataConfiguration (Media)
 - GetMetadataConfigurations (Media)
 - AddMetadataConfiguration (Media)
 - RemoveMetadataConfiguration (Media)
 - SetMetadataConfiguration (Media)
 - GetCompatibleMetadataConfigurations (Media)
 - GetMetadataConfigurationOptions (Media)
 - GetVideoSources (Media)
 - GetVideoSourceConfiguration (Media)
 - SetVideoSourceConfiguration (Media)
 - GetVideoSourceConfigurationOptions (Media)
- b. Check that Audio related features are supported by DUT. If **Media Service/Audio** is regarded as supported by DUT, then it is Audio related features related features are supported by DUT. Those features are:
- GetAudioSourceConfigurations (Media)
 - AddAudioSourceConfiguration (Media)
 - RemoveAudioSourceConfiguration (Media)
 - GetCompatibleAudioSourceConfigurations (Media)
 - GetAudioEncoderConfiguration (Media)
 - GetAudioEncoderConfigurations (Media)
 - AddAudioEncoderConfiguration (Media)
 - RemoveAudioEncoderConfiguration (Media)
 - SetAudioEncoderConfiguration (Media)
 - GetCompatibleAudioEncoderConfigurations (Media)



- GetAudioEncoderConfigurationOptions (Media)
- GetAudioSources (Media)
- GetAudioSourceConfiguration (Media)
- SetAudioSourceConfiguration (Media)
- GetAudioSourceConfigurationOptions (Media)

16. Check that at least one from Recording Control – Using an on-board media source and Recording Control – Using a Receiver as Source is supported by DUT. If both **Media Service** and **Receiver Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed.



5 Profile C Conformance

5.1 Feature category classification for ONVIF Profile C

In order for ONVIF Device Test Tool to conduct conformance testing toward [ONVIF Profile C], it would need to identify whether DUT implements the expected feature set.

This section classifies supported features as multiple categories that are related to [ONVIF Profile C] conformance. Those category classifications will be used to do some preliminary checking prior to the test case execution and also they will be used to determine whether DUT can be considered to be [ONVIF Profile C] conformant device.

The following discovery scope is defined as the scope that signals that DUT is [ONVIF Profile C] product.

Table 5: Profile C Discovery Scope

<code>onvif://www.onvif.org/Profile/C</code>
--

The following table shows the classified feature categories based on commands and/or functional blocks that are referenced by DUT.

Table 6: Profile C Features Categories

Profile Mandatory Features	
Capabilities	GetServices (Device)
	GetServiceCapabilities (Device)
	GetServiceCapabilities (Event)
	MaxPullPoint capability is supported and value is not less than 2
	GetServiceCapabilities (Access Control)
	GetServiceCapabilities (Door Control)
	GetWsdUrl (Device)
System component information – Access points	GetAccessPointInfoList (Access Control)
	GetAccessPointInfo (Access Control)



System component information – Doors	GetDoorInfoList (Door Control)
	GetDoorInfo (Door Control)
System component information – Areas	GetAreaInfoList (Access Control)
	GetAreaInfo (Access Control)
Access point state	GetAccessPointState (Access Control)
	tns1:AccessPoint/State/Enabled
Door state	GetDoorState (Door Control)
	tns1:Door/State/DoorMode
	tns1:Door/State/DoorPhysicalState
	tns1:Door/State/LockPhysicalState
	tns1:Door/State/DoubleLockPhysicalState
	tns1:Door/State/DoorAlarm
	tns1:Door/State/DoorTamper
	tns1:Door/State/DoorFault
Door control	AccessDoor (Door Control)
	LockDoor (Door Control)
	UnlockDoor (Door Control)
	DoubleLockDoor (Door Control)
	BlockDoor (Door Control)
	LockDownDoor (Door Control)
	LockDownReleaseDoor (Door Control)
	LockOpenDoor (Door Control)
LockOpenReleaseDoor (Door Control)	



Access control decisions	tns1:AccessControl/AccessGranted/Credential
	tns1:AccessControl/AccessGranted/Anonymous
	tns1:AccessControl/Denied/Credential
	tns1:AccessControl/Denied/Anonymous
	tns1:AccessControl/Denied/CredentialNotFound/Card
	tns1:AccessControl/AccessTaken/Credential
	tns1:AccessControl/AccessTaken/Anonymous
	tns1:AccessControl/AccessNotTaken/Credential
	tns1:AccessControl/AccessNotTaken/Anonymous
Event Handling	Renew (Event)
	Unsubscribe (Event)
	SetSynchronizationPoint (Event)
	CreatePullPointSubscription (Event)
	PullMessage (Event)
	GetEventProperties (Event)
	TopicFilter (Event)
Profile Conditional Features	
Configuration change – Access points	tns1:Configuration/AccessPoint/Changed
	tns1:Configuration/AccessPoint/Removed
Configuration change – Doors	tns1:Configuration/Door/Changed
	tns1:Configuration/Door/Removed
Configuration change – Areas	tns1:Configuration/Area/Changed



	tns1:Configuration/Area/Removed
Access Point Control	EnableAccessPoint (Access Control)
	DisableAccessPoint (Access Control)
External authorization	ExternalAuthorization (Access Control)
	tns1:AccessControl/Request/Credential
	tns1:AccessControl/Request/Anonymous
	tns1:AccessControl/Request/Timeout
Duress	tns1:AccessControl/Duress
Persistent notification storage	Seek (Event)
IP Filtering	GetIPAddressFilter (Device)
	SetIPAddressFilter (Device)
	AddIPAddressFilter (Device)
	RemoveIPAddressFilter (Device)
Device Mandatory Features	
Discovery	WS-Discovery
	GetDiscoveryMode (Device)
	SetDiscoveryMode (Device)
	GetScopes (Device)
	SetScopes (Device)
	AddScopes (Device)
	RemoveScopes (Device)
Network Configuration	GetHostname (Device)
	SetHostname (Device)



	GetDNS (Device)
	SetDNS (Device)
	GetNetworkInterfaces (Device)
	SetNetworkInterfaces (Device)
	GetNetworkProtocols (Device)
	SetNetworkProtocols (Device)
	GetNetworkDefaultGateway (Device)
	SetNetworkDefaultGateway (Device)
System	GetDeviceInformation (Device)
	GetSystemDateAndTime (Device)
	SetSystemDateAndTime (Device)
	SetSystemFactoryDefault (Device)
	Reboot (Device)
User Handling	GetUsers (Device)
	CreateUsers (Device)
	DeleteUsers (Device)
	SetUser (Device)

5.2 Profile C support check

Preliminary checking for feature discovery will be performed prior to the test execution. For the details of the preliminary feature discovery, refer to [ONVIF Feature Discovery].

According to the result of test case execution, final determination of [ONVIF Profile C] support toward DUT is performed based on the following procedure.

Procedure:



1. Check that scope list contains the scope given in Table 5. If there is no such scope in the scope list of the DUT, then it is determined that [ONVIF Profile C] is not supported.
2. Check Capabilities feature.
 - a. Check that GetServices command is supported by the DUT. If **Device Service/Capabilities/GetServices** is not supported by the DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that Capabilities category is supported with the following features included:
 - GetServices (Device Management Service)
 - GetServiceCapabilities (Device Management Service)
 - GetServiceCapabilities (Event Service)
3. Check Discovery feature category of ONVIF profile support. This is a mandatory feature for any of ONVIF device implementation. The following features are defined as supported:
 - WS-Discovery
 - GetDiscoveryMode (Device Management Service)
 - SetDiscoveryMode (Device Management Service)
 - GetScopes (Device Management Service)
 - SetScopes (Device Management Service)
 - AddScopes (Device Management Service)
 - RemoveScopes (Device Management Service)
4. Check Discovery Types support. If **Discovery/Types/tds:Device** is not supported by the DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed.
5. Check Network Configuration feature category of ONVIF profile support. This is mandatory a feature for any of ONVIF device implementation. The following features are defined as supported:
 - GetHostname (Device Management Service)
 - SetHostname (Device Management Service)
 - GetDNS (Device Management Service)
 - SetDNS (Device Management Service)
 - GetNetworkInterfaces (Device Management Service)
 - SetNetworkInterfaces (Device Management Service)
 - GetNetworkProtocols (Device Management Service)
 - SetNetworkProtocols (Device Management Service)
 - GetNetworkDefaultGateway (Device Management Service)



- SetNetworkDefaultGateway (Device Management Service)
6. Check System feature category of ONVIF profile support. This feature is mandatory for any of ONVIF device implementation. The following features are defined as supported:
 - GetDeviceInformation (Device Management Service)
 - GetSystemDateAndTime (Device Management Service)
 - SetSystemDateAndTime (Device Management Service)
 - SetSystemFactoryDefault (Device Management Service)
 - Reboot (Device Management Service)
 7. Check User Handling feature category of ONVIF profile support. This is a mandatory feature for any of ONVIF device implementation. The following features are defined as supported:
 - GetUsers (Device Management Service)
 - CreateUsers (Device Management Service)
 - DeleteUsers (Device Management Service)
 - SetUser (Device Management Service)
 8. Check Event Handling feature category of ONVIF profile support. This is a mandatory feature for any of ONVIF device implementation. The following features are defined as supported:
 - Notify (Event Service)
 - Subscribe (Event Service)
 - Renew (Event Service)
 - Unsubscribe (Event Service)
 - SetSynchronizationPoint (Event Service)
 - CreatePullPointSubscription (Event Service)
 - PullMessage (Event Service)
 - GetEventProperties (Event Service)
 - TopicFilter (Event Service)
 9. Check that at least two PullPoint subscriptions are supported by the DUT. If **Event Service/Event/MaxPullPoint** is not supported by the DUT or it has value less than 2, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that Event Handling feature category is supported with the following feature included:
 - At least two PullPoint subscriptions
 10. Check Security feature category.



- a. Check that HTTP Digest Authentication is supported by the DUT. If **Security\Digest** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that HTTP Digest Authentication feature is supported by DUT.
11. Check Persistent notification storage feature category of ONVIF profile support. If **Event Service\Persistent notification storage** is regarded as supported by DUT, then it is determined that Store events feature category with Seek (Event Service) feature is supported by DUT.
 12. Check Access Control Service related features.
 - a. Check that Access Control Service is supported by DUT. If **Access Control Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that Access Control related features are supported by DUT. Those features are:
 - i. Capabilities feature category
 - GetServiceCapabilities (Access Control Service)
 - ii. System component information – Access points feature category
 - GetAccessPointInfoList (Access Control Service)
 - GetAccessPointInfo (Access Control Service)
 - iii. System component information – Areas feature category
 - GetAreaInfoList (Access Control Service)
 - GetAreaInfo (Access Control Service)
 - iv. Access point state feature category
 - GetAccessPointState (Access Control Service)
 - tns1:AccessPoint/State/Enabled
 - v. Access control decisions
 - tns1:AccessControl/AccessGranted/Credential
 - tns1:AccessControl/Denied/Credential
 - b. Check that Access point control feature category is supported by the DUT. If **Access Control Service\Access Point Entity\Enable/Disable Access Point** is regarded as supported by DUT, then it is determined that EnableAccessPoint (Access Control Service) and DisableAccessPoint (Access Control Service) features are supported by the DUT.
 - c. Check that tns1:AccessControl/AccessGranted/Anonymous feature is supported by the DUT. If **Access Control Service\Access Point Entity\Anonymous Access** is regarded as supported by DUT, then it is determined that tns1:AccessControl/AccessGranted/Anonymous features are supported by the DUT.
 - d. Check that tns1:AccessControl/Denied/Anonymous feature is supported by the DUT. If **Access Control Service\Access Point Entity\Anonymous Access** and **Access Control Service\Access Point Entity\External Authorization** is regarded as



supported by DUT, then it is determined that `tns1:AccessControl/Denied/Anonymous` feature is supported by the DUT.

- e. Check that `tns1:AccessControl/AccessTaken/Credential` and `tns1:AccessControl/AccessNotTaken/Credential` features are supported by the DUT. If **Access Control Service\Access Point Entity\Access Taken** is regarded as supported by DUT, then it is determined that `tns1:AccessControl/AccessTaken/Credential` and `tns1:AccessControl/AccessNotTaken/Credential` features are supported by the DUT.
- f. Check that `tns1:AccessControl/AccessTaken/Anonymous` and `tns1:AccessControl/AccessNotTaken/Anonymous` features are supported by the DUT. If **Access Control Service\Access Point Entity\Access Taken** and **Access Control Service\Access Point Entity\Anonymous Access** are regarded as supported by DUT, then it is determined that `tns1:AccessControl/AccessTaken/Anonymous` and `tns1:AccessControl/AccessNotTaken/Anonymous` features are supported by the DUT.
- g. Check that `tns1:AccessControl/Denied/CredentialNotFound/Card` feature are supported by the DUT. If **Access Control Service\Access Control Events\AccessControl/Denied/CredentialNotFound/Card** is regarded as supported by DUT, then it is determined that `tns1:AccessControl/Denied/CredentialNotFound/Card` feature is supported by the DUT.
- h. Check that External authorization feature category is supported by the DUT. If **AccessControl\External Authorization** is regarded as supported by DUT, then it is determined that External authorization feature category is supported by DUT. Those features are:
 - ExternalAuthorization (Access Control)
 - `tns1:AccessControl/Request/Credential`
 - `tns1:AccessControl/Request/Timeout`
- i. Check that `tns1:AccessControl/Request/Anonymous` of External authorization feature category is supported by the DUT. If **AccessControl\External Authorization** and **Access Control Service\Access Point Entity\Anonymous Access** is regarded as supported by DUT, then it is determined that `tns1:AccessControl/Request/Anonymous` feature is supported by the DUT.
- j. Check that `tns1:Configuration/AccessPoint/Changed` feature are supported by the DUT. If **Access Control Service\Access Control Events\Configuration/AccessPoint/Changed** is regarded as supported by DUT, then it is determined that `tns1:Configuration/AccessPoint/Changed` feature is supported by the DUT.
- k. Check that `tns1:Configuration/AccessPoint/Removed` feature are supported by the DUT. If **Access Control Service\Access Control Events\Configuration/AccessPoint/Removed** is regarded as supported by DUT, then it is determined that `tns1:Configuration/AccessPoint/Removed` feature is supported by the DUT.
- l. Check that `tns1:Configuration/Area/Changed` feature are supported by the DUT. If **Access Control Service\Access Control Events\Configuration/Area/Changed** is regarded as supported by DUT, then it is determined that `tns1:Configuration/Area/Changed` feature is supported by the DUT.



- m. Check that `tns1:Configuration/Area/Removed` feature are supported by the DUT. If **Access Control Service\Access Control Events\Configuration/Area/Removed** is regarded as supported by DUT, then it is determined that `tns1:Configuration/Area/Removed` feature is supported by the DUT.
- n. Check that **Duress** feature category is supported by the DUT. If **Access Control Service\Access Point Entity\Duress** is regarded as supported by DUT, then it is determined that `tns1:AccessControl/Duress` feature is supported by the DUT.

13. Check Door Control Service related features.

- a. Check that Door Control Service is supported by DUT. If Door Control Service is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that Door Control related features are supported by DUT. Those features are:
 - i. Capabilities feature category
 - `GetServiceCapabilities` (Door Control Service)
 - ii. System component information – Doors feature category
 - `GetDoorInfoList` (Door Control Service)
 - `GetDoorInfo` (Door Control Service)
 - iii. Door state feature category
 - `GetDoorState` (Door Control Service)
 - `tns1:Door/State/DoorMode`
- b. Check that `AccessDoor` (Door Control Service) feature is supported by the DUT. If **Door Control Service\Door Entity\Access Door** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that `AccessDoor` (Door Control Service) feature is supported by the DUT.
- c. Check that `LockDoor` (Door Control Service) feature is supported by the DUT. If **Door Control Service\Door Entity\Lock Door** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that `LockDoor` (Door Control Service) feature is supported by the DUT.
- d. Check that `UnlockDoor` (Door Control Service) feature is supported by the DUT. If **Door Control Service\Door Entity\Unlock Door** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that `UnlockDoor` (Door Control Service) feature is supported by the DUT.
- e. Check that `DoubleLockDoor` (Door Control Service) feature is supported by the DUT. If **Door Control Service\Door Entity\Double Lock Door** is regarded as supported by DUT, then it is determined that `DoubleLockDoor` (Door Control Service) feature is supported by the DUT.
- f. Check that `BlockDoor` (Door Control Service) feature is supported by the DUT. If **Door Control Service\Door Entity\Block Door** is regarded as supported by DUT, then it is determined that `BlockDoor` (Door Control Service) feature is supported by the DUT.



- g. Check that LockDownDoor (Door Control Service) and LockDownReleaseDoor (Door Control Service) features are supported by the DUT. If **Door Control Service\Door Entity\Lock Down Door** is regarded as supported by DUT, then it is determined that LockDownDoor (Door Control Service) and LockDownReleaseDoor (Door Control Service) features are supported by the DUT.
- h. Check that LockOpenDoor (Door Control Service) and LockOpenReleaseDoor (Door Control Service) features are supported by the DUT. If **Door Control Service\Door Entity\Lock Open Door** is regarded as supported by DUT, then it is determined that LockOpenDoor (Door Control Service) and LockOpenReleaseDoor (Door Control Service) features are supported by the DUT.
- i. Check that tns1:Door/State/DoorPhysicalState feature are supported by the DUT. If Door Control Service\Door Entity\Door Monitor is regarded as supported by DUT, then it is determined that tns1:Door/State/DoorPhysicalState feature is supported by the DUT.
- j. Check that tns1:Door/State/LockPhysicalState feature are supported by the DUT. If Door Control Service\Door Entity\Lock Monitor is regarded as supported by DUT, then it is determined that tns1:Door/State/LockPhysicalState feature is supported by the DUT.
- k. Check that tns1:Door/State/DoubleLockPhysicalState feature are supported by the DUT. If Door Control Service\Door Entity\Double Lock Monitor is regarded as supported by DUT, then it is determined that tns1:Door/State/DoubleLockPhysicalState feature is supported by the DUT.
- l. Check that tns1:Door/State/DoorAlarm feature are supported by the DUT. If Door Control Service\Door Entity\Alarm is regarded as supported by DUT, then it is determined that tns1:Door/State/DoorAlarm feature is supported by the DUT.
- m. Check that tns1:Door/State/DoorTamper feature are supported by the DUT. If Door Control Service\Door Entity\Tamper is regarded as supported by DUT, then it is determined that tns1:Door/State/DoorTamper feature is supported by the DUT.
- n. Check that tns1:Door/State/DoorFault feature are supported by the DUT. If Door Control Service\Door Entity\Fault is regarded as supported by DUT, then it is determined that tns1:Door/State/DoorFault feature is supported by the DUT.
- o. Check that tns1:Configuration/Door/Changed feature are supported by the DUT. If **Access Control Service\Access Control Events\Configuration/Door/Changed** is regarded as supported by DUT, then it is determined that tns1:Configuration/Door/Changed feature is supported by the DUT.
- p. Check that tns1:Configuration/Door/Removed feature are supported by the DUT. If **Access Control Service\Access Control Events\Configuration/Door/Removed** is regarded as supported by DUT, then it is determined that tns1:Configuration/Door/Removed feature is supported by the DUT.



6 Profile Q Conformance

6.1 Feature category classification for ONVIF Profile Q

In order for ONVIF Device Test Tool to conduct conformance testing toward [ONVIF Profile Q], it would need to identify whether DUT implements the expected feature set.

This section classifies supported features as multiple categories that are related to [ONVIF Profile Q] conformance. Those category classifications will be used to do some preliminary checking prior to the test case execution and also they will be used to determine whether DUT can be considered to be [ONVIF Profile Q] conformant device.

The following discovery scope is defined as the scope that signals that DUT is [ONVIF Profile Q] product.

Table 7: Profile Q Discovery Scope

```
onvif://www.onvif.org/Profile/Q/FactoryDefault
onvif://www.onvif.org/Profile/Q/Operational
```

The following table shows the classified feature categories based on commands and/or functional blocks that are referenced by DUT.

Table 8: Profile Q Features Categories

Profile Mandatory Features	
Capabilities	GetServices (Device)
	GetServiceCapabilities (Device)
	GetServiceCapabilities (Event)
	MaxUsernameLength capability is supported
	MaxPasswordLength capability is supported
Network Configuration	GetHostname (Device)
	SetHostname (Device)
	GetDNS (Device)
	SetDNS (Device)
	GetNetworkInterfaces (Device)



	SetNetworkInterfaces (Device)
	GetNetworkProtocols (Device)
	SetNetworkProtocols (Device)
	GetNetworkDefaultGateway (Device)
	SetNetworkDefaultGateway (Device)
	GetZeroConfiguration (Device)
	SetZeroConfiguration (Device)
System	GetDeviceInformation (Device)
	GetSystemDateAndTime (Device)
	SetSystemDateAndTime (Device)
	GetNTP (Device)
	SetNTP (Device)
	SetSystemFactoryDefault (Device)
	Reboot (Device)
User Handling	MaxUsers capability is supported
	GetUsers (Device)
	CreateUsers (Device)
	DeleteUsers (Device)
	SetUser (Device)
Standard Events for Monitoring	tns1:Monitoring/ProcessorUsage
	tns1:Monitoring/OperatingTime/LastReset
	tns1:Monitoring/OperatingTime/LastReboot
	tns1:Monitoring/OperatingTime/LastClockSynchronization



Event Handling		MaxPullPoint capability is supported and value is not less than 2
		SetSynchronizationPoint (Event)
		CreatePullPointSubscription (Event)
		PullMessages (Event)
		GetEventProperties (Event)
		Renew (Event)
		Unsubscribe (Event)
		TopicFilter (Event)
Profile Conditional Features		
Remote Management	User	GetRemoteUser (Device)
		SetRemoteUser (Device)
Firmware Upgrade		StartFirmwareUpgrade (Device)
Backup and Restore		GetSystemUris (Device)
		StartSystemRestore (Device)
TLS Configuration - Keystore		CreateCertificationPath (Advanced Security)
		CreatePKCS10CSR (Advanced Security)
		CreateRSAKeyPair (Advanced Security)
		CreateSelfSignedCertificate (Advanced Security)
		DeleteCertificate (Advanced Security)
		DeleteCertificationPath (Advanced Security)
		DeleteKey (Advanced Security)
		DeletePassphrase (Advanced Security)
	GetAllCertificates (Advanced Security)	



	GetAllCertificationPaths (Advanced Security)
	GetAllKeys (Advanced Security)
	GetAllPassphrases (Advanced Security)
	GetCertificate (Advanced Security)
	GetCertificationPath (Advanced Security)
	GetKeyStatus (Advanced Security)
	UploadCertificate (Advanced Security)
	UploadCertificateWithPrivateKeyInPKCS12 (Advanced Security)
	UploadKeyPairInPKCS8 (Advanced Security)
	UploadPassphrase (Advanced Security)
TLS Configuration - TLS Server	AddServerCertificateAssignment (Advanced Security)
	GetAssignedServerCertificates (Advanced Security)
	RemoveServerCertificateAssignment (Advanced Security)
	ReplaceServerCertificateAssignment (Advanced Security)
Media Service	GetProfiles (Media)
	GetStreamUri (Media)
	GetServiceCapabilities (Media)
	Media Streaming using RTSP
Standard Events for Device Management	tns1:Device/HardwareFailure/FanFailure
	tns1:Device/HardwareFailure/PowerSupplyFailure
	tns1:Device/HardwareFailure/StorageFailure
	tns1:Device/HardwareFailure/TemperatureCritical
	tns1:Monitoring/Backup/Last



Factory Default State	
Factory Default State	Factory Default State is signaled by the scope value <code>onvif://www.onvif.org/Profile/Q/FactoryDefault</code>
	Anonymous access in Factory Default State
	User configuration in Factory Default State
Device Discovery	WS-Discovery
	GetScopes (Device)
ZeroConfiguration Network Configuration	Dynamic IP configuration enabled in Factory Default State
Automatic IP Assignment	IPv4 DHCP enabled in Factory Default State
	IP v6 stateless autoconfiguration enabled in Factory Default State
Operational State	
Operational State	Operational State is signaled by the scope value <code>onvif://www.onvif.org/Profile/Q/Operational</code>
Authentication	HTTP digest authentication
Default Access Policy	Default Access Policy

6.2 Profile Q support check

Preliminary checking for feature discovery will be performed prior to the test execution. For the details of the preliminary feature discovery, refer to [ONVIF Feature Discovery].

According to the result of test case execution, final determination of [ONVIF Profile Q] support toward DUT is performed based on the following procedure.

Procedure:

1. Check that scope list contains at least one scope given in Table 7 **Error! Reference source not found.** If there is no such scope on the scope list of the DUT, then it is determined that [ONVIF Profile Q] is not supported.
2. Check Discovery Types support. If **Discovery/Types/tds:Device** is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed.



3. Check Capabilities feature category of ONVIF profile support:

- a. Check that `GetServices` command is supported by the DUT. If **Device Service/Capabilities/GetServices** is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed. Otherwise, it is determined that Capabilities category is supported with the following features included:
 - `GetServices` (Device Management Service)
 - `GetServiceCapabilities` (Device Management Service)
 - `GetServiceCapabilities` (Event Service)
- b. Check that `MaxUsernameLength` capability is supported by the DUT. If **Device Service/Security/MaxUsernameLength capability** is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed. Otherwise, it is determined that Capabilities category is supported with the following features included:
 - `MaxUsernameLength` capability is supported
- c. Check that `MaxPasswordLength` capability is supported by the DUT. If **Device Service/Security/MaxPasswordLength capability** is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed. Otherwise, it is determined that Capabilities category is supported with the following features included:
 - `MaxPasswordLength` capability is supported

4. Check Network feature category of ONVIF profile support:

- a. The following features are a mandatory features for any of ONVIF device implementation and are defined as supported:
 - `GetHostname` (Device Management Service)
 - `SetHostname` (Device Management Service)
 - `GetDNS` (Device Management Service)
 - `SetDNS` (Device Management Service)
 - `GetNetworkInterfaces` (Device Management Service)
 - `SetNetworkInterfaces` (Device Management Service)
 - `GetNetworkProtocols` (Device Management Service)
 - `SetNetworkProtocols` (Device Management Service)
 - `GetNetworkDefaultGateway` (Device Management Service)
 - `SetNetworkDefaultGateway` (Device Management Service)
- b. Check that `ZeroConfiguration` capability is supported by the DUT. If **Device Service/Network/Zero Configuration** is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be



failed. Otherwise, it is determined that Network feature category is supported with the following features included:

- GetZeroConfiguration (Device)
- SetZeroConfiguration (Device)

5. Check System feature category of ONVIF profile support:

a. This feature is mandatory for any of ONVIF device implementation. The following features are defined as supported:

- GetDeviceInformation (Device Management Service)
- GetSystemDateAndTime (Device Management Service)
- SetSystemDateAndTime (Device Management Service)
- SetSystemFactoryDefault (Device Management Service)
- Reboot (Device Management Service)

b. Check that NTP capability is supported by the DUT. If **Device Management/Network/NTP** is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed. Otherwise, it is determined that System category is supported with the following features included:

- GetNTP (Device)
- SetNTP (Device)

6. Check User Handling feature category of ONVIF profile support:

a. The following features are a mandatory features for any of ONVIF device implementation and are defined as supported:

- GetUsers (Device Management Service)
- CreateUsers (Device Management Service)
- DeleteUsers (Device Management Service)
- SetUser (Device Management Service)

b. Check that MaxUsers capability is supported by the DUT. If **Device Service/Security/Maximum Users** is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed. Otherwise, it is determined that User Handling category is supported with the following features included:

- MaxUsers capability is supported

7. Check Standard Events for Monitoring feature category of ONVIF profile support:

a. Check that tns1:Monitoring/ProcessorUsage feature is supported by the DUT. If **Monitoring events\Monitoring/ProcessorUsage** is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will



- be failed. Otherwise, it is determined that tns1:Monitoring/ProcessorUsage feature is supported by the DUT.
- b. Check that tns1:Monitoring/OperatingTime/LastReset feature is supported by the DUT. If **Monitoring events\Monitoring/OperatingTime/LastReset** is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed. Otherwise, it is determined that tns1:Monitoring/OperatingTime/LastReset feature is supported by the DUT.
 - c. Check that tns1:Monitoring/OperatingTime/LastReboot feature is supported by the DUT. If **Monitoring events\Monitoring/OperatingTime/LastReboot** is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed. Otherwise, it is determined that tns1:Monitoring/OperatingTime/LastReboot feature is supported by the DUT.
 - d. Check that tns1:Monitoring/OperatingTime/LastClockSynchronization feature is supported by the DUT. If **Monitoring events\Monitoring/OperatingTime/LastClockSynchronization** is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed. Otherwise, it is determined that tns1:Monitoring/OperatingTime/LastClockSynchronization feature is supported by the DUT.
8. Check Event Handling feature category of ONVIF profile support. This is a mandatory feature for any of ONVIF device implementation. The following features are defined as supported:
 - Notify (Event Service)
 - Subscribe (Event Service)
 - Renew (Event Service)
 - Unsubscribe (Event Service)
 - SetSynchronizationPoint (Event Service)
 - CreatePullPointSubscription (Event Service)
 - PullMessage (Event Service)
 - GetEventProperties (Event Service)
 - TopicFilter (Event Service)
 9. Check Remote User Management feature category of ONVIF profile support. If **Device Service\Security\Remote User Handling** is regarded as supported by DUT, then it is determined that Remote User Management feature category with the following features is supported by DUT:
 - GetRemoteUser (Device)
 - SetRemoteUser (Device)
 10. Check Firmware Upgrade feature category of ONVIF profile support. If **Device Service\System\HTTP Firmware Upgrade** is regarded as supported by DUT, then it is determined that Firmware Upgrade feature category with the following features is supported by DUT:



- StartFirmwareUpgrade (Device)
11. Check Backup and Restore feature category of ONVIF profile support. If **Device Service\System\HTTP System Backup** is regarded as supported by DUT, then it is determined that Backup and Restore feature category with the following features is supported by DUT:
- GetSystemUris (Device)
 - StartSystemRestore (Device)
12. If **Advanced Security Service** is regarded as supported:
- a. Check TLS Configuration - Keystore feature category of ONVIF profile support:
 - i. If Advanced Security Service\Keystore features support\RSA Key Pair Generation is not supported by the DUT and Advanced Security Service\Keystore features support\PKCS#12 Container Upload is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by the DUT and certification will be failed. Otherwise, it is determined that feature is supported by the DUT:
 - 1) If **Advanced Security Service\Keystore features support\RSA Key Pair Generation** is regarded as supported by the DUT:
 - CreateRSAKeyPair (Advanced Security)
 - GetKeyStatus (Advanced Security)
 - GetAllKeys (Advanced Security)
 - DeleteKey (Advanced Security)
 - 2) If **Advanced Security Service\Keystore features support\PKCS#12 Container Upload** is regarded as supported by the DUT:
 - DeleteCertificate (Advanced Security)
 - DeleteCertificationPath (Advanced Security)
 - DeleteKey (Advanced Security)
 - DeletePassphrase (Advanced Security)
 - GetAllCertificates (Advanced Security)
 - GetAllCertificationPaths (Advanced Security)
 - GetAllKeys (Advanced Security)
 - GetAllPassphrases (Advanced Security)
 - GetCertificate (Advanced Security)
 - GetCertificationPath (Advanced Security)
 - GetKeyStatus (Advanced Security)
 - UploadPassphrase (Advanced Security)



- ii. If Advanced Security Service\Keystore features support\RSA Key Pair Generation is supported by the DUT:
 - 1) If Advanced Security Service\Keystore features support\Self-Signed Certificate Creation With RSA is not supported by the DUT or Advanced Security Service\Keystore features support\PKCS10 External Certification With RSA is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed. Otherwise, it is determined that feature is supported by the DUT:
 - CreatePKCS10CSR (Advanced Security)
 - CreateSelfSignedCertificate (Advanced Security)
 - DeleteCertificate (Advanced Security)
 - GetAllCertificates (Advanced Security)
 - GetCertificate (Advanced Security)
 - UploadCertificate (Advanced Security)
 - iii. If Advanced Security Service\Keystore features support\PKCS#8 Container Upload is regarded as supported by the DUT, then it is determined that the following feature is supported by the DUT:
 - UploadKeyPairInPKCS8 (Advanced Security)
 - iv. If DUT returns MaximumNumberOfKeys less than 16, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed.
 - v. If DUT returns MaximumNumberOfCertificates less than 16, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed.
- b. Check TLS Configuration - TLS server feature category of ONVIF profile support:
- i. If Advanced Security Service\TLS features support\TLS Server Support is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed. Otherwise, it is determined that feature is supported by the DUT:
 - CreateCertificationPath (Advanced Security)
 - GetCertificationPath (Advanced Security)
 - GetAllCertificationPaths (Advanced Security)
 - DeleteCertificationPath (Advanced Security)
 - AddTLSServerCertificateAssignment (Advanced Security)
 - RemoveTLSServerCertificateAssignment (Advanced Security)
 - ReplaceTLSServerCertificateAssignment (Advanced Security)
 - GetAssignedServerCertificates (Advanced Security)



13. Check Media Service feature category of ONVIF profile support:

- a. If **Media Service** is regarded as supported by DUT, then it is determined that the following features is supported by DUT:
 - GetProfiles (Media)
- b. If **Media Service** is regarded as supported by DUT and **Device Service/Capabilities/GetServices** is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features is supported by DUT:
 - GetServiceCapabilities (Media)
- c. If **Media Service** is regarded as supported by DUT and **Media Service/Real-time Streaming** is not supported by the DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features is supported by DUT:
 - GetStreamUri (Media)
 - Media Streaming using RTSP

14. Check Standard events for Device Management feature category of ONVIF profile support:

- a. Check that tns1:Device/HardwareFailure/FanFailure feature is supported by the DUT. If **Monitoring events\Device/HardwareFailure/FanFailure** is regarded as supported by DUT, then it is determined that tns1:Device/HardwareFailure/FanFailure feature is supported by the DUT.
- b. Check that tns1:Device/HardwareFailure/PowerSupplyFailure feature is supported by the DUT. If **Monitoring events\Device/HardwareFailure/PowerSupplyFailure** is regarded as supported by DUT, then it is determined that tns1:Device/HardwareFailure/PowerSupplyFailure feature is supported by the DUT.
- c. Check that tns1:Device/HardwareFailure/StorageFailure feature is supported by the DUT. If **Monitoring events\Device/HardwareFailure/StorageFailure** is regarded as supported by DUT, then it is determined that tns1:Device/HardwareFailure/StorageFailure feature is supported by the DUT.
- d. Check that tns1:Device/HardwareFailure/TemperatureCritical feature is supported by the DUT. If **Monitoring events\Device/HardwareFailure/TemperatureCritical** is regarded as supported by DUT, then it is determined that tns1:Device/HardwareFailure/TemperatureCritical feature is supported by the DUT.
- e. Check that tns1:Monitoring/Backup/Last feature is supported by the DUT. If **Monitoring events\Monitoring/Backup/Last** is regarded as supported by DUT, then it is determined that tns1:Monitoring/Backup/Last feature is supported by the DUT.

15. Check Device Discovery feature category of ONVIF profile support:

- a. The following features are a mandatory features for any of ONVIF device implementation and are defined as supported:
 - WS-Discovery
 - GetScopes (Device)



16. If **Profile Q** is regarded as supported by DUT the following feature categories and related features will be regarded as supported:

- a. Factory Default State feature category:
 - i. Factory Default State is signalled by the scope value `onvif://www.onvif.org/Profile/Q/FactoryDefault`
 - ii. Anonymous access in Factory Default State
 - iii. User configuration in Factory Default State
- b. ZeroConfiguration Network Configuration feature category:
 - i. Dynamic IP configuration enabled in Factory Default State
- c. Automatic IP Assignment feature category:
 - i. IPv4 DHCP enabled in Factory Default State
- d. Operational State feature category:
 - i. Operational State is signaled by the scope value `onvif://www.onvif.org/Profile/Q/Operational`

17. If **Profile Q** is regarded as supported by DUT and **Device Service\Network\IPv6** is regarded as supported by DUT the following related features will be regarded as supported:

- a. IP v6 stateless autoconfiguration enabled in Factory Default State

18. Check Default Access Policy feature category.

- a. Check that Default Access Policy is supported by the DUT. If **Device Service\Security\Default Access Policy** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed. Otherwise, it is determined that Default Access Policy feature is supported by DUT.

19. Check Authentication feature category.

- a. Check that HTTP Digest Authentication is supported by the DUT. If **Security\Digest** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile Q] is not supported by DUT and certification will be failed. Otherwise, it is determined that HTTP Digest Authentication feature is supported by DUT.

6.3 Profile Q testing preparation

If a DUT has Profile Q scope, the test tool prepares a DUT to Quick Install test cases during conformance procedure following the procedure of Profile Q testing preparation test case:

Procedure:

1. ONVIF Client invokes `SetSystemFactoryDefault` with parameters
 - `FactoryDefault := Hard`
2. The DUT responds with a **SetSystemFactoryDefaultResponse** message.



3. Until *timeout1* timeout expires repeat the following steps:
 - a. The DUT will send Multicast Hello message after it is successfully rebooted with parameters:
 - EndpointReference.Address equal to unique endpoint reference of the DUT
 - Types list
 - Scopes list := *scopesList*
 - XAddrs list := *xaddrsList*
 - MetadataVersion
 - b. If *xaddrsList* contains URI address with not a LinkLocal IPv4 address from ONVIF Client subnet, go to step 6.
4. If *timeout1* timeout expires for step 3 without Hello with URI address with not a LinkLocal IPv4 address from ONVIF Client subnet, FAIL the test and skip other steps.
5. ONVIF client waits for 5 seconds after Hello was received.
6. ONVIF Client invokes **SetNTP** without any authentication with parameters
 - FromDHCP := true
 - NTPManual skipped
7. The DUT responds with a **SetNTPResponse** message.
8. ONVIF client invokes **GetSystemDateAndTime** without any authentication.
9. The DUT responds with **GetSystemDateAndTimeResponse** message with parameters
 - SystemDateAndTime := *dateAndTimeSettings*
10. ONVIF Client invokes **SetSystemDateAndTime** without any authentication with parameters
 - DateTimeType := NTP
 - DaylightSavings := *dateAndTimeSettings.DaylightSavings*
 - TimeZone := *dateAndTimeSettings.TimeZone*
 - UTCDateTime skipped
11. The DUT responds with a **SetSystemDateAndTime** message.
12. ONVIF Client invokes **GetServiceCapabilities**.
13. The DUT responds with a **GetServiceCapabilitiesResponse** message with parameters
 - Capabilities =: *cap*
14. If *cap* does not contain Security.MaxPasswordLength or Security.MaxUserNameLength, FAIL the test and skip other steps.
15. ONVIF Client invokes **GetUsers** without any authentication.



16. The DUT responds with a **GetUsersResponse** message with parameters.

- User list =: *userList*

17. If *userList* contains user with user level Administrator:

a. Set the following:

- *passwordLength* := *cap.Security.MaxPasswordLength*
- *userLogin* := Username of user with user level equal to Administrator from *userList*
- *password* := random string, contains *passwordLength* ASCII characters

b. ONVIF Client invokes SetUser with parameters

- *User[0].Username* := *userLogin*
- *User[0].Password* := *password*
- *User[0].UserLevel* := Administrator
- Extension skipped

c. If the DUT responds with **SetUserResponse** message, skip other steps.

d. If the DUT returns env:Sender\ter:OperationProhibited\ter>Password SOAP 1.2 fault:

i. Set the following:

- *password* := random string, contains *passwordLength* ASCII characters

ii. Go to the step b.

e. If the DUT returns other SOAP 1.2 fault, FAIL the test and skip other steps.

18. If *userList* does not contain user with user level Administrator:

a. Set the following:

- *userLoginLength* := *cap.Security.MaxUserNameLength*
- *passwordLength* := *cap.Security.MaxPasswordLength*
- *userLogin* := random string, contains *userLoginLength* low case alphabet characters, differs from usernames listed in *userList*
- *password* := random string, contains *passwordLength* ASCII characters

b. ONVIF Client invokes CreateUsers with parameters

- *User[0].Username* := *userLogin*
- *User[0].Password* := *password*
- *User[0].UserLevel* := Administrator
- Extension skipped



- c. If the DUT responds with **CreateUsersResponse** message, skip other steps.
- d. If the DUT returns env:Sender\ter:OperationProhibited\ter>Password SOAP 1.2 fault:
 - i. Set the following:
 - *password* := random string, contains *passwordLength* ASCII characters
 - ii. Go to the step b.
 - iii. If the DUT returns other SOAP 1.2 fault, FAIL the test.

Procedure Result:

PASS –

The DUT passed all assertions.

FAIL –

The DUT did not send **SetSystemFactoryDefaultResponse** message.

The DUT did not send **GetServiceCapabilitiesResponse** message.

The DUT did not send **GetUsersResponse** message.

The DUT did not send **SetUsersResponse** message.

The DUT did not send **CreateUsersResponse** message.

The DUT did not send **SetNTPResponse** message.

The DUT did not send **GetSystemDateAndTimeResponse** message.

The DUT did not send **SetSystemDateAndTimeResponse** message.

Note: User with username *userLogin* and password *password* shall be used for further test cases.

Note: *timeout1* will be taken from Reboot Timeout field of ONVIF Device Test Tool.

Note: IPv4 address from Hello shall be used for further test cases.



7 Profile A Conformance

7.1 Feature category classification for ONVIF Profile A

In order for ONVIF Device Test Tool to conduct conformance testing toward [ONVIF Profile A], it would need to identify whether DUT implements the expected feature set.

This section classifies supported features as multiple categories that are related to [ONVIF Profile A] conformance. Those category classifications will be used to do some preliminary checking prior to the test case execution and they will be used to determine whether DUT can be considered [ONVIF Profile A] conformant device.

The following discovery scope is defined as the scope that signals that DUT is [ONVIF Profile A] product.

Table 9: Profile A Discovery Scope

<code>onvif://www.onvif.org/Profile/A</code>
--

The following table shows the classified feature categories based on commands and/or functional blocks that are referenced by the DUT.

Table 10: Profile A Features Categories

Profile Mandatory Features	
Security	HTTP Digest Authentication
Capabilities	GetServices (Device)
	GetServiceCapabilities (Device)
	GetServiceCapabilities (Event)
	GetServiceCapabilities (Access Rules)
	GetServiceCapabilities (Credential)
	GetServiceCapabilities (Schedule)
	GetWsdUrl (Device)
	MaxPullPoint capability is supported and value is not less than 2
Access Profiles	GetAccessProfiles (Access Rules)



	GetAccessProfileList (Access Rules)
	GetAccessProfileInfo (Access Rules)
	GetAccessProfileInfoList (Access Rules)
	CreateAccessProfile (Access Rules)
	ModifyAccessProfile (Access Rules)
	DeleteAccessProfile (Access Rules)
	tns1:Configuration/AccessProfile/Changed
	tns1:Configuration/AccessProfile/Removed
Credentials	GetCredentials (Credential)
	GetCredentialList (Credential)
	GetCredentialInfo (Credential)
	GetCredentialInfoList (Credential)
	CreateCredential (Credential)
	ModifyCredential (Credential)
	DeleteCredential (Credential)
	GetCredentialAccessProfiles (Credential)
	SetCredentialAccessProfiles (Credential)
	DeleteCredentialAccessProfiles (Credential)
	GetCredentialIdentifiers (Credential)
	SetCredentialIdentifier (Credential)
	DeleteCredentialIdentifier (Credential)
	EnableCredential (Credential)
	DisableCredential (Credential)



	GetCredentialState (Credential)
	GetSupportedFormatTypes (Credential)
	tns1:Configuration/Credential/Changed
	tns1:Configuration/Credential/Removed
Schedules	GetSchedules (Schedule)
	GetScheduleList (Schedule)
	GetScheduleInfo (Schedule)
	GetScheduleInfoList (Schedule)
	CreateSchedule (Schedule)
	ModifySchedule (Schedule)
	DeleteSchedule (Schedule)
	GetScheduleState (Schedule)
	tns1:Configuration/Schedule/Changed
	tns1:Configuration/ Schedule /Removed
	tns1:Schedule/State/Active
Event Handling	Renew (Event)
	Unsubscribe (Event)
	SetSynchronizationPoint (Event)
	CreatePullPointSubscription (Event)
	PullMessage (Event)
	GetEventProperties (Event)
	TopicFilter (Event)
Discovery	WS-Discovery



	GetDiscoveryMode (Device)
	SetDiscoveryMode (Device)
	GetScopes (Device)
	SetScopes (Device)
	AddScopes (Device)
	RemoveScopes (Device)
Network Configuration	GetHostname (Device)
SetHostname (Device)	
GetDNS (Device)	
SetDNS (Device)	
GetNetworkInterfaces (Device)	
SetNetworkInterfaces (Device)	
GetNetworkProtocols (Device)	
SetNetworkProtocols (Device)	
GetNetworkDefaultGateway (Device)	
	SetNetworkDefaultGateway (Device)
System	GetDeviceInformation (Device)
	GetSystemDateAndTime (Device)
	SetSystemDateAndTime (Device)
	SetSystemFactoryDefault (Device)
	Reboot (Device)
User Handling	GetUsers (Device)
	CreateUsers (Device)



	DeleteUsers (Device)
	SetUser (Device)
Profile Conditional Features	
Reset Antipassback Violations	ResetAntipassbackViolation (Credential)
	tns1:Credential/State/ApbViolation
Special Days Schedule	GetSpecialDayGroups (Schedule)
	GetSpecialDayGroupList (Schedule)
	GetSpecialDayGroupInfo (Schedule)
	GetSpecialDayGroupInfoList (Schedule)
	CreateSpecialDayGroup (Schedule)
	ModifySpecialDayGroup (Schedule)
	DeleteSpecialDayGroup (Schedule)
	tns1:Configuration/SpecialDays/Changed
	tns1:Configuration/SpecialDays/Removed
Persistent notification storage	Seek (Event)
IP Filtering	GetIPAddressFilter (Device)
	SetIPAddressFilter (Device)
	AddIPAddressFilter (Device)
	RemoveIPAddressFilter (Device)



7.2 Profile A support check

Preliminary checking for feature discovery will be performed prior to the test execution. For the details of the preliminary feature discovery, refer to [ONVIF Feature Discovery].

According to the result of test case execution, final determination of [ONVIF Profile A] support toward DUT is performed based on the following procedure.

Procedure:

1. Check that scope list contains the scope given in Table 9. If there is no such scope in the scope list of the DUT, then it is determined that [ONVIF Profile A] is not supported.
2. Check Discovery Types support. If **Discovery/Types/tds:Device** is not supported by the DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed.
3. Check Security feature category:
 - a. Check that HTTP Digest Authentication is supported by the DUT. If **Security\Digest** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that HTTP Digest Authentication feature is supported by DUT.
4. Check Capabilities feature category:
 - a. Check that GetServices command is supported by the DUT. If **Device Service/Capabilities/GetServices** is not supported by the DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that Capabilities category is supported with the following features included:
 - GetServices (Device Management Service)
 - GetServiceCapabilities (Device Management Service)
 - GetServiceCapabilities (Event Service)
 - b. The following features are defined as supported, because this is a mandatory feature for any of ONVIF device implementation:
 - GetWsdUrl (Device)
 - c. Check that at least two PullPoint subscriptions are supported by the DUT. If **Event Service/Event/MaxPullPoint** is not supported by the DUT or it has value less than two, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that Event Handling feature category is supported with the following feature included:
 - At least two PullPoint subscriptions
5. Check Access Rules Service related features:
 - a. Check that Access Rules Service is supported by DUT. If **Access Rules Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that Access Rules Service related features are supported by DUT. Those features are:



- i. Capabilities feature category:
 - GetServiceCapabilities (Access Rules)
- ii. Access Profiles feature category:
 - GetAccessProfiles (Access Rules)
 - GetAccessProfileList (Access Rules)
 - GetAccessProfileInfo (Access Rules)
 - GetAccessProfileInfoList (Access Rules)
 - CreateAccessProfile (Access Rules)
 - ModifyAccessProfile (Access Rules)
 - DeleteAccessProfile (Access Rules)
 - tns1:Configuration/AccessProfile/Changed
 - tns1:Configuration/AccessProfile/Removed

6. Check Credential Service related features:

- a. Check that Credential Service is supported by DUT. If **Credential Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that Credential Service related features are supported by DUT. Those features are:

- i. Capabilities feature category:
 - GetServiceCapabilities (Credential)
- ii. Credentials feature category:
 - GetCredentials (Credential)
 - GetCredentialList (Credential)
 - GetCredentialInfo (Credential)
 - GetCredentialInfoList (Credential)
 - CreateCredential (Credential)
 - ModifyCredential (Credential)
 - DeleteCredential (Credential)
 - GetCredentialAccessProfiles (Credential)
 - SetCredentialAccessProfiles (Credential)
 - DeleteCredentialAccessProfiles (Credential)
 - GetCredentialIdentifiers (Credential)



- SetCredentialIdentifier (Credential)
 - DeleteCredentialIdentifier (Credential)
 - EnableCredential (Credential)
 - DisableCredential (Credential)
 - GetCredentialState (Credential)
 - GetSupportedFormatTypes (Credential)
 - tns1:Configuration/Credential/Changed
 - tns1:Configuration/Credential/Removed
- b. Check that Reset Antipassback Violations feature category is supported by the DUT. If **Credential Service\Reset Antipassback Violation** is regarded as supported by DUT, it is determined that Reset Antipassback Violations feature category are supported by DUT. The following features are defined as supported:
- ResetAntipassbackViolation (Credential)
 - tns1:Credential/State/ApbViolation

7. Check Schedule Service related features:

- a. Check that Schedule Service is supported by DUT. If **Schedule Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that Schedule Service related features are supported by DUT. Those features are:
- i. Capabilities feature category:
 - GetServiceCapabilities (Schedule)
 - ii. Schedules feature category:
 - GetSchedules (Schedule)
 - GetScheduleList (Schedule)
 - GetScheduleInfo (Schedule)
 - GetScheduleInfoList (Schedule)
 - CreateSchedule (Schedule)
 - ModifySchedule (Schedule)
 - DeleteSchedule (Schedule)
 - tns1:Configuration/Schedule/Changed
 - tns1:Configuration/ Schedule /Removed
- b. Check that GetScheduleState (Schedule) feature and tns1:Schedule/State/Active feature are supported by the DUT. If **Schedule Service\State Reporting** is regarded as supported by DUT, it is determined that the following features are defined as



supported:

- iii. GetScheduleState (Schedule)
 - iv. tns1:Schedule/State/Active
- c. Check that Special Days Schedule feature category is supported by the DUT. If **Schedule Service\Special Days** is regarded as supported by DUT, it is determined that Special Days Schedule feature category are supported by DUT. The following features are defined as supported:
- GetSpecialDayGroups (Schedule)
 - GetSpecialDayGroupList (Schedule)
 - GetSpecialDayGroupInfo (Schedule)
 - GetSpecialDayGroupInfoList (Schedule)
 - CreateSpecialDayGroup (Schedule)
 - ModifySpecialDayGroup (Schedule)
 - DeleteSpecialDayGroup (Schedule)
 - tns1:Configuration/SpecialDays/Changed
 - tns1:Configuration/SpecialDays/Removed
8. Check Discovery feature category of ONVIF profile support. This is a mandatory feature for any of ONVIF device implementation. The following features are defined as supported:
- WS-Discovery
 - GetDiscoveryMode (Device Management Service)
 - SetDiscoveryMode (Device Management Service)
 - GetScopes (Device Management Service)
 - SetScopes (Device Management Service)
 - AddScopes (Device Management Service)
 - RemoveScopes (Device Management Service)
9. Check Network Configuration feature category of ONVIF profile support. This is mandatory a feature for any of ONVIF device implementation. The following features are defined as supported:
- GetHostname (Device Management Service)
 - SetHostname (Device Management Service)
 - GetDNS (Device Management Service)
 - SetDNS (Device Management Service)
 - GetNetworkInterfaces (Device Management Service)



- SetNetworkInterfaces (Device Management Service)
 - GetNetworkProtocols (Device Management Service)
 - SetNetworkProtocols (Device Management Service)
 - GetNetworkDefaultGateway (Device Management Service)
 - SetNetworkDefaultGateway (Device Management Service)
10. Check System feature category of ONVIF profile support. This feature is mandatory for any of ONVIF device implementation. The following features are defined as supported:
- GetDeviceInformation (Device Management Service)
 - GetSystemDateAndTime (Device Management Service)
 - SetSystemDateAndTime (Device Management Service)
 - SetSystemFactoryDefault (Device Management Service)
 - Reboot (Device Management Service)
11. Check User Handling feature category of ONVIF profile support. This is a mandatory feature for any of ONVIF device implementation. The following features are defined as supported:
- GetUsers (Device Management Service)
 - CreateUsers (Device Management Service)
 - DeleteUsers (Device Management Service)
 - SetUser (Device Management Service)
12. Check Event Handling feature category of ONVIF profile support. This is a mandatory feature for any of ONVIF device implementation. The following features are defined as supported:
- Notify (Event Service)
 - Subscribe (Event Service)
 - Renew (Event Service)
 - Unsubscribe (Event Service)
 - SetSynchronizationPoint (Event Service)
 - CreatePullPointSubscription (Event Service)
 - PullMessage (Event Service)
 - GetEventProperties (Event Service)
 - TopicFilter (Event Service)
13. Check Persistent notification storage feature category of ONVIF profile support. If **Event Service\Persistent notification storage** is regarded as supported by DUT, then it is



determined that Persistent notification storage feature category feature category is supported by DUT. The following features are defined as supported:

- Seek (Event)

14. Check IP Filtering of ONVIF profile support. If **Device Service\Network\IP Filter** is regarded as supported by DUT, then it is determined that IP Filtering feature category is supported by DUT. The following features are defined as supported:

- GetIPAddressFilter (Device)
- SetIPAddressFilter (Device)
- AddIPAddressFilter (Device)
- RemoveIPAddressFilter (Device)