

ONVIF®

Profiles Conformance Device Test Specification

Version 26.06

June 2026

© 2026 ONVIF, Inc. All rights reserved.

Recipients of this document may copy, distribute, publish, or display this document so long as this copyright notice, license and disclaimer are retained with all copies of the document. No license is granted to modify this document.

THIS DOCUMENT IS PROVIDED "AS IS," AND THE CORPORATION AND ITS MEMBERS AND THEIR AFFILIATES, MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THIS DOCUMENT ARE SUITABLE FOR ANY PURPOSE; OR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

IN NO EVENT WILL THE CORPORATION OR ITS MEMBERS OR THEIR AFFILIATES BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES, ARISING OUT OF OR RELATING TO ANY USE OR DISTRIBUTION OF THIS DOCUMENT, WHETHER OR NOT (1) THE CORPORATION, MEMBERS OR THEIR AFFILIATES HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, OR (2) SUCH DAMAGES WERE REASONABLY FORESEEABLE, AND ARISING OUT OF OR RELATING TO ANY USE OR DISTRIBUTION OF THIS DOCUMENT. THE FOREGOING DISCLAIMER AND LIMITATION ON LIABILITY DO NOT APPLY TO, INVALIDATE, OR LIMIT REPRESENTATIONS AND WARRANTIES MADE BY THE MEMBERS AND THEIR RESPECTIVE AFFILIATES TO THE CORPORATION AND OTHER MEMBERS IN CERTAIN WRITTEN POLICIES OF THE CORPORATION.

REVISION HISTORY

Vers.	Date	Description
17.01	Jan, 2017	First issue
17.12	Jul 24, 2017	Check Replay Service related features in Profile G support check section was updated according to #1377.
17.12	Aug 29, 2017	The document formatting were updated.
17.12	Oct 19, 2017	Profile T Conformance section added according to #1450.
18.06	Jan 26, 2018	Profile T Conformance section updated according to #1567 (GetRelayOutputOptions check added).
18.06	Mar, 2018	Note added into Profile Q testing preparation section according to #1584.
18.06	May 24, 2018	Profile T Conformance section updated according to #1618 (Message Content Filter Dialect check added).
18.06	Jun 21, 2018	Reformatting document using new template
18.12	Nov 16, 2018	The following were updated in the scope of #1653: "Advanced Security" was replaced with "Security Configuration" in many places
19.12	Oct 08, 2019	Profile T support check section was updated in the scope of #1894: Check of Media2 Service\Metadata feature was added into 'Check Metadata Streaming feature category' section
20.06	Mar 12, 2020	Profile T support check section was updated in the scope of #1901: Description was refactored with editorial changes Additional checks for tns1:Media/ConfigurationChanged (Event) and tns1:Media/ProfileChanged (Event) were added
20.06	May 08, 2020	The following were updated in the scope of #1999: Profile S Support Check section (step 8 was updated) Profile G Support Check section (GetServiceCapabilities (Event) was removed from step 2, step 8 was updated, step 9 was moved to step 8) Profile C Support Check section (GetServiceCapabilities (Event) was removed from step 2, step 8 was updated, step 9 was moved to step 8) Profile Q Support Check section (GetServiceCapabilities (Event) was removed from step 3, step 8 was updated) Profile A Support Check section (GetServiceCapabilities (Event) and step c was removed from step 4, step 12 was updated, step 13 was moved to step 12) Profile T Support Check section (step 5 was updated, step 13 was moved to step 12)
20.12	Sep 28, 2020	Check of User Handling was updated in the scope of #2093:

		Profile S Support Check section (step 7 was updated) Profile G Support Check section (step 7 was updated) Profile C Support Check section (step 7 was updated) Profile Q Support Check section (step 6 was updated) Profile A Support Check section (step 11 was updated) Profile T Support Check section (step 4.1.v was updated)
20.12	Sep 29, 2020	The following were updated in the scope of #2088: Profile T Support Check section (Media2 Service functionality check was reorganized. Video Encoder Configuration commands were moved under Video feature.)
20.12	Oct 22, 2020	The following were updated in the scope of #1867: Profile M Support Check section (added)
20.12	Oct 26, 2020	The following were updated in the scope of #1866: Profile C Support Check: Step 11 updated with Access Point Entity check Step 12 updated with Door Entity check Profile A Support Check: Step 6 updated with Credential Entity check
20.12	Nov 10, 2020	The following were updated in the scope of #1866: Profile C Support Check: Check of AccessControl/AccessGranted/Credential was updated Check of AccessControl/Denied/Credential was updated Check of AccessControl/AccessGranted/Anonymous was updated Check of AccessControl/Denied/Anonymous was updated Check of AccessControl/AccessTaken/Credential was updated Check of AccessControl/AccessNotTaken/Credential was updated Check of AccessControl/Request/Credential was updated
21.06	Dec 22, 2020	The following were updated in the scope of #1866: Profile D Support Check section (added)
21.06	Jan 29, 2021	The following were updated in the scope of #2124: Profile M Support Check section (Discovery detection updated) Profile A Support Check section (Check that Discovery is supported added) Profile C Support Check section (Check that Discovery is supported added)

		Profile D Support Check section (Check that Discovery is supported added) Profile G Support Check section (Check that Discovery is supported added) Profile Q Support Check section (Check that Discovery is supported added) Profile S Support Check section (Check that Discovery is supported added) Profile T Support Check section (Check that Discovery is supported added)
21.06	May 13, 2021	The following were updated in the scope of #2032: Access Control events added into Profile D Support Check section (steps 7.5.6 - 7.5.9)
21.06	Jun 07, 2021	Profile M was updated in the scope of #2221: ws and wss protocols of MQTT changed from mandatory to optional (steps 8.3.iv and 8.3.v)
21.12	Dec 15, 2021	Profile Q was removed according to #2204
26.06	Mar 23, 2026	The following were updated/added according #381: Profile V Editorial changes that not affect tests implementation

Table of Contents

1	Introduction	8
1.1	Scope	8
1.2	Normative references	8
1.3	Informative References	9
1.4	Requirement by the Profile	9
2	Terms and Definitions	10
2.1	Definitions	10
2.2	Abbreviations	10
3	Profile S Conformance	11
3.1	Feature category classification for ONVIF Profile S	11
3.2	Profile S Support Check	15
4	Profile G Conformance	20
4.1	Feature category classification for ONVIF Profile G	20
4.2	Profile G Support Check	25
5	Profile C Conformance	36
5.1	Feature category classification for ONVIF Profile C	36
5.2	Profile C Support Check	39
6	Profile A Conformance	49
6.1	Feature category classification for ONVIF Profile A	49
6.2	Profile A Support Check	52
7	Profile T Conformance	60
7.1	Feature category classification for ONVIF Profile T	60
7.2	Profile T Support Check	68
8	Profile M Conformance	94
8.1	Feature category classification for ONVIF Profile M	94
8.2	Profile M Support Check	98
9	Profile D Conformance	112
9.1	Feature Category Classification for ONVIF Profile D	112
9.2	Profile D Support Check	116
10	Profile V Conformance	133

10.1	Feature category classification for ONVIF Profile V	133
10.2	Profile V Support Check	138

1 Introduction

The goal of the ONVIF Profiles Conformance Test Specification document is to provide some details about logic of profiles' supporting check.

Profile S Conformance item focuses on ONVIF Profile S specification ([ONVIF Profile S]) as a referenced Profile by an ONVIF device implementation under test.

Profile G Conformance item focuses on ONVIF Profile G specification ([ONVIF Profile G]) as a referenced Profile by an ONVIF device implementation under test.

Profile C Conformance item focuses on ONVIF Profile C specification ([ONVIF Profile C]) as a referenced Profile by an ONVIF device implementation under test.

Profile A Conformance item focuses on ONVIF Profile A specification ([ONVIF Profile A]) as a referenced Profile by an ONVIF device implementation under test.

Profile T Conformance item focuses on ONVIF Profile T specification ([ONVIF Profile T]) as a referenced Profile by an ONVIF device implementation under test.

Profile M Conformance item focuses on ONVIF Profile M specification ([ONVIF Profile M]) as a referenced Profile by an ONVIF device implementation under test.

Profile D Conformance item focuses on ONVIF Profile D specification ([ONVIF Profile D]) as a referenced Profile by an ONVIF device implementation under test.

Profile V Conformance item focuses on ONVIF Profile V specification ([ONVIF Profile V]) as a referenced Profile by an ONVIF device implementation under test.

1.1 Scope

This ONVIF Profiles Conformance Test Specification document defines and regulates the conformance testing procedure for the ONVIF conformant devices. The objective of this specification is to provide the logic of ONVIF Profiles detection according to ONVIF Profile S Specification, ONVIF Profile G Specification, ONVIF Profile C Specification, ONVIF Profile A Specification, and ONVIF Profile V Specification.

1.2 Normative references

- [ONVIF Network Interface Specs] ONVIF Network Interface Specification documents:
<https://www.onvif.org/profiles/specifications/>
- [ONVIF Conformance] ONVIF Conformance Process Specification:

<https://www.onvif.org/profiles/conformance/>

1.3 Informative References

- [ONVIF Feature Discovery] ONVIF Feature Discovery Specification:

<http://www.onvif.org/Documents/Specifications.aspx>

1.4 Requirement by the Profile

The following define denotations to indicate the required level by the Profile towards ONVIF device implementation (DUT).

M = mandatory function that shall be SUPPORTED by DUT

C = conditional mandatory function that shall be SUPPORTED by DUT if they support that functionality. On the list of test cases such functionalities are described after C - the content of parenthesis.

2 Terms and Definitions

2.1 Definitions

Profile See ONVIF Profile Policy.

2.2 Abbreviations

This section describes abbreviations used in this document.

DHCP Dynamic Host Configuration Protocol

DNS Domain Name System

DUT Device Under Test

HTTP Hyper Text Transport Protocol

IP Internet Protocol

IPv4 Internet Protocol version 4

IPv6 Internet Protocol version 6

NTP Network Time Protocol

RTP Real-time Transport Protocol

RTSP Real Time Streaming Protocol

UDP User Datagram Protocol

URI Uniform Resource Identifier

UTC Coordinated Universal Time

3 Profile S Conformance

3.1 Feature category classification for ONVIF Profile S

In order for ONVIF Device Test Tool to conduct conformance testing toward [ONVIF Profile S], it would need to identify whether DUT implements the expected feature set.

This section classifies supported features as multiple categories that are related to [ONVIF Profile S] conformance. Those category classifications will be used to do some preliminary checking prior to the test case execution and also they will be used to determine whether DUT can be considered to be [ONVIF Profile S] conformant device.

The following discovery scope is defined as the scope that signals that DUT is [ONVIF Profile S] product.

Table 3.1. Profile S Discovery Scope

onvif://www.onvif.org/Profile/Streaming

The following table shows the classified feature categories based on commands and/or functional blocks that are referenced by DUT.

Table 3.2. Profile S Features Categories

Media Streaming	GetStreamUri
	SetSynchronizationPoint
	Media Streaming RTSP
	Media Streaming RTSP (JPEG RTP Header Extension)
Video Encoder Configuration	GetVideoEncoderConfiguration
	GetVideoEncoderConfigurations
	AddVideoEncoderConfiguration
	RemoveVideoEncoderConfiguration
	SetVideoEncoderConfiguration
	GetCompatibleVideoEncoderConfigurations
	GetVideoEncoderConfigurationOptions
	GetGuaranteedNumberOfVideoEncoderInstances
User Authentication	WS-UsernameToken Authentication
	HTTP Digest Authentication

Capabilities	GetCapabilities
	GetWsdlUrl
PTZ	AddPTZConfiguration
	RemovePTZConfiguration
	GetNodes
	GetNode
	GetConfigurations
	GetConfiguration
	GetConfigurationOptions
	SetConfiguration
	ContinuousMove
	Stop
	GetStatus
PTZ - Absolute Positioning	AbsoluteMove
PTZ - Relative Positioning	RelativeMove
PTZ - Presets	SetPreset
	GetPresets
	GotoPreset
	RemovePreset
PTZ - Home Position	GotoHomePosition
	SetHomePosition
PTZ - Auxiliary	Command SendAuxiliaryCommand
Audio Streaming	GetAudioSources
	GetAudioSourceConfiguration
	GetAudioSourceConfigurations
	AddAudioSourceConfiguration
	RemoveAudioSourceConfiguration
	SetAudioSourceConfiguration
	GetCompatibleAudioSourceConfigurations
	GetAudioSourceConfigurationOptions
	GetAudioEncoderConfiguration
	GetAudioEncoderConfigurations
	AddAudioEncoderConfiguration

	RemoveAudioEncoderConfiguration
	SetAudioEncoderConfiguration
	GetCompatibleAudioEncoderConfigurations
	GetAudioEncoderConfigurationOptions
Media Streaming - Multicast	StartMulticastStreaming
	StopMulticastStreaming
Relay Outputs	GetRelayOutputs
	SetRelayOutputSettings
	SetRelayOutputState
NTP	GetNTP
	SetNTP
Dynamic DNS	GetDynamicDNS
	SetDynamicDNS
Zero Configuration	GetZeroConfiguration
	SetZeroConfiguration
IP Address Filtering	GetIPAddressFilter
	SetIPAddressFilter
	AddIPAddressFilter
	RemoveIPAddressFilter
Discovery	WS-Discovery
	GetDiscoveryMode
	SetDiscoveryMode
	GetScopes
	SetScopes
	AddScopes
	RemoveScopes
Network Configuration	GetHostname
	SetHostname
	GetDNS
	SetDNS
	GetNetworkInterfaces
	SetNetworkInterfaces
	GetNetworkProtocols

	SetNetworkProtocols
	GetNetworkDefaultGateway
	SetNetworkDefaultGateway
System	GetDeviceInformation
	GetSystemDateAndTime
	SetSystemDateAndTime
	SetSystemFactoryDefault
	Reboot
User Handling	GetUsers
	CreateUsers
	DeleteUsers
	SetUser
Event Handling	Notify
	Subscribe
	Renew
	Unsubscribe
	SetSynchronizationPoint (Event)
	CreatePullPointSubscription
	PullMessage
	GetEventProperties
	TopicFilter
	MessageContentFilter
Media Profile Configuration	GetProfiles
	GetProfile
	CreateProfile
	DeleteProfile
Video Source Configuration	GetVideoSources
	GetVideoSourceConfiguration
	GetVideoSourceConfigurations
	AddVideoSourceConfiguration
	RemoveVideoSourceConfiguration
	SetVideoSourceConfiguration
	GetCompatibleVideoSourceConfigurations

	GetVideoSourceConfigurationOptions
Metadata Configuration	GetMetadataConfiguration
	GetMetadataConfigurations
	AddMetadataConfiguration
	RemoveMetadataConfiguration
	SetMetadataConfiguration
	GetCompatibleMetadataConfigurations
	GetMetadataConfigurationOptions

3.2 Profile S Support Check

Preliminary checking for feature discovery will be performed prior to the test execution. For the details of the preliminary feature discovery, refer to [ONVIF Feature Discovery].

According to the result of test case execution, final determination of [ONVIF Profile S] support toward DUT is performed based on the following procedure.

Procedure:

1. Check that scope list contains the scope given in [Table 3.1](#). If there is no such scope in the scope list of the DUT, then it is determined that [ONVIF Profile S] is not supported.
2. Check Capabilities feature.
 - a. Check that GetCapabilities command is supported by the DUT. If GetCapabilities is not supported by the DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that Capabilities category is supported.
3. Check Discovery feature. If **Discovery** feature is regarded as unsupported, then it is determined that [ONVIF Profile S] is not supported by DUT and certification will be failed.
4. Check Discovery Types support. If Discovery/Types/dn:NetworkVideoTransmitter feature is not supported by the DUT, then it is determined that [ONVIF Profile S] is not supported by DUT and certification will be failed.
5. Check that **Device Service/System/Network Configuration** is supported by the DUT. If **Device Service/System/Network Configuration** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by the DUT and certification will be failed.
6. Check System feature of ONVIF profile support. If System feature is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. This feature is mandatory for any of ONVIF device implementation.

7. Check that **Device Service/System/User Handling** is supported by the DUT. If **Device Service/System/User Handling** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. User Handling feature category:
 - GetUsers (Device Management)
 - CreateUsers (Device Management)
 - DeleteUsers (Device Management)
 - SetUser (Device Management)
8. Check Event Handling feature. of ONVIF profile support. If Event Handling feature is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. This is a mandatory feature for any of ONVIF device implementation.
 - a. Check that Event Service is supported by DUT. If Event Service is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that Event Handling feature category is supported by DUT.
 - b. Check that WS-BasicNotification is supported by the DUT. If WS-BasicNotification is not supported by the DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that WS-BasicNotification is supported.
 - c. Check that Pull-Point Notification is supported by the DUT. If Pull-Point Notification is not supported by the DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that Pull-Point Notification is supported.
9. Check NTP feature.
 - a. Check that NTP is supported by the DUT. If NTP is regarded as supported, then it is determined that NTP feature category is supported by DUT.
10. Check Dynamic DNS feature.
 - a. Check that Dynamic DNS is supported by the DUT. If Dynamic DNS is regarded as supported, then Dynamic DNS feature category is supported by DUT.
11. Check Zero Configuration feature.

- a. Check that Zero Configuration is supported by the DUT. If Zero Configuration is regarded as supported by DUT, then it is determined that Zero Configuration feature category is supported by DUT.

12. Check IP Address Filtering feature.

- a. Check that IP Address Filter is supported by the DUT. If IP Address Filter is regarded as supported, then it is determined that IP Address Filtering feature category is supported by DUT.

13. Check User Authentication feature.

- a. Check that WS-UsernameToken Authentication is supported by the DUT. If WS-UsernameToken is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that WS-UsernameToken Authentication feature is supported by DUT.
- b. Check that HTTP Digest Authentication is supported by the DUT.

14. Check Media Profile Configuration feature.

- a. Check that Media Service is supported by DUT. If Media Service is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that Media Profile Configuration feature category is supported by DUT.

15. Check Media Streaming feature of ONVIF profile support.

- a. Check that Real-time Streaming is supported by DUT. If Real-time Streaming is regarded unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that Media Streaming feature category is supported by DUT.

16. Check Video Source Configuration feature of ONVIF profile support.

- a. Check that Media Service is supported by DUT. If Media Service is regarded unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that Video Source Configuration feature category is supported by DUT.

17. Check Video Encoder Configuration feature.

- a. Check that Media Service is supported by the DUT. If Media Service is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that Video Encoder Configuration feature category is supported by DUT.

18. Check Metadata Configuration feature.

- a. Check that Media Service is supported by the DUT. If Media Service is regarded as unsupported by DUT, then it is determined that [ONVIF Profile S] is not supported by DUT. Otherwise, it is determined that Metadata Configuration feature category is supported by DUT.

19. Check Media Streaming - Multicast feature.

- a. Check that RTP-Multicast/UDP is supported by the DUT. If RTP-Multicast/UDP is regarded as supported, then it is determined that Media Streaming - Multicast feature category is supported by DUT.

20. Check PTZ feature.

- a. Check that PTZ Service and Preset position are supported by DUT. If PTZ Service and Preset position are regarded as supported then, it is determined that PTZ - Presets feature category is supported by DUT.

21. Check PTZ - Home Position feature.

- a. Check that PTZ Service and Home Position are supported by DUT. If PTZ Service and Home Position are regarded as supported, then it is determined that PTZ - Home Position feature category is supported by DUT.

22. Check PTZ - Absolute Positioning feature.

- a. Check that PTZ Service and Absolute Move are supported by DUT. If PTZ Service and Absolute Move are regarded as supported, then it is determined that PTZ - Absolute Positioning feature category is supported by DUT.

23. Check PTZ - Relative Positioning feature.

- a. Check that PTZ Service and Relative Move are supported by the DUT. If PTZ Service and Relative Move are regarded as supported, then it is determined that PTZ - Relative Positioning feature category is supported by DUT.

24. Check PTZ - Auxiliary Commands feature.

- a. Check that PTZ Service and Auxiliary Commands are supported by DUT. If PTZ Service and Auxiliary Commands are regarded as supported, then it is determined that PTZ - Auxiliary Commands feature category is supported by DUT.

25. Check Audio Streaming feature.

- a. Check that Audio feature is supported by DUT. If Audio feature is regarded as supported, then it is determined that Audio Streaming feature category is supported by DUT.

26. Check Relay Outputs feature.

- a. Check that Relay Outputs from Device Service are supported by the DUT. If Relay Outputs are regarded as supported, then it is determined that Relay Outputs feature category is supported by DUT.

4 Profile G Conformance

4.1 Feature category classification for ONVIF Profile G

In order for ONVIF Device Test Tool to conduct conformance testing toward [ONVIF Profile G], it would need to identify whether DUT implements the expected feature set.

This section classifies supported features as multiple categories that are related to [ONVIF Profile G] conformance. Those category classifications will be used to do some preliminary checking prior to the test case execution and also they will be used to determine whether DUT can be considered to be [ONVIF Profile G] conformant device.

The following discovery scope is defined as the scope that signals that DUT is [ONVIF Profile G] product.

Table 4.1. Profile G Discovery Scope

onvif://www.onvif.org/Profile/G

The following table shows the classified feature categories based on commands and/or functional blocks that are referenced by DUT.

Table 4.2. Profile G Features Categories

Profile Mandatory Features	
Security	HTTP Digest
Capabilities	GetServices (Device Management)
	GetServiceCapabilities (Device Management)
	GetServiceCapabilities (Recording Control)
	GetServiceCapabilities (Replay)
	GetServiceCapabilities (Recording Search)
	GetServiceCapabilities (Receiver)
	GetServiceCapabilities (Event)
	MaxPullPoint capability is supported and value is not less than 2
	GetServiceCapabilities (Media)
	GetWsdlUrl (Device Management)
Recording Search - Media Search	FindRecordings (Recording Search)
	GetRecordingSearchResults (Recording Search)

	EndSearch (Recording Search)
	FindEvents (Recording Search)
	GetEventSearchResults (Recording Search)
	GetRecordingSummary (Recording Search)
	GetRecordingInformation (Recording Search)
	GetMediaAttributes (Recording Search)
	tns1:RecordingHistory/Track/State
	tns1:RecordingHistory/Recording/State
	XPath dialect filtering
Replay Control	RTP header extension
	“onvif-replay” RTSP feature tag
	Media Replay
	Reverse Replay
	GetReplayUri (Replay)
	SetReplayConfiguration (Replay)
	GetReplayConfiguration (Replay)
	Encodings (JPEG, H.264, or MPEG4)
Profile Conditional Features	
Recording Search - Metadata Search	FindMetadata (Recording Search)
	GetMetadataSearchResults (Recording Search)
Recording Control - Dynamic Recording	Create Recording (Recording Control)
	Delete Recording (Recording Control)
	tns1:RecordingConfig/CreateRecording
	tns1:RecordingConfig/DeleteRecording
	CreateTrack (Recording Control)
	DeleteTrack (Recording Control)
	tns1:RecordingConfig/CreateTrack
	tns1:RecordingConfig/DeleteTrack
Recording Search - PTZ Position Search	FindPTZPosition (Recording Search)
	GetPTZPositionSearchResults (Recording Search)
Device Mandatory Features	
Recording Control	GetRecordings (Recording Control)

	CreateRecordingJob (Recording Control)
	DeleteRecordingJob (Recording Control)
	GetRecordingJobs (Recording Control)
	GetRecordingJobState (Recording Control)
	SetRecordingJobMode (Recording Control)
	GetRecordingOptions (Recording Control)
	tns1:RecordingConfig/JobState
	tns1:RecordingConfig/DeleteTrackData
Recording Control - Using an on-board media source	GetProfiles (Media)
	GetProfile (Media)
	CreateProfile (Media)
	DeleteProfile (Media)
	GetVideoSources (Media)
	GetVideoSourceConfiguration (Media)
	GetVideoSourceConfigurations (Media)
	AddVideoSourceConfiguration (Media)
	RemoveVideoSourceConfiguration (Media)
	SetVideoSourceConfiguration (Media)
	GetCompatibleVideoSourceConfigurations (Media)
	GetVideoSourceConfigurationOptions (Media)
	GetVideoEncoderConfiguration (Media)
	GetVideoEncoderConfigurations (Media)
	AddVideoEncoderConfiguration (Media)
	RemoveVideoEncoderConfiguration (Media)
	SetVideoEncoderConfiguration (Media)
	GetCompatibleVideoEncoderConfigurations (Media)
	GetVideoEncoderConfigurationOptions (Media)
	GetGuaranteedNumberOfVideoEncoderInstances (Media)
	GetMetadataConfiguration (Media)
	GetMetadataConfigurations (Media)

	AddMetadataConfiguration (Media)
	RemoveMetadataConfiguration (Media)
	SetMetadataConfiguration (Media)
	GetCompatibleMetadataConfigurations (Media)
	GetMetadataConfigurationOptions (Media)
	GetAudioSources (Media)
	GetAudioSourceConfiguration (Media)
	GetAudioSourceConfigurations (Media)
	AddAudioSourceConfiguration (Media)
	RemoveAudioSourceConfiguration (Media)
	SetAudioSourceConfiguration (Media)
	GetCompatibleAudioSourceConfigurations (Media)
	GetAudioSourceConfigurationOptions (Media)
	GetAudioEncoderConfiguration (Media)
	GetAudioEncoderConfigurations (Media)
	AddAudioEncoderConfiguration (Media)
	RemoveAudioEncoderConfiguration (Media)
	SetAudioEncoderConfiguration (Media)
	GetCompatibleAudioEncoderConfigurations (Media)
	GetAudioEncoderConfigurationOptions (Media)
Recording Control - Using a Receiver as Source	GetReceivers (Receiver)
	GetReceiver (Receiver)
	CreateReceiver (Receiver)
	DeleteReceiver (Receiver)
	ConfigureReceiver (Receiver)
	SetReceiverMode (Receiver)
	GetReceiverState (Receiver)
	tns1:Receiver/ChangeState
	tns1:Receiver/ConnectionFailed
	Media Streaming using RTSP
Recording Configuration/Configuration of the Recording Source	SetRecordingConfiguration (Recording Control)

	GetRecordingConfiguration (Recording Control)
	GetTrackConfiguration (Recording Control)
	SetTrackConfiguration (Recording Control)
	SetRecordingJobConfiguration (Recording Control)
	GetRecordingJobConfiguration (Recording Control)
	tns1:RecordingConfig/RecordingConfiguration
	tns1:RecordingConfig/TrackConfiguration
	tns1:RecordingConfig/ RecordingJobConfiguration
Discovery	WS-Discovery
	GetDiscoveryMode (Device Management)
	SetDiscoveryMode (Device Management)
	GetScopes (Device Management)
	SetScopes (Device Management)
	AddScopes (Device Management)
	RemoveScopes (Device Management)
Network Configuration	GetHostname (Device Management)
	SetHostname (Device Management)
	GetDNS (Device Management)
	SetDNS (Device Management)
	GetNetworkInterfaces (Device Management)
	SetNetworkInterfaces (Device Management)
	GetNetworkProtocols (Device Management)
	SetNetworkProtocols (Device Management)
	GetNetworkDefaultGateway (Device Management)
	SetNetworkDefaultGateway (Device Management)
System	GetDeviceInformation (Device Management)
	GetSystemDateAndTime (Device Management)
	SetSystemDateAndTime (Device Management)
	SetSystemFactoryDefault (Device Management)

	Reboot (Device Management)
User Handling	GetUsers (Device Management)
	CreateUsers (Device Management)
	DeleteUsers (Device Management)
	SetUser (Device Management)
Event Handling	SetSynchronizationPoint (Event)
	CreatePullPointSubscription (Event)
	PullMessage (Event)
	GetEventProperties (Event)
	Renew (Event)
	Unsubscribe (Event)
	TopicFilter (Event)
	MessageContentFilter
	At least two PullPoint subscriptions

4.2 Profile G Support Check

Preliminary checking for feature discovery will be performed prior to the test execution. For the details of the preliminary feature discovery, refer to [ONVIF Feature Discovery].

According to the result of test case execution, final determination of [ONVIF Profile G] support toward DUT is performed based on the following procedure.

Procedure:

1. Check that scope list contains the scope given in [Table 4.2](#). If there is no such scope in the scope list of the DUT, then it is determined that [ONVIF Profile G] is not supported.
2. Check Capabilities feature.
 - a. Check that GetServices command is supported by the DUT. If **Device Service/Capabilities/GetServices** is not supported by the DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that Capabilities category is supported with the following features included:
 - i. GetServices (Device Management)
 - ii. GetServiceCapabilities (Device Management)
3. Check that Discovery is supported by the DUT. If **Discovery** feature is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile G] is not supported by the

DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

- WS-Discovery
 - GetDiscoveryMode (Device Management)
 - SetDiscoveryMode (Device Management)
 - GetScopes (Device Management)
 - SetScopes (Device Management)
 - AddScopes (Device Management)
 - RemoveScopes (Device Management)
4. Check Discovery Types support. If **Discovery/Types/tds:Device** is not supported by the DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed.
5. Check that **Device Service/System/Network Configuration** is supported by the DUT. If **Device Service/System/Network Configuration** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- GetHostname (Device Management)
 - SetHostname (Device Management)
 - GetDNS (Device Management)
 - SetDNS (Device Management)
 - GetNetworkInterfaces (Device Management)
 - SetNetworkInterfaces (Device Management)
 - GetNetworkProtocols (Device Management)
 - SetNetworkProtocols (Device Management)
 - GetNetworkDefaultGateway (Device Management)
 - SetNetworkDefaultGateway (Device Management)
6. Check System feature category of ONVIF profile support. This feature is a mandatory for any of ONVIF device implementation. The following features are defined as supported:

- GetDeviceInformation (Device Management)
 - GetSystemDateAndTime (Device Management)
 - SetSystemDateAndTime (Device Management)
 - SetSystemFactoryDefault (Device Management)
 - Reboot (Device Management)
7. Check that **Device Service/System/User Handling** is supported by the DUT. If **Device Service/System/User Handling** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- i. User Handling feature category:
 - GetUsers (Device Management)
 - CreateUsers (Device Management)
 - DeleteUsers (Device Management)
 - SetUser (Device Management)
8. Check Event Handling feature category.
- a. Check that Event Service is supported by DUT. If **Event Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that Event Handling features is supported by DUT. The following features are defined as supported:
 - i. Capabilities feature category
 - GetServiceCapabilities (Event)
 - ii. Event Handling feature category
 - GetEventProperties (Event)
 - b. Check that Pull-Point Notification is supported by DUT. If **Event Service/Pull-Point Notification** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are defined as supported:
 - i. Event Handling feature category

- Renew (Event)
 - Unsubscribe (Event)
 - SetSynchronizationPoint (Event)
 - CreatePullPointSubscription (Event)
 - PullMessage (Event)
 - TopicFilter (Event)
 - MessageContentFilter (Event)
- c. Check that at least two PullPoint subscriptions are supported by the DUT. If **Event Service/GetServiceCapabilities/MaxPullPoints capability** is not supported by the DUT or it has value less than 2, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that Event Handling is supported with the following feature category included:
- a. At least two PullPoint subscriptions
9. Check Security feature category.
- a. Check that HTTP Digest Authentication is supported by the DUT. If Security\Digest is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that HTTP Digest Authentication feature is supported by DUT.
10. Check Recording Search Service related features.
- a. Check that Recording Search Service is supported by DUT. If **Recording Search Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that Recording Search related features are supported by DUT. Those features are:
 - i. Capabilities feature category
 - GetServiceCapabilities (Recording Search)
 - ii. Recording Control
 - FindRecordings (Recording Search)
 - GetRecordingSearchResults (Recording Search)

- EndSearch (Recording Search)
 - FindEvents (Recording Search)
 - GetEventSearchResults (Recording Search)
 - GetRecordingSummary (Recording Search)
 - GetRecordingInformation (Recording Search)
 - GetMediaAttributes (Recording Search)
 - tns1:RecordingHistory/Track/State
 - tns1:RecordingHistory/Recording/State
 - XPath dialect filtering
- b. Check that Recording Search - Metadata Search feature category is supported by the DUT. If **Recording Search Service\Metadata Search** is regarded as supported by DUT, then it is determined that the following features are supported by the DUT:
- FindMetadata (Recording Search)
 - GetMetadataSearchResults (Recording Search)
- c. Check that Recording Search - PTZ Position Search feature category is supported by the DUT. If **Recording Search Service\PTZ Position Search** is regarded as supported by DUT, then it is determined that the following features are supported by the DUT:
- FindPTZPosition (Recording Search)
 - GetPTZPositionSearchResults (Recording Search)
11. Check Replay Service related features.
- a. Check that Replay Service is supported by DUT. If **Replay Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that Replay related features are supported by DUT. Those features are:
- i. Capabilities feature category
 - GetServiceCapabilities (Replay)
 - ii. Replay Control

- RTP header extension
 - “onvif-replay” RTSP feature tag
 - Media Replay
 - GetReplayUri (Replay)
 - SetReplayConfiguration (Replay)
 - GetReplayConfiguration (Replay)
- b. Check that at least one from **Recording Control Service\Encoding\JPEG**, **Recording Control Service\Encoding\H.264**, and **Recording Control Service\Encoding\MPEG4** features is supported by DUT. If **Recording Control Service\Encoding\JPEG**, **Recording Control Service\Encoding\H.264**, and **Recording Control Service\Encoding\MPEG4** features are regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Those features are:
- i. Replay Control
 - Encodings (JPEG, H.264, or MPEG4)
- c. Check that Reverse Replay feature is supported by the DUT. If **Replay Service\Reverse Replay** is regarded as supported by DUT, then it is determined that Reverse Replay feature is supported by the DUT:
- i. Replay Control
 - Reverse Replay
12. Check Recording Control Service related features.
- a. Check that Recording Service is supported by DUT. If **Recording Control Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that Recording control related features are supported by DUT. Those features are:
- i. Capabilities feature category
 - GetServiceCapabilities (Recording Control)
 - ii. Recording Control
 - GetRecordings (Recording Control)

- CreateRecordingJob (Recording Control)
 - DeleteRecordingJob (Recording Control)
 - GetRecordingJobs (Recording Control)
 - GetRecordingJobState (Recording Control)
 - SetRecordingJobMode (Recording Control)
 - GetRecordingOptions (Recording Control)
 - tns1:RecordingConfig/JobState
- iii. Recording Configuration/Configuration of the Recording Source
- SetRecordingConfiguration (Recording Control)
 - GetRecordingConfiguration (Recording Control)
 - GetTrackConfiguration (Recording Control)
 - SetRecordingJobConfiguration (Recording Control)
 - GetRecordingJobConfiguration (Recording Control)
- b. Check that tns1:RecordingConfig/DeleteTrackData event is supported by the DUT. If **Recording Control/Recording Control Events\RecordingConfig/DeleteTrackData** is regarded as supported by DUT, then it is determined that the following feature is supported by the DUT:
- tns1:RecordingConfig/DeleteTrackData
- c. Check that tns1:RecordingConfig/RecordingConfiguration event is supported by the DUT. If **Recording Control/Recording Control Events\RecordingConfig/RecordingConfiguration** is regarded as supported by DUT, then it is determined that the following feature is supported by the DUT:
- tns1:RecordingConfig/RecordingConfiguration
- d. Check that tns1:RecordingConfig/RecordingJobConfiguration event is supported by the DUT. If **Recording Control/Recording Control Events\RecordingConfig/RecordingJobConfiguration** is regarded as supported by DUT, then it is determined that the following feature is supported by the DUT:
- tns1:RecordingConfig/RecordingJobConfiguration

- e. Check that tns1:RecordingConfig/TrackConfiguration event is supported by the DUT. If **Recording Control/Recording Control Events\RecordingConfig/TrackConfiguration** is regarded as supported by DUT, then it is determined that the following feature is supported by the DUT:

- tns1:RecordingConfig/TrackConfiguration

- f. Check that GetRecordingOptions is supported by DUT. If **Recording Control Service/Recording Options** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed. Otherwise, it is determined that GetRecordingOptions is supported by DUT.

13. Check Receiver Service related features.

- a. Check that Receiver Service is supported by DUT. If Receiver Service is regarded as supported by DUT, then it is determined that Receiver related features are supported by DUT. Those features are:

- i. Capabilities feature category

- GetServiceCapabilities (Receiver)

- ii. Recording Control - Using a Receiver as Source

- GetReceivers (Receiver)
- GetReceiver (Receiver)
- CreateReceiver (Receiver)
- DeleteReceiver (Receiver)
- ConfigureReceiver (Receiver)
- SetReceiverMode (Receiver)
- GetReceiverState (Receiver)
- tns1:Receiver/ChangeState
- tns1:Receiver/ConnectionFailed
- Media Streaming using RTSP

14. Check Media Service related features.

- a. Check that Media Service is supported by DUT. If **Media Service** is regarded as supported by DUT, then it is determined that Media related features are supported by DUT. Those features are:
 - i. Capabilities feature category
 - GetServiceCapabilities (Media)
 - ii. Recording Control - Using an on-board media source
 - GetProfiles (Media)
 - GetProfile (Media)
 - CreateProfile (Media)
 - DeleteProfile (Media)
 - GetVideoSourceConfigurations (Media)
 - AddVideoSourceConfiguration (Media)
 - RemoveVideoSourceConfiguration (Media)
 - GetCompatibleVideoSourceConfigurations (Media)
 - GetVideoEncoderConfiguration (Media)
 - GetVideoEncoderConfigurations (Media)
 - AddVideoEncoderConfiguration (Media)
 - RemoveVideoEncoderConfiguration (Media)
 - SetVideoEncoderConfiguration (Media)
 - GetCompatibleVideoEncoderConfigurations (Media)
 - GetVideoEncoderConfigurationOptions (Media)
 - GetGuaranteedNumberOfVideoEncoderInstances (Media)
 - GetMetadataConfiguration (Media)
 - GetMetadataConfigurations (Media)
 - AddMetadataConfiguration (Media)

- RemoveMetadataConfiguration (Media)
 - SetMetadataConfiguration (Media)
 - GetCompatibleMetadataConfigurations (Media)
 - GetMetadataConfigurationOptions (Media)
 - GetVideoSources (Media)
 - GetVideoSourceConfiguration (Media)
 - SetVideoSourceConfiguration (Media)
 - GetVideoSourceConfigurationOptions (Media)
- b. Check that Audio related features are supported by DUT. If **Media Service/Audio** is regarded as supported by DUT, then it is Audio related features related features are supported by DUT. Those features are:
- GetAudioSourceConfigurations (Media)
 - AddAudioSourceConfiguration (Media)
 - RemoveAudioSourceConfiguration (Media)
 - GetCompatibleAudioSourceConfigurations (Media)
 - GetAudioEncoderConfiguration (Media)
 - GetAudioEncoderConfigurations (Media)
 - AddAudioEncoderConfiguration (Media)
 - RemoveAudioEncoderConfiguration (Media)
 - SetAudioEncoderConfiguration (Media)
 - GetCompatibleAudioEncoderConfigurations (Media)
 - GetAudioEncoderConfigurationOptions (Media)
 - GetAudioSources (Media)
 - GetAudioSourceConfiguration (Media)
 - SetAudioSourceConfiguration (Media)

- GetAudioSourceConfigurationOptions (Media)
15. Check that at least one from Recording Control - Using an on-board media source and Recording Control - Using a Receiver as Source is supported by DUT. If both **Media Service** and **Receiver Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile G] is not supported by DUT and certification will be failed.

5 Profile C Conformance

5.1 Feature category classification for ONVIF Profile C

In order for ONVIF Device Test Tool to conduct conformance testing toward [ONVIF Profile C], it would need to identify whether DUT implements the expected feature set.

This section classifies supported features as multiple categories that are related to [ONVIF Profile C] conformance. Those category classifications will be used to do some preliminary checking prior to the test case execution and also they will be used to determine whether DUT can be considered to be [ONVIF Profile C] conformant device.

The following discovery scope is defined as the scope that signals that DUT is [ONVIF Profile C] product.

Table 5.1. Profile C Discovery Scope

onvif://www.onvif.org/Profile/C

The following table shows the classified feature categories based on commands and/or functional blocks that are referenced by DUT.

Table 5.2. Profile C Features Categories

Profile Mandatory Features	
Capabilities	GetServices (Device Management)
	GetServiceCapabilities (Device Management)
	GetServiceCapabilities (Event)
	MaxPullPoint capability is supported and value is not less than 2
	GetServiceCapabilities (Access Control)
	GetServiceCapabilities (Door Control)
	GetWsdlUrl (Device Management)
System component information - Access points	GetAccessPointInfoList (Access Control)
	GetAccessPointInfo (Access Control)
System component information - Doors	GetDoorInfoList (Door Control)
	GetDoorInfo (Door Control)
System component information - Areas	GetAreaInfoList (Access Control)
	GetAreaInfo (Access Control)

Access point state	GetAccessPointState (Access Control)
	tns1:AccessPoint/State/Enabled
Door state	GetDoorState (Door Control)
	tns1:Door/State/DoorMode
	tns1:Door/State/DoorPhysicalState
	tns1:Door/State/LockPhysicalState
	tns1:Door/State/DoubleLockPhysicalState
	tns1:Door/State/DoorAlarm
	tns1:Door/State/DoorTamper
	tns1:Door/State/DoorFault
Door control	AccessDoor (Door Control)
	LockDoor (Door Control)
	UnlockDoor (Door Control)
	DoubleLockDoor (Door Control)
	BlockDoor (Door Control)
	LockDownDoor (Door Control)
	LockDownReleaseDoor (Door Control)
	LockOpenDoor (Door Control)
	LockOpenReleaseDoor (Door Control)
Access control decisions	tns1:AccessControl/AccessGranted/Credential
	tns1:AccessControl/AccessGranted/Anonymous
	tns1:AccessControl/Denied/Credential
	tns1:AccessControl/Denied/Anonymous
	tns1:AccessControl/Denied/CredentialNotFound/ Card
	tns1:AccessControl/AccessTaken/Credential
	tns1:AccessControl/AccessTaken/Anonymous
	tns1:AccessControl/AccessNotTaken/Credential
	tns1:AccessControl/AccessNotTaken/ Anonymous
Event Handling	Renew (Event)
	Unsubscribe (Event)
	SetSynchronizationPoint (Event)

	CreatePullPointSubscription (Event)
	PullMessage (Event)
	GetEventProperties (Event)
	TopicFilter (Event)
Profile Conditional Features	
Configuration change - Access points	tns1:Configuration/AccessPoint/Changed
	tns1:Configuration/AccessPoint/Removed
Configuration change - Doors	tns1:Configuration/Door/Changed
	tns1:Configuration/Door/Removed
Configuration change - Areas	tns1:Configuration/Area/Changed
	tns1:Configuration/Area/Removed
Access Point Control	EnableAccessPoint (Access Control)
	DisableAccessPoint (Access Control)
External authorization	ExternalAuthorization (Access Control)
	tns1:AccessControl/Request/Credential
	tns1:AccessControl/Request/Anonymous
	tns1:AccessControl/Request/Timeout
Duress	tns1:AccessControl/Duress
Persistent notification storage	Seek (Event)
IP Filtering	GetIPAddressFilter (Device Management)
	SetIPAddressFilter (Device Management)
	AddIPAddressFilter (Device Management)
	RemoveIPAddressFilter (Device Management)
Device Mandatory Features	
Discovery	WS-Discovery
	GetDiscoveryMode (Device Management)
	SetDiscoveryMode (Device Management)
	GetScopes (Device Management)
	SetScopes (Device Management)
	AddScopes (Device Management)
	RemoveScopes (Device Management)
Network Configuration	GetHostname (Device Management)
	SetHostname (Device Management)

	GetDNS (Device Management)
	SetDNS (Device Management)
	GetNetworkInterfaces (Device Management)
	SetNetworkInterfaces (Device Management)
	GetNetworkProtocols (Device Management)
	SetNetworkProtocols (Device Management)
	GetNetworkDefaultGateway (Device Management)
	SetNetworkDefaultGateway (Device Management)
System	GetDeviceInformation (Device Management)
	GetSystemDateAndTime (Device Management)
	SetSystemDateAndTime (Device Management)
	SetSystemFactoryDefault (Device Management)
	Reboot (Device Management)
User Handling	GetUsers (Device Management)
	CreateUsers (Device Management)
	DeleteUsers (Device Management)
	SetUser (Device Management)

5.2 Profile C Support Check

Preliminary checking for feature discovery will be performed prior to the test execution. For the details of the preliminary feature discovery, refer to [ONVIF Feature Discovery].

According to the result of test case execution, final determination of [ONVIF Profile C] support toward DUT is performed based on the following procedure.

Procedure:

1. Check that scope list contains the scope given in [Table 5.1](#). If there is no such scope in the scope list of the DUT, then it is determined that [ONVIF Profile C] is not supported.
2. Check Capabilities feature.
 - a. Check that GetServices command is supported by the DUT. If **Device Service/Capabilities/GetServices** is not supported by the DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that Capabilities category is supported with the following features included:

- GetServices (Device Management)
 - GetServiceCapabilities (Device Management)
3. Check that Discovery is supported by the DUT. If **Discovery** feature is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile C] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- WS-Discovery
 - GetDiscoveryMode (Device Management)
 - SetDiscoveryMode (Device Management)
 - GetScopes (Device Management)
 - SetScopes (Device Management)
 - AddScopes (Device Management)
 - RemoveScopes (Device Management)
4. Check Discovery Types support. If **Discovery/Types/tds:Device** is not supported by the DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed.
5. Check that **Device Service/System/Network Configuration** is supported by the DUT. If **Device Service/System/Network Configuration** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- GetHostname (Device Management)
 - SetHostname (Device Management)
 - GetDNS (Device Management)
 - SetDNS (Device Management)
 - GetNetworkInterfaces (Device Management)
 - SetNetworkInterfaces (Device Management)
 - GetNetworkProtocols (Device Management)
 - SetNetworkProtocols (Device Management)

- GetNetworkDefaultGateway (Device Management)
 - SetNetworkDefaultGateway (Device Management)
6. Check System feature category of ONVIF profile support. This feature is mandatory for any of ONVIF device implementation. The following features are defined as supported:
- GetDeviceInformation (Device Management)
 - GetSystemDateAndTime (Device Management)
 - SetSystemDateAndTime (Device Management)
 - SetSystemFactoryDefault (Device Management)
 - Reboot (Device Management)
7. Check that **Device Service/System/User Handling** is supported by the DUT. If **Device Service/System/User Handling** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- i. User Handling feature category:
 - GetUsers (Device Management)
 - CreateUsers (Device Management)
 - DeleteUsers (Device Management)
 - SetUser (Device Management)
8. Check Event Handling feature category.
- a. Check that Event Service is supported by DUT. If **Event Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that Event Handling features is supported by DUT. The following features are defined as supported:
 - i. Capabilities feature category
 - GetServiceCapabilities (Event)
 - ii. Event Handling feature category
 - GetEventProperties (Event)

- b. Check that Pull-Point Notification is supported by DUT. If **Event Service/Pull-Point Notification** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are defined as supported:
 - i. Event Handling feature category
 - Renew (Event)
 - Unsubscribe (Event)
 - SetSynchronizationPoint (Event)
 - CreatePullPointSubscription (Event)
 - PullMessage (Event)
 - TopicFilter (Event)
 - c. Check that at least two PullPoint subscriptions are supported by the DUT. If **Event Service/GetServiceCapabilities/MaxPullPoints capability** is not supported by the DUT or it has value less than 2, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that Event Handling is supported with the following feature category included:
 - a. At least two PullPoint subscriptions
9. Check Security feature category.
- a. Check that HTTP Digest Authentication is supported by the DUT. If **SecurityDigest** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that HTTP Digest Authentication feature is supported by DUT.
10. Check Persistent notification storage feature category of ONVIF profile support. If **Event Service\Persistent notification storage** is regarded as supported by DUT, then it is determined that Store events feature category with Seek (Event) feature is supported by DUT.
11. Check Access Control Service related features.
- a. Check that Access Control Service is supported by DUT. If **Access Control Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that Access Control related features are supported by DUT. Those features are:

- i. Capabilities feature category
 - GetServiceCapabilities (Access Control)
- ii. System component information - Access points feature category
 - GetAccessPointInfoList (Access Control)
 - GetAccessPointInfo (Access Control)
- iii. System component information - Areas feature category
 - GetAreaInfoList (Access Control)
 - GetAreaInfo (Access Control)
- iv. Check that Access Point Entity is supported by DUT. If **Access Control Service/Access Point Entity** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Access point state feature category
 - GetAccessPointState (Access Control)
 - tns1:AccessPoint/State/Enabled
 - v. Check that tns1:AccessControl/AccessGranted/Credential topic is supported by DUT. If **Access Control Service\Access Control Events\AccessControl/AccessGranted/Credential** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Access control decisions
 - tns1:AccessControl/AccessGranted/Credential
 - vi. Check that tns1:AccessControl/Denied/Credential topic is supported by DUT. If **Access Control Service\Access Control Events\AccessControl/Denied/Credential** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Access control decisions

- tns1:AccessControl/Denied/Credential
- b. Check that Access point control feature category is supported by the DUT. If **Access Control Service\Access Point Entity\Enable/Disable Access Point** is regarded as supported by DUT, then it is determined that EnableAccessPoint (Access Control) and DisableAccessPoint (Access Control) features are supported by the DUT.
- c. Check that Anonymous Access feature is supported by the DUT. If **Access Control Service\Access Point Entity\Anonymous Access** is regarded as supported by DUT
1. Check that tns1:AccessControl/AccessGranted/Anonymous feature is supported by the DUT. If **Access Control Service\Access Control Events\AccessControl/AccessGranted/Anonymous** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Access control decisions
 - tns1:AccessControl/AccessGranted/Anonymous
 2. Check that tns1:AccessControl/Denied/Anonymous feature is supported by the DUT. If **Access Control Service\Access Control Events\AccessControl/Denied/Anonymous** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Access control decisions
 - tns1:AccessControl/Denied/Anonymous
- d. Check that Access Taken feature is supported by the DUT. If **Access Control Service\Access Point Entity\Access Taken** is regarded as supported by DUT
1. Check that tns1:AccessControl/AccessTaken/Credential feature is supported by the DUT. If **Access Control Service\Access Control Events\AccessControl/AccessTaken/Credential** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Access control decisions
 - tns1:AccessControl/AccessTaken/Credential

2. Check that `tns1:AccessControl/AccessNotTaken/Credential` feature is supported by the DUT. If **Access Control Service\Access Control Events\AccessControl/AccessNotTaken/Credential** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Access control decisions
 - `tns1:AccessControl/AccessNotTaken/Credential`
- e. Check that `tns1:AccessControl/AccessTaken/Anonymous` and `tns1:AccessControl/AccessNotTaken/Anonymous` features are supported by the DUT. If **Access Control Service\Access Point Entity\Access Taken** and **Access Control Service\Access Point Entity\Anonymous Access** are regarded as supported by DUT, then it is determined that `tns1:AccessControl/AccessTaken/Anonymous` and `tns1:AccessControl/AccessNotTaken/Anonymous` features are supported by the DUT.
- f. Check that `tns1:AccessControl/Denied/CredentialNotFound/Card` feature are supported by the DUT. If **Access Control Service\Access Control Events\AccessControl/Denied/CredentialNotFound/Card** is regarded as supported by DUT, then it is determined that `tns1:AccessControl/Denied/CredentialNotFound/Card` feature is supported by the DUT.
- g. Check that External authorization feature category is supported by the DUT. If **AccessControl\External Authorization** is regarded as supported by DUT:
 - i. It is determined that the following features are supported by the DUT:
 - i. External authorization
 - ExternalAuthorization (Access Control)
 - `tns1:AccessControl/Request/Timeout`
 - ii. Check that `tns1:AccessControl/Request/Credential` is supported by the DUT. If **Access Control Service\Access Control Events\AccessControl/Request/Credential** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. External authorization
 - `tns1:AccessControl/Request/Credential`

- h. Check that tns1:AccessControl/Request/Anonymous of External authorization feature category is supported by the DUT. If **AccessControl\External Authorization** and **Access Control Service\Access Point Entity\Anonymous Access** is regarded as supported by DUT, then it is determined that tns1:AccessControl/Request/Anonymous feature is supported by the DUT.
 - i. Check that tns1:Configuration/AccessPoint/Changed feature are supported by the DUT. If **Access Control Service\Access Control Events\Configuration/AccessPoint/Changed** is regarded as supported by DUT, then it is determined that tns1:Configuration/AccessPoint/Changed feature is supported by the DUT.
 - j. Check that tns1:Configuration/AccessPoint/Removed feature are supported by the DUT. If **Access Control Service\Access Control Events\Configuration/AccessPoint/Removed** is regarded as supported by DUT, then it is determined that tns1:Configuration/AccessPoint/Removed feature is supported by the DUT.
 - k. Check that tns1:Configuration/Area/Changed feature are supported by the DUT. If **Access Control Service\Access Control Events\Configuration/Area/Changed** is regarded as supported by DUT, then it is determined that tns1:Configuration/Area/Changed feature is supported by the DUT.
 - l. Check that tns1:Configuration/Area/Removed feature are supported by the DUT. If **Access Control Service\Access Control Events\Configuration/Area/Removed** is regarded as supported by DUT, then it is determined that tns1:Configuration/Area/Removed feature is supported by the DUT.
 - m. Check that Duress feature category is supported by the DUT. If **Access Control Service\Access Point Entity\Duress** is regarded as supported by DUT, then it is determined that tns1:AccessControl/Duress feature is supported by the DUT.
12. Check Door Control Service related features.
- a. Check that Door Control Service is supported by DUT. If **Door Control Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that Door Control related features are supported by DUT. Those features are:
 - i. Capabilities feature category
 - GetServiceCapabilities (Door Control)
 - ii. System component information - Doors feature category
 - GetDoorInfoList (Door Control)

- GetDoorInfo (Door Control)
- iii. Check that Door Entity is supported by DUT. If **Door Control Service\Door Entity** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- i. Door state feature category
 - GetDoorState (Door Control)
 - tns1:Door/State/DoorMode
- b. Check that AccessDoor (Door Control) feature is supported by the DUT. If **Door Control Service\Door Entity\Access Door** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that AccessDoor (Door Control) feature is supported by the DUT.
- c. Check that LockDoor (Door Control) feature is supported by the DUT. If **Door Control Service\Door Entity\Lock Door** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that LockDoor (Door Control) feature is supported by the DUT.
- d. Check that UnlockDoor (Door Control) feature is supported by the DUT. If **Door Control Service\Door Entity\Unlock Door** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile C] is not supported by DUT and certification will be failed. Otherwise, it is determined that UnlockDoor (Door Control) feature is supported by the DUT.
- e. Check that DoubleLockDoor (Door Control) feature is supported by the DUT. If **Door Control Service\Door Entity\Double Lock Door** is regarded as supported by DUT, then it is determined that DoubleLockDoor (Door Control) feature is supported by the DUT.
- f. Check that BlockDoor (Door Control) feature is supported by the DUT. If **Door Control Service\Door Entity\Block Door** is regarded as supported by DUT, then it is determined that BlockDoor (Door Control) feature is supported by the DUT.
- g. Check that LockDownDoor (Door Control) and LockDownReleaseDoor (Door Control) features are supported by the DUT. If **Door Control Service\Door Entity\Lock Down Door** is regarded as supported by DUT, then it is determined that LockDownDoor (Door Control) and LockDownReleaseDoor (Door Control) features are supported by the DUT.

- h. Check that LockOpenDoor (Door Control) and LockOpenReleaseDoor (Door Control) features are supported by the DUT. If **Door Control Service\Door Entity\Lock Open Door** is regarded as supported by DUT, then it is determined that LockOpenDoor (Door Control) and LockOpenReleaseDoor (Door Control) features are supported by the DUT.
- i. Check that tns1:Door/State/DoorPhysicalState feature are supported by the DUT. If **Door Control Service\Door Entity\Door Monitor** is regarded as supported by DUT, then it is determined that tns1:Door/State/DoorPhysicalState feature is supported by the DUT.
- j. Check that tns1:Door/State/LockPhysicalState feature are supported by the DUT. If **Door Control Service\Door Entity\Lock Monitor** is regarded as supported by DUT, then it is determined that tns1:Door/State/LockPhysicalState feature is supported by the DUT.
- k. Check that tns1:Door/State/DoubleLockPhysicalState feature are supported by the DUT. If **Door Control Service\Door Entity\Double Lock Monitor** is regarded as supported by DUT, then it is determined that tns1:Door/State/DoubleLockPhysicalState feature is supported by the DUT.
- l. Check that tns1:Door/State/DoorAlarm feature are supported by the DUT. If **Door Control Service\Door Entity\Alarm** is regarded as supported by DUT, then it is determined that tns1:Door/State/DoorAlarm feature is supported by the DUT.
- m. Check that tns1:Door/State/DoorTamper feature are supported by the DUT. If **Door Control Service\Door Entity\Tamper** is regarded as supported by DUT, then it is determined that tns1:Door/State/DoorTamper feature is supported by the DUT.
- n. Check that tns1:Door/State/DoorFault feature are supported by the DUT. If **Door Control Service\Door Entity\Fault** is regarded as supported by DUT, then it is determined that tns1:Door/State/DoorFault feature is supported by the DUT.
- o. Check that tns1:Configuration/Door/Changed feature are supported by the DUT. If **Access Control Service\Access Control Events\Configuration/Door/Changed** is regarded as supported by DUT, then it is determined that tns1:Configuration/Door/Changed feature is supported by the DUT.
- p. Check that tns1:Configuration/Door/Removed feature are supported by the DUT. If **Access Control Service\Access Control Events\Configuration/Door/Removed** is regarded as supported by DUT, then it is determined that tns1:Configuration/Door/Removed feature is supported by the DUT.

6 Profile A Conformance

6.1 Feature category classification for ONVIF Profile A

In order for ONVIF Device Test Tool to conduct conformance testing toward [ONVIF Profile A], it would need to identify whether DUT implements the expected feature set.

This section classifies supported features as multiple categories that are related to [ONVIF Profile A] conformance. Those category classifications will be used to do some preliminary checking prior to the test case execution and they will be used to determine whether DUT can be considered [ONVIF Profile A] conformant device.

The following discovery scope is defined as the scope that signals that DUT is [ONVIF Profile A] product.

Table 6.1. Profile A Discovery Scope

onvif://www.onvif.org/Profile/A

The following table shows the classified feature categories based on commands and/or functional blocks that are referenced by DUT.

Table 6.2. Profile A Features Categories

Profile Mandatory Features	
Security	HTTP Digest Authentication
Capabilities	GetServices (Device Management)
	GetServiceCapabilities (Device Management)
	GetServiceCapabilities (Event)
	GetServiceCapabilities (Access Rules)
	GetServiceCapabilities (Credential)
	GetServiceCapabilities (Schedule)
	GetWsdUrl (Device Management)
	MaxPullPoint capability is supported and value is not less than 2
Access Profiles	GetAccessProfiles (Access Rules)
	GetAccessProfileList (Access Rules)
	GetAccessProfileInfo (Access Rules)
	GetAccessProfileInfoList (Access Rules)

	CreateAccessProfile (Access Rules)
	ModifyAccessProfile (Access Rules)
	DeleteAccessProfile (Access Rules)
	tns1:Configuration/AccessProfile/Changed
	tns1:Configuration/AccessProfile/Removed
Credentials	GetCredentials (Credential)
	GetCredentialList (Credential)
	GetCredentialInfo (Credential)
	GetCredentialInfoList (Credential)
	CreateCredential (Credential)
	ModifyCredential (Credential)
	DeleteCredential (Credential)
	GetCredentialAccessProfiles (Credential)
	SetCredentialAccessProfiles (Credential)
	DeleteCredentialAccessProfiles (Credential)
	GetCredentialIdentifiers (Credential)
	SetCredentialIdentifier (Credential)
	DeleteCredentialIdentifier (Credential)
	EnableCredential (Credential)
	DisableCredential (Credential)
	GetCredentialState (Credential)
	GetSupportedFormatTypes (Credential)
	tns1:Configuration/Credential/Changed
	tns1:Configuration/Credential/Removed
Schedules	GetSchedules (Schedule)
	GetScheduleList (Schedule)
	GetScheduleInfo (Schedule)
	GetScheduleInfoList (Schedule)
	CreateSchedule (Schedule)
	ModifySchedule (Schedule)
	DeleteSchedule (Schedule)
	GetScheduleState (Schedule)
	tns1:Configuration/Schedule/Changed

	tns1:Configuration/ Schedule /Removed
	tns1:Schedule/State/Active
Event Handling	Renew (Event)
	Unsubscribe (Event)
	SetSynchronizationPoint (Event)
	CreatePullPointSubscription (Event)
	PullMessage (Event)
	GetEventProperties (Event)
	TopicFilter (Event)
Discovery	WS-Discovery
	GetDiscoveryMode (Device Management)
	SetDiscoveryMode (Device Management)
	GetScopes (Device Management)
	SetScopes (Device Management)
	AddScopes (Device Management)
	RemoveScopes (Device Management)
Network Configuration	GetHostname (Device Management)
	SetHostname (Device Management)
	GetDNS (Device Management)
	SetDNS (Device Management)
	GetNetworkInterfaces (Device Management)
	SetNetworkInterfaces (Device Management)
	GetNetworkProtocols (Device Management)
	SetNetworkProtocols (Device Management)
	GetNetworkDefaultGateway (Device Management)
	SetNetworkDefaultGateway (Device Management)
System	GetDeviceInformation (Device Management)
	GetSystemDateAndTime (Device Management)
	SetSystemDateAndTime (Device Management)
	SetSystemFactoryDefault (Device Management)
	Reboot (Device Management)

User Handling	GetUsers (Device Management)
	CreateUsers (Device Management)
	DeleteUsers (Device Management)
	SetUser (Device Management)
Profile Conditional Features	
Reset Antipassback Violations	ResetAntipassbackViolation (Credential)
	tns1:Credential/State/ApbViolation
Special Days Schedule	GetSpecialDayGroups (Schedule)
	GetSpecialDayGroupList (Schedule)
	GetSpecialDayGroupInfo (Schedule)
	GetSpecialDayGroupInfoList (Schedule)
	CreateSpecialDayGroup (Schedule)
	ModifySpecialDayGroup (Schedule)
	DeleteSpecialDayGroup (Schedule)
	tns1:Configuration/SpecialDays/Changed
	tns1:Configuration/SpecialDays/Removed
Persistent notification storage	Seek (Event)
IP Filtering	GetIPAddressFilter (Device Management)
	SetIPAddressFilter (Device Management)
	AddIPAddressFilter (Device Management)
	RemoveIPAddressFilter (Device Management)

6.2 Profile A Support Check

Preliminary checking for feature discovery will be performed prior to the test execution. For the details of the preliminary feature discovery, refer to [ONVIF Feature Discovery].

According to the result of test case execution, final determination of [ONVIF Profile A] support toward DUT is performed based on the following procedure.

Procedure:

1. Check that scope list contains the scope given in [Table 6.1](#). If there is no such scope in the scope list of the DUT, then it is determined that [ONVIF Profile A] is not supported.
2. Check Discovery Types support. If **Discovery/Types/tds:Device** is not supported by the DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed.

3. Check Security feature category:
 - a. Check that HTTP Digest Authentication is supported by the DUT. If **Security\Digest** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that HTTP Digest Authentication feature is supported by DUT.
4. Check Capabilities feature category:
 - a. Check that GetServices command is supported by the DUT. If **Device Service/Capabilities/GetServices** is not supported by the DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that Capabilities category is supported with the following features included:
 - GetServices (Device Management)
 - GetServiceCapabilities (Device Management)
 - b. The following features are defined as supported, because this is a mandatory feature for any of ONVIF device implementation:
 - GetWsdUrl (Device Management)
5. Check Access Rules Service related features:
 - a. Check that Access Rules Service is supported by DUT. If **Access Rules Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that Access Rules Service related features are supported by DUT. Those features are:
 - i. Capabilities feature category:
 - GetServiceCapabilities (Access Rules)
 - ii. Access Profiles feature category:
 - GetAccessProfiles (Access Rules)
 - GetAccessProfileList (Access Rules)
 - GetAccessProfileInfo (Access Rules)
 - GetAccessProfileInfoList (Access Rules)
 - CreateAccessProfile (Access Rules)
 - ModifyAccessProfile (Access Rules)

- DeleteAccessProfile (Access Rules)
- tns1:Configuration/AccessProfile/Changed
- tns1:Configuration/AccessProfile/Removed

6. Check Credential Service related features:

- a. Check that Credential Service is supported by DUT. If **Credential Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that Credential Service related features are supported by DUT. Those features are:

i. Capabilities feature category:

- GetServiceCapabilities (Credential)

ii. Credentials feature category:

- GetCredentialList (Credential)
- GetCredentialInfoList (Credential)

- iii. Check that Credential Entity is supported by DUT. If **Credential Service/Credential Entity** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Credentials feature category:

- GetCredentials (Credential)
- GetCredentialList (Credential)
- GetCredentialInfo (Credential)
- GetCredentialInfoList (Credential)
- CreateCredential (Credential)
- ModifyCredential (Credential)
- DeleteCredential (Credential)
- GetCredentialAccessProfiles (Credential)
- SetCredentialAccessProfiles (Credential)

- DeleteCredentialAccessProfiles (Credential)
 - GetCredentialIdentifiers (Credential)
 - SetCredentialIdentifier (Credential)
 - DeleteCredentialIdentifier (Credential)
 - EnableCredential (Credential)
 - DisableCredential (Credential)
 - GetCredentialState (Credential)
 - GetSupportedFormatTypes (Credential)
 - tns1:Configuration/Credential/Changed
 - tns1:Configuration/Credential/Removed
- b. Check that Reset Antipassback Violations feature category is supported by the DUT. If **Credential Service\Reset Antipassback Violation** is regarded as supported by DUT, it is determined that Reset Antipassback Violations feature category are supported by DUT. The following features are defined as supported:
- ResetAntipassbackViolation (Credential)
 - tns1:Credential/State/ApbViolation
7. Check Schedule Service related features:
- a. Check that Schedule Service is supported by DUT. If **Schedule Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that Schedule Service related features are supported by DUT. Those features are:
- i. Capabilities feature category:
- GetServiceCapabilities (Schedule)
- ii. Schedules feature category:
- GetSchedules (Schedule)
 - GetScheduleList (Schedule)
 - GetScheduleInfo (Schedule)

- GetScheduleInfoList (Schedule)
 - CreateSchedule (Schedule)
 - ModifySchedule (Schedule)
 - DeleteSchedule (Schedule)
 - tns1:Configuration/Schedule/Changed
 - tns1:Configuration/ Schedule /Removed
- b. Check that GetScheduleState (Schedule) feature and tns1:Schedule/State/Active feature are supported by the DUT. If **Schedule Service\State Reporting** is regarded as supported by DUT, it is determined that the following features are defined as supported:
- i. GetScheduleState (Schedule)
 - ii. tns1:Schedule/State/Active
- c. Check that Special Days Schedule feature category is supported by the DUT. If **Schedule Service\Special Days** is regarded as supported by DUT, it is determined that Special Days Schedule feature category are supported by DUT. The following features are defined as supported:
- GetSpecialDayGroups (Schedule)
 - GetSpecialDayGroupList (Schedule)
 - GetSpecialDayGroupInfo (Schedule)
 - GetSpecialDayGroupInfoList (Schedule)
 - CreateSpecialDayGroup (Schedule)
 - ModifySpecialDayGroup (Schedule)
 - DeleteSpecialDayGroup (Schedule)
 - tns1:Configuration/SpecialDays/Changed
 - tns1:Configuration/SpecialDays/Removed
8. Check that Discovery is supported by the DUT. If **Discovery** feature is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile A] is not supported by the

DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

- WS-Discovery
- GetDiscoveryMode (Device Management)
- SetDiscoveryMode (Device Management)
- GetScopes (Device Management)
- SetScopes (Device Management)
- AddScopes (Device Management)
- RemoveScopes (Device Management)

9. Check that **Device Service/System/Network Configuration** is supported by the DUT. If **Device Service/System/Network Configuration** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile A] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

- GetHostname (Device Management)
- SetHostname (Device Management)
- GetDNS (Device Management)
- SetDNS (Device Management)
- GetNetworkInterfaces (Device Management)
- SetNetworkInterfaces (Device Management)
- GetNetworkProtocols (Device Management)
- SetNetworkProtocols (Device Management)
- GetNetworkDefaultGateway (Device Management)
- SetNetworkDefaultGateway (Device Management)

10. Check System feature category of ONVIF profile support. This feature is mandatory for any of ONVIF device implementation. The following features are defined as supported:

- GetDeviceInformation (Device Management)
- GetSystemDateAndTime (Device Management)

- SetSystemDateAndTime (Device Management)
 - SetSystemFactoryDefault (Device Management)
 - Reboot (Device Management)
11. Check that **Device Service/System/User Handling** is supported by the DUT. If **Device Service/System/User Handling** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile A] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- i. User Handling feature category:
 - GetUsers (Device Management)
 - CreateUsers (Device Management)
 - DeleteUsers (Device Management)
 - SetUser (Device Management)
12. Check Event Handling feature category.
- a. Check that Event Service is supported by DUT. If **Event Service** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that Event Handling features is supported by DUT. The following features are defined as supported:
 - i. Capabilities feature category
 - GetServiceCapabilities (Event)
 - ii. Event Handling feature category
 - GetEventProperties (Event)
 - b. Check that Pull-Point Notification is supported by DUT. If **Event Service/Pull-Point Notification** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are defined as supported:
 - i. Event Handling feature category
 - Renew (Event)
 - Unsubscribe (Event)

- SetSynchronizationPoint (Event)
 - CreatePullPointSubscription (Event)
 - PullMessage (Event)
 - TopicFilter (Event)
- c. Check that at least two PullPoint subscriptions are supported by the DUT. If **Event Service/GetServiceCapabilities/MaxPullPoints capability** is not supported by the DUT or it has value less than 2, then it is determined that [ONVIF Profile A] is not supported by DUT and certification will be failed. Otherwise, it is determined that Event Handling is supported with the following feature category included:
- a. At least two PullPoint subscriptions
- d. Check Persistent notification storage feature category of ONVIF profile support. If **Event Service\Persistent notification storage** is regarded as supported by DUT, then it is determined that Persistent notification storage feature category is supported by DUT. The following features are defined as supported:
- Seek (Event)
13. Check IP Filtering of ONVIF profile support. If **Device Service\Network\IP Filter** is regarded as supported by DUT, then it is determined that IP Filtering feature category is supported by DUT. The following features are defined as supported:
- GetIPAddressFilter (Device Management)
 - SetIPAddressFilter (Device Management)
 - AddIPAddressFilter (Device Management)
 - RemoveIPAddressFilter (Device Management)

7 Profile T Conformance

7.1 Feature category classification for ONVIF Profile T

In order for ONVIF Device Test Tool to conduct conformance testing toward [ONVIF Profile T], it would need to identify whether DUT implements the expected feature set.

This section classifies supported features as multiple categories that are related to [ONVIF Profile T] conformance. Those category classifications will be used to do some preliminary checking prior to the test case execution and they will be used to determine whether DUT can be considered [ONVIF Profile T] conformant device.

The following discovery scope is defined as the scope that signals that DUT is [ONVIF Profile T] product.

Table 7.1. Profile T Discovery Scope

onvif://www.onvif.org/Profile/T

The following table shows the classified feature categories based on commands and/or functional blocks that are referenced by DUT.

Table 7.2. Profile T Features Categories

Profile Mandatory Features	
User authentication	HTTP Digest Authentication
	RTSP Digest Authentication
Capabilities	GetServices (Device Management)
	GetServiceCapabilities (Device Management)
	GetServiceCapabilities (Event)
	GetServiceCapabilities (Media 2)
	GetServiceCapabilities (Imaging)
	GetServiceCapabilities (PTZ)
	GetServiceCapabilities (Analytics)
	GetServiceCapabilities (DeviceIO)
	GetWsdUrl (Device Management)
	MaximumNumberOfProfiles Capability (Media 2)
	MaxPullPoint capability is supported and value is not less than 2 (Event)

Discovery	WS-Discovery
	GetDiscoveryMode (Device Management)
	SetDiscoveryMode (Device Management)
	GetScopes (Device Management)
	SetScopes (Device Management)
	AddScopes (Device Management)
	RemoveScopes (Device Management)
Network Configuration	GetHostname (Device Management)
	SetHostname (Device Management)
	GetDNS (Device Management)
	SetDNS (Device Management)
	GetNetworkInterfaces (Device Management)
	SetNetworkInterfaces (Device Management)
	GetNetworkProtocols (Device Management)
	SetNetworkProtocols (Device Management)
	GetNetworkDefaultGateway (Device Management)
	SetNetworkDefaultGateway (Device Management)
System	GetDeviceInformation (Device Management)
	GetSystemDateAndTime (Device Management)
	SetSystemDateAndTime (Device Management)
	SetSystemFactoryDefault (Device Management)
	System Reboot (Device Management)
User Handling	GetUsers (Device Management)
	CreateUsers (Device Management)
	DeleteUsers (Device Management)
	SetUser (Device Management)
Event Handling	SetSynchronizationPoint (Event)
	CreatePullPointSubscription (Event)
	PullMessage (Event)
	GetEventProperties (Event)
	Unsubscribe (Event)

	TopicFilter (Event)
	MessageContentFilter (Event)
	ONVIF Message Content Filter Dialect (Event)
Media Profile Management	CreateProfile (Media 2)
	DeleteProfile (Media 2)
	GetVideoSourceConfigurations (Media 2)
	GetVideoEncoderInstances (Media 2)
	tns1:Media/ProfileChanged (Event)
Video Streaming	Ready-to-use Media Profile for streaming H.264 or H.265 video per video source (Media 2)
	GetProfiles (Media 2)
	GetStreamUri (Media 2)
	Video Streaming using RTSP (Streaming)
	H.264 Encoding (Media 2)
	H.265 Encoding (Media 2)
	Streaming over RTP/UDP (Streaming)
	Streaming over RTP/RTSP/HTTP/TCP (Streaming)
	Streaming over RTP/RTSP/HTTPS/TCP (Streaming)
	Streaming over RTP/UDP Multicast (Streaming)
	Streaming over RTP/RTSP/TCP/WebSocket (Streaming)
	SetSynchronizationPoint (Media 2)
Configuration of Video Profile	GetProfiles (Media 2)
	GetVideoSources (DeviceIO)
	GetVideoSourceConfigurations (Media 2)
	AddConfiguration (Video Source Configuration) (Media 2)
	AddConfiguration (Video Encoder Configuration) (Media 2)
	GetVideoEncoderConfigurations (Media 2)
	RemoveConfiguration (Video Source Configuration) (Media 2)

	RemoveConfiguration (Video Encoder Configuration) (Media 2)
	tns1:Media/ProfileChanged (Event)
Video Source Configuration	GetVideoSourceConfigurations (Media 2)
	GetVideoSourceConfigurationOptions (Media 2)
	SetVideoSourceConfiguration (Media 2)
	tns1:Media/ConfigurationChanged (Event)
Video Encoder Configuration	GetVideoEncoderConfigurations (Media 2)
	GetVideoEncoderConfigurationOptions (Media 2)
	SetVideoEncoderConfiguration (Media 2)
	tns1:Media/ConfigurationChanged (Event)
Metadata Streaming	GetProfiles (Media 2)
	GetStreamUri (Media 2)
	Metadata Streaming using RTSP (Streaming)
	Streaming over RTP/UDP (Streaming)
	Streaming over RTP/RTSP/HTTP/TCP (Streaming)
	Streaming over RTP/RTSP/HTTPS/TCP (Streaming)
	Streaming over RTP/UDP Multicast (Streaming)
	Streaming over RTP/RTSP/TCP/WebSocket (Streaming)
	SetSynchronizationPoint (Media 2)
Configuration of Metadata Profile	GetProfiles (Media 2)
	GetMetadataConfigurations (Media 2)
	AddConfiguration (Metadata Configuration) (Media 2)
	RemoveConfiguration (Metadata Configuration) (Media 2)
	tns1:Media/ProfileChanged (Event)
Metadata Configuration	GetMetadataConfigurations (Media 2)
	GetMetadataConfigurationOptions (Media 2)
	SetMetadataConfiguration (Media 2)
	tns1:Media/ConfigurationChanged (Event)

Imaging Settings	GetVideoSources (DeviceIO)
	GetImagingSettings (Imaging)
	GetOptions (Imaging)
	SetImagingSettings (Imaging)
Tampering	tns1:VideoSource/ImageTooBlurry (Event)
	tns1:VideoSource/ImageTooDark (Event)
	tns1:VideoSource/ImageTooBright (Event)
	tns1:VideoSource/GlobalSceneChange (Event)
Configuration of On-Screen Display (OSD)	CreateOSD, text (Media 2)
	CreateOSD, image (Media 2)
	DeleteOSD (Media 2)
	GetVideoSourceConfigurations (Media 2)
	GetOSDs (Media 2)
	GetOSDOptions (Media 2)
	SetOSD (Media 2)
JPEG Snapshot	GetSnapshotUri (Media 2)
Motion Alarm Events	tns1:VideoSource/MotionAlarm (Event)
Absolute PTZ Move	Ready-to-use Media Profile for PTZ control per PTZ node
	MoveStatus capability (PTZ)
	StatusPosition capability (PTZ)
	GetStatus (PTZ)
	AbsoluteMove (PTZ)
	http://www.onvif.org/ver10/tptz/PanTiltSpaces/SphericalPositionSpaceDegrees (PTZ)
	http://www.onvif.org/ver10/tptz/PanTiltSpaces/PositionGenericSpace (PTZ)
	http://www.onvif.org/ver10/tptz/ZoomSpaces/PositionGenericSpace (PTZ)
Continuous PTZ Move	Ready-to-use Media Profile for PTZ control per PTZ node
	MoveStatus capability (PTZ)
	GetStatus (PTZ)
	ContinuousMove (PTZ)

	Stop (PTZ)
	http://www.onvif.org/ver10/tptz/PanTiltSpaces/VelocityGenericSpace (PTZ)
	http://www.onvif.org/ver10/tptz/ZoomSpaces/VelocityGenericSpace (PTZ)
Profile Conditional Features	
Configuration of PTZ Profile	GetProfiles (Media 2)
	GetCompatibleConfigurations (PTZ)
	AddConfiguration, PTZ Configuration (Media 2)
	RemoveConfiguration, PTZ Configuration (Media 2)
	tns1:Media/ProfileChanged (Event)
PTZ Configuration	GetNodes (PTZ)
	GetNode (PTZ)
	GetConfigurationOptions (PTZ)
	SetConfiguration (PTZ)
	tns1:Media/ConfigurationChanged (Event)
PTZ Presets	MaximumNumberOfPresets capability is supported and value is not less than 1 (PTZ)
	GetPresets (PTZ)
	SetPreset (PTZ)
	GotoPreset (PTZ)
	RemovePreset (PTZ)
PTZ Home Position	HomeSupported capability = true (PTZ)
	SetHomePosition (PTZ)
	GotoHomePosition (PTZ)
Configuration of Analytics Profile	GetProfiles (Media 2)
	GetAnalyticsConfigurations (Media 2)
	AddConfiguration, Analytics Configuration (Media 2)
	RemoveConfiguration, Analytics Configuration (Media 2)
	tns1:Media/ProfileChanged (Event)
Motion Region Detector	GetSupportedRules (Analytics)

	GetRules (Analytics)
	GetRuleOptions (Analytics)
	CreateRules (Analytics)
	ModifyRules (Analytics)
	DeleteRules (Analytics)
	tns1:RuleEngine/MotionRegionDetector/Motion (Event)
Video Source Mode	GetVideoSources (DeviceIO)
	GetVideoSourceModes (Media 2)
	SetVideoSourceMode (Media 2)
NTP	GetNTP (Device Management)
	SetNTP (Device Management)
Audio Output Configuration	GetAudioOutputConfigurations (Media 2)
	GetAudioOutputConfigurationOptions (Media 2)
	SetAudioOutputConfiguration (Media 2)
	tns1:Media/ConfigurationChanged (Event)
Audio Streaming	GetProfiles (Media 2)
	GetStreamUri (Media 2)
	Audio Streaming using RTSP (Streaming)
	G.711 Encoding (Media 2)
	AAC Encoding (Media 2)
	Streaming over RTP/UDP (Streaming)
	Streaming over RTP/RTSP/HTTP/TCP (Streaming)
	Streaming over RTP/RTSP/HTTPS/TCP (Streaming)
	Streaming over RTP/UDP Multicast (Streaming)
	Streaming over RTP/RTSP/TCP/WebSocket (Streaming)
Configuration of Audio Profile	GetProfiles (Media 2)
	GetAudioSources (DeviceIO)
	GetAudioSourceConfigurations (Media 2)
	AddConfiguration, Audio Source Configuration (Media 2)

	AddConfiguration, Audio Encoder Configuration (Media 2)
	GetAudioEncoderConfigurations (Media 2)
	RemoveConfiguration, Audio Source Configuration (Media 2)
	RemoveConfiguration, Audio Encoder Configuration (Media 2)
	tns1:Media/ProfileChanged (Event)
Audio Encoder Configuration	GetAudioEncoderConfigurations (Media 2)
	GetAudioEncoderConfigurationOptions (Media 2)
	SetAudioEncoderConfiguration (Media 2)
	tns1:Media/ConfigurationChanged (Event)
Audio Output Streaming	GetProfiles (Media 2)
	GetStreamUri (Media 2)
	Streaming using RTSP - Back Channel (Streaming)
	G.711 Decoding (Media 2)
	AAC Decoding (Media 2)
	Streaming over RTP/UDP (Streaming)
	Streaming over RTP/RTSP/HTTP/TCP (Streaming)
	Streaming over RTP/RTSP/HTTPS/TCP (Streaming)
	Streaming over RTP/RTSP/TCP/WebSocket (Streaming)
Configuration of Audio Output Profile	GetProfiles (Media 2)
	GetAudioOutputs (DeviceIO)
	GetAudioOutputConfigurations (Media 2)
	GetAudioDecoderConfigurations (Media 2)
	AddConfiguration, Audio Output Configuration (Media 2)
	AddConfiguration, Audio Decoder Configuration (Media 2)
	RemoveConfiguration, Audio Output Configuration (Media 2)

	RemoveConfiguration, Audio Decoder Configuration (Media 2)
	tns1:Media/ProfileChanged (Event)
Focus Control	GetVideoSources (DeviceIO)
	GetMoveOptions (Imaging)
	Move (Imaging)
	Stop (Imaging)
	GetStatus (Imaging)
Relay Outputs	GetRelayOutputs (DeviceIO)
	GetRelayOutputOptions (DeviceIO)
	SetRelayOutputSettings (DeviceIO)
	SetRelayOutputState (DeviceIO)
	tns1:Device/Trigger/Relay (Event)
Digital Inputs	GetDigitalInputs (DeviceIO)
	GetDigitalInputConfigurationOptions (DeviceIO)
	SetDigitalInputConfigurations (DeviceIO)
	tns1:Device/Trigger/DigitalInput (Event)
Auxiliary Commands	SendAuxiliaryCommand (Device Management)
	tt:Wiper On (Device Management)
	tt:Wiper Off (Device Management)
	tt:Washer On (Device Management)
	tt:Washer Off (Device Management)
	tt:WashingProcedure On (Device Management)
	tt:WashingProcedure Off (Device Management)
	tt:IRLamp On (Device Management)
	tt:IRLamp Off (Device Management)
	tt:IRLamp Auto(Device Management)

7.2 Profile T Support Check

Preliminary checking for feature discovery will be performed prior to the test execution. For the details of the preliminary feature discovery, refer to [ONVIF Feature Discovery].

According to the result of test case execution, final determination of [ONVIF Profile T] support toward DUT is performed based on the following procedure.

Procedure:

1. Check that scope list contains the scope given in [Table 7.1](#). If there is no such scope in the scope list of the DUT, then it is determined that [ONVIF Profile T] is not supported.
2. Check Discovery Types support. If **Discovery/Types/tds:Device** is not supported by the DUT, then it is determined that [ONVIF Profile T] is not supported by DUT and certification will be failed.
3. Check that Digest Authentication is supported by the DUT. If **Security/Digest** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. User authentication feature category:
 - HTTP Digest Authentication
 - RTSP Digest Authentication
4. Check Device Management Service related features:
 - 4.1. Check that Discovery is supported by the DUT. If **Discovery** feature is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - 4.1.1. Discovery feature category:
 - WS-Discovery
 - GetDiscoveryMode (Device Management)
 - SetDiscoveryMode (Device Management)
 - GetScopes (Device Management)
 - SetScopes (Device Management)
 - AddScopes (Device Management)
 - RemoveScopes (Device Management)
 - 4.2. The following features are supported by the DUT, because these are mandatory features for any ONVIF device implementation:
 - i. Capabilities feature category:

- GetWsdlUrl (Device Management)
- GetServiceCapabilities (Device Management)
- ii. Check that Network Configuration is supported by the DUT. If **Device Service/System/Network Configuration** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Network Configuration feature category:
 - GetHostname (Device Management)
 - SetHostname (Device Management)
 - GetDNS (Device Management)
 - SetDNS (Device Management)
 - GetNetworkInterfaces (Device Management)
 - SetNetworkInterfaces (Device Management)
 - GetNetworkProtocols (Device Management)
 - SetNetworkProtocols (Device Management)
 - GetNetworkDefaultGateway (Device Management)
 - SetNetworkDefaultGateway (Device Management)
 - iii. System feature category:
 - GetDeviceInformation (Device Management)
 - GetSystemDateAndTime (Device Management)
 - SetSystemDateAndTime (Device Management)
 - SetSystemFactoryDefault (Device Management)
 - Reboot (Device Management)
 - iv. Check that User Handling is supported by the DUT. If **Device Service/System/User Handling** is regarded as unsupported by DUT, then it is determined that

[ONVIF Profile T] is not supported by the DUT and certification will be failed.
Otherwise, it is determined that the following features are supported by the DUT:

- i. User Handling feature category:
 - GetUsers (Device Management)
 - CreateUsers (Device Management)
 - DeleteUsers (Device Management)
 - SetUser (Device Management)

4.3. Check that NTP is supported by the DUT. If **Device Service/Network/NTP** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. NTP feature category:
 - GetNTP (Device Management)
 - SetNTP (Device Management)

4.4. Check that Auxiliary Commands is supported by the DUT. If **Device Service/Auxiliary Commands** is regarded as supported by the DUT, then:

4.4.1. It is determined that the following features are supported by the DUT:

- i. Auxiliary Commands feature category:
 - SendAuxiliaryCommand (Device Management)

4.4.2. Check that tt:Wiper|On Auxiliary Command is supported by the DUT. If **Device Service/Auxiliary Commands/Wiper On** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Auxiliary Commands feature category:
 - tt:Wiper|On (Device Management)

4.4.3. Check that tt:Wiper|Off Auxiliary Command is supported by the DUT. If **Device Service/Auxiliary Commands/Wiper Off** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Auxiliary Commands feature category:
 - tt:Wiper|Off (Device Management)

- 4.4.4. Check that tt:Washer|On Auxiliary Command is supported by the DUT. If **Device Service/Auxiliary Commands/Washer On** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Auxiliary Commands feature category:
 - tt:Washer|On (Device Management)
- 4.4.5. Check that tt:Washer|Off Auxiliary Command is supported by the DUT. If **Device Service/Auxiliary Commands/Washer Off** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Auxiliary Commands feature category:
 - tt:Washer|Off (Device Management)
- 4.4.6. Check that tt:WashingProcedure|On Auxiliary Command is supported by the DUT. If **Device Service/Auxiliary Commands/Washing Procedure On** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Auxiliary Commands feature category:
 - tt:WashingProcedure|On (Device Management)
- 4.4.7. Check that tt:WashingProcedure|Off Auxiliary Command is supported by the DUT. If **Device Service/Auxiliary Commands/Washing Procedure Off** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Auxiliary Commands feature category:
 - tt:WashingProcedure|Off (Device Management)
- 4.4.8. Check that tt:IRLamp|On Auxiliary Command is supported by the DUT. If **Device Service/Auxiliary Commands/IR Lamp On** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Auxiliary Commands feature category:
 - tt:IRLamp|On (Device Management)

- 4.4.9. Check that tt:IRLamp|Off Auxiliary Command is supported by the DUT. If **Device Service/Auxiliary Commands/IR Lamp Off** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Auxiliary Commands feature category:
 - tt:IRLamp|Off (Device Management)
- 4.4.10. Check that tt:IRLamp|Auto Auxiliary Command is supported by the DUT. If **Device Service/Auxiliary Commands/IR Lamp Auto** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Auxiliary Commands feature category:
 - tt:IRLamp|Auto (Device Management)
5. Check that Event Service is supported by the DUT. If **Event Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise:
- 5.1. It is determined that the following features are supported by the DUT:
- i. Capabilities feature category:
 - GetServiceCapabilities (Event)
 - ii. Event Handling feature category:
 - GetEventProperties (Event)
- 5.2. Check that Pull-Point Notification is supported by the DUT. If **Event Service/Pull-Point Notification** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise:
- i. Event Handling feature category:
 - SetSynchronizationPoint (Event)
 - CreatePullPointSubscription (Event)
 - PullMessage (Event)
 - Unsubscribe (Event)

- TopicFilter (Event)
- 5.3. Check that at least two PullPoint subscriptions are supported by DUT. If **Event Service/GetServiceCapabilities/MaxPullPoints capability** is regarded as unsupported by DUT or it has value less than two, then it is determined that [ONVIF Profile T] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- i. Capabilities feature category:
 - MaxPullPoint capability is supported and value is not less than 2 (Event)
- 5.4. Check that ONVIF Message Content Filter Dialect is supported by DUT. If **Event Service/Message Content Filter/ONVIF Message Content Filter Dialect** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- i. Event Handling feature category:
 - Message Content Filter (Event)
 - ONVIF Message Content Filter Dialect (Event)
6. Check that Media2 Service is supported by the DUT. If **Media2 Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise:
- 6.1. It is determined that the following features are supported by the DUT:
- i. Capabilities feature category:
 - GetServiceCapabilities (Media 2)
 - ii. Media Profile Management feature category:
 - CreateProfile (Media 2)
 - DeleteProfile (Media 2)
 - GetVideoSourceConfigurations (Media 2)
 - iii. Video Streaming feature category:
 - Ready-to-use Media Profile for streaming H.264 or H.265 video per video source (Media 2)

- GetProfiles (Media 2)
 - Streaming over RTP/UDP (Streaming)
 - Streaming over RTP/RTSP/HTTP/TCP (Streaming)
- iv. Configuration of Video Profile feature category:
- GetProfiles (Media 2)
 - GetVideoSourceConfigurations (Media 2)
 - AddConfiguration (Video Source Configuration) (Media 2)
 - RemoveConfiguration (Video Source Configuration) (Media 2)
- v. Video Source Configuration feature category:
- GetVideoSourceConfigurations (Media 2)
 - GetVideoSourceConfigurationOptions (Media 2)
 - SetVideoSourceConfiguration (Media 2)
- vi. Metadata Streaming feature category:
- GetProfiles (Media 2)
- vii. Configuration of Metadata Profile feature category:
- GetProfiles (Media 2)
 - GetMetadataConfigurations (Media 2)
 - AddConfiguration (Metadata Configuration) (Media 2)
 - RemoveConfiguration (Metadata Configuration) (Media 2)
- viii. Metadata Configuration feature category:
- GetMetadataConfigurations (Media 2)
 - GetMetadataConfigurationOptions (Media 2)
 - SetMetadataConfiguration (Media 2)
- ix. Configuration of On-Screen Display (OSD) feature category:

- GetVideoSourceConfigurations (Media 2)
- 6.2. Check that Video Encoder Configuration is supported by the DUT. If **Media2 Service/Video** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- i. Media Profile Management feature category:
 - GetVideoEncoderInstances (Media 2)
 - ii. Configuration of Video Profile feature category:
 - AddConfiguration (Video Encoder Configuration) (Media 2)
 - GetVideoEncoderConfigurations (Media 2)
 - RemoveConfiguration (Video Encoder Configuration) (Media 2)
 - iii. Video Encoder Configuration feature category:
 - GetVideoEncoderConfigurations (Media 2)
 - GetVideoEncoderConfigurationOptions (Media 2)
 - SetVideoEncoderConfiguration (Media 2)
- 6.3. Check that tns1:Media/ProfileChanged event is supported by the DUT. If **Media2 Service/Media2 Events/Media/ProfileChanged** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- i. Media Profile Management category:
 - tns1:Media/ProfileChanged (Event)
 - ii. Configuration of Video Profile category:
 - tns1:Media/ProfileChanged (Event)
 - iii. Configuration of Metadata Profile category:
 - tns1:Media/ProfileChanged (Event)

6.4. Check that `tns1:Media/ConfigurationChanged` event is supported by the DUT. If **Media2 Service/Media2 Events/Media/ConfigurationChanged** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Video Source Configuration category:

- `tns1:Media/ConfigurationChanged` (Event)

ii. Video Encoder Configuration category:

- `tns1:Media/ConfigurationChanged` (Event)

iii. Metadata Configuration category:

- `tns1:Media/ConfigurationChanged` (Event)

6.5. Check that RTSP streaming is supported by the DUT. If **Media2 Service/Real-time Streaming** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise:

6.5.1. It is determined that the following features are supported by the DUT:

i. Video Streaming feature category:

- `GetStreamUri` (Media 2)
- Video Streaming using RTSP (Streaming)
- Streaming over RTP/UDP (Streaming)
- Streaming over RTP/RTSP/HTTP/TCP (Streaming)
- `SetSynchronizationPoint` (Media 2)

6.5.2. Check that Video Streaming over RTP/RTSP/HTTPS is supported by the DUT. If **Media2 Service/Real-time Streaming/RTP/RTSP/HTTPS** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Video Streaming feature category:

- Streaming over RTP/RTSP/HTTPS/TCP (Streaming)

- 6.5.3. Check that Video Streaming over RTP/UDP Multicast is supported by the DUT. If **Media2 Service/Real-time Streaming/RTP-Multicast/UDP** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Video Streaming feature category:
 - Streaming over RTP/UDP Multicast (Streaming)
- 6.5.4. Check that Video Streaming over RTP/RTSP/TCP/WebSocket is supported by the DUT. If **Media2 Service/RTSP Web Socket** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Video Streaming feature category:
 - Streaming over RTP/RTSP/TCP/WebSocket (Streaming)
- 6.6. Check that H.264 encoding is supported by the DUT. If **Media2 Service/Video/H.264** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Video Streaming feature category:
 - H.264 Encoding (Media 2)
- 6.7. Check that H.265 encoding is supported by the DUT. If **Media2 Service/Video/H.264** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Video Streaming feature category:
 - H.265 Encoding (Media 2)
- 6.8. Check that H.264 encoding or H.265 encoding are supported by the DUT. If both **Media2 Service/Video/H.264** and **Media2 Service/Video/H.265** are regarded as unsupported by the DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed.
- 6.9. Check that JPEG Snapshot is supported by the DUT. If **Media2 Service/Snapshot URI** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- i. JPEG Snapshot feature category:

- GetSnapshotUri (Media 2)

6.10. Check that Metadata is supported by the DUT. If **Media2 Service/Metadata** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise:

6.10.1. It is determined that the following features are supported by the DUT:

- i. Metadata Streaming feature category:
 - GetStreamUri (Media 2)
 - Metadata Streaming using RTSP (Streaming)
 - Streaming over RTP/UDP (Streaming)
 - Streaming over RTP/RTSP/HTTP/TCP (Streaming)
 - SetSynchronizationPoint (Media 2)

6.10.2. Check that Metadata Streaming over RTP/RTSP/HTTPS is supported by the DUT. If **Media2 Service/Real-time Streaming/RTP/RTSP/HTTPS** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Metadata Streaming feature category:
 - Streaming over RTP/RTSP/HTTPS/TCP (Streaming)

6.10.3. Check that Metadata Streaming over RTP/UDP Multicast is supported by the DUT. If **Media2 Service/Real-time Streaming/RTP-Multicast/UDP** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Metadata Streaming feature category:
 - Streaming over RTP/UDP Multicast (Streaming)

6.10.4. Check that Metadata Streaming over RTP/RTSP/TCP/WebSocket is supported by the DUT. If **Media2 Service/RTSP Web Socket** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Metadata Streaming feature category:
 - Streaming over RTP/RTSP/TCP/WebSocket (Streaming)

6.11. Check that Configuration of On-Screen Display is supported by the DUT. If **Media2 Service/OSD** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise:

6.11.1. It is determined that the following features are supported by the DUT:

i. Configuration of On-Screen Display (OSD) feature category:

- CreateOSD (Media 2)
- DeleteOSD (Media 2)
- GetOSDs (Media 2)
- GetOSDOptions (Media 2)
- SetOSD (Media 2)

6.11.2. Check that Text Configuration of On-Screen Display is supported by the DUT. If **Media2 Service/OSD/Text** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Configuration of On-Screen Display (OSD) feature category:

- CreateOSD, text (Media 2)

6.11.3. Check that Image Configuration of On-Screen Display is supported by the DUT. If **Media2 Service/OSD/Image** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Configuration of On-Screen Display (OSD) feature category:

- CreateOSD, image (Media 2)

6.12. Check that Video Source Mode is supported by the DUT. If **Media2 Service/Video Source Mode** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Video Source Mode feature category:

- GetVideoSourceModes (Media 2)
- SetVideoSourceMode (Media 2)

6.13. Check Audio features. If **Media2 Service/Audio** is regarded as supported by DUT:

6.13.1. It is determined that the following features are supported by the DUT:

- i. Audio Streaming feature category:
 - GetProfiles (Media 2)
 - GetStreamUri (Media 2)
 - Audio Streaming using RTSP (Streaming)
 - Streaming over RTP/UDP (Streaming)
 - Streaming over RTP/RTSP/HTTP/TCP (Streaming)
- ii. Configuration of Audio Profile feature category:
 - GetProfiles (Media 2)
 - GetAudioSourceConfigurations (Media 2)
 - AddConfiguration, Audio Source Configuration (Media 2)
 - AddConfiguration, Audio Encoder Configuration (Media 2)
 - GetAudioEncoderConfigurations (Media 2)
 - RemoveConfiguration, Audio Source Configuration (Media 2)
 - RemoveConfiguration, Audio Encoder Configuration (Media 2)
- iii. Audio Encoder Configuration feature category:
 - GetAudioEncoderConfigurations (Media 2)
 - GetAudioEncoderConfigurationOptions (Media 2)
 - SetAudioEncoderConfiguration (Media 2)

6.13.2. If **Media2 Service/Media2 Events/Media/ProfileChanged** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:

- i. Configuration of Audio Profile feature category:
 - tns1:Media/ProfileChanged (Event)

6.13.3. If **Media2 Service/Media2 Events/Media/ConfigurationChanged** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:

i. Audio Encoder Configuration feature category:

- tns1:Media/ConfigurationChanged (Event)

6.13.4. Check that Audio Streaming over RTP/RTSP/HTTPS is supported by the DUT. If **Media2 Service/Real-time Streaming/RTP/RTSP/HTTPS** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Audio Streaming feature category:

- Streaming over RTP/RTSP/HTTPS/TCP (Streaming)

6.13.5. Check that Audio Streaming over RTP/UDP Multicast is supported by the DUT. If **Media2 Service/Real-time Streaming/RTP-Multicast/UDP** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Audio Streaming feature category:

- Streaming over RTP/UDP Multicast (Streaming)

6.13.6. Check that Audio Streaming over RTP/RTSP/TCP/WebSocket is supported by the DUT. If **Media2 Service/RTSP Web Socket** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Audio Streaming feature category:

- Streaming over RTP/RTSP/TCP/WebSocket (Streaming)

6.13.7. Check that G.711 μ -law encoding is supported by the DUT. If **Media2 Service/Audio/G.711** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Audio Streaming feature category:

- G.711 μ -law Encoding (Media 2)

6.13.8. Check that AAC encoding is supported by the DUT. If **Media2 Service/Audio/AAC** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Audio Streaming feature category:

- AAC Encoding (Media 2)

6.13.9. Check that G.711 μ -law encoding or AAC encoding are supported by the DUT. If both **Media2 Service/Audio/G.711** and **Media2 Service/Audio/AAC** are regarded as unsupported by the DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed.

6.14. Check Audio Output features. If **Media2 Service/Audio Output** is regarded as supported by DUT:

6.14.1. It is determined that the following features are supported by the DUT:

i. Audio Output Configuration feature category:

- GetAudioOutputConfigurations (Media 2)
- GetAudioOutputConfigurationOptions (Media 2)
- SetAudioOutputConfiguration (Media 2)

ii. Audio Output Streaming feature category:

- GetProfiles (Media 2)
- GetStreamUri (Media 2)
- Streaming using RTSP - Back Channel (Streaming)
- Streaming over RTP/UDP (Streaming)
- Streaming over RTP/RTSP/HTTP/TCP (Streaming)

iii. Configuration of Audio Output Profile feature category:

- GetProfiles (Media 2)
- GetAudioOutputs (Media 2)
- GetAudioOutputConfigurations (Media 2)
- GetAudioDecoderConfigurations (Media 2)

- AddConfiguration, Audio Output Configuration (Media 2)
- AddConfiguration, Audio Decoder Configuration (Media 2)
- RemoveConfiguration, Audio Output Configuration (Media 2)
- RemoveConfiguration, Audio Decoder Configuration (Media 2)

6.14.2. If **Media2 Service/Media2 Events/Media/ProfileChanged** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:

- i. Configuration of Audio Output Profile feature category:
 - tns1:Media/ProfileChanged (Event)

6.14.3. If **Media2 Service/Media2 Events/Media/ConfigurationChanged** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:

- i. Audio Output Configuration feature category:
 - tns1:Media/ConfigurationChanged (Event)

6.14.4. Check that Audio Output Streaming over RTP/RTSP/HTTPS is supported by the DUT. If **Media2 Service/Real-time Streaming/RTP/RTSP/HTTPS** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Audio Output Streaming feature category:
 - Streaming over RTP/RTSP/HTTPS/TCP (Streaming)

6.14.5. Check that Audio Output Streaming over RTP/RTSP/TCP/WebSocket is supported by the DUT. If **Media2 Service/RTSP Web Socket** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Audio Output Streaming feature category:
 - Streaming over RTP/RTSP/TCP/WebSocket (Streaming)

6.14.6. Check that G.711 μ -law decoding is supported by the DUT. If **Media2 Service/Audio Outputs/G.711** is not supported by the DUT, then it is determined that

[ONVIF Profile T] is not supported by DUT and certification will be failed.
Otherwise, it is determined that the following feature is supported:

i. Audio Streaming feature category:

- G.711 μ -law Decoding (Media 2)

6.14.7. Check that AAC decoding is supported by the DUT. If **Media2 Service/Audio Outputs/AAC** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Audio Streaming feature category:

- AAC Decoding (Media 2)

7. Check that Imaging Service is supported by the DUT. If **Imaging Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise:

7.1. It is determined that the following features are supported by the DUT:

i. Capabilities feature category:

- GetServiceCapabilities (Imaging)

ii. Imaging Settings feature category:

- GetImagingSettings (Imaging)
- GetOptions (Imaging)
- SetImagingSettings (Imaging)

7.2. Check that tns1:VideoSource/ImageTooBlurry event is supported by the DUT. If **Imaging Service/Tampering Events/Image Too Blurry** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Tampering feature category:

- tns1:VideoSource/ImageTooBlurry (Event)

7.3. Check that tns1:VideoSource/ImageTooDark event is supported by the DUT. If **Imaging Service/Tampering Events/Image Too Dark** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Tampering feature category:

- tns1:VideoSource/ImageTooDark (Event)
- 7.4. Check that tns1:VideoSource/ImageTooBright event is supported by the DUT. If **Imaging Service/Tampering Events/Image Too Bright** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Tampering feature category:
 - tns1:VideoSource/ImageTooBright (Event)
- 7.5. Check that tns1:VideoSource/GlobalSceneChange event is supported by the DUT. If **Imaging Service/Tampering Events/Global Scene Change** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Tampering feature category:
 - tns1:VideoSource/GlobalSceneChange (Event)
- 7.6. Check that at least one Tampering Event is supported by the DUT. If all **Imaging Service/Tampering Events/Image Too Blurry**, **Imaging Service/Tampering Events/Image Too Dark**, **Imaging Service/Tampering Events/Image Too Bright**, and **Imaging Service/Tampering Events/Global Scene Change** are regarded as unsupported by the DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed.
- 7.7. Check that Focus Control is supported by the DUT. If **Imaging Service/Focus Control** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Focus Control feature category:
 - GetMoveOptions (Imaging)
 - Move (Imaging)
 - Stop (Imaging)
 - GetStatus (Imaging)
8. Check that Device IO Service is supported by the DUT. If **Device IO Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise:
- 8.1. It is determined that the following features are supported by the DUT:

- i. Capabilities feature category:
 - GetServiceCapabilities (DeviceIO)
- 8.2. If **Media2 Service** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:
 - i. Configuration of Video Profile feature category:
 - GetVideoSources (DeviceIO)
 - ii. Video Source Mode feature category:
 - GetVideoSources (DeviceIO)
- 8.3. If **Imaging Service** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:
 - i. Imaging Settings feature category:
 - GetVideoSources (DeviceIO)
 - ii. Focus Control feature category:
 - GetVideoSources (DeviceIO)
- 8.4. If **Media2 Service/Audio** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:
 - i. Configuration of Audio Profile feature category:
 - GetAudioSources (DeviceIO)
- 8.5. If **Media2 Service/Audio Outputs** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:
 - i. Configuration of Audio Output Profile feature category:
 - GetAudioOutputs (DeviceIO)
- 8.6. Check that Relay Outputs are supported by the DUT. If **DeviceIO Service/Relay outputs** is regarded as supported by DUT:
 - 8.6.1. It is determined that the following features are supported by the DUT:
 - i. Relay Outputs feature category:

- GetRelayOutputs (DeviceIO)
- SetRelayOutputSettings (DeviceIO)
- SetRelayOutputState (DeviceIO)
- tns1:Device/Trigger/Relay (Event)

8.6.2. Check that Relay Output Options is supported by the DUT. If **DeviceIO Service \Relay outputs\Relay Output Options** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Relay Outputs feature category:

- GetRelayOutputOptions (DeviceIO)

8.7. Check that Relay Outputs are supported by the DUT. If **DeviceIO Service/Digital Inputs** is regarded as supported by DUT:

8.7.1. It is determined that the following features are supported by the DUT:

i. Digital Inputs feature category:

- GetDigitalInputs (DeviceIO)
- SetDigitalInputConfigurations (DeviceIO)
- tns1:Device/Trigger/DigitalInput (Event)

8.7.2. Check that Digital Input Options is supported by the DUT. If **DeviceIO Service/ Digital Inputs/Digital Input Options** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Digital Inputs feature category:

- GetDigitalInputConfigurationOptions (DeviceIO)

9. Check that PTZ Service is supported by the DUT. If **PTZ Service** is regarded as supported by the DUT, then:

9.1. It is determined that the following features are supported by the DUT:

- i. Capabilities feature category:
 - GetServiceCapabilities (PTZ)
 - ii. PTZ Configuration feature category:
 - GetNodes (PTZ)
 - GetNode (PTZ)
 - GetConfigurationOptions (PTZ)
 - SetConfiguration (PTZ)
- 9.2. If **Media2 Service** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:
- i. Configuration of PTZ Profile feature category:
 - GetProfiles (Media 2)
 - AddConfiguration, PTZ Configuration (Media 2)
 - RemoveConfiguration, PTZ Configuration (Media 2)
- 9.3. If **Media2 Service/Media2 Events/Media/ProfileChanged** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:
- i. Configuration of PTZ Profile feature category:
 - tns1:Media/ProfileChanged (Event)
- 9.4. If **Media2 Service/Media2 Events/Media/ConfigurationChanged** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:
- i. Configuration of PTZ Configuration feature category:
 - tns1:Media/ConfigurationChanged (Event)
- 9.5. Check that GetCompatibleConfigurations command is supported by the DUT. If **PTZ Service\Get Compatible Configuration** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- i. Configuration of PTZ Profile feature category:

- GetCompatibleConfigurations (PTZ)

9.6. Check that Absolute PTZ Movement is supported by the DUT. If **PTZ Service/Absolute Move** is regarded as supported by DUT:

9.6.1. It is determined that the following features are supported by the DUT:

i. Absolute PTZ Move feature category:

- Ready-to-use Media Profile for PTZ control per PTZ node
- GetStatus (PTZ)
- AbsoluteMove (PTZ)
- <http://www.onvif.org/ver10/tptz/PanTiltSpaces/SphericalPositionSpaceDegrees> (PTZ)
- <http://www.onvif.org/ver10/tptz/PanTiltSpaces/PositionGenericSpace> (PTZ)
- <http://www.onvif.org/ver10/tptz/ZoomSpaces/PositionGenericSpace> (PTZ)

9.6.2. Check that Move Status is supported by the DUT. If **PTZ Service/Move Status** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Absolute PTZ Move feature category:

- MoveStatus capability (PTZ)

9.6.3. Check that Status Position is supported by the DUT. If **PTZ Service/Status Position** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Absolute PTZ Move feature category:

- StatusPosition capability (PTZ)

9.7. Check that Continuous PTZ Movement is supported by the DUT. If **PTZ Service/Continuous Move** is regarded as supported by DUT:

9.7.1. It is determined that the following features are supported by the DUT:

i. Continuous PTZ Move feature category:

- Ready-to-use Media Profile for PTZ control per PTZ node
- GetStatus (PTZ)
- ContinuousMove (PTZ)
- <http://www.onvif.org/ver10/tptz/PanTiltSpaces/VelocityGenericSpace> (PTZ)
- <http://www.onvif.org/ver10/tptz/ZoomSpaces/VelocityGenericSpace> (PTZ)

9.7.2. Check that Move Status is supported by the DUT. If **PTZ Service/Move Status** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Continuous PTZ Move feature category:

- MoveStatus capability (PTZ)

9.8. Check that PTZ Presets are supported by the DUT. If **PTZ Service\Presets** is regarded as supported by DUT, it is determined that the following features are supported by the DUT:

i. PTZ Presets feature category:

- MaximumNumberOfPresets capability is supported and value is not less than 1 (PTZ)
- GetPresets (PTZ)
- SetPreset (PTZ)
- GotoPreset (PTZ)
- RemovePreset (PTZ)

9.9. Check that PTZ Home Position is supported by the DUT. If **PTZ Service\Home Position** is regarded as supported by DUT, it is determined that the following features are supported by the DUT:

i. PTZ Home Position feature category:

- HomeSupported capability = true (PTZ)
- SetHomePosition (PTZ)
- GotoHomePosition (PTZ)

10. Check that Analytics Service is supported by the DUT. If **Analytics Service** is regarded as supported by the DUT, then:

10.1. It is determined that the following features are supported by the DUT:

- i. Capabilities feature category:
 - GetServiceCapabilities (Analytics)

10.2. If **Media2 Service** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:

- i. Configuration of Analytics Profile feature category:
 - GetProfiles (Media 2)
 - GetAnalyticsConfigurations (Media 2)
 - AddConfiguration, Analytics Configuration (Media 2)
 - RemoveConfiguration, Analytics Configuration (Media 2)

10.3. If **Media2 Service/Media2 Events/Media/ProfileChanged** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:

- i. Configuration of Analytics Profile feature category:
 - tns1:Media/ProfileChanged (Event)

10.4. Check that Motion Region Detector Rule is supported by the DUT. If **Analytics Service/Rule Engine/Motion Region Detector Rule** is regarded as supported by DUT:

10.4.1. It is determined that the following features are supported by the DUT:

- i. Motion Region Detector feature category:
 - GetSupportedRules (Analytics)
 - GetRules (Analytics)

- GetRuleOptions (Analytics)
- CreateRules (Analytics)
- ModifyRules (Analytics)
- DeleteRules (Analytics)
- tns1:RuleEngine/MotionRegionDetector/Motion (Event)

10.4.2. Check that Rule Options is supported by the DUT. If **Analytics Service/Rule Engine/Rule Options** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile T] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

- i. Motion Region Detector feature category:
 - GetRuleOptions (Analytics)

8 Profile M Conformance

8.1 Feature category classification for ONVIF Profile M

In order for ONVIF Device Test Tool to conduct conformance testing toward [ONVIF Profile M], it would need to identify whether DUT implements the expected feature set.

This section classifies supported features as multiple categories that are related to [ONVIF Profile M] conformance. Those category classifications will be used to do some preliminary checking prior to the test case execution and they will be used to determine whether DUT can be considered [ONVIF Profile M] conformant device.

The following discovery scope is defined as the scope that signals that DUT is [ONVIF Profile M] product.

Table 8.1. Profile M Discovery Scope

onvif://www.onvif.org/Profile/M

The following table shows the classified feature categories based on commands and/or functional blocks that are referenced by DUT.

Table 8.2. Profile M Features Categories

Profile Mandatory Features	
User authentication	HTTP Digest Authentication
	RTSP Digest Authentication
Get services	GetServices (Device Management)
	GetServiceCapabilities (Device Management)
	GetServiceCapabilities (Analytics)
	GetServiceCapabilities (Media 2)
	GetServiceCapabilities (Event)
Discovery	WS-Discovery
	GetDiscoveryMode (Device Management)
	SetDiscoveryMode (Device Management)
	GetScopes (Device Management)
	SetScopes (Device Management)
	AddScopes (Device Management)
	RemoveScopes (Device Management)

System	GetDeviceInformation (Device Management)
	GetSystemDateAndTime (Device Management)
	System Reboot (Device Management)
Metadata Streaming	Ready-to-use Media Profile for streaming metadata (Media2)
	GetProfiles (Media 2)
	GetStreamUri (Media 2)
	Metadata Streaming using RTSP (Streaming)
	Streaming over RTP/UDP (Streaming)
	Streaming over RTP/RTSP/HTTP/TCP (Streaming)
	Streaming over RTP/RTSP/HTTPS/TCP (Streaming)
	SetSynchronizationPoint (Media 2)
Metadata information	GetSupportedMetadata (Analytics)
Configuration of Metadata Profile	GetProfiles (Media 2)
	GetVideoSourceConfigurations (Media 2)
	GetMetadataConfigurations (Media 2)
	AddConfiguration (Video Source Configuration) (Media 2)
	AddConfiguration (Metadata Configuration) (Media 2)
	RemoveConfiguration (Video Source Configuration) (Media 2)
	RemoveConfiguration (Metadata Configuration) (Media 2)
	tns1:Media/ProfileChanged (Event)
Metadata Configuration	GetMetadataConfigurations (Media 2)
	GetMetadataConfigurationOptions (Media 2)
	SetMetadataConfiguration (Media 2)
	tns1:Media/ConfigurationChanged (Event)
Configuration of Analytics profile	GetProfiles (Media 2)
	GetAnalyticsConfigurations (Media 2)
	AddConfiguration (Analytics Configuration) (Media 2)

	RemoveConfiguration (Analytics Configuration) (Media 2)
	tns1:Media/ProfileChanged (Event)
Analytics Module configuration	GetSupportedAnalyticsModules (Analytics)
	GetAnalyticsModules (Analytics)
	CreateAnalyticsModules (Analytics)
	DeleteAnalyticsModules (Analytics)
	GetAnalyticsModuleOptions (Analytics)
	ModifyAnalyticsModules (Analytics)
Profile Conditional Features	
Media Profile Management	CreateProfile (Media 2)
	DeleteProfile (Media 2)
	tns1:Media/ProfileChanged (Event)
Video Streaming	Ready-to-use Media Profile for streaming video (Media 2)
	GetProfiles (Media 2)
	GetStreamUri (Media 2)
	Video Streaming using RTSP (Streaming)
	H.264 Encoding (Media 2)
	H.265 Encoding (Media 2)
	Streaming over RTP/UDP (Streaming)
	Streaming over RTP/RTSP/HTTP/TCP (Streaming)
	Streaming over RTP/RTSP/HTTPS/TCP (Streaming)
	SetSynchronizationPoint (Media 2)
Image sending	Sending image via image URI (Analytics)
	Sending base64 encoding image data (Analytics)
Event handling using pull points	SetSynchronizationPoint (Event)
	CreatePullPointSubscription (Event)
	PullMessage (Event)
	GetEventProperties (Event)
	Unsubscribe (Event)
	TopicFilter (Event)

	MaxPullPoint capability is supported and value is not less than 2 (Event)
Event handling via MQTT	SetSynchronizationPoint (Event)
	GetEventBrokers (Event)
	AddEventBroker (Event)
	DeleteEventBroker (Event)
	GetEventProperties (Event)
	MQTT events via mqtt protocol
	MQTT events via mqttts protocol
	MQTT events via ws protocol
	MQTT events via wss protocol
	TopicFilter (Event)
Rule configuration	GetSupportedRules (Analytics)
	GetRules (Analytics)
	CreateRules (Analytics)
	DeleteRules (Analytics)
	GetRuleOptions (Analytics)
	ModifyRules (Analytics)
Object classification	MetadataStream /VideoAnalyticsStream/Frame/ Object/ Appearance/Class/Type (Analytics)
Human face metadata	MetadataStream /VideoAnalyticsStream/Frame/ Object/ Appearance/HumanFace (Analytics)
Human Body metadata	MetadataStream /VideoAnalyticsStream/Frame/ Object/ Appearance/HumanBody (Analytics)
Vehicle metadata	MetadataStream /VideoAnalyticsStream/Frame/ Object/ Appearance/VehicleInfo (Analytics)
License plate metadata	MetadataStream /VideoAnalyticsStream/Frame/ Object/ Appearance/LicensePlateInfo (Analytics)
GeoLocation metadata	MetadataStream/VideoAnalyticsStream/Frame/ Object/ Appearance/GeoLocation (Analytics)
Face recognition event	GetEventProperties (Event)
	GetSupportedRules (Analytics)
	FaceRecognition Rule (Analytics)
	tns1:RuleEngine/Recognition/Face (Event)

License plate recognition event	GetEventProperties (Event)
	GetSupportedRules (Analytics)
	License plate recognition Rule (Analytics)
	tns1:RuleEngine/Recognition/LicensePlate (Event)
Line crossing counter	GetEventProperties (Event)
	GetSupportedRules (Analytics)
	Line Crossing Counting Rule (Analytics)
	tns1:RuleEngine/CountAggregation/Counter (Event)

8.2 Profile M Support Check

Preliminary checking for feature discovery will be performed prior to the test execution. For the details of the preliminary feature discovery, refer to [ONVIF Feature Discovery].

According to the result of test case execution, final determination of [ONVIF Profile M] support toward DUT is performed based on the following procedure.

Procedure:

1. Check that scope list contains the scope given in [Table 8.1](#). If there is no such scope in the scope list of the DUT, then it is determined that [ONVIF Profile M] is not supported.
2. Check Capabilities feature.
 - a. Check that GetServices command is supported by the DUT. If **Device Service/Capabilities/GetServices** is not supported by the DUT, then it is determined that [ONVIF Profile M] is not supported by DUT and certification will be failed. Otherwise, it is determined that Capabilities category is supported with the following features included:
 - i. Get services feature category:
 - GetServices (Device Management)
 - GetServiceCapabilities (Device Management)
3. Check that Discovery is supported by the DUT. If **Discovery** feature is regarded as supported by the DUT
 - 3.1. Check Discovery Types support. If **Discovery/Types/tds:Device** is not supported by the DUT, then it is determined that [ONVIF Profile M] is not supported by DUT and certification will be failed.

- 3.2. It is determined that the following features are supported by the DUT:
- i. Discovery feature category:
 - WS-Discovery
 - GetDiscoveryMode (Device Management)
 - SetDiscoveryMode (Device Management)
 - SetScopes (Device Management)
 - AddScopes (Device Management)
 - RemoveScopes (Device Management)
4. Check that Digest Authentication is supported by the DUT. If **Security/Digest** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- i. User authentication feature category:
 - HTTP Digest Authentication
 - RTSP Digest Authentication
5. Check Device Management Service related features:
- 5.1. The following features are supported by the DUT, because these are mandatory features for any ONVIF device implementation:
- i. Discovery feature category:
 - GetScopes (Device Management)
 - ii. System feature category:
 - GetDeviceInformation (Device Management)
 - GetSystemDateAndTime (Device Management)
 - Reboot (Device Management)
6. Check that Media2 Service is supported by the DUT. If **Media2 Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed. Otherwise:

6.1. It is determined that the following features are supported by the DUT:

- i. Get services feature category:
 - GetServiceCapabilities (Media 2)
- ii. Metadata Streaming feature category:
 - GetProfiles (Media 2)
- iii. Configuration of Metadata profile feature category:
 - GetProfiles (Media 2)
 - GetVideoSourceConfigurations (Media 2)
 - AddConfiguration (Video Source Configuration) (Media 2)
 - RemoveConfiguration (Video Source Configuration) (Media 2)
- iv. Configuration of Analytics profile feature category:
 - GetProfiles (Media 2)
- v. Media Profile Management feature category:
 - CreateProfile (Media 2)
 - DeleteProfile (Media 2)

6.2. Check that Metadata is supported by the DUT. If **Media2 Service/Metadata** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed. Otherwise:

6.2.1. It is determined that the following features are supported by the DUT:

- i. Configuration of Metadata profile feature category:
 - GetMetadataConfigurations (Media 2)
 - AddConfiguration (Metadata Configuration) (Media 2)
 - RemoveConfiguration (Metadata Configuration) (Media 2)
- ii. Metadata Configuration feature category:
 - GetMetadataConfigurations (Media 2)

- GetMetadataConfigurationOptions (Media 2)
- SetMetadataConfiguration (Media 2)

6.2.2. Check that Metadata RTSP streaming is supported by the DUT. If **Media2 Service/Real-time Streaming** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed. Otherwise:

6.2.2.1. It is determined that the following features are supported by the DUT:

i. Metadata Streaming feature category:

- Ready-to-use Media Profile for streaming metadata (Media2)
- GetStreamUri (Media 2)
- Metadata Streaming using RTSP (Streaming)
- Streaming over RTP/UDP (Streaming)
- Streaming over RTP/RTSP/HTTP/TCP (Streaming)
- SetSynchronizationPoint (Media2)

6.2.2.2. Check that Metadata Streaming over RTP/RTSP/HTTPS is supported by the DUT. If **Media2 Service/Real-time Streaming/RTP/RTSP/HTTPS** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Metadata Streaming feature category:

- Streaming over RTP/RTSP/HTTPS/TCP (Streaming)

6.3. Check that Analytics Configuration is supported by the DUT. If **Media2 Service/Analytics** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed. Otherwise:

6.3.1. It is determined that the following features are supported by the DUT:

i. Configuration of Analytics profile feature category:

- GetAnalyticsConfigurations (Media 2)
- AddConfiguration (Analytics Configuration) (Media 2)

- RemoveConfiguration (Analytics Configuration) (Media 2)

6.4. Check that Video Encoder Configuration is supported by the DUT. If **Media2 Service/Video** is regarded as supported by DUT, it is determined that the following features are supported by the DUT::

6.4.1. Check that H.264 encoding is supported by the DUT. If **Media2 Service/Video/H.264** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Video Streaming feature category:

- H.264 Encoding (Media 2)

6.4.2. Check that H.265 encoding is supported by the DUT. If **Media2 Service/Video/H.265** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Video Streaming feature category:

- H.265 Encoding (Media 2)

6.4.3. Check that H.264 encoding or H.265 encoding is supported by the DUT. If both **Media2 Service/Video/H.264** and **Media2 Service/Video/H.265** are regarded as unsupported by the DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed.

6.4.4. Check that Video RTSP streaming is supported by the DUT. If **Media2 Service/Real-time Streaming** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed. Otherwise:

6.4.4.1. It is determined that the following features are supported by the DUT:

i. Video Streaming feature category:

- Ready-to-use Media Profile for streaming video (Media2)
- GetStreamUri (Media 2)
- Video Streaming using RTSP (Streaming)
- Streaming over RTP/UDP (Streaming)
- Streaming over RTP/RTSP/HTTP/TCP (Streaming)

- SetSynchronizationPoint (Media2)

6.4.5. Check that Video Streaming over RTP/RTSP/HTTPS is supported by the DUT. If **Media2 Service/Real-time Streaming/RTP/RTSP/HTTPS** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Video Streaming feature category:

- Streaming over RTP/RTSP/HTTPS/TCP (Streaming)

7. Check that Analytics Service is supported by the DUT. If **Analytics Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed. Otherwise:

7.1. It is determined that the following features are supported by the DUT:

- i. Get services feature category:

- GetServiceCapabilities (Analytics)

7.2. Check that Metadata information is supported by the DUT. If **Analytics Service/Supported Metadata** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed. Otherwise:

7.2.1. It is determined that the following features are supported by the DUT:

- i. Metadata information feature category:

- GetSupportedMetadata (Analytics)

7.2.2. Check that Object classification is supported by the DUT. If **Analytics Service/Supported Metadata/Metadata Types/Object Classification** is regarded as supported by DUT

7.2.2.1. It is determined that the following features are supported by the DUT:

- i. Object classification feature category:

- MetadataStream /VideoAnalyticsStream/Frame/Object/
Appearance/Class/Type (Analytics)

7.2.3. Check that Human face metadata is supported by the DUT. If **Analytics Service/Supported Metadata/Metadata Types/Human Face** is regarded as supported by DUT

7.2.3.1. It is determined that the following features are supported by the DUT:

i. Human face metadata feature category:

- MetadataStream /VideoAnalyticsStream/Frame/Object/
Appearance/HumanFace (Analytics)

7.2.4. Check that Human Body metadata is supported by the DUT. If **Analytics Service/Supported Metadata/Metadata Types/Human Body** is regarded as supported by DUT

7.2.4.1. It is determined that the following features are supported by the DUT:

i. Human face metadata feature category:

- MetadataStream /VideoAnalyticsStream/Frame/Object/
Appearance/HumanBody (Analytics)

7.2.5. Check that Vehicle metadata is supported by the DUT. If **Analytics Service/Supported Metadata/Metadata Types/Vehicle Info** is regarded as supported by DUT

7.2.5.1. It is determined that the following features are supported by the DUT:

i. Vehicle metadata feature category:

- MetadataStream /VideoAnalyticsStream/Frame/Object/
Appearance/VehicleInfo (Analytics)

7.2.6. Check that License plate metadata is supported by the DUT. If **Analytics Service/Supported Metadata/Metadata Types/License Plate Info** is regarded as supported by DUT

7.2.6.1. It is determined that the following features are supported by the DUT:

i. License plate metadata feature category:

- MetadataStream /VideoAnalyticsStream/Frame/Object/
Appearance/LicensePlateInfo (Analytics)

7.2.7. Check that Geo Location metadata is supported by the DUT. If **Analytics Service/Supported Metadata/Geo Location** is regarded as supported by DUT

7.2.7.1. It is determined that the following features are supported by the DUT:

i. GeoLocation metadata feature category:

- MetadataStream/VideoAnalyticsStream/Frame/Object/
Appearance/GeoLocation (Analytics)

7.3. Check that Analytics Module is supported by the DUT. If **Analytics Service/Analytics Modules** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed. Otherwise:

7.3.1. It is determined that the following features are supported by the DUT:

i. Analytics Module configuration feature category:

- GetSupportedAnalyticsModules (Analytics)
- GetAnalyticsModules (Analytics)
- CreateAnalyticsModules (Analytics)
- DeleteAnalyticsModules (Analytics)
- Check that Analytics Module Options is supported by the DUT. If **Analytics Service/Analytics Modules/Analytics Module Options** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Analytics Module configuration feature category:

- GetAnalyticsModuleOptions (Analytics)
- ModifyAnalyticsModules (Analytics)

7.4. Check that Image sending is supported by the DUT. If **Analytics Service/Image Sending** is regarded as supported by the DUT:

7.4.1. Check that sending image via image URI is supported by the DUT. If either **Analytics Service/Image Sending/Local Storage Image Sending Type** or **Analytics Service/Image Sending/Remote Storage Image Sending Type**

is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Image sending feature category:
 - Sending image via image URI (Analytics)

7.4.2. Check that sending base64 encoding data is supported by the DUT. If **Analytics Service/Image Sending/Embedded Image Sending Type** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Image sending feature category:
 - Sending base64 encoding image data (Analytics)

7.4.3. Check that sending image via image URI or sending base64 encoding data is supported by the DUT. If all **Analytics Service/Image Sending/Local Storage Image Sending Type** and **Analytics Service/Image Sending/Remote Storage Image Sending Type** and **Analytics Service/Image Sending/Embedded Image Sending Type** are regarded as unsupported by the DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed.

7.5. Check that Rule Engine is supported by the DUT. If **Analytics Service/Rule Engine** is regarded as supported by DUT:

7.5.1. It is determined that the following features are supported by the DUT:

- i. Rule configuration feature category:
 - GetSupportedRules (Analytics)
 - GetRules (Analytics)
 - CreateRules (Analytics)
 - DeleteRules (Analytics)

7.5.2. Check that Rule Options is supported by the DUT. If **Analytics Service/Rule Engine/Rule Options** is regarded as supported by DUT it is determined that the following features are supported by the DUT:

- i. Rule configuration feature category:
 - GetRuleOptions (Analytics)

- ModifyRules (Analytics)

7.5.3. Check that Face recognition is supported by the DUT. If **Analytics Service/Rule Engine/Face Recognition Rule** is regarded as supported by DUT it is determined that the following features are supported by the DUT:

i. Face recognition event feature category:

- GetSupportedRules (Analytics)
- FaceRecognition Rule (Analytics)
- Check that Event Service is supported by the DUT. If **Event Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed. Otherwise it is determined that the following features are supported by the DUT:

i.1. Face recognition event feature category:

- GetEventProperties (Event)
- tns1:RuleEngine/Recognition/Face (Event)

7.5.4. Check that License plate recognition is supported by the DUT. If **Analytics Service/Rule Engine/License Plate Recognition Rule** is regarded as supported by DUT it is determined that the following features are supported by the DUT:

i. License plate recognition event feature category:

- GetSupportedRules (Analytics)
- License Plate Recognition Rule (Analytics)
- Check that Event Service is supported by the DUT. If **Event Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed. Otherwise it is determined that the following features are supported by the DUT:

i.1. Face recognition event feature category:

- GetEventProperties (Event)

- tns1:RuleEngine/Recognition/LicensePlate (Event)

7.5.5. Check that Line crossing counter is supported by the DUT. If **Analytics Service/Rule Engine/Line Crossing Counting** is regarded as supported by DUT it is determined that the following features are supported by the DUT:

i. Line crossing counter feature category:

- GetSupportedRules (Analytics)
- Line Crossing Counting Rule (Analytics)
- Check that Event Service is supported by the DUT. If **Event Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed. Otherwise it is determined that the following features are supported by the DUT:

i.1. Face recognition event feature category:

- GetEventProperties (Event)
- tns1:RuleEngine/CountAggregation/Counter (Event)

8. Check that Event Service is supported by the DUT. If **Event Service** is regarded as supported by the DUT

8.1. It is determined that the following features are supported by the DUT:

i. Get services feature category:

- GetServiceCapabilities (Event)

8.2. Check that Pull-Point Notification is supported by the DUT. If **Event Service/Pull-Point Notification** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:

i. Event handling using pull points feature category:

- SetSynchronizationPoint (Event)
- CreatePullPointSubscription (Event)
- PullMessage (Event)
- Unsubscribe (Event)

- GetEventProperties (Event)
- TopicFilter (Event)
- ii. Check that at least two PullPoint subscriptions are supported by DUT. If **Event Service/GetServiceCapabilities/MaxPullPoints capability** is regarded as unsupported by DUT or it has value less than two, then it is determined that [ONVIF Profile M] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Event handling using pull points feature category:
 - MaxPullPoint capability is supported and value is not less than 2 (Event)
- 8.3. Check that MQTT is supported by the DUT. If **Event Service/Event Broker** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:
 - i. Event handling via MQTT feature category:
 - SetSynchronizationPoint (Event)
 - GetEventBrokers (Event)
 - AddEventBroker (Event)
 - DeleteEventBroker (Event)
 - GetEventProperties (Event)
 - TopicFilter (Event)
 - ii. Check that mqtt protocol is supported by DUT. If **Event Service/Event Broker/Protocols/mqtt** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile M] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Event handling via MQTT feature category:
 - MQTT events via mqtt protocol
 - iii. Check that mqttts protocol is supported by DUT. If **Event Service/Event Broker/Protocols/mqttts** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile M] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

- i. Event handling via MQTT feature category:
 - MQTT events via mqttts protocol
- iv. Check that ws protocol is supported by DUT. If **Event Service/Event Broker/Protocols/ws** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:
 - i. Event handling via MQTT feature category:
 - MQTT events via ws protocol
 - v. Check that wss protocol is supported by DUT. If **Event Service/Event Broker/Protocols/wss** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:
 - i. Event handling via MQTT feature category:
 - MQTT events via wss protocol
- 8.4. Check that tns1:Media/ProfileChanged event is supported by the DUT. If **Media2 Service/Media2 Events/Media/ProfileChanged** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Configuration of Metadata profile feature category:
 - tns1:Media/ProfileChanged (Event)
 - ii. Configuration of Analytics profile feature category:
 - tns1:Media/ProfileChanged (Event)
 - iii. Media profile management feature category:
 - tns1:Media/ProfileChanged (Event)
- 8.5. Check that tns1:Media/ConfigurationChanged event is supported by the DUT. If **Media2 Service/Media2 Events/Media/ConfigurationChanged** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile M] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Metadata configuration feature category:

- tns1:Media/ConfigurationChanged (Event)

9 Profile D Conformance

9.1 Feature Category Classification for ONVIF Profile D

In order for ONVIF Device Test Tool to conduct conformance testing toward [ONVIF Profile D], it would need to identify whether a DUT implements the expected feature set.

This section classifies supported features as multiple categories that are related to [ONVIF Profile D] conformance. Those category classifications will be used to do some preliminary checking prior to the test case execution and they will be used to determine whether DUT can be considered [ONVIF Profile D] conformant device.

The following discovery scope is defined as the scope that signals that DUT is [ONVIF Profile D] product.

Table 9.1. Profile D Discovery Scope

onvif://www.onvif.org/Profile/D

The following table shows the classified feature categories based on commands and/or functional blocks that are referenced by DUT.

Table 9.2. Profile D Features Categories

Profile Mandatory Features	
User authentication	HTTP Digest Authentication
	RTSP Digest Authentication
Capabilities	GetServices (Device Management)
	GetServiceCapabilities (Device Management)
	GetServiceCapabilities (Event)
	GetServiceCapabilities (Access Control)
	GetServiceCapabilities (Door Control)
	GetServiceCapabilities (Credential)
	MaxAccessPoints Capability (Access Control)
	MaxDoors Capability (Door Control)
	MaxPullPoint capability is supported and value is not less than 2 (Event)
	At least one of MaxAccessPoints and MaxDoors is larger than zero (Access Control or Door Control)

Discovery	WS-Discovery
	GetDiscoveryMode (Device Management)
	SetDiscoveryMode (Device Management)
	GetScopes (Device Management)
	SetScopes (Device Management)
	AddScopes (Device Management)
	RemoveScopes (Device Management)
Network Configuration	GetHostname (Device Management)
	SetHostname (Device Management)
	GetDNS (Device Management)
	SetDNS (Device Management)
	GetNetworkInterfaces (Device Management)
	SetNetworkInterfaces (Device Management)
	GetNetworkProtocols (Device Management)
	SetNetworkProtocols (Device Management)
	GetNetworkDefaultGateway (Device Management)
	SetNetworkDefaultGateway (Device Management)
System	GetDeviceInformation (Device Management)
	GetSystemDateAndTime (Device Management)
	SetSystemDateAndTime (Device Management)
	SetSystemFactoryDefault (Device Management)
	System Reboot (Device Management)
User Handling	GetUsers (Device Management)
	CreateUsers (Device Management)
	DeleteUsers (Device Management)
	SetUser (Device Management)
Event Handling	SetSynchronizationPoint (Event)
	CreatePullPointSubscription (Event)
	PullMessage (Event)
	GetEventProperties (Event)
	Unsubscribe (Event)

	TopicFilter (Event)
	MessageContentFilter (Event)
	ONVIF Message Content Filter Dialect (Event)
Access Point Information	GetAccessPointInfoList (Access Control)
	GetAccessPointInfo (Access Control)
	GetAccessPointList (Access Control)
	GetAccessPoints (Access Control)
	tns1:Configuration/AccessPoint/Changed (Event)
	tns1:Configuration/AccessPoint/Removed (Event)
Door Information	GetDoorInfoList (Door Control)
	GetDoorInfo (Door Control)
	GetDoorList (Door Control)
	GetDoors (Door Control)
	tns1:Configuration/Door/Changed (Event)
	tns1:Configuration/Door/Removed (Event)
Profile Conditional Features	
Access Point State	GetAccessPointState (Access Control)
	tns1:AccessPoint/State/Enabled (Event)
Access Control	ExternalAuthorization (Access Control)
	tns1:AccessControl/AccessGranted/Anonymous (Event)
	tns1:AccessControl/AccessGranted/Credential (Event)
	tns1:AccessControl/Denied/Anonymous (Event)
	tns1:AccessControl/Denied/Credential (Event)
	Feedback (Access Control)
	tns1:AccessControl/Request/Identifier (Event)
	tns1:AccessControl/Request/Anonymous (Event)
	tns1:AccessControl/Request/Timeout (Event)
Access Taken	tns1:AccessControl/AccessTaken/Identifier (Event)
	tns1:AccessControl/AccessNotTaken/Identifier (Event)

	tns1:AccessControl/AccessTaken/Anonymous (Event)
	tns1:AccessControl/AccessNotTaken/Anonymous (Event)
Door State	GetDoorState (Door Control)
	tns1:Door/State/DoorMode (Event)
	tns1:Door/State/DoorPhysicalState (Event)
	tns1:Door/State/LockPhysicalState (Event)
	tns1:Door/State/DoubleLockPhysicalState (Event)
	tns1:Door/State/DoorAlarm (Event)
	tns1:Door/State/DoorTamper (Event)
	tns1:Door/State/DoorFault (Event)
Door Control	AccessDoor (Door Control)
	LockDoor (Door Control)
	UnlockDoor (Door Control)
	DoubleLockDoor (Door Control)
	BlockDoor (Door Control)
	LockDownDoor (Door Control)
	LockDownReleaseDoor (Door Control)
	LockOpenDoor (Door Control)
	LockOpenReleaseDoor (Door Control)
Access Point Management	CreateAccessPoint (Access Control)
	ModifyAccessPoint (Access Control)
	DeleteAccessPoint (Access Control)
	SetAccessPoint (Access Control)
	tns1:Configuration/AccessPoint/Changed (Event)
	tns1:Configuration/AccessPoint/Removed (Event)
Access Point Control	EnableAccessPoint (Access Control)
	DisableAccessPoint (Access Control)
Door Management	CreateDoor (Door Control)
	ModifyDoor (Door Control)
	DeleteDoor (Door Control)

	SetDoor (Door Control)
	tns1:Configuration/Door/Changed (Event)
	tns1:Configuration/Door/Removed (Event)
Credential Format Types	GetSupportedFormatTypes (Credential)
Credential Whitelisting	GetWhitelist (Credential)
	AddToWhitelist (Credential)
	RemoveFromWhitelist (Credential)
	DeleteWhitelist (Credential)
	tns1:AccessControl/AccessGranted/Identifier (Event)
Credential Blacklisting	GetBlacklist (Credential)
	AddToBlacklist (Credential)
	RemoveFromBlacklist (Credential)
	DeleteBlacklist (Credential)
	tns1:AccessControl/Denied/Identifier (Event)

9.2 Profile D Support Check

Preliminary checking for feature discovery will be performed prior to the test execution. For the details of the preliminary feature discovery, refer to [ONVIF Feature Discovery].

According to the result of test case execution, final determination of [ONVIF Profile D] support toward DUT is performed based on the following procedure.

Procedure:

1. Check that scope list contains the scope given in [Table 9.1](#). If there is no such scope in the scope list of the DUT, then it is determined that [ONVIF Profile D] is not supported.
2. Check Discovery Types support. If **Discovery/Types/tds:Device** is not supported by the DUT, then it is determined that [ONVIF Profile D] is not supported by DUT and certification will be failed.
3. Check that Digest Authentication is supported by the DUT. If **Security/Digest** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. User authentication feature category:

- HTTP Digest Authentication
4. Check that RTSP Streaming is supported by the DUT. If **Media2 Service/Real-time Streaming** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. User authentication feature category:
 - RTSP Digest Authentication
5. Check Device Management Service related features:
- 5.1. Check that Discovery is supported by the DUT. If **Discovery** feature is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- 5.1.1. Discovery feature category:
- WS-Discovery
 - GetDiscoveryMode (Device Management)
 - SetDiscoveryMode (Device Management)
 - GetScopes (Device Management)
 - SetScopes (Device Management)
 - AddScopes (Device Management)
 - RemoveScopes (Device Management)
- 5.2. The following features are supported by the DUT, because these are mandatory features for any ONVIF device implementation:
- i. Check that Network Configuration is supported by the DUT. If **Device Service/System/Network Configuration** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Network Configuration feature category:
 - GetHostname (Device Management)

- SetHostname (Device Management)
 - GetDNS (Device Management)
 - SetDNS (Device Management)
 - GetNetworkInterfaces (Device Management)
 - SetNetworkInterfaces (Device Management)
 - GetNetworkProtocols (Device Management)
 - SetNetworkProtocols (Device Management)
 - GetNetworkDefaultGateway (Device Management)
 - SetNetworkDefaultGateway (Device Management)
- ii. System feature category:
- GetDeviceInformation (Device Management)
 - GetSystemDateAndTime (Device Management)
 - SetSystemDateAndTime (Device Management)
 - SetSystemFactoryDefault (Device Management)
 - Reboot (Device Management)
- iii. Check that User Handling is supported by the DUT. If **Device Service/System/ User Handling** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- i. User Handling feature category:
- GetUsers (Device Management)
 - CreateUsers (Device Management)
 - DeleteUsers (Device Management)
 - SetUser (Device Management)

6. Check that Event Handling is supported by the DUT. If **Event Handling Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise:

6.1. It is determined that the following features are supported by the DUT:

- i. Capabilities feature category:
 - **GetServiceCapabilities** (Event)
- ii. Event Handling feature category:
 - **GetEventProperties** (Event)

6.2. Check that Pull-Point Notification are supported by DUT. If **Event Service/Pull-Point Notification** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

- i. Event Handling feature category:
 - **SetSynchronizationPoint** (Event)
 - **CreatePullPointSubscription** (Event)
 - **PullMessage** (Event)
 - **Unsubscribe** (Event)
 - **TopicFilter** (Event)

6.3. Check that at least two PullPoint subscriptions are supported by DUT. If **Event Service/GetServiceCapabilities/MaxPullPoints capability** is regarded as unsupported by DUT or it has value less than two, then it is determined that [ONVIF Profile D] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

- i. Capabilities feature category:
 - **MaxPullPoint** capability is supported and value is not less than 2 (Event)

6.4. Check that ONVIF Message Content Filter Dialect is supported by DUT. If **Event Service/Message Content Filter/ONVIF Message Content Filter Dialect** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

- i. Event Handling feature category:
 - Message Content Filter (Event)
 - ONVIF Message Content Filter Dialect (Event)
7. Check that Access Control Service is supported by the DUT. If **Access Control Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise:
 - 7.1. It is determined that the following features are supported by the DUT:
 - i. Capabilities feature category:
 - GetServiceCapabilities (Access Control)
 - ii. Access Point Information feature category:
 - GetAccessPointInfoList (Access Control)
 - GetAccessPointInfo (Access Control)
 - GetAccessPointList (Access Control)
 - GetAccessPoints (Access Control)
 - 7.2. Check that MaxAccessPoints Capability is supported by DUT. If **Access Control Service/MaxAccessPoints Capability** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Capabilities feature category:
 - MaxAccessPoints Capability (Access Control)
 - 7.3. Check that tns1:Configuration/AccessPoint/Changed event is supported by the DUT. If **Access Control Service/Access Control Events/Configuration/AccessPoint/Changed** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
 - i. Access Point Information feature category:
 - tns1:Configuration/AccessPoint/Changed (Event)
 - 7.4. Check that tns1:Configuration/AccessPoint/Removed event is supported by the DUT. If **Access Control Service/Access Control Events/Configuration/AccessPoint/**

Removed is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Access Point Information feature category:
 - tns1:Configuration/AccessPoint/Removed (Event)

7.5. Check that Access Point Entity feature is supported by the DUT. If **Access Control Service/Access Point Entity** is regarded as supported by DUT:

7.5.1. It is determined that the following features are supported by the DUT:

- i. Access Point State feature category:
 - GetAccessPointState (Access Control)

7.5.2. Check that tns1:AccessPoint/State/Enabled event is supported by the DUT. If **Access Control Service/Access Control Events/AccessPoint/State/Enabled** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Access Point State feature category:
 - tns1:AccessPoint/State/Enabled (Event)

7.5.3. Check that External Authorization is supported by the DUT. If **Access Control Service/Access Point Entity/External Authorization** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise:

7.5.3.1. It is determined that the following features are supported by the DUT:

- i. Access Control feature category:
 - ExternalAuthorization (Access Control)

7.5.3.2. Check that tns1:AccessControl/Request/Timeout topic is supported by the DUT. If **Access Control Service/Access Control Events/tns1:AccessControl\Request\Timeout** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

- i. Access Control feature category:
 - tns1:AccessControl/Request/Timeout (Event)

- 7.5.3.3. Check that Identifier External Authorization is supported by the DUT. If **Access Control Service/Access Point Entity/Identifier Access** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- i. Access Control feature category:
 - tns1:AccessControl/Request/Identifier (Event)
- 7.5.3.4. Check that Feedback is supported by the DUT. If **Access Control Service/Access Point Entity/Feedback** is regarded as supported by DUT, it is determined that the following features are supported by the DUT:
- i. Access Control feature category:
 - Feedback (Access Control)
- 7.5.3.5. If **Access Control Service/Access Point Entity/Anonymous Access** is regarded as supported by the DUT
- i. If **Access Control Service/Access Control Events/AccessControl\Request\Anonymous** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - Access Control feature category:
 - tns1:AccessControl/Request/Anonymous (Event)
- 7.5.4. Check that Access Taken is supported by the DUT. If **Access Control Service/Access Point Entity/Access Taken** is regarded as supported by DUT:
- 7.5.4.1. Check that Identifier Access Taken is supported by the DUT. If **Access Control Service/Access Point Entity/Identifier Access** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

- i. Access Taken feature category:
 - tns1:AccessControl/AccessTaken/Identifier (Event)
 - tns1:AccessControl/AccessNotTaken/Identifier (Event)
- 7.5.4.2. Check that Anonymous Access Taken is supported by the DUT. If **Access Control Service/Access Point Entity/Anonymous Access** is regarded as supported by DUT
- i. If **Access Control Service/Access Control Events/AccessControl\AccessTaken\Anonymous** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - Access Taken feature category:
 - tns1:AccessControl/AccessTaken/Anonymous (Event)
 - ii. If **Access Control Service/Access Control Events/AccessControl\AccessNotTaken\Anonymous** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
 - Access Taken feature category:
 - tns1:AccessControl/AccessNotTaken/Anonymous (Event)
- 7.5.5. Check that Access Point Management is supported by the DUT. If **Access Control Service/Access Point Management** is regarded as supported by DUT:
- 7.5.5.1. It is determined that the following features are supported by the DUT:
- i. Access Point Management feature category:
 - CreateAccessPoint (Access Control)
 - ModifyAccessPoint (Access Control)
 - DeleteAccessPoint (Access Control)

7.5.5.2. Check that `tns1:Configuration/AccessPoint/Changed` event is supported by the DUT. If **Access Control Service/Access Control Events/Configuration/AccessPoint/Changed** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Access Point Management feature category:

- `tns1:Configuration/AccessPoint/Changed` (Event)

7.5.5.3. Check that `tns1:Configuration/AccessPoint/Removed` event is supported by the DUT. If **Access Control Service/Access Control Events/Configuration/AccessPoint/Removed** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Access Point Management feature category:

- `tns1:Configuration/AccessPoint/Removed` (Event)

7.5.5.4. Check that Client-Supplied Token for Access Points is supported by the DUT. If **Access Control Service/Client Supplied Token** is regarded as supported by DUT, it is determined that the following features are supported by the DUT:

i. Access Point Management feature category:

- `SetAccessPoint` (Access Control)

7.5.6. Check that `tns1:AccessControl/AccessGranted/Anonymous` event is supported by the DUT. If **Access Control Service\Access Control Events\AccessControl/AccessGranted/Anonymous** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Access Control feature category:

- `tns1:AccessControl/AccessGranted/Anonymous` (Event)

7.5.7. Check that `tns1:AccessControl/AccessGranted/Credential` event is supported by the DUT. If **Access Control Service\Access Control Events**

AccessControl/AccessGranted/Credential is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Access Control feature category:

- tns1:AccessControl/AccessGranted/Credential (Event)

7.5.8. Check that tns1:AccessControl/Denied/Anonymous event is supported by the DUT. If **Access Control Service\Access Control Events\AccessControl/Denied/Anonymous** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Access Control feature category:

- tns1:AccessControl/Denied/Anonymous (Event)

7.5.9. Check that tns1:AccessControl/Denied/Credential event is supported by the DUT. If **Access Control Service\Access Control Events\AccessControl/Denied/Credential** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Access Control feature category:

- tns1:AccessControl/Denied/Credential (Event)

7.5.10. Check that Access Point Control is supported by the DUT. If **Access Control Service/Access Point Entity/Enable/Disable Access Point** is regarded as supported by DUT:

7.5.10.1. It is determined that the following features are supported by the DUT:

i. Access Point Control feature category:

- EnableAccessPoint (Access Control)
- DisableAccessPoint (Access Control)

7.5.10.2. Check that tns1:AccessPoint/State/Enabled event is supported by the DUT. If **Access Control Service/Access Control Events/**

AccessPoint/State/Enabled is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Access Point State feature category:

- tns1:AccessPoint/State/Enabled (Event)

8. Check that Door Control Service is supported by the DUT. If **Door Control Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise:

8.1. It is determined that the following features are supported by the DUT:

i. Capabilities feature category:

- GetServiceCapabilities (Door Control)

ii. Door Information feature category:

- GetDoorInfoList (Door Control)
- GetDoorInfo (Door Control)
- GetDoorList (Door Control)
- GetDoors (Door Control)

8.2. Check that MaxDoors Capability is supported by DUT. If **Door Control Service/MaxDoors Capability** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Capabilities feature category:

- MaxDoors Capability (Door Control)

8.3. Check that tns1:Configuration/Door/Changed event is supported by the DUT. If **Door Control Service/Door Control Events/Configuration/Door/Changed** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Door Information feature category:

- tns1:Configuration/Door/Changed (Event)

- 8.4. Check that tns1:Configuration/Door/Removed event is supported by the DUT. If **Door Control Service/Door Control Events/Configuration/Door/Removed** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Door Information feature category:
 - tns1:Configuration/Door/Removed (Event)
- 8.5. Check that Door Entity feature is supported by the DUT. If **Door Control Service/Door Entity** is regarded as supported by DUT:
- 8.5.1. It is determined that the following features are supported by the DUT:
- i. Door State feature category:
 - GetDoorState (Door Control)
 - tns1:Door/State/DoorMode (Event)
- 8.5.2. Check that tns1:Door/State/DoorPhysicalState event is supported by the DUT. If **Door Control Service/Door Entity/Door Monitor** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Door State feature category:
 - tns1:Door/State/DoorPhysicalState (Event)
- 8.5.3. Check that tns1:Door/State/LockPhysicalState event is supported by the DUT. If **Door Control Service/Door Entity/Lock Monitor** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Door State feature category:
 - tns1:Door/State/LockPhysicalState (Event)
- 8.5.4. Check that tns1:Door/State/DoubleLockPhysicalState event is supported by the DUT. If **Door Control Service/Door Entity/Double Lock Monitor** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Door State feature category:

- tns1:Door/State/DoubleLockPhysicalState (Event)
- 8.5.5. Check that tns1:Door/State/DoorAlarm event is supported by the DUT. If **Door Control Service/Door Entity/Alarm** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Door State feature category:
 - tns1:Door/State/DoorAlarm (Event)
- 8.5.6. Check that tns1:Door/State/DoorTamper event is supported by the DUT. If **Door Control Service/Door Entity/Tamper** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Door State feature category:
 - tns1:Door/State/DoorTamper (Event)
- 8.5.7. Check that tns1:Door/State/DoorFault event is supported by the DUT. If **Door Control Service/Door Entity/Fault** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:
- i. Door State feature category:
 - tns1:Door/State/DoorFault (Event)
- 8.5.8. Check that Door Management is supported by the DUT. If **Door Control Service/Door Management** is regarded as supported by DUT:
- 8.5.8.1. It is determined that the following features are supported by the DUT:
- i. Door Management feature category:
 - CreateDoor (Door Control)
 - ModifyDoor (Door Control)
 - DeleteDoor (Door Control)
- 8.5.8.2. Check that tns1:Configuration/Door/Changed event is supported by the DUT. If **Door Control Service/Door Control Events/Configuration/Door/Changed** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Door Management feature category:

- tns1:Configuration/Door/Changed (Event)

8.5.8.3. Check that tns1:Configuration/Door/Removed event is supported by the DUT. If **Door Control Service/Door Control Events/Configuration/Door/Removed** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Door Management feature category:

- tns1:Configuration/Door/Removed (Event)

8.5.8.4. Check that Client-Supplied Token for Doors is supported by the DUT. If **Door Control Service/Client Supplied Token** is regarded as supported by DUT, it is determined that the following features are supported by the DUT:

i. Door Management feature category:

- SetDoor (Door Control)

8.5.9. Check that AccessDoor command is supported by the DUT. If **Door Control Service/Door Entity/Access Door** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Door Control feature category:

- AccessDoor (Door Control)

8.5.10. Check that LockDoor command is supported by the DUT. If **Door Control Service/Door Entity/Lock Door** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Door Control feature category:

- LockDoor (Door Control)

8.5.11. Check that UnlockDoor command is supported by the DUT. If **Door Control Service/Door Entity/Unlock Door** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Door Control feature category:

- UnlockDoor (Door Control)

8.5.12. Check that DoubleLockDoor command is supported by the DUT. If **Door Control Service/Door Entity/Double Lock Door** is regarded as supported by DUT, it is determined that the following features are supported by the DUT:

i. Door Control feature category:

- DoubleLockDoor (Door Control)

8.5.13. Check that BlockDoor command is supported by the DUT. If **Door Control Service/Door Entity/Block Door** is regarded as supported by DUT, it is determined that the following features are supported by the DUT:

i. Door Control feature category:

- BlockDoor (Door Control)

8.5.14. Check that LockDownDoor command and LockDownReleaseDoor command is supported by the DUT. If **Door Control Service/Door Entity/Lock Down Door** is regarded as supported by DUT, it is determined that the following features are supported by the DUT:

i. Door Control feature category:

- LockDownDoor (Door Control)
- LockDownReleaseDoor (Door Control)

8.5.15. Check that LockOpenDoor command and LockOpenReleaseDoor command is supported by the DUT. If **Door Control Service/Door Entity/Lock Open Door** is regarded as supported by DUT, it is determined that the following features are supported by the DUT:

i. Door Control feature category:

- LockOpenDoor (Door Control)

- LockOpenReleaseDoor (Door Control)
9. Check that at least one Door or at least one Access Point is supported by DUT. If both **Access Control Service/Access Point Entity** and **Door Control Service/Door Entity** are regarded as unsupported by DUT, then it is determined that [ONVIF Profile D] is not supported by DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:
- i. Capabilities feature category:
 - At least one of MaxAccessPoints and MaxDoors is larger than zero (Access Control or Door Control)
10. Check that Credential Service is supported by the DUT. If **Credential Service** is regarded as supported by the DUT, then:
- 10.1. It is determined that the following features are supported by the DUT:
- i. Capabilities feature category:
 - GetServiceCapabilities (Credential)
 - ii. Credential Format Types feature category:
 - GetSupportedFormatTypes (Credential)
- 10.2. Check that Credential Whitelisting is supported by the DUT. If **Credential Service/Whitelist** is regarded as supported by the DUT, then:
- 10.2.1. It is determined that the following features are supported by the DUT:
- i. Credential Whitelisting feature category:
 - GetWhitelist (Credential)
 - AddToWhitelist (Credential)
 - RemoveFromWhitelist (Credential)
 - DeleteWhitelist (Credential)
- 10.2.2. Check that tns1:AccessControl/AccessGranted/Identifier event is supported by the DUT. If **Access Control Service/Access Point Events/AccessControl/AccessGranted/Identifier** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile D] is not supported by

the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Credential Whitelisting feature category:

- tns1:AccessControl/AccessGranted/Identifier (Event)

10.3. Check that Credential Blacklisting is supported by the DUT. If **Credential Service/Blacklist** is regarded as supported by the DUT, then:

10.3.1. It is determined that the following features are supported by the DUT:

i. Credential Blacklisting feature category:

- GetBlacklist (Credential)
- AddToBlacklist (Credential)
- RemoveFromBlacklist (Credential)
- DeleteBlacklist (Credential)

10.3.2. Check that tns1:AccessControl/Denied/Identifier event is supported by the DUT. If **Access Control Service/Access Point Events/AccessControl/Denied/Identifier** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile D] is not supported by the DUT and certification will be failed. Otherwise, it is determined that the following features are supported by the DUT:

i. Credential Blacklisting feature category:

- tns1:AccessControl/Denied/Identifier (Event)

10 Profile V Conformance

10.1 Feature category classification for ONVIF Profile V

In order for ONVIF Device Test Tool to conduct conformance testing toward [ONVIF Profile V], it would need to identify whether DUT implements the expected feature set.

This section classifies supported features as multiple categories that are related to [ONVIF Profile V] conformance. Those category classifications will be used to do some preliminary checking prior to the test case execution and they will be used to determine whether DUT can be considered [ONVIF Profile V] conformant device.

The following discovery scope is defined as the scope that signals that DUT is [ONVIF Profile V] product.

Table 10.1. Profile V Discovery Scope

onvif://www.onvif.org/Profile/V

The following Add-Ons identifiers are valid as indication of [ONVIF Profile V Security Add-On] for [ONVIF Profile V] support.

Table 10.2. Profile V Security Add-On Addons Capability

ProfileVSecurityAddon_v1.0

The following table shows the classified feature categories based on commands and/or functional blocks that are referenced by DUT.

Table 10.3. Profile V Features Categories

Profile Mandatory Features	
Security Primitives	Profile V Security Add-On
Uplink	GetUplinks (Uplink)
	SetUplink (Uplink)
	DeleteUplink (Uplink)
	Access token based Authorization (Security)
	mTLS based Authorization (Security)
	WebSocket h2c-reverse tunnel (Uplink)
	MaxUplinks capability is supported and value is not less than 3 (Uplink)
Get Services	GetServices (Device Management)

	GetServiceCapabilities (Device Management)
	GetServiceCapabilities (Security)
	GetServiceCapabilities (Uplink)
	GetServiceCapabilities (Media 2)
	GetServiceCapabilities (DeviceIO)
	GetServiceCapabilities (Recording)
	GetServiceCapabilities (Event)
Network Configuration	GetSystemDateAndTime (Device Management)
	SetSystemDateAndTime (Device Management)
	GetNTP (Device Management)
	SetNTP (Device Management)
System	GetDeviceInformation (Device Management)
	SystemReboot (Device Management)
	GetScopes (Device Management)
Media Profile Management	CreateProfile (Media 2)
	DeleteProfile (Media 2)
	GetVideoSourceConfigurations (Media 2)
	GetVideoEncoderInstances (Media 2)
	tns1:Media/ProfileChanged (Event)
Video Streaming	Ready-to-use Media Profile for streaming H.264 video per video source (Media 2)
	GetProfiles (Media 2)
	GetWebRTCConfigurations (Media 2)
	SetWebRTCConfigurations (Media 2)
	Video Streaming using WebRTC (WebRTC)
	H.264 Encoding (Media 2)
Configuration of Video Profile	GetProfiles (Media 2)
	GetVideoSources (DeviceIO)
	GetVideoSourceConfigurations (Media 2)
	AddConfiguration (Video Source Configuration) (Media 2)
	AddConfiguration (Video Encoder Configuration) (Media 2)

	GetVideoEncoderConfigurations (Media 2)
	RemoveConfiguration (Video Source Configuration) (Media 2)
	RemoveConfiguration (Video Encoder Configuration) (Media 2)
	tns1:Media/ProfileChanged (Event)
Video Source Configuration	GetVideoSourceConfigurations (Media 2)
	GetVideoSourceConfigurationOptions (Media 2)
	SetVideoSourceConfiguration (Media 2)
	tns1:Media/ConfigurationChanged (Event)
Video Encoder Configuration	GetVideoEncoderConfigurations (Media 2)
	GetVideoEncoderConfigurationOptions (Media 2)
	SetVideoEncoderConfiguration (Media 2)
	tns1:Media/ConfigurationChanged (Event)
Storage Configuration	GetStorageConfigurations (Device Management)
	GetStorageConfiguration (Device Management)
	CreateStorageConfiguration (Device Management)
	DeleteStorageConfiguration (Device Management)
	SetStorageConfiguration (Device Management)
	Storage Configuration Renewal (Device Management)
	ObjectStorageS3 Storage Type (Device Management)
	ObjectStorageAzure Storage Type (Device Management)
Recording Configuration	CreateRecording (Recording)
	DeleteRecording (Recording)
	GetRecordings (Recording)
	CreateTrack (Recording)
	DeleteTrack (Recording)
	GetTrackConfiguration (Recording)
	SetTrackConfiguration (Recording)

	SetRecordingConfiguration (Recording)
	GetRecordingConfiguration (Recording)
	OverrideSegmentDuration (Recording)
	tns1:RecordingConfig/CreateRecording (Event)
	tns1:RecordingConfig/DeleteRecording (Event)
	tns1:RecordingConfig/CreateTrack (Event)
	tns1:RecordingConfig/DeleteTrack (Event)
	tns1:RecordingConfig/RecordingConfiguration (Event)
	tns1:RecordingConfig/TrackConfiguration (Event)
	H.264 Encoding (Recording)
	OPUS Encoding (Recording)
	AAC Encoding (Recording)
	MP4 Target Format (Recording)
	CMAF Target Format (Recording)
Recording Job Configuration	CreateRecordingJob (Recording)
	DeleteRecordingJob (Recording)
	SetRecordingJobConfiguration (Recording)
	GetRecordingJobConfiguration (Recording)
	GetRecordingJobs (Recording)
	GetRecordingJobState (Recording)
	SetRecordingJobMode (Recording)
	GetRecordingOptions (Recording)
	tns1:RecordingConfig/JobState (Event)
	tns1:RecordingConfig/ RecordingJobConfiguration (Event)
Event Handling using pull points	SetSynchronizationPoint (Event)
	CreatePullPointSubscription (Event)
	PullMessage (Event)
	GetEventProperties (Event)
	Unsubscribe (Event)
	TopicFilter (Event)
	MessageContentFilter (Event)

Event handling via MQTT	ONVIF Message Content Filter Dialect (Event)
	MaxPullPoint capability is supported and value is not less than 2 (Event)
	GetEventBrokers (Event)
	AddEventBroker (Event)
	DeleteEventBroker (Event)
	GetEventProperties (Event)
	MQTT events via mqtt protocol
	MQTT events via mqttts protocol
	MQTT events via ws protocol
	MQTT events via wss protocol
Profile Conditional Features	
Video Source Mode	GetVideoSources (DeviceIO)
	GetVideoSourceModes (Media 2)
	SetVideoSourceMode (Media 2)
Audio Streaming	GetProfiles (Media 2)
	GetWebRTCConfigurations (Media 2)
	SetWebRTCConfigurations (Media 2)
	Audio Streaming using WebRTC (WebRTC)
	G.711 μ -law Encoding (Media 2)
	OPUS Encoding (Media 2)
Configuration of Audio Profile	GetProfiles (Media 2)
	GetAudioSources (DeviceIO)
	GetAudioSourceConfigurations (Media 2)
	AddConfiguration, Audio Source Configuration (Media 2)
	AddConfiguration, Audio Encoder Configuration (Media 2)
	GetAudioEncoderConfigurations (Media 2)
	RemoveConfiguration, Audio Source Configuration (Media 2)
	RemoveConfiguration, Audio Encoder Configuration (Media 2)

	tns1:Media/ProfileChanged (Event)
Audio Encoder Configuration	GetAudioEncoderConfigurations (Media 2)
	GetAudioEncoderConfigurationOptions (Media 2)
	SetAudioEncoderConfiguration (Media 2)
	tns1:Media/ConfigurationChanged (Event)
Audio Output Streaming	GetProfiles (Media 2)
	GetWebRTCConfigurations (Media 2)
	SetWebRTCConfigurations (Media 2)
	Audio Output Streaming using WebRTC (Streaming)
	GetAudioDecoderConfigurationOptions (Media 2)
	G.711 μ -law Decoding (Media 2)
	OPUS Decoding (Media 2)
Configuration of Audio Output Profile	GetProfiles (Media 2)
	GetAudioOutputs (DeviceIO)
	GetAudioOutputConfigurations (Media 2)
	GetAudioDecoderConfigurations (Media 2)
	AddConfiguration, Audio Output Configuration (Media 2)
	AddConfiguration, Audio Decoder Configuration (Media 2)
	RemoveConfiguration, Audio Output Configuration (Media 2)
	RemoveConfiguration, Audio Decoder Configuration (Media 2)
	tns1:Media/ProfileChanged (Event)

10.2 Profile V Support Check

Preliminary checking for feature discovery will be performed prior to the test execution. For the details of the preliminary feature discovery, refer to [ONVIF Feature Discovery].

According to the result of test case execution, final determination of [ONVIF Profile V] support toward DUT is performed based on the following procedure.

Procedure:

1. Check that scope list contains the scope given in [Table 10.1](#). If there is no such scope in the scope list of the DUT, then it is determined that [ONVIF Profile V] is not supported.
2. Check that at least one version of Security Add-On is supported by the DUT. If **Device Management Service/GetServiceCapabilities/System/Addons capability** does not contain at least one of strings listed in [Table 10.2](#), then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED.
3. Check Device Management Service related features:
 - 3.1. The following features are supported by the DUT, because these are mandatory features for any ONVIF device implementation:
 - i. Get Services feature category:
 - GetServices (Device Management)
 - GetServiceCapabilities (Device Management)
 - ii. Network Configuration feature category:
 - GetSystemDateAndTime (Device Management)
 - SetSystemDateAndTime (Device Management)
 - iii. System feature category:
 - GetDeviceInformation (Device Management)
 - SystemReboot (Device Management)
 - GetScopes (Device Management)
 - 3.2. Check that NTP is supported by the DUT. If **Device Service/Network/NTP** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:
 - i. Network Configuration feature category:
 - GetNTP (Device Management)
 - SetNTP (Device Management)
 - 3.3. Check that storage configuration is supported by the DUT. If **Device Service/System/Storage Configuration** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:

3.3.1. It is determined that the following features are supported by the DUT:

- i. Storage Configuration feature category:
 - GetStorageConfigurations (Device Management)
 - GetStorageConfiguration (Device Management)
 - CreateStorageConfiguration (Device Management)
 - DeleteStorageConfiguration (Device Management)
 - SetStorageConfiguration (Device Management)

3.3.2. Check that storage configuration renewal is supported by the DUT. If **Device Service/System/Storage Configuration/Storage Configuration Renewal** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:

- i. Storage Configuration feature category:
 - Storage Configuration Renewal (Device Management)

3.3.3. Check that ObjectStorageS3 object storage is supported by the DUT. If **Device Service/System/Storage Configuration/Storage Type/Object Storage S3** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:

- i. Storage Configuration feature category:
 - ObjectStorageS3 Storage Type (Device Management)

3.3.4. Check that ObjectStorageAzure object storage is supported by the DUT. If **Device Service/System/Storage Configuration/Storage Type/Object Storage Azure** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:

- i. Storage Configuration feature category:
 - ObjectStorageAzure Storage Type (Device Management)

4. Check that Event Service is supported by the DUT. If **Event Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:

- 4.1. It is determined that the following features are supported by the DUT:
- i. Capabilities feature category:
 - GetServiceCapabilities (Event)
 - ii. Event Handling using pull points feature category:
 - GetEventProperties (Event)
 - iii. Event handling via MQTT feature category:
 - GetEventProperties (Event)
- 4.2. Check that Pull-Point Notification is supported by the DUT. If **Event Service/Pull-Point Notification** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:
- i. Event Handling using pull points feature category:
 - SetSynchronizationPoint (Event)
 - CreatePullPointSubscription (Event)
 - PullMessage (Event)
 - Unsubscribe (Event)
 - TopicFilter (Event)
- 4.3. Check that at least two PullPoint subscriptions are supported by DUT. If **Event Service/GetServiceCapabilities/MaxPullPoints capability** is regarded as unsupported by DUT or it has value less than two, then it is determined that [ONVIF Profile V] is not supported by DUT and certification will be FAILED. Otherwise, it is determined that the following features are supported by the DUT:
- i. Event Handling using pull points feature category:
 - MaxPullPoint capability is supported and value is not less than 2 (Event)
- 4.4. Check that ONVIF Message Content Filter Dialect is supported by DUT. If **Event Service/Message Content Filter/ONVIF Message Content Filter Dialect** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by DUT and certification will be FAILED. Otherwise, it is determined that the following features are supported by the DUT:

- i. Event Handling feature category:
 - Message Content Filter (Event)
 - ONVIF Message Content Filter Dialect (Event)
- 4.5. Check that MQTT is supported by the DUT. If **Event Service/Event Broker** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by DUT and certification will be FAILED. Otherwise, it is determined that the following features are supported by the DUT:
- i. Event handling via MQTT feature category:
 - GetEventBrokers (Event)
 - AddEventBroker (Event)
 - DeleteEventBroker (Event)
 - PublishFilter (Event)
 - ii. Check that mqtt protocol is supported by DUT. If **Event Service/Event Broker/Protocols/mqtt** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by DUT and certification will be FAILED. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Event handling via MQTT feature category:
 - MQTT events via mqtt protocol
 - iii. Check that mqttts protocol is supported by DUT. If **Event Service/Event Broker/Protocols/mqttts** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by DUT and certification will be FAILED. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Event handling via MQTT feature category:
 - MQTT events via mqttts protocol
 - iv. Check that ws protocol is supported by DUT. If **Event Service/Event Broker/Protocols/ws** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:
 - i. Event handling via MQTT feature category:
 - MQTT events via ws protocol

- v. Check that wss protocol is supported by DUT. If **Event Service/Event Broker/Protocols/wss** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:
 - i. Event handling via MQTT feature category:
 - MQTT events via wss protocol
- 5. Check that Advanced Security Service is supported by the DUT. If **Security Configuration Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:
 - 5.1. It is determined that the following features are supported by the DUT:
 - i. Get Services feature category:
 - GetServiceCapabilities (Security)
 - 6. Check that Uplink Service is supported by the DUT. If **Uplink Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:
 - 6.1. It is determined that the following features are supported by the DUT:
 - i. Get Services feature category:
 - GetServiceCapabilities (Uplink)
 - ii. Uplink feature category:
 - GetUplinks (Uplink)
 - SetUplink (Uplink)
 - DeleteUplink (Uplink)
 - 6.2. Check that WebSocket h2c-reverse tunnel is supported by the DUT. If **Uplink Service/Protocols/WSS** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise, it is determined that the following features are supported by the DUT:
 - i. Uplink feature category:
 - WebSocket h2c-reverse tunnel (Uplink)

- 6.3. Check that at least three Uplink connections are supported by DUT. If **Uplink Service/GetServiceCapabilities/MaxUplinks capability** is regarded as unsupported by DUT or it has value less than three, then it is determined that [ONVIF Profile V] is not supported by DUT and certification will be FAILED. Otherwise, it is determined that the following features are supported by the DUT:
- i. Uplink feature category:
 - MaxUplinks capability is supported and value is not less than 3 (Uplink)
- 6.4. Check that at least three Uplink connections are supported by DUT. If **Uplink Service/Authorization Modes/mTLS** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by DUT and certification will be FAILED. Otherwise, it is determined that the following features are supported by the DUT:
- i. Uplink feature category:
 - mTLS based Authorization (Security)
- 6.5. Check that at least three Uplink connections are supported by DUT. If **Uplink Service/Authorization Modes/Access Token** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by DUT and certification will be FAILED. Otherwise, it is determined that the following features are supported by the DUT:
- i. Uplink feature category:
 - Access token based Authorization (Security)
7. Check that Media2 Service is supported by the DUT. If **Media2 Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:
- 7.1. It is determined that the following features are supported by the DUT:
- i. Get Services feature category:
 - GetServiceCapabilities (Media 2)
 - ii. Media Profile Management feature category:
 - CreateProfile (Media 2)
 - DeleteProfile (Media 2)

- iii. Video Streaming feature category:
 - Ready-to-use Media Profile for streaming H.264 or H.265 video per video source (Media 2)
 - GetProfiles (Media 2)
 - iv. Configuration of Video Profile feature category:
 - GetProfiles (Media 2)
 - v. Audio Streaming feature category:
 - GetProfiles (Media 2)
 - vi. Configuration of Audio Profile feature category:
 - GetProfiles (Media 2)
 - vii. Audio Output Streaming feature category:
 - GetProfiles (Media 2)
 - viii. Configuration of Audio Output Profile feature category:
 - GetProfiles (Media 2)
- 7.2. Check that Video Source Configuration is supported by the DUT. If **Media2 Service/ Video Source Configuration** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise, it is determined that the following features are supported by the DUT:
- i. Media Profile Management feature category:
 - GetVideoSourceConfigurations (Media 2)
 - ii. Configuration of Video Profile feature category:
 - AddConfiguration (Video Source Configuration) (Media 2)
 - RemoveConfiguration (Video Source Configuration) (Media 2)
 - iii. Video Source Configuration feature category:
 - GetVideoSourceConfigurations (Media 2)

- GetVideoSourceConfigurationOptions (Media 2)
- SetVideoSourceConfiguration (Media 2)

7.3. Check that Video Encoder Configuration is supported by the DUT. If **Media2 Service/Video Encoder Configuration** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise, it is determined that the following features are supported by the DUT:

7.3.1. It is determined that the following features are supported by the DUT:

- i. Media Profile Management feature category:
 - GetVideoEncoderInstances (Media 2)
- ii. Configuration of Video Profile feature category:
 - AddConfiguration (Video Encoder Configuration) (Media 2)
 - GetVideoEncoderConfigurations (Media 2)
 - RemoveConfiguration (Video Encoder Configuration) (Media 2)
- iii. Video Encoder Configuration feature category:
 - GetVideoEncoderConfigurations (Media 2)
 - GetVideoEncoderConfigurationOptions (Media 2)
 - SetVideoEncoderConfiguration (Media 2)

7.3.2. Check that H.264 encoding is supported by the DUT. If **Media2 Service/Video Encoder configuration/H.264** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:

- i. Video Streaming feature category:
 - H.264 Encoding (Media 2)

7.4. Check that Audio Source Configuration is supported by the DUT. If **Media2 Service/Audio Source Configuration** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Configuration of Audio Profile feature category:

- GetAudioSourceConfigurations (Media 2)
- AddConfiguration (Audio Source Configuration) (Media 2)
- RemoveConfiguration (Audio Source Configuration) (Media 2)

7.5. Check that Audio Encoder Configuration is supported by the DUT. If **Media2 Service/ Audio Encoder Configuration** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

7.5.1. It is determined that the following features are supported by the DUT:

- i. Configuration of Audio Profile feature category:
 - AddConfiguration (Audio Encoder Configuration) (Media 2)
 - GetAudioEncoderConfigurations (Media 2)
 - RemoveConfiguration (Audio Encoder Configuration) (Media 2)
- ii. Audio Encoder Configuration feature category:
 - GetAudioEncoderConfigurations (Media 2)
 - GetAudioEncoderConfigurationOptions (Media 2)
 - SetAudioEncoderConfiguration (Media 2)

7.5.2. Check that G.711 μ -law encoding is supported by the DUT. If **Media2 Service/ Audio Encoder configuration/G.711** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Audio Streaming feature category:
 - G.711 Encoding (Media 2)

7.5.3. Check that OPUS encoding is supported by the DUT. If **Media2 Service/ Audio Encoder configuration/OPUS** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Audio Streaming feature category:
 - OPUS Encoding (Media 2)

7.5.4. Check that G.711 μ -law encoding or OPUS encoding are supported by the DUT. If both **Media2 Service/ Audio Encoder Configuration/G.711**

and **Media2 Service/Audio Encoder Configuration/OPUS** are regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED.

7.6. Check that Audio Output is supported by the DUT. If **Media2 Service/Audio Output** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

7.6.1. It is determined that the following features are supported by the DUT:

i. Audio Output Streaming feature category:

- GetAudioDecoderConfigurationOptions (Media 2)

ii. Configuration of Audio Profile feature category:

- GetAudioOutputConfigurations (Media 2)
- GetAudioDecoderConfigurations (Media 2)
- AddConfiguration (Audio Output Configuration) (Media 2)
- RemoveConfiguration (Audio Output Configuration) (Media 2)
- AddConfiguration (Audio Decoder Configuration) (Media 2)
- RemoveConfiguration (Audio Decoder Configuration) (Media 2)

7.6.2. Check that G.711 μ -law decoding is supported by the DUT. If **Media2 Service/Audio Output/G.711** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:

i. Audio Output Streaming feature category:

- G.711 Decoding (Media 2)

7.6.3. Check that OPUS decoding is supported by the DUT. If **Media2 Service/Audio Output/OPUS** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

i. Audio Output Streaming feature category:

- OPUS Decoding (Media 2)

7.7. Check that tns1:Media/ProfileChanged event is supported by the DUT. If **Media2 Service/Media2 Events/Media/ProfileChanged** is regarded as unsupported by DUT,

then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise, it is determined that the following features are supported by the DUT:

- i. Media Profile Management category:
 - tns1:Media/ProfileChanged (Event)
- ii. Configuration of Video Profile category:
 - tns1:Media/ProfileChanged (Event)
- iii. Configuration of Audio Profile category:
 - tns1:Media/ProfileChanged (Event)
- iv. Configuration of Audio Output Profile category:
 - tns1:Media/ProfileChanged (Event)

7.8. Check that tns1:Media/ConfigurationChanged event is supported by the DUT. If **Media2 Service/Media2 Events/Media/ConfigurationChanged** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise, it is determined that the following features are supported by the DUT:

- i. Video Source Configuration category:
 - tns1:Media/ConfigurationChanged (Event)
- ii. Video Encoder Configuration category:
 - tns1:Media/ConfigurationChanged (Event)
- iii. Audio Encoder Configuration category:
 - tns1:Media/ConfigurationChanged (Event)
- iv. Audio Encoder Configuration category:
 - tns1:Media/ConfigurationChanged (Event)

7.9. Check that WebRTC streaming is supported by the DUT. If **Media2 Service/WebRTC** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:

7.9.1. It is determined that the following features are supported by the DUT:

- i. Video Streaming feature category:
 - GetWebRTCCConfigurations (Media 2)
 - SetWebRTCCConfigurations (Media 2)
- ii. Audio Streaming feature category:
 - GetWebRTCCConfigurations (Media 2)
 - SetWebRTCCConfigurations (Media 2)
- iii. Audio Output Streaming feature category:
 - GetWebRTCCConfigurations (Media 2)
 - SetWebRTCCConfigurations (Media 2)

7.9.2. Check that Video Streaming over WebRTC is supported by the DUT. If **Media2 Service/Video Encoder Configuration** is regarded as unsupported by DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:

- i. Video Streaming feature category:
 - Video Streaming using WebRTC (WebRTC)

7.9.3. Check that Audio Streaming over WebRTC is supported by the DUT. If **Media2 Service/Audio Encoder Configuration** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Audio Streaming feature category:
 - Audio Streaming using WebRTC (WebRTC)

7.9.4. Check that Audio Output Streaming over WebRTC is supported by the DUT. If **Media2 Service/Audio Output** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Audio Output Streaming feature category:
 - Audio Output Streaming using WebRTC (WebRTC)

7.10. Check that Video Source Mode is supported by the DUT. If **Media2 Service/Video Source Mode** is regarded as supported by the DUT, then it is determined that the following features are supported by the DUT:

- i. Video Source Mode feature category:
 - GetVideoSourceModes (Media 2)
 - SetVideoSourceMode (Media 2)
8. Check that Device IO Service is supported by the DUT. If **Device IO Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:
 - 8.1. It is determined that the following features are supported by the DUT:
 - i. Get Services feature category:
 - GetServiceCapabilities (DeviceIO)
 - 8.2. If **Media2 Service/Video Source Configuration** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:
 - i. Configuration of Video Profile feature category:
 - GetVideoSources (DeviceIO)
 - ii. Video Source Mode feature category:
 - GetVideoSources (DeviceIO)
 - 8.3. If **Media2 Service/Audio Source Configuration** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:
 - i. Configuration of Audio Profile feature category:
 - GetAudioSources (DeviceIO)
 - 8.4. If **Media2 Service/Audio Outputs** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:
 - i. Configuration of Audio Output Profile feature category:
 - GetAudioOutputs (DeviceIO)
9. Check that Recording Control Service is supported by the DUT. If **Recording Control Service** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:
 - 9.1. It is determined that the following features are supported by the DUT:

- i. Get Services feature category:
 - GetServiceCapabilities (Recording)
- ii. Recording Configuration feature category:
 - GetRecordings (Recording)
 - GetTrackConfiguration (Recording)
 - SetTrackConfiguration (Recording)
 - SetRecordingConfiguration (Recording)
 - GetRecordingConfiguration (Recording)
 - tns1:RecordingConfig/RecordingConfiguration (Event)
 - tns1:RecordingConfig/TrackConfiguration (Event)
- iii. Recording Job Configuration feature category:
 - CreateRecordingJob (Recording)
 - DeleteRecordingJob (Recording)
 - SetRecordingJobConfiguration (Recording)
 - GetRecordingJobConfiguration (Recording)
 - GetRecordingJobs (Recording)
 - GetRecordingJobState (Recording)
 - SetRecordingJobMode (Recording)
 - tns1:RecordingConfig/JobState (Event)
 - tns1:RecordingConfig/RecordingJobConfiguration (Event)

9.2. If **Recording control Service/Dynamic Recordings** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:

- i. Recording Configuration feature category:
 - CreateRecording (Recording)
 - DeleteRecording (Recording)

- tns1:RecordingConfig/CreateRecording (Event)
- tns1:RecordingConfig/DeleteRecording (Event)
- tns1:RecordingConfig/CreateTrack (Event)
- tns1:RecordingConfig/DeleteTrack (Event)

9.3. If **Recording control Service/Dynamic Tracks** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:

i. Recording Configuration feature category:

- CreateTrack (Recording)
- DeleteTrack (Recording)
- tns1:RecordingConfig/CreateTrack (Event)
- tns1:RecordingConfig/DeleteTrack (Event)

9.4. Check that H.264 Recording is supported by the DUT. If **Recording Service/Video Encoding/H.264** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:

i. Recording Configuration feature category:

- H.264 Encoding (Recording)

9.5. Check that OPUS encoding is supported for recording by the DUT. If **Recording Service/Audio Encoding/OPUS** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:

i. Recording Configuration feature category:

- OPUS Encoding (Recording)

9.6. Check that AAC encoding is supported for recording by the DUT. If **Recording Service/Audio Encoding/AAC** is regarded as supported by the DUT, it is determined that the following features are supported by the DUT:

i. Recording Configuration feature category:

- AAC Encoding (Recording)

- 9.7. Check that AAC encoding or OPUS encoding are supported for recording by the DUT. If both **Recording Service/Audio Encoding/AAC** and **Recording Service/Audio Encoding/OPUS** are regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED.
- 9.8. Check that recording options is supported by the DUT. If **Recording Service/External Target Recording** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:
- 9.8.1. Check that MP4 format type is supported by the DUT. If **Recording Service/External Target Recording/MP4** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:
- i. Recording Configuration feature category:
 - MP4 Target Format (Recording)
- 9.8.2. Check that CMAF format type is supported by the DUT. If **Recording Service/External Target Recording/CMAF** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:
- i. Recording Configuration feature category:
 - CMAF Target Format (Recording)
- 9.9. Check that recording options is supported by the DUT. If **Recording Service/Recording Options** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:
- i. Recording Job Configuration feature category:
 - GetRecordingOptions (Recording)
- 9.10. Check that override of segment duration is supported by the DUT. If **Recording Service/Override Segment Duration** is regarded as unsupported by the DUT, then it is determined that [ONVIF Profile V] is not supported by the DUT and certification will be FAILED. Otherwise:
- i. Recording Configuration feature category:

- OverrideSegmentDuration (Recording)